

General Information

Mission Information

Project name	20211112_F1_Basestation
Processing date	2021-12-07 12:54:42
Mission date	2021-11-12 02:44:10
Mission duration	04:03:11.000
Processing mode	IN-Fusion Single Base
GPS Station	DHLG Durmid Hill

Rover Hardware Information

Product	POS AV 610 VER6 HW2.5-12
Serial number	S/N12299
IMU type	57
Receiver type	BD982
Antenna type	AV39

Project File List

Rover Data Files

File name	File type
VQ1560.765	POS Data
VQ1560.766	POS Data
VQ1560.767	POS Data
VQ1560.768	POS Data
VQ1560.769	POS Data
VQ1560.770	POS Data
VQ1560.771	POS Data
VQ1560.772	POS Data
VQ1560.773	POS Data
VQ1560.774	POS Data
VQ1560.775	POS Data
VQ1560.776	POS Data
VQ1560.777	POS Data
VQ1560.778	POS Data
VQ1560.779	POS Data
VQ1560.780	POS Data
VQ1560.781	POS Data
VQ1560.782	POS Data
VQ1560.783	POS Data
VQ1560.784	POS Data
VQ1560.785	POS Data
VQ1560.786	POS Data
VQ1560.787	POS Data
VQ1560.788	POS Data
VQ1560.789	POS Data
VQ1560.790	POS Data
VQ1560.791	POS Data
VQ1560.792	POS Data
VQ1560.793	POS Data
VQ1560.794	POS Data
VQ1560.795	POS Data
VQ1560.796	POS Data
VQ1560.797	POS Data
VQ1560.798	POS Data

Input Files

File Name	File type
Ephm3160.21g	GLONASS Broadcast Ephemeris
Ephm3160.21n	GPS Broadcast Ephemeris
dhl3160.21o	GNSS SingleBase

Output Files

Filename	File type
sbt_20211112_F1_Basestation.out	SBET Trajectory File
export_20211112_F1_Basestation_NAD83_2011.	Custom Smoothed BET Export Output

Rover Data Summary


First raw data file	VQ1560.765		
Last raw data file	VQ1560.798		
Start GPS week	2183		
Start time	441847.721 (11/12/2021 02:44:07)		
End time	456423.338 (11/12/2021 06:47:03)		
Start of fine alignment	442296.685 (11/12/2021 02:51:36)		
Available subsystems	Primary GNSS, IMU		
POS Event Input	None		
Correction data	None		
IMU Installation Lever Arms & Mounting Angles			
Reference to IMU lever arm [m]	0.018	-0.010	-0.464
Reference to IMU mounting angles [deg]	0.000	0.000	0.000
Reference to Primary GNSS lever arm [m]	0.000	0.000	-1.000
Reference to Primary GNSS lever arm std dev [m]	-1.000		
Aircraft to Reference mounting angles [deg]	0.000	0.000	0.000

Raw Data QC


Raw IMU Import QC Summary

IMU data input file	imu_20211112_F1_Basestation.dat
IMU data check log file	imudt_20211112_F1_Basestation.log
IMU Records Processed	2917620
Termination Status	Warnings
IMU Anomalies	1
IMU Failure Messages	
441847.536 : WARNING : Gap of 441831.5730 seconds in CHECKDT input data	


L1 Satellite Lock/Elevation




L2 Satellite Lock/Elevation



GPS L1 SNR




GPS L2 SNR




- | | | | |
|---------------------------|---------------------------|---------------------------|---------------------------|
| GPS PRN 01 L2 SNR (dB/Hz) | GPS PRN 02 L2 SNR (dB/Hz) | GPS PRN 05 L2 SNR (dB/Hz) | GPS PRN 06 L2 SNR (dB/Hz) |
| GPS PRN 07 L2 SNR (dB/Hz) | GPS PRN 08 L2 SNR (dB/Hz) | GPS PRN 09 L2 SNR (dB/Hz) | GPS PRN 12 L2 SNR (dB/Hz) |
| GPS PRN 13 L2 SNR (dB/Hz) | GPS PRN 14 L2 SNR (dB/Hz) | GPS PRN 15 L2 SNR (dB/Hz) | GPS PRN 17 L2 SNR (dB/Hz) |
| GPS PRN 19 L2 SNR (dB/Hz) | GPS PRN 21 L2 SNR (dB/Hz) | GPS PRN 24 L2 SNR (dB/Hz) | GPS PRN 30 L2 SNR (dB/Hz) |

GLONASS L1 SNR





- | | | |
|---------------------------|---------------------------|---------------------------|
| GLONASS 02 L1 SNR (dB/Hz) | GLONASS 03 L1 SNR (dB/Hz) | GLONASS 04 L1 SNR (dB/Hz) |
| GLONASS 05 L1 SNR (dB/Hz) | GLONASS 12 L1 SNR (dB/Hz) | GLONASS 13 L1 SNR (dB/Hz) |
| GLONASS 14 L1 SNR (dB/Hz) | GLONASS 15 L1 SNR (dB/Hz) | GLONASS 16 L1 SNR (dB/Hz) |
| GLONASS 17 L1 SNR (dB/Hz) | GLONASS 18 L1 SNR (dB/Hz) | GLONASS 19 L1 SNR (dB/Hz) |
| GLONASS 22 L1 SNR (dB/Hz) | GLONASS 23 L1 SNR (dB/Hz) | GLONASS 24 L1 SNR (dB/Hz) |

GLONASS L2 SNR




BEIDOU SNR




Trajectory Information


Top View




Altitude




Roll/Pitch




Heading




North/East Velocity




Down Velocity




Total Speed




Ground Speed




Body Acceleration



Total Body Acceleration



Body Angular Rate



Base Station Information


Station ID	DHLG Durmid Hill		
Filename	dhlg3160.21o		
Start date	11/12/2021 00:00:00		
End date	11/12/2021 23:59:59		
Duration	23:59:59.000		
Data type	GNSS		
Receiver manufacturer, model, serial no.	Topcon	NET-G3A	618-01037
Antenna manufacturer, model	Topcon	TPS CR.G3 w/SCIS	
Antenna height [m]	0.122		
Antenna measurement method	Bottom of antenna mount		
Offset from measured point to APC [m]	0.08417		
Latitude	N33°23'23.28790"		
Longitude	W115°47'16.85576"		
Ellipsoidal height [m]	-82.15100		
Frame	NAD83_2011		
Epoch	2010		
Ellipsoid	GRS_1980		
Velocity North [mm/y]	36.2		
Velocity East [mm/y]	-29.88		
Velocity Up [mm/y]	-1.08		

GNSS QC

GNSS QC Statistics


Statistics	Min	Max	Mean
Baseline length [km]	3.73	123.64	
Number of GPS SV	3	11	9
Number of GLONASS SV	4	8	6
Number of QZSS SV	0	0	0
Number of BEIDOU SV	0	0	0
Total number of SV	7	18	15
PDOP	1.12	2.36	1.41
QC Solution Gaps	0.00	0.00	
Solution Type	Fixed	Float	No solution
Epoch (s)	14556.00	0.00	0.00
Percentage	100.00	0.00	0.00

Num SVs in solution




— Number of GPS — Number of GLONASS — Number of QZSS — Number of BEIDOU — Total Number


Forward/Reverse Separation



PDOP



Estimated Position Accuracy




GNSS-Inertial Processor Configuration

Processing mode	IN-Fusion Single Base		
Stabilized mount	False		
Base station	DHLG Durmid Hill		
Processing start time	441832.000 (11/12/2021 02:43:52)		
Processing end time	456423.000 (11/12/2021 06:47:03)		
Initial attitude source	Real-Time VNAV/RNAV Attitude		
IMU Sensor Context	Processing with Onboard IMU		
Reference to IMU lever arm [m]	0.000	0.000	0.000
Reference to IMU mounting angles [deg]	0.000	0.000	0.000
Reference to Primary GNSS lever arm [m]	-0.028	-0.054	-0.948
Reference to Primary GNSS lever arm std dev [m]	0.030	0.030	0.030
Aircraft to Reference mounting angles [deg]	0.000	0.000	0.000


Calibrated Installation Parameters

Reference-Primary GNSS Lever Arm


X Reference-Primary GNSS Lever Arm (m)




Y Reference-Primary GNSS Lever Arm (m)



Z Reference-Primary GNSS Lever Arm (m)




Reference-Primary GNSS Lever Arm Figure of Merit




Smoothed IN-Fusion QC

Smoothed Estimated Errors, Reference Frame


Accelerometer Bias (micro-g)




X Accelerometer Bias (micro-g)




Y Accelerometer Bias (micro-g)




Z Accelerometer Bias (micro-g)




Accelerometer Scale Error (ppm)




X Accelerometer Scale Error (ppm)




Y Accelerometer Scale Error (ppm)




Z Accelerometer Scale Error (ppm)




Gyro Bias (deg/h)




X Gyro Bias (deg/h)




Y Gyro Bias (deg/h)




Z Gyro Bias (deg/h)




Gyro Scale Error (ppm)




X Gyro Scale Error (ppm)



Y Gyro Scale Error (ppm)




Z Gyro Scale Error (ppm)




Smoothed Performance Metrics


Position Error RMS (m)




Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)




Heading Error RMS (arc-min)




Smoothed Solution Status

Processing Mode




0 = Fixed NL, 1 = Fixed WL, 2 = Float, 3 = DGNSS, 4 = RTCM, 5 = IAPPP, 6 = C/A, 7 = GNSS Nav, 8 = DR

Number of Satellites




— Number of GPS Satellites — Number of GLONASS Satellites — Number of QZSS Satellites — Number of BEIDOU Satellites

Baseline Length



SBET IAKAR Separation



Export Summary

Export file	export_20211112_F1_Basestation_NAD83_2011.out		
Export format	Custom Smoothed BET		
Solution in use	Post-processed		
Output rate	All Records		
Reference to Output lever arm [m]	0.000	0.000	0.000
Reference mounting angles [deg]	0.000	0.000	0.000
Output units (Coordinate / Lat & Lon)	Meter	Deg Decimal	
Export start time	442298.001 (11/12/2021 02:51:38)		
Export end time	456423.003 (11/12/2021 06:47:03)		
Height option	Ellipsoid Height		
WGS84 height flag	False		
Grid	Universal Transverse Mercator		
Zone	UTM North 11 (120W to 114W)		
Datum	NAD83 (2011)		
Ellipsoid	GRS 1980		
Local Transformation	NONE		
Target Epoch	2010		

EO Summary

EO file			
EO format			
Lever arm [m]	0.000	0.000	0.000
Boresight angles [arcmin]	0.000	0.000	0.000
Output rate	All Records		
Rotation sequence	x omega	y phi	z kappa
Local shift [m]	0.000	0.000	0.000
Output units (coordinate / angle / lat & lon)	Meter	Degree	Deg Decimal
Height option	Ellipsoid Height		
WGS84 height flag	False		
Scale height option	False		
Kappa cardinal rotation [deg]	0		
Solution in use	Post-processed		
EO start time	442298.001 (11/12/2021 02:51:38)		
EO end time	456423.003 (11/12/2021 06:47:03)		
Grid	Universal Transverse Mercator		
Zone	UTM North 11 (120W to 114W)		
Datum	WGS84		
Ellipsoid	WGS84		
Local Transformation	NONE		
Target Epoch	2021.863014		