

General Information

Mission Information

Project name	20211106_F2_Basestation
Processing date	2021-12-06 14:51:01
Mission date	2021-11-06 09:56:02
Mission duration	02:01:09.000
Processing mode	IN-Fusion Single Base
GPS Station	DHLG Durmid Hill

Rover Hardware Information

Product	POS AV 610 VER6 HW2.5-12
Serial number	S/N12299
IMU type	57
Receiver type	BD982
Antenna type	AV39

Project File List

Rover Data Files

File name	File type
VQ1560.519	POS Data
VQ1560.520	POS Data
VQ1560.521	POS Data
VQ1560.522	POS Data
VQ1560.523	POS Data
VQ1560.524	POS Data
VQ1560.525	POS Data
VQ1560.526	POS Data
VQ1560.527	POS Data
VQ1560.528	POS Data
VQ1560.529	POS Data
VQ1560.530	POS Data
VQ1560.531	POS Data
VQ1560.532	POS Data
VQ1560.533	POS Data
VQ1560.534	POS Data
VQ1560.535	POS Data

Input Files

File Name	File type
Ephm3100.21g	GLONASS Broadcast Ephemeris
Ephm3100.21n	GPS Broadcast Ephemeris
dhl3100.21o	GNSS SingleBase

Output Files

Filename	File type
sbt_20211106_F2_Basestation.out	SBET Trajectory File
export_20211106_F2_Basestation_NAD83_2011.	Custom Smoothed BET Export Output

Rover Data Summary


First raw data file	VQ1560.519		
Last raw data file	VQ1560.535		
Start GPS week	2182		
Start time	554155.966 (11/06/2021 09:55:55)		
End time	561413.767 (11/06/2021 11:56:53)		
Start of fine alignment	554496.905 (11/06/2021 10:01:36)		
Available subsystems	Primary GNSS, IMU		
POS Event Input	None		
Correction data	None		
IMU Installation Lever Arms & Mounting Angles			
Reference to IMU lever arm [m]	0.018	-0.010	-0.464
Reference to IMU mounting angles [deg]	0.000	0.000	0.000
Reference to Primary GNSS lever arm [m]	0.000	0.000	-1.000
Reference to Primary GNSS lever arm std dev [m]	-1.000		
Aircraft to Reference mounting angles [deg]	0.000	0.000	0.000

Raw Data QC


Raw IMU Import QC Summary

IMU data input file	imu_20211106_F2_Basestation.dat
IMU data check log file	imudt_20211106_F2_Basestation.log
IMU Records Processed	1453659
Termination Status	Warnings
IMU Anomalies	1
IMU Failure Messages	
554155.776 : WARNING : Gap of 554143.8196 seconds in CHECKDT input data	


L1 Satellite Lock/Elevation




L2 Satellite Lock/Elevation



GPS L1 SNR




GPS L2 SNR





- | | | | |
|---------------------------|---------------------------|---------------------------|---------------------------|
| GPS PRN 02 L2 SNR (dB/Hz) | GPS PRN 05 L2 SNR (dB/Hz) | GPS PRN 06 L2 SNR (dB/Hz) | GPS PRN 12 L2 SNR (dB/Hz) |
| GPS PRN 13 L2 SNR (dB/Hz) | GPS PRN 15 L2 SNR (dB/Hz) | GPS PRN 18 L2 SNR (dB/Hz) | GPS PRN 20 L2 SNR (dB/Hz) |
| GPS PRN 23 L2 SNR (dB/Hz) | GPS PRN 24 L2 SNR (dB/Hz) | GPS PRN 25 L2 SNR (dB/Hz) | GPS PRN 26 L2 SNR (dB/Hz) |
| GPS PRN 29 L2 SNR (dB/Hz) | GPS PRN 31 L2 SNR (dB/Hz) | | |

GLONASS L1 SNR





- | | | |
|---------------------------|---------------------------|---------------------------|
| GLONASS 04 L1 SNR (dB/Hz) | GLONASS 05 L1 SNR (dB/Hz) | GLONASS 06 L1 SNR (dB/Hz) |
| GLONASS 07 L1 SNR (dB/Hz) | GLONASS 09 L1 SNR (dB/Hz) | GLONASS 10 L1 SNR (dB/Hz) |
| GLONASS 12 L1 SNR (dB/Hz) | GLONASS 20 L1 SNR (dB/Hz) | GLONASS 21 L1 SNR (dB/Hz) |
| GLONASS 22 L1 SNR (dB/Hz) | | |

GLONASS L2 SNR




BEIDOU SNR




Trajectory Information

Top View




Altitude




Roll/Pitch




Heading




North/East Velocity




Down Velocity




Total Speed




Ground Speed




Body Acceleration



Total Body Acceleration



Body Angular Rate



Base Station Information


Station ID	DHLG Durmid Hill		
Filename	dhlG3100.21o		
Start date	11/06/2021 00:00:00		
End date	11/06/2021 23:59:59		
Duration	23:59:59.000		
Data type	GNSS		
Receiver manufacturer, model, serial no.	Topcon	NET-G3A	618-01037
Antenna manufacturer, model	Topcon	TPS CR.G3 w/SCIS	
Antenna height [m]	0.122		
Antenna measurement method	Bottom of antenna mount		
Offset from measured point to APC [m]	0.08417		
Latitude	N33°23'23.28790"		
Longitude	W115°47'16.85576"		
Ellipsoidal height [m]	-82.15100		
Frame	NAD83_2011		
Epoch	2010		
Ellipsoid	GRS_1980		
Velocity North [mm/y]	36.2		
Velocity East [mm/y]	-29.88		
Velocity Up [mm/y]	-1.08		

GNSS QC

GNSS QC Statistics


Statistics	Min	Max	Mean
Baseline length [km]	2.71	69.72	
Number of GPS SV	6	11	8
Number of GLONASS SV	3	6	5
Number of QZSS SV	0	0	0
Number of BEIDOU SV	0	0	0
Total number of SV	10	16	12
PDOP	1.24	3.54	1.84
QC Solution Gaps	0.00	0.00	
Solution Type	Fixed	Float	No solution
Epoch (s)	7223.00	0.00	0.00
Percentage	100.00	0.00	0.00

Num SVs in solution




— Number of GPS — Number of GLONASS — Number of QZSS — Number of BEIDOU — Total Number


Forward/Reverse Separation



PDOP



Estimated Position Accuracy




GNSS-Inertial Processor Configuration

Processing mode	IN-Fusion Single Base		
Stabilized mount	False		
Base station	DHLG Durmid Hill		
Processing start time	554144.000 (11/06/2021 09:55:44)		
Processing end time	561413.000 (11/06/2021 11:56:53)		
Initial attitude source	Real-Time VNAV/RNAV Attitude		
IMU Sensor Context	Processing with Onboard IMU		
Reference to IMU lever arm [m]	0.000	0.000	0.000
Reference to IMU mounting angles [deg]	0.000	0.000	0.000
Reference to Primary GNSS lever arm [m]	-0.028	-0.054	-0.948
Reference to Primary GNSS lever arm std dev [m]	0.030	0.030	0.030
Aircraft to Reference mounting angles [deg]	0.000	0.000	0.000


Calibrated Installation Parameters

Reference-Primary GNSS Lever Arm


X Reference-Primary GNSS Lever Arm (m)




Y Reference-Primary GNSS Lever Arm (m)



Z Reference-Primary GNSS Lever Arm (m)




Reference-Primary GNSS Lever Arm Figure of Merit




Smoothed IN-Fusion QC

Smoothed Estimated Errors, Reference Frame


Accelerometer Bias (micro-g)




X Accelerometer Bias (micro-g)




Y Accelerometer Bias (micro-g)




Z Accelerometer Bias (micro-g)




Accelerometer Scale Error (ppm)



X Accelerometer Scale Error (ppm)




Y Accelerometer Scale Error (ppm)




Z Accelerometer Scale Error (ppm)




Gyro Bias (deg/h)




X Gyro Bias (deg/h)




Y Gyro Bias (deg/h)




Z Gyro Bias (deg/h)




Gyro Scale Error (ppm)




X Gyro Scale Error (ppm)



Y Gyro Scale Error (ppm)




Z Gyro Scale Error (ppm)




Smoothed Performance Metrics


Position Error RMS (m)




Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)




Heading Error RMS (arc-min)




Smoothed Solution Status

Processing Mode




0 = Fixed NL, 1 = Fixed WL, 2 = Float, 3 = DGNSS, 4 = RTCM, 5 = IAPPP, 6 = C/A, 7 = GNSS Nav, 8 = DR

Number of Satellites



— Number of GPS Satellites — Number of GLONASS Satellites — Number of QZSS Satellites — Number of BEIDOU Satellites

Baseline Length



SBET IAKAR Separation



Export Summary

Export file	export_20211106_F2_Basestation_NAD83_2011.out		
Export format	Custom Smoothed BET		
Solution in use	Post-processed		
Output rate	All Records		
Reference to Output lever arm [m]	0.000	0.000	0.000
Reference mounting angles [deg]	0.000	0.000	0.000
Output units (Coordinate / Lat & Lon)	Meter	Deg Decimal	
Export start time	554498.001 (11/06/2021 10:01:38)		
Export end time	561413.002 (11/06/2021 11:56:53)		
Height option	Ellipsoid Height		
WGS84 height flag	False		
Grid	Universal Transverse Mercator		
Zone	UTM North 11 (120W to 114W)		
Datum	NAD83 (2011)		
Ellipsoid	GRS 1980		
Local Transformation	NONE		
Target Epoch	2010		

EO Summary

EO file			
EO format			
Lever arm [m]	0.000	0.000	0.000
Boresight angles [arcmin]	0.000	0.000	0.000
Output rate	All Records		
Rotation sequence	x omega	y phi	z kappa
Local shift [m]	0.000	0.000	0.000
Output units (coordinate / angle / lat & lon)	Meter	Degree	Deg Decimal
Height option	Ellipsoid Height		
WGS84 height flag	False		
Scale height option	False		
Kappa cardinal rotation [deg]	0		
Solution in use	Post-processed		
EO start time	554498.001 (11/06/2021 10:01:38)		
EO end time	561413.002 (11/06/2021 11:56:53)		
Grid	Universal Transverse Mercator		
Zone	UTM North 11 (120W to 114W)		
Datum	WGS84		
Ellipsoid	WGS84		
Local Transformation	NONE		
Target Epoch	2021.846575		