

# West Coast El Nino 2016 B16 LiDAR

Report Produced for U.S. Geological Survey

USGS Contract: G10PC00020

Task Order: G16PD00366

Report Date: 11/03/2016

SUBMITTED BY:

**Dewberry**

1000 North Ashley Drive Suite 801  
Tampa, FL 33602  
813.225.1325

SUBMITTED TO:

**U.S. Geological Survey**

1400 Independence Road  
Rolla, MO 65401  
573.308.3810

## Table of Contents

Executive Summary .....	4
The Project Team .....	4
Survey Area.....	4
Date of Survey .....	4
Coordinate Reference System .....	4
LiDAR Vertical Accuracy .....	5
Project Deliverables .....	5
Project Tiling Footprint .....	6
LiDAR Acquisition Report .....	8
LiDAR Acquisition Details.....	8
LiDAR System parameters .....	11
Acquisition Status Report and Flightlines.....	11
LiDAR Control.....	12
Airborn GPS Kinematic .....	13
Generation and Calibration of Laser Points (raw data) .....	14
Boresight and Relative accuracy .....	14
Preliminary Vertical Accuracy Assessment.....	16
LiDAR Processing & Qualitative Assessment .....	18
Initial Processing.....	18
Final Swath Vertical Accuracy Assessment.....	18
Inter-Swath (Between Swath) Relative Accuracy.....	19
Intra-Swath (Within a Single Swath) Relative Accuracy .....	20
Horizontal Alignment.....	21
Point Density and Spatial Distribution.....	22
Data Classification and Editing .....	23
LiDAR Qualitative Assessment.....	25
Visual Review .....	25
Data Voids .....	25
Artifacts .....	26
Bridge Removal Artifacts .....	27
Culverts and Bridges.....	29
Tidal Window Requirements .....	30
Temporal Ground .....	31
Formatting.....	32
LiDAR Positional Accuracy.....	33

Background.....	33
Survey Vertical Accuracy Checkpoints .....	33
Vertical Accuracy Test Procedures.....	38
NVA.....	38
VVA.....	39
Vertical Accuracy Results .....	39
Horizontal Accuracy Test Procedures.....	42
Horizontal Accuracy Results .....	43
Breakline Production & Qualitative Assessment Report .....	44
Breakline Production Methodology .....	44
Breakline Qualitative Assessment.....	44
Breakline Checklist .....	45
Data Dictionary .....	46
Horizontal and Vertical Datum .....	46
Coordinate System and Projection .....	46
Tidal Waters .....	46
Beneath Bridge Breaklines .....	47
DEM Production & Qualitative Assessment .....	48
DEM Production Methodology .....	48
DEM Qualitative Assessment.....	50
DEM Vertical Accuracy Results .....	51
DEM Checklist.....	52
Appendix A: Survey Report.....	54
Appendix B: Complete List of Delivered Tiles .....	70
Appendix C: GPS Processing .....	84

## Executive Summary

The primary purpose of this project was to develop a consistent and accurate surface elevation dataset derived from high-accuracy Light Detection and Ranging (LiDAR) technology for the USGS West Coast El Nino LiDAR Project Area.

The LiDAR data were processed and classified according to project specifications. Detailed breaklines and bare-earth Digital Elevation Models (DEMs) were produced for the project area. The project encompasses approximately 75 square miles of coast in Oregon, 486 square miles of coast in Washington and California, and an additional 44 square miles for USACE defined harbors. The data was collected in a corridor approximately 500 meters wide. The project consists of two UTM Zones: UTM 10N and UTM 11N. A total of 2,377 UTM10N tiles and 487 UTM11N tiles were produced for the project. Each tile's extent is 1,500 meters by 1,500 meters.

## THE PROJECT TEAM

Dewberry served as the prime contractor for the project. In addition to project management, Dewberry was responsible for LAS classification, all LiDAR products, breakline production, Digital Elevation Model (DEM) production, and quality assurance.

Towill completed ground surveying for the project and delivered surveyed checkpoints. Their task was to acquire surveyed checkpoints for the project to use in independent testing of the vertical accuracy of the LiDAR-derived surface model. Towill also verified the GPS base station coordinates used during LiDAR data acquisition to ensure that the base station coordinates were accurate. Please see Appendix A to view the separate Survey Report that was created for this portion of the project.

Towill completed LiDAR data acquisition and data calibration for the project area.

## SURVEY AREA

The project area addressed by this report includes California, Washington, and Oregon coastlines.

## DATE OF SURVEY

The LiDAR aerial acquisition was conducted from April 28, 2016 thru May 28, 2016.

## COORDINATE REFERENCE SYSTEM

Data produced for the project were delivered in the following reference system.

**Horizontal Datum:** The horizontal datum for the project is North American Datum of 1983 with the 2011 Adjustment (NAD 83 (2011))

**Vertical Datum:** The Vertical datum for the project is North American Vertical Datum of 1988 (NAVD88)

**Coordinate System:** UTM Zone 10 and UTM Zone 11

**Units:** Horizontal units are in meters, Vertical units are in meters.

**Geoid Model:** Geoid12B (Geoid 12B was used to convert ellipsoid heights to orthometric heights).

## **LIDAR VERTICAL ACCURACY**

For the USGS West Coast El Nino LiDAR Project, the tested RMSE<sub>z</sub> of the classified LiDAR data for checkpoints in non-vegetated terrain equaled **5.8 cm** compared with the 10 cm specification; and the NVA of the classified LiDAR data computed using RMSE<sub>z</sub> x 1.9600 was equal to **11.4 cm**, compared with the 19.6 cm specification.

For the USGS West Coast El Nino LiDAR Project, the tested VVA of the classified LiDAR data computed using the 95<sup>th</sup> percentile was equal to **21.1 cm**, compared with the 29.4 cm specification.

Additional accuracy information and statistics for the classified LiDAR data, raw swath data, and bare earth DEM data are found in the following sections of this report.

## **PROJECT DELIVERABLES**

The deliverables for the project are listed below.

1. Raw Point Cloud Data (Swaths)
2. Classified Point Cloud Data (Tiled)
3. Bare Earth Surface (Raster DEM – IMG Format)
4. Intensity Images (16-bit gray scale, tiled, GeoTIFF format)
5. Breakline Data (File GDB)
6. Independent Survey Checkpoint Data (Report with Photos & Points)
7. Calibration Points
8. Metadata
9. Project Report (Acquisition, Processing, QC)
10. Project Extents, Including a shapefile derived from the LiDAR Deliverable

### PROJECT TILING FOOTPRINT

A total of two thousand three hundred seventy-seven (2,377) UTM10N tiles and four hundred eighty seven (487) UTM11N tiles were delivered for the project. Each tile's extent is 1,500 meters by 1,500 meters (see Appendix B for a complete listing of delivered tiles).




Figure 1 – UTM 10 Project Map

## West Coast El Nino UTM 11 Lidar Project



Figure 2 – UTM 11 Project Map

## LiDAR Acquisition Report

Dewberry elected to subcontract the LiDAR Acquisition and Calibration activities to Towill. Towill was responsible for providing LiDAR acquisition, calibration and delivery of LiDAR data files to Dewberry.

Dewberry received calibrated swath data from Towill in increments beginning in May 2016 and ending in June 2016. Reflights due to data voids were flown in August 2016.


### LIDAR ACQUISITION DETAILS

The primary acquisition concept consisted of a combination of both single and multiple passes to ensure adequate coverage of the acquisition boundary on the inland side of the corridor and the land-to-water interface on the coastal side of the corridor. The target flying height for the majority of the acquisition was 800 to 900 meters above mean terrain (AMT). In some cases, due to airspace restrictions or inclement weather, data was collected at a lower altitude but always above 300 meters.

Data covering the coastal side of the corridor was acquired within a 2-hour period centered on the daytime low-tide. Where additional inland passes were necessary for coverage, these data were, at times, acquired outside of the low-tide window. The predicted tides provided by NOAA were used to identify the low-tide times for applicable tidal stations along the coast. The images below show the data acquisition missions versus low-tide periods for each flight day.

A daily review of the real-time, sampled LiDAR data was undertaken to identify missing coverage or data anomalies. Emphasis was placed on ensuring data returns from the water on the coastal side of the corridor and complete coverage of the boundary on the inland side of the corridor.








Figure 3 – Data acquisition missions versus low-tide periods for each flight day.

## LIDAR SYSTEM PARAMETERS

Towill operated a Bell 206-L3 helicopter (Tail # N545SA) outfitted with an Optech Orion M300 LiDAR system during the collection of the study area. Table 1 illustrates Towill's system parameters for LiDAR acquisition on this project.

Item	Parameter
System	Optech Orion M300
Altitude (AGL meters)	400-900
Approx. Flight Speed (knots)	50
Scanner Pulse Rate (kHz)	275
Scan Frequency (hz)	44
Pulse Duration of the Scanner (nanoseconds)	4
Pulse Width of the Scanner (m)	1.1
Swath width (m)	500
Central Wavelength of the Sensor Laser (nanometers)	1064
Did the Sensor Operate with Multiple Pulses in The Air? (yes/no)	Yes
Beam Divergence (milliradians)	0.25
Nominal Swath Width on the Ground (m)	500
Swath Overlap (%)	n/a
Total Sensor Scan Angle (degree)	45
Computed Down Track spacing (m) per beam	0.32
Computed Cross Track Spacing (m) per beam	0.26
Nominal Pulse Spacing (single swath), (m)	0.3
Nominal Pulse Density (single swath) (ppsm), (m)	12
Aggregate NPS (m) (if ANPS was designed to be met through single coverage, ANPS and NPS will be equal)	0.3
Aggregate NPD (m) (if ANPD was designed to be met through single coverage, ANPD and NPD will be equal)	12
Maximum Number of Returns per Pulse	7

Table 1: Towill LiDAR System Parameters

## ACQUISITION STATUS REPORT AND FLIGHTLINES

Upon notification to proceed, the flight crew began acquisition at the southern terminus of the project area. A portion of the coastline was skipped between Long Beach and Ventura and that area located within the Vandenberg restricted airspace. These two areas were collected during the return flight after the appropriate permissions had been obtained.

Due to the enormous linear geographic extent of the project area, and the desire to maximize production during low-tide periods, the exclusive source of control/base station support for this LiDAR campaign consisted of Continuously Operating Reference Stations operated by the Plate Boundary Observatory (PBO) branch of UNAVCO (<http://www.unavco.org/projects/major-projects/pbo/pbo.html>). The western coastal and coast mountain ranges of the United States include hundreds of the PBO CORS that are publically funded and, with coordination in

advance, can be operated at a high collection rate (1-hertz) and the data obtained via simple File Transfer Protocol.

## LIDAR CONTROL

Regional PBO stations were identified and arranged to operate and record at a 1-hertz rate during the campaign period. Some missions included a GPS base station operated by the flight crew at the airport of operations. The base station point was tied back to the PBO CORS via common static data. The 1-hertz PBO data and, when applicable, the Towill base station data, were combined appropriately to serve as the Airborne GPS base station data for all missions of the campaign.

The coordinates of all used base stations are provided in the table below. All control and calibration points are also provided in shapefile format as part of the final deliverables.

Name	NAD83 (2011) UTM 10 and UTM11		Ellipsoid Ht (NAD83, m)	Orthometric Ht (NAVD88 Geoid12B, m)
	Easting X (m)	Northing Y (m)		
CABL	372236.2	4743799	38.286	3.3138
CHZZ	423565.5	5037463.2	51.161	13.7379
LFLO	411167.1	4870647.9	-6.042	-41.8686
NEAH	379491.8	5350682	460.245	423.7638
P059	437054.9	4309075.4	-10.822	-44.8962
P067	681014.7	3936067.4	107.594	-999999
P157	388747.2	4456053.3	696.236	662.5538
P172	610788.4	4009949.8	313.19	281.5747
P173	654202.2	3979278	339.828	309.3613
P181	554784.2	4196516.4	72.732	41.3917
P185	435354	4346041.5	146.834	112.3609
P188	480030.4	4279943.9	209.358	176.2669
P210	613110.7	4075226	3.6	-28.7312
P231	597875.7	4053462.4	-25.764	-58.384
P316	409430.6	4601398.3	235.389	200.6068
P415	444157.8	5167195	-15.081	-51.3069
P472	509791.1	3639009.2	138.603	107.0939
P474	523137	3690692	183.653	152.2421
P475	522871.5	3614330.4	-24.285	-56.0208
P523	694544.1	3908905.8	41.984	8.845
P534	567781.8	4101936.4	204.804	172.881
PABH	408787	5229515.5	13.277	-22.5567
PTSG	395694.9	4626415.6	-9.764	-44.8977

SBCC	438595.8	3712790.9	89.406	58.7143
TJRN	763333	3819497	157.816	121.9146
TRND	403289.6	4545376.5	78.68	45.0388
VNDP	718694.2	3826422.3	-9.147	-43.9109
CIRX	321313.4	3775997.2	488.885	459.4922
P161	397420.7	4499209.1	32.868	-0.4304
P177	544617.1	4153585.7	72.321	40.8522
P182	484196	4260755.4	397.293	364.6506
P193	508052.8	4219458.8	67.104	35.7911
P312	439980.5	4375735.2	255.394	221.0791
P315	438685.3	4412861.9	258.381	224.408
P364	385300	4771809	6.807	-28.0971
P365	398489.3	4805500.5	27.467	-7.6408
P366	420956.1	4829502.3	529.468	494.0651
P367	415731.8	4937425.8	23.277	-12.8936
P395	432441.3	4985782.5	53.385	16.4871
P396	435494.7	5017663.2	54.908	17.5736
P397	438592.3	5141203.8	566.625	530.2933
P398	430254.7	5197323.8	23.811	-12.132
P401	383715.2	5310491.7	36.486	0.0991
P402	402148.8	5291142.5	24.01	-12.1035
P403	415000.3	5323856.2	284.951	248.1235
P407	427852.6	5089429.6	-12.778	-49.7953
P435	462502.3	5323040.9	287.623	250.569
P436	489988.3	5321343.7	191.191	154.2866
P437	540344.2	5316642.4	12.789	-24.4073
P525	698986.5	3922467.2	271.978	238.9553
P548	270013.4	3816761.2	1135.502	1105.5551
P733	383767.8	4699821.7	184.951	150.0165
P734	393024.5	4659093.7	113.718	78.6323
PVRS	377721.4	3737865.9	60.538	31.3037
VIMT	360349.9	3777211.6	554.389	525.1132
VNCO	294008.2	3794998.6	26.345	-3.5789

Table 2 – Base Stations used to control LiDAR acquisition

### AIRBORN GPS KINEMATIC

The kinematic AGPS data was post-processed using Grafnav version 8.40 software, the de facto kinematic GPS post-processing package in the airborne remote sensing industry. Data is post-processed forward and backward in time exploiting the software's robust Kinematic Ambiguity

Resolution and Multi-Baseline features to mitigate ambiguity drift and minimize poor data as a result of satellite loss of lock. Appendix C summarizes the comparison of the forward and reverse solutions of the post-processed GPS data as well as PDOP and trajectory map for each of the missions.

## **GENERATION AND CALIBRATION OF LASER POINTS (RAW DATA)**

The Optech Orion M300 LiDAR system is subject to a regular maintenance and calibration schedule. The intent of periodic calibration is to monitor and validate components of the overall error budget including IMU boresight and performance, mirror angle readings and pulse gate timing. Several of these parameters can vary during and between missions due to changes in ambient meteorological conditions, different flying heights above ground, and different acquisition variables. The processing software, LMS, carries out a self-calibration of user-defined variables using areas of overlap between flight lines to improve the relative accuracy of the data.

Final LiDAR data processing is accomplished using Optech's Lidar Mapping Suite (LMS) software, version 3.1. During processing of the LiDAR data within LMS, flight lines are processed together in a block and the calibration parameters are adjusted mission-wise, block-wise and strip-wise to improve the overall relative fit of the data. The decoded raw laser observations (ranges, intensities, and mirror angles) and the final processed SBET are combined within LMS to compute the final 3-dimensional coordinates of the return(s) of each laser pulse and output data to LAS version 1.4 file format.

## **BORESIGHT AND RELATIVE ACCURACY**

Data overlap located at the respective beginnings and ends of flight lines, as well as that overlapping data within adjacent flight lines, was analyzed to verify the quality of the data calibration by LMS. This analysis was completed both by manual inspection of terrain and features within the overlapping data and generating "delta-Z" colorized images of the areas of overlap. Vertical differences between ground surfaces of each line are displayed. Color scale is adjusted so that errors greater than the specifications are flagged. Cross sections are visually inspected across each block to validate point to point, flight line to flight line and mission to mission agreement.

For this project the specifications used are as follow:

Relative accuracy  $\leq 6$  cm maximum differences within individual swaths and  $\leq 8$  cm RMSDz between adjacent and overlapping swaths.




Figure 4 – Profile views showing correct roll and pitch adjustments.




Figure 5 – QC area colored by elevation difference

A different set of QC blocks are generated for final review after all transformations have been applied.

## PRELIMINARY VERTICAL ACCURACY ASSESSMENT

A preliminary  $RMSE_z$  error check was performed by Towill using internal check points obtained using GPS static observation techniques and compared to  $RMSE_z$  project specifications. The LiDAR data is examined in non-vegetated, flat areas away from breaks. LiDAR ground points for each flight line generated by an automatic classification routine are used.

Prior to delivery to Dewberry, the elevation data was verified internally to ensure it met Non-vegetated Vertical Accuracy (NVA) requirements ( $RMSE_z \leq 10$  cm and  $Accuracy_z$  at the 95% confidence level  $\leq 19.6$  cm) when compared to the checkpoints. Table 3 summarizes the results of the test.

The calibrated West Coast El Nino LiDAR dataset was tested to 0.127 m vertical accuracy at 95% confidence level based on  $RMSE_z$  (0.065 m x 1.9600) when compared to 81 GPS static check points.

The following are the final statistics for the GPS static checkpoints used by Towill to internally verify vertical accuracy.

Point ID	NAVD88 (Geoid 12B)		
	Known Z (m)	Laser Z (m)	Delta Z
MA45	9.323	9.199	-0.124
MA46	9.335	9.187	-0.148
MA47	7.135	6.992	-0.143
MA48	51.679	51.792	0.113
MA49	6.836	6.982	0.146
MA50	5.563	5.732	0.169
MA51	16.523	16.546	0.023
MA52	5.692	5.659	-0.033
MA53	7.35	7.36	0.01
MA54	14.267	14.29	0.023
MA55	19.994	20.077	0.083
MA56	8.305	8.195	-0.11
MA57	6.625	6.609	-0.016
MA60	4.532	4.566	0.034
MA61	14.192	14.209	0.017
MA62	12.582	12.564	-0.018
MA64	34.356	34.328	-0.028
MA65	5.937	5.981	0.044
MA66	10.004	10.011	0.007
MA67	8.934	8.903	-0.031
MA68	58.84	58.828	-0.012
MA69	10.246	10.25	0.004



MA70	5.922	5.902	-0.02
MA71	6.375	6.347	-0.028
MA72	5.988	5.902	-0.086
MA73	5.842	5.893	0.051
MA74	6.771	6.819	0.048
MA75	23.941	23.89	-0.051
MA76	26.519	26.583	0.064
MA77	4.503	4.505	0.002
MA78	19.311	19.192	-0.119
MA79	45.419	45.485	0.066
MA80	6.022	6.131	0.109
MA81	7.576	7.63	0.054
MA82	4.543	4.627	0.084
MA83	43.709	43.653	-0.056
MA84	3.42	3.386	-0.034
MA85	3.771	3.564	-0.207
MA01	4.749	4.71	-0.039
MA02	6.146	6.158	0.012
MA04	46.484	46.481	-0.003
MA05	69.679	69.675	-0.004
MA06	3.498	3.497	-0.001
MA07	4.57	4.575	0.005
MA08	46.806	46.798	-0.008
MA09	4.858	4.851	-0.007
MA10	34.595	34.633	0.038
MA11	5.638	5.655	0.017
MA12	6.556	6.506	-0.05
MA13	2.933	2.943	0.01
MA14	3.737	3.698	-0.039
MA15	35.956	35.997	0.041
MA16	4.602	4.554	-0.048
MA17	16.05	16.02	-0.03
MA18	7.69	7.734	0.044
MA19	3.969	4.01	0.041
MA20	5.97	6	0.03
MA21	13.111	13.114	0.003
MA22	17.75	17.816	0.066
MA23	47.265	47.241	-0.024
MA24	88.745	88.679	-0.066
MA25	47.612	47.521	-0.091

MA26	26.904	26.837	-0.067
MA27	26.807	26.709	-0.098
MA28	15.025	15.06	0.035
MA29	29.955	29.96	0.005
MA30	12.526	12.636	0.11
MA31	22.59	22.562	-0.028
MA32	61.21	61.225	0.015
MA33	148.681	148.72	0.039
MA34	10.149	10.118	-0.031
MA35	13.675	13.571	-0.104
MA36	2.691	2.707	0.016
MA37	152.314	152.31	-0.004
MA38	36.892	36.88	-0.012
MA39	24.592	24.526	-0.066
MA40	53.236	53.261	0.025
MA41	25.378	25.346	-0.032
MA42	26.438	26.443	0.005
MA43	84.583	84.555	-0.028
MA44	7.975	7.98	0.005

Table 3 – Final statistics for the GPS static checkpoints

Overall the calibrated LiDAR data products collected by Towill meet or exceed the requirements set out in the Statement of Work. The quality control requirements of Towill’s quality management program were adhered to throughout the acquisition stage for this project to ensure product quality.

## LiDAR Processing & Qualitative Assessment

### INITIAL PROCESSING

Once Dewberry receives the calibrated swath data from the acquisition provider, Dewberry performs several validations on the dataset prior to starting full-scale production on the project. These validations include vertical accuracy of the swath data, inter-swath (between swath) relative accuracy validation, intra-swath (within a single swath) relative accuracy validation, verification of horizontal alignment between swaths, and confirmation of point density and spatial distribution. This initial assessment allows Dewberry to determine if the data are suitable for full-scale production. Addressing issues at this stage allows the data to be corrected while imposing the least disruption possible on the overall production workflow and overall schedule.

### Final Swath Vertical Accuracy Assessment

Once Dewberry received the calibrated swath data from Towill, Dewberry tested the vertical accuracy of the non-vegetated terrain swath data prior to additional processing. Dewberry tested the vertical accuracy of the swath data using the fifty non-vegetated (open terrain and urban) independent survey check points. The vertical accuracy is tested by comparing survey

checkpoints in non-vegetated terrain to a triangulated irregular network (TIN) that is created from the raw swath points. Only checkpoints in non-vegetated terrain can be tested against raw swath data because the data has not undergone classification techniques to remove vegetation, buildings, and other artifacts from the ground surface. Checkpoints are always compared to interpolated surfaces from the LiDAR point cloud because it is unlikely that a survey checkpoint will be located at the location of a discrete LiDAR point. Dewberry typically uses LP360 software to test the swath LIDAR vertical accuracy, Terrascan software to test the classified LiDAR vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project. Project specifications require a NVA of 19.6 cm based on the  $RMSE_z$  (10 cm) x 1.96. The dataset for the West Coast El Nino LiDAR Project satisfies this criteria. This raw LiDAR swath data set was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm  $RMSE_z$  Vertical Accuracy Class. Actual NVA accuracy was found to be  $RMSE_z = 5.7$  cm, equating to +/- 11.2 cm at 95% confidence level. The table below shows all calculated statistics for the raw swath data.

100 % of Totals	# of Points	$RMSE_z$ NVA Spec=0.10 m	NVA – Non-vegetated Vertical Accuracy ( $RMSE_z \times 1.9600$ ) Spec=0.196 m	Mean (m)	Median (m)	Skew	Std Dev (m)	Min (m)	Max (m)	Kurtosis
Non-Vegetated Terrain	50	0.057	0.112	-0.009	-0.001	-0.115	0.057	-0.173	0.123	0.723

Table 4: NVA at 95% Confidence Level for Raw Swaths

### Inter-Swath (Between Swath) Relative Accuracy

Dewberry verified inter-swath or between swath relative accuracy of the dataset by creating Delta-Z (DZ) orthos. According to the SOW, USGS LiDAR Base Specifications v1.2, and ASPRS Positional Accuracy Standards for Digital Geospatial Data, 10 cm Vertical Accuracy Class or QL1 data must meet inter-swath relative accuracy of 8 cm RMSDz or less with maximum differences less than 16 cm. These measurements are to be taken in non-vegetated and flat open terrain using single or only returns from all classes. Measurements are calculated in the DZ orthos on 1-meter pixels or cell sizes. Areas in the dataset where overlapping flight lines are within 8 cm of each other within each pixel are colored green, areas in the dataset where overlapping flight lines have elevation differences in each pixel between 8 cm -16 cm are colored yellow, and areas in the dataset where overlapping flight lines have elevation differences in each pixel greater than 16 cm are colored red. Pixels that do not contain points from overlapping flight lines are colored according to their intensity values. Areas of vegetation and steep slopes (slopes with 16 cm or more of valid elevation change across 1 linear meter) are expected to appear yellow or red in the DZ orthos. If the project area is heavily vegetated, Dewberry may also create DZ Orthos from the initial ground classification only, while keeping all other parameters consistent. This allows Dewberry to review the ground classification relative accuracy beneath vegetation and to ensure flight line ridges or other issues do not exist in the final classified data.

Flat, open areas are expected to be green in the DZ orthos. Large or continuous sections of yellow or red pixels can indicate the data was not calibrated correctly or that there were issues during acquisition that could affect the usability of the data, especially when these yellow/red sections follow the flight lines and not the terrain or areas of vegetation. The DZ orthos for El

Nino West Coast are shown in the figure below; this project meets inter-swath relative accuracy specifications.





Figure 6– Single return DZ Orthos for the E Nino West Coast Inter-swath relative accuracy passes specifications.

### **Intra-Swath (Within a Single Swath) Relative Accuracy**

Dewberry verifies the intra-swath or within swath relative accuracy by using Quick Terrain Modeler (QTM) scripting and visual reviews. QTM scripting is used to calculate the maximum difference of all points within each 1-meter pixel/cell size of each swath. Dewberry analysts then identify planar surfaces acceptable for repeatability testing and analysts review the QTM results in those areas. According to the SOW, USGS LiDAR Base Specifications v1.2, and ASPRS


Positional Accuracy Standards for Digital Geospatial Data, 10 cm Vertical Accuracy Class or QL1 data must meet intra-swath relative accuracy of 6 cm maximum difference or less. The image below shows two examples of the intra-swath relative accuracy of West Coast El Nino; this project meets intra-swath relative accuracy specifications.



**Figure 7–Intra-swath relative accuracy.** These images show a portion of the dataset; flat, open areas are colored green as they are within 6 cm whereas sloped or vegetated terrain is colored red because it exceeds 6 cm maximum difference, as expected, due to actual slope/terrain change or the height of vegetation. Intra-swath relative accuracy passes specifications.

### Horizontal Alignment

To ensure horizontal alignment between adjacent or overlapping flight lines, Dewberry uses QTM scripting and visual reviews. QTM scripting is used to create files similar to DZ orthos for each swath but this process highlights planar surfaces, such as roof tops. In particular, horizontal shifts or misalignments between swaths on roof tops and other elevated planar surfaces are highlighted. Visual reviews of these features, including additional profile verifications, are used to confirm the results of this process. The image below shows an example of the horizontal alignment between swaths for West Coast El Nino; no horizontal alignment issues were identified.



**Figure 8 Horizontal Alignment.** Two separate flight lines differentiated by color (Red/Green) are shown in this profile. There is no visible offset between these two flight lines. No horizontal alignment issues were identified.

### Point Density and Spatial Distribution

The required Aggregate Nominal Point Spacing (ANPS) for this project is no greater than 0.35 meters, which equates to an Aggregate Nominal Point Density (ANPD) of 8 points per square meter or greater. Density calculations were performed using first return data only located in the geometrically usable center portion (typically ~90%) of each swath. By utilizing statistics, the project area was determined to have an ANPS of 0.12 meters or an ANPD of 66 points per square meter which satisfies the project requirements.

The spatial distribution of points must be uniform and free of clustering. This specification is tested by creating a grid with cell sizes equal to the design  $NPS^2$ . QTM scripting is then used to calculate the number of first return points of each swath within each grid cell. At least 90% of the cells must contain 1 LiDAR point, excluding acceptable void areas such as water or low NIR reflectivity features, i.e. some asphalt and roof composition materials. This project passes spatial distribution requirements, as shown in the image below.




Figure 9– Spatial Distribution. The 2\*NPS tile grid is shown in green and all tiles containing at least one LiDAR point are colored pink.

### DATA CLASSIFICATION AND EDITING

Once the calibration, absolute swath vertical accuracy, and relative accuracy of the data was confirmed, Dewberry utilized a variety of software suites for data processing. The data was processed using GeoCue and TerraScan software. The initial step is the setup of the GeoCue project, which is done by importing a project defined tile boundary index encompassing the

entire project area. The acquired 3D laser point clouds, in LAS binary format, were imported into the GeoCue project and tiled according to the project tile grid. Once tiled, the laser points were classified using a proprietary routine in TerraScan. This routine classifies any obvious low outliers in the dataset to class 7 and high outliers in the dataset to class 18. Points along flight line edges that are geometrically unusable are identified as withheld and classified to a separate class so that they will not be used in the initial ground algorithm. After points that could negatively affect the ground are removed from class 1, the ground layer is extracted from this remaining point cloud. The ground extraction process encompassed in this routine takes place by building an iterative surface model.

This surface model is generated using three main parameters: building size, iteration angle and iteration distance. The initial model is based on low points being selected by a "roaming window" with the assumption that these are the ground points. The size of this roaming window is determined by the building size parameter. The low points are triangulated and the remaining points are evaluated and subsequently added to the model if they meet the iteration angle and distance constraints. This process is repeated until no additional points are added within iterations. A second critical parameter is the maximum terrain angle constraint, which determines the maximum terrain angle allowed within the classification model.

Each tile was then imported into Terrascan and a surface model was created to examine the ground classification. Dewberry analysts visually reviewed the ground surface model and corrected errors in the ground classification such as vegetation, buildings, and bridges that were present following the initial processing conducted by Dewberry. Dewberry analysts employ 3D visualization techniques to view the point cloud at multiple angles and in profile to ensure that non-ground points are removed from the ground classification. Bridge decks are classified to class 17 using bridge breaklines compiled by Dewberry. After the ground classification corrections were completed, the dataset was processed through a water classification routine that utilizes breaklines compiled by Dewberry to automatically classify hydro features. The water classification routine selects ground points within the breakline polygons and automatically classifies them as class 9, water. During this water classification routine, points that are within 1x NPS or less of the hydrographic features are moved to class 10, an ignored ground due to breakline proximity. Coastal areas in the project that were flown outside of low tide acquisition periods were classified to Class 64 so that these points were not used in the final ground. With one exception (discussed in more detail in the LiDAR Qualitative Assessment section below), the beach or land/water interface bare earth points were classified from those points flown within the low tide acquisition windows. In some areas along the land/water interface, multiple flight lines were acquired within low tide windows, but temporal differences exist between the overlapping flight lines. Bare earth ground points from these overlapping flight lines are not always consistent. In these instances, Dewberry chose one flight line to classify as bare earth class 2. The alternate bare earth points from the overlapping flight lines were classified to Class 65, temporal ground, so that data users have easy access to the alternate ground surface. Overage points are then identified in Terrascan and GeoCue is used to set the overlap bit for the overage points and the withheld bit is set on the withheld points previously identified in Terrascan before the ground classification routine was performed.

The LiDAR tiles were classified to the following classification schema:

- Class 1 = Unclassified, used for all other features that do not fit into the Classes 2, 7, 9, 10, 17, or 18, including vegetation, buildings, etc.



- Class 2 = Bare-Earth Ground
- Class 7 = Low Noise
- Class 9 = Water, points located within collected breaklines
- Class 10 = Ignored Ground due to breakline proximity
- Class 17 = Bridge Decks
- Class 18 = High Noise
- Class 64 = Flown Outside of Low Tide Window
- Class 65 = Temporal Ground

After manual classification, the LAS tiles were peer reviewed and then underwent a final QA/QC. After the final QA/QC and corrections, the LAS files were then converted from LAS v1.2 to LAS v1.4 using GeoCue software. At this time, all headers, appropriate point data records, and variable length records, including spatial reference information, are updated in GeoCue software and then verified using proprietary Dewberry tools.

## LiDAR Qualitative Assessment

Dewberry's qualitative assessment utilizes a combination of statistical analysis and interpretative methodology or visualization to assess the quality of the data for a bare-earth digital terrain model (DTM). This includes creating pseudo image products such as LiDAR orthos produced from the intensity returns, Triangular Irregular Network (TIN)'s, Digital Elevation Models (DEM) and 3-dimensional models as well as reviewing the actual point cloud data. This process looks for anomalies in the data, areas where man-made structures or vegetation points may not have been classified properly to produce a bare-earth model, and other classification errors. This report will present representative examples where the LiDAR and post processing had issues as well as examples of where the LiDAR performed well.

## VISUAL REVIEW

The following sections describe common types of issues identified in LiDAR data and the results of the visual review for West Coast El Nino.

### Data Voids

The LAS files are used to produce density grids using the commercial software package QT Modeler (QTM) which creates a 3-dimensional data model derived from Class 2 (ground) points in the LAS files. Grid spacing is based on the project density deliverable requirement for un-obscured areas. Acceptable voids (areas with no LiDAR returns in the LAS files) that are present in the majority of LiDAR projects include voids caused by bodies of water. One small void impacting one tile is present in the West Coast El Nino LiDAR project. This small void is inland and does not impact the beach or land/water interface. The presence of this void was brought to the attention of USGS and deemed OK since it impacted very little data.




Figure 10 – Tile number 10SGD70353892. Red polygon is the void. Blue is the USGS boundary.

### Artifacts

Artifacts are caused by the misclassification of ground points and usually represent vegetation and/or man-made structures. The artifacts identified are usually low lying structures, such as porches or low vegetation used as landscaping in neighborhoods and other developed areas. These low lying features are extremely difficult for the automated algorithms to detect as non-ground and must be removed manually. The vast majority of these features have been removed but a small number of these features are still in the ground classification. The limited numbers of features remaining in the ground are usually 0.3 meters or less above the actual ground surface, and should not negatively impact the usability of the dataset.




Figure 11 – Tile number 11SKT29403781. Profile with points colored by class (class 1=white, class 2=orange) is shown in the top view and a TIN of the surface is shown in the bottom view. A limited number of these small features are still classified as ground but do not impact the usability of the dataset.

### Bridge Removal Artifacts

The DEM surface models are created from TINs or Terrains. TIN and Terrain models create continuous surfaces from the inputs. Because a continuous surface is being created, the TIN or Terrain will use interpolation to continue the surface beneath the bridge where no LiDAR data was acquired. Locations where bridges were removed will generally contain less detail in the bare-earth surface because these areas are interpolated.




Figure 12 – Tile number 11SKT28953793. The DEM in the bottom view shows an area where bridges have been removed from ground. The surface model must make a continuous model and in order to do so, points are connected through interpolation. This results in less detail where the surface must be interpolated. The profile in the top view shows the LiDAR points of this particular feature colored by class. All bridge points have been removed from ground (orange) and are bridge deck (green).

### Culverts and Bridges

Bridges have been removed from the bare earth surface while culverts remain in the bare earth surface. In instances where it is difficult to determine if the feature is a culvert or bridge, such as with some small bridges, Dewberry erred on assuming they would be culverts especially if they are on secondary or tertiary roads. Below is an example of a culvert that has been left in the ground surface.




Figure 13– Tile number 15SKT28203798. Profile with points colored by class (class 1=white, class 2=orange) is shown in the top view and the DEM is shown in the bottom view. This culvert remains in the bare earth surface. Bridges have been removed from the bare earth surface and classified to class 17.

### Tidal Window Requirements

Dewberry identified an approximate 8 mile stretch where the flight line covering the land/water interface was flown within one hour past the 2 hour low tide window. This time delay results in the flight line being acquired when the tide is approximately 1 foot higher than the low tide. The flight line was still acquired approximately 2.5 feet lower than the high tide for the day. The affected area is in California along a particularly rocky shoreline where there is little beach before the cliffs. An image is shown below.




Figure 14- Image above shows the area flown outside of low tide window. Red= Boundary of area affected.

### Temporal Ground

Dewberry noticed artifacts along beaches affecting 248 tiles throughout the El Nino Lidar project during one of our internal DEM reviews. The artifacts are a result of temporal differences between two overlapping swaths flown on two separate dates but within the low tide window of each date flown. Dewberry used one swath to classify the most consistent ground and classified ground from the overlapping swath to class 65, Temporal Ground.




Figure 15- Tile 10TDQ41854975- The top image shows artifacts in the beach area due to temporal differences of overlapping flight lines. The bottom image shows the artifacts removed from the final ground once class 65, Temporal Ground, was implemented in the classification routine.

## FORMATTING

After the final QA/QC is performed and all corrections have been applied to the dataset, all LiDAR files are updated to the final format requirements and the final formatting, header information, point data records, and variable length records are verified using Dewberry proprietary tools. The table below lists some of the main LiDAR header fields that are updated and verified.

Classified LiDAR Formatting		
Parameter	Requirement	Pass/Fail
LAS Version	1.4	Pass
Point Data Format	Format 6	Pass
Coordinate Reference System	NAD83 (2011) UTM Zone 10 and UTM Zone 11, meters and NAVD88 (Geoid 12B), meters in WKT Format	Pass
Global Encoder Bit	Should be set to 17 for Adjusted GPS Time	Pass
Time Stamp	Adjusted GPS Time (unique timestamps)	Pass
System ID	Should be set to the processing system/software and is set to NIIRS10 for GeoCue software	Pass
Multiple Returns	The sensor shall be able to collect multiple returns per pulse and the return numbers are recorded	Pass
Intensity	16 bit intensity values are recorded for each pulse	Pass
Classification	Required Classes include: Class 1: Unclassified Class 2: Ground Class 7: Low Noise Class 9: Water Class 10: Ignored Ground Class 17: Bridge Decks Class 18: High Noise Class 64: Flown Outside Low Tide Window Class 65: Temporal Ground	Pass
Overlap and Withheld Points	Overlap (Overage) and Withheld points are set to the Overlap and Withheld bits	Pass
Scan Angle	Recorded for each pulse	Pass



XYZ Coordinates	Unique Easting, Northing, and Elevation coordinates are recorded for each pulse	Pass
-----------------	---	------

Table 5: Main LiDAR header fields

## LiDAR Positional Accuracy

### BACKGROUND

Dewberry quantitatively tested the dataset by testing the vertical accuracy of the LiDAR. The vertical accuracy is tested by comparing the discreet measurement of the survey checkpoints to that of the interpolated value within the three closest LiDAR points that constitute the vertices of a three-dimensional triangular face of the TIN. Therefore, the end result is that only a small sample of the LiDAR data is actually tested. However there is an increased level of confidence with LiDAR data due to the relative accuracy. This relative accuracy in turn is based on how well one LiDAR point "fits" in comparison to the next contiguous LiDAR measurement, and is verified as part of the initial processing. If the relative accuracy of a dataset is within specifications and the dataset passes vertical accuracy requirements at the location of survey checkpoints, the vertical accuracy results can be applied to the whole dataset with high confidence due to the passing relative accuracy. Dewberry typically uses LP360 software to test the swath LIDAR vertical accuracy, Terrascan software to test the classified LiDAR vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project.

Dewberry also tests the horizontal accuracy of LiDAR datasets when checkpoints are photo-identifiable in the intensity imagery. Photo-identifiable checkpoints in intensity imagery typically include checkpoints located at the ends of paint stripes on concrete or asphalt surfaces or checkpoints located at 90 degree corners of different reflectivity, e.g. a sidewalk corner adjoining a grass surface. The XY coordinates of checkpoints, as defined in the intensity imagery, are compared to surveyed XY coordinates for each photo-identifiable checkpoint. These differences are used to compute the tested horizontal accuracy of the LiDAR. As not all projects contain photo-identifiable checkpoints, the horizontal accuracy of the LiDAR cannot always be tested.

### SURVEY VERTICAL ACCURACY CHECKPOINTS

For the vertical accuracy assessment, ninety two (92) check points were surveyed for the project and are located within bare earth/open terrain, grass/weeds/crops, and forested/fully grown land cover categories. Please see appendix A to view the survey report which details and validates how the survey was completed for this project.

Checkpoints were evenly distributed throughout the project area so as to cover as many flight lines as possible using the "dispersed method" of placement.

All checkpoints surveyed for vertical accuracy testing purposes are listed in the following table.

Point ID	NAD83 (2011) UTM Zone 10 and Zone 11		NAVD88 (Geoid 12B)
	Easting X (m)	Northing Y (m)	Elevation (m)
CP01	487356.7	3609421.133	3.825
CP03	471758.807	3658464.484	16.183
CP05	433872.508	3702708.923	69.622
CP07	390351.568	3736550.9	3.588
CP09	362828.378	3763139.519	4.864
CP11	312071.298	3773517.429	11.753
CP13	268033.741	3808653.053	2.805
CP15	762983.115	3818429.812	39.3874
CP17	719418.3	3840433.867	16.3765
CP18	714535.253	3871687.284	7.5056
CP20	694036.4315	3916332.96	5.8322
CP23	653409.087	3952420.495	15.7076
CP24	638337.011	3976303.729	47.0066
CP26	599243.1435	4020824.97	47.52
CP28	605387.78	4057845.356	27.8267
CP30	574274.6015	4094257.208	30.5789
CP32	552705.1215	4128352.701	6.15715
CP34	544575.938	4168860.774	61.6958
CP36	510773.226	4208749.869	10.3
CP38	497187.908	4240705.328	2.71385
CP40	463297.377	4280958.534	34.97435
CP41	443369.632	4301363.329	32.5174
CP43	430229.559	4353595.893	25.3917
CP45	428478.1975	4403366.107	84.49625
CP46	408770.633	4430846.417	15.928
CP48	385736.8845	4492179.976	9.0742
CP50	403496.42	4545768.153	6.63825
CP52	408471.547	4605246.942	5.9577
CP53	395918.095	4626484.284	16.543
CP55	384141.112	4681306.538	6.6905
CP56	385036.855	4710238.546	14.1749
CP58	372662.896	4743708.906	59.3349
CP59	383287.053	4773464.005	22.83135
CP61	396721.634	4812014.777	5.41055
CP63	407340.877	4859446.28	4.2792
CP65	413740.802	4918436.985	12.38685
CP67	419275.9445	4976310.139	39.47065

CP69	424154.255	5034574.766	8.30305
CP71	424551.497	5085566.442	62.0716
CP73	418543.3055	5138520.068	6.0258
CP75	416133.956	5184591.198	6.2273
CP76	410795.543	5197870.813	6.2858
CP77	411039.8565	5213669.419	5.6367
CP79	397929.9365	5267764.194	23.261
CP81	377652.0645	5308779.769	4.44215
CP83	385505.203	5356684.107	21.72125
CP85	429261.236	5335065.501	7.59595
CP87	481486.688	5328820.27	43.6411
CP89	508589.0765	5327794.062	3.80555
KK23	653412.379	3952411.703	15.5171
CP02	475530.07	3629985.235	27.9
CP04	455068.821	3686247.479	45.717
CP06	412168.712	3720974.7	3.521
CP08	368269.371	3737869.464	45.734
CP10	338016.754	3766897.193	33.59
CP12	291334.175	3791124.412	6.42
CP14	240089.549	3812051.689	4.434
CP16	729406.082	3821560.589	5.1935
CP90	518140.234	5332263.165	3.36705
CP91	404763.367	5345724.904	10.2712
CP88	493944.41	5330196.512	3.2883
CP86	457612.162	5332216.305	4.2269
CP84	406885.053	5345828.918	5.9472
CP82	376627.234	5351115.071	22.6317
CP80	393891.755	5284758.814	35.312
CP78	405778.708	5239138.461	7.3061
CP74	418733.586	5155512.475	6.5263
CP72	424494.105	5114205.189	11.0967
CP70	426677.169	5064028.358	9.5295
CP68	424001.72	5004781.23	7.1447
CP66	414619.804	4947527.748	27.5028
CP64	410685.631	4890294.787	14.4585
CP62	402620.774	4834790.803	7.25
CP60	387060.361	4787945.602	5.5383
CP57	375915.297	4735419.35	20.54855
CP54	395011.734	4655570.846	5.656
CP51	408563.356	4570850.714	7.00205
CP49	399629.622	4519519.624	7.2396
CP47	384417.874	4467920.598	9.7166
CP44	433978.9935	4379890.558	27.7015

CP42	438114.933	4330526.523	55.98315
CP39	481785.369	4261184.436	146.836
CP37	502193.835	4214337.607	14.6302
CP35	536432.4965	4190736.529	147.6003
CP33	549283.726	4143770.156	22.231
CP31	553906.465	4115390.783	16.7149
CP29	601407.291	4087985.261	14.3482
CP27	595926.814	4046163.777	28.1387
CP25	621407.995	4000196.84	88.5666
CP21	684959.475	3925852.275	13.1725
CP22	672943.2175	3934846.461	12.82895
CP19	706269.857	3895404.942	2.0663

Table 6: West Coast El Nino LiDAR project surveyed accuracy checkpoints

The figures below shows the location of the QA/QC checkpoints used to test the positional accuracy of the dataset.

### West Coast El Nino UTM 10 Checkpoint Locations




Figure 16 – Location of QA/QC Checkpoints in UTM Zone 10

## West Coast El Nino UTM 11 Checkpoint Locations




Figure 17 – Location of QA/QC Checkpoints in UTM Zone 11

### VERTICAL ACCURACY TEST PROCEDURES

**NVA** (Non-vegetated Vertical Accuracy) is determined with check points located only in non-vegetated terrain, including open terrain (grass, dirt, sand, and/or rocks) and urban areas, where there is a very high probability that the LiDAR sensor will have detected the bare-earth ground surface and where random errors are expected to follow a normal error distribution. The NVA determines how well the calibrated LiDAR sensor performed. With a normal error distribution, the vertical accuracy at the 95% confidence level is computed as the vertical root

mean square error ( $RMSE_z$ ) of the checkpoints x 1.9600. For the West Coast El Nino LiDAR project, vertical accuracy must be 19.6 cm or less based on an  $RMSE_z$  of 10 cm x 1.9600.

**VVA** (Vegetated Vertical Accuracy) is determined with all checkpoints in vegetated land cover categories, including tall grass, weeds, crops, brush and low trees, and fully forested areas, where there is a possibility that the LiDAR sensor and post-processing may yield elevation errors that do not follow a normal error distribution. VVA at the 95<sup>th</sup> confidence level equals the 95<sup>th</sup> percentile error for all checkpoints in all vegetated land cover categories combined. The West Coast El Nino LiDAR Project VVA standard is 29.4 cm based on the 95<sup>th</sup> percentile. The VVA is accompanied by a listing of the 5% outliers that are larger than the 95<sup>th</sup> percentile used to compute the VVA; these are always the largest outliers that may depart from a normal error distribution. Here,  $Accuracy_z$  differs from VVA because  $Accuracy_z$  assumes elevation errors follow a normal error distribution where RMSE procedures are valid, whereas VVA assumes LiDAR errors may not follow a normal error distribution in vegetated categories, making the RMSE process invalid.

The relevant testing criteria are summarized in Table 7.

Quantitative Criteria	Measure of Acceptability
Non-Vegetated Vertical Accuracy (NVA) in open terrain and urban land cover categories using $RMSE_z$ *1.9600	19.6 cm (based on $RMSE_z$ (10 cm) * 1.9600)
Vegetated Vertical Accuracy (VVA) in all vegetated land cover categories combined at the 95% confidence level	29.4 cm (based on combined 95 <sup>th</sup> percentile)

**Table 7 – Acceptance Criteria**

The primary QA/QC vertical accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry’s team surveyed QA/QC vertical checkpoints in accordance with the project’s specifications.
2. Next, Dewberry interpolated the bare-earth LiDAR DTM to provide the z-value for every checkpoint.
3. Dewberry then computed the associated z-value differences between the interpolated z-value from the LiDAR data and the ground truth survey checkpoints and computed NVA, VVA, and other statistics.
4. The data were analyzed by Dewberry to assess the accuracy of the data. The review process examined the various accuracy parameters as defined by the scope of work. The overall descriptive statistics of each dataset were computed to assess any trends or anomalies. This report provides tables, graphs and figures to summarize and illustrate data quality.

## **VERTICAL ACCURACY RESULTS**

The table below summarizes the tested vertical accuracy resulting from a comparison of the surveyed checkpoints to the elevation values present within the fully classified LiDAR LAS files.

Land Cover Category	# of Points	NVA – Non-vegetated Vertical Accuracy (RMSE <sub>z</sub> x 1.9600) Spec=19.6 cm	VVA – Vegetated Vertical Accuracy (95th Percentile) Spec=29.4 cm
NVA	50	11.4	
VVA	42		21.1

Table 8 – Tested NVA and VVA

This LiDAR dataset was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm RMSE<sub>z</sub> Vertical Accuracy Class. Actual NVA accuracy was found to be RMSE<sub>z</sub> =5.8 cm, equating to +/- 11.4 cm at 95% confidence level. Actual VVA accuracy was found to be +/- 21.1 cm at the 95th percentile.

The figure below illustrates the magnitude of the differences between the QA/QC checkpoints and LiDAR data. This shows that the majority of LiDAR elevations were within +/- 10 cm of the checkpoints elevations, but there were some outliers where LiDAR and checkpoint elevations differed by up to -50 cm.




Figure 18 – Magnitude of elevation discrepancies per land cover category



Table 9 lists the 5% outliers that are larger than the VVA 95<sup>th</sup> percentile.

Point ID	NAD83 (2011) UTM Zone 10 and Zone 11		NAVD88 (Geoid 12B)	LiDAR Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
CP31	553906.465	4115390.783	16.715	16.929	0.214	0.214
CP57	375915.297	4735419.350	20.549	20.029	-0.520	0.520
CP80	393891.755	5284758.814	35.312	35.571	0.259	0.259

Table 9 – 5% Outliers

Table 10 provides overall descriptive statistics.

100 % of Totals	# of Points	RMSEz (m) NVA Spec=0.1 m	Mean (m)	Median (m)	Skew	Std Dev (m)	Kurtosis	Min (m)	Max (m)
NVA	50	0.058	-0.012	-0.010	-0.076	0.058	0.633	-0.177	0.123
VVA	42	N/A	0.021	0.030	-2.100	0.120	9.411	-0.520	0.259

Table 10 – Overall Descriptive Statistics

The figure below illustrates a histogram of the associated elevation discrepancies between the QA/QC checkpoints and elevations interpolated from the LiDAR triangulated irregular network (TIN). The frequency shows the number of discrepancies within each band of elevation differences. Although the discrepancies vary between a low of -0.520 meters and a high of +0.259 meters, the histogram shows that the majority of the discrepancies are skewed on the positive side. The vast majority of points are within the ranges of -0.05 meters to +0.05 meters.




Figure 19 – Histogram of Elevation Discrepancies with errors in meters

**Based on the vertical accuracy testing conducted by Dewberry, the LiDAR dataset for the West Coast El Nino LiDAR Project satisfies the project’s pre-defined vertical accuracy criteria.**

### **HORIZONTAL ACCURACY TEST PROCEDURES**

Horizontal accuracy testing requires well-defined checkpoints that can be identified in the dataset. Elevation datasets, including LiDAR datasets, do not always contain well-defined checkpoints suitable for horizontal accuracy assessment. However, the ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) recommends at least half of the NVA vertical check points should be located at the ends of paint stripes or other point features visible on the LiDAR intensity image, allowing them to double as horizontal check points.

Dewberry reviews all NVA checkpoints to determine which, if any, of these checkpoints are located on photo-identifiable features in the intensity imagery. This subset of checkpoints are then used for horizontal accuracy testing.

The primary QA/QC horizontal accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry’s team surveyed QA/QC vertical checkpoints in accordance with the project’s specifications and tried to locate half of the NVA checkpoints on features photo-identifiable in the intensity imagery.
2. Next, Dewberry identified the well-defined features in the intensity imagery.
3. Dewberry then computed the associated xy-value differences between the coordinates of the well-defined feature in the LiDAR intensity imagery and the ground truth survey checkpoints.
4. The data were analyzed by Dewberry to assess the accuracy of the data. Horizontal accuracy was assessed using NSSDA methodology where horizontal accuracy is calculated at the 95% confidence level. This report provides the results of the horizontal accuracy testing.

### HORIZONTAL ACCURACY RESULTS

Three checkpoints were determined to be photo-identifiable in the intensity imagery and were used to test the horizontal accuracy of the LiDAR dataset. As only three (3) checkpoints were photo-identifiable, the results are not statistically significant enough to report as a final tested value, but the results of the testing are still shown in the table below.

Using NSSDA methodology (endorsed by the ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014)), horizontal accuracy at the 95% confidence level (called ACCURACY<sub>r</sub>) is computed by the formula  $RMSE_r * 1.7308$  or  $RMSE_{xy} * 2.448$ .

No horizontal accuracy requirements or thresholds were provided for this project. However, LiDAR datasets are generally calibrated by methods designed to ensure a horizontal accuracy of 1 meter or less at the 95% confidence level.

# of Points	RMSE <sub>x</sub> (Target=0.409 m)	RMSE <sub>y</sub> (Target=0.409 m)	RMSE <sub>r</sub> (Target=0.578 m)	ACCURACY <sub>r</sub> (RMSE <sub>r</sub> x 1.7308) Target=1 m
3	0.041	0.115	0.122	0.211

Table 11-Tested horizontal accuracy at the 95% confidence level

**Actual positional accuracy of this dataset was found to be RMSE<sub>x</sub> = 4.1 cm and RMSE<sub>y</sub> = 11.5 cm which equates to +/- 21.1 cm at 95% confidence level.**

## **Breakline Production & Qualitative Assessment Report**

### **BREAKLINE PRODUCTION METHODOLOGY**

Dewberry used GeoCue software to develop LiDAR stereo models of the West Coast El Nino LiDAR Project area so the LiDAR derived data could be viewed in 3-D stereo using Socet Set softcopy photogrammetric software. Using LiDARgrammetry procedures with LiDAR intensity imagery, Dewberry used the stereo models developed by Dewberry to stereo-compile the tidal breaklines in accordance with the project's Data Dictionary.

### **BREAKLINE QUALITATIVE ASSESSMENT**

Dewberry completed breakline qualitative assessments according to a defined workflow. The following workflow diagram represents the steps taken by Dewberry to provide a thorough qualitative assessment of the breakline data.

Completeness and horizontal placement is verified through visual reviews against LiDAR intensity imagery. Automated checks are applied on all breakline features to validate topology, including the 3D connectivity of features.

The next step is to compare the elevation of the breakline vertices against the ground elevation extracted from the ESRI Terrain built from the LiDAR ground points, keeping in mind that a discrepancy is expected because of the hydro-enforcement applied to the breaklines and because of the interpolated imagery used to acquire the breaklines. A given tolerance is used to validate if the elevations differ too much from the LiDAR.

After all corrections and edits to the breakline features, the breaklines are imported into the final GDB and verified for correct formatting.




Figure 20-Breakline QA/QC workflow

## BREAKLINE CHECKLIST

The following table represents a portion of the high-level steps in Dewberry’s Production and QA/QC checklist that were performed for this project.

Pass/Fail	Validation Step
Pass	Use intensity imagery, stereo pairs, and terrains to collect breaklines according to project specifications.
Pass	In areas of heavy vegetation or where the exact shoreline is hard to delineate, it is better to err on placing the breakline <i>slightly</i> inside or seaward of the shoreline (breakline can be inside shoreline by 1x-2x NPS).

Pass	After each producer finishes breakline collection for a block, each producer must perform a completeness check, breakline variance check, and all automated checks on their block before calling that block complete and ready for the final merge and QC
Pass	After breaklines are completed for production blocks, all production blocks should be merged together and all checks-completeness, breakline variance, and automated checks-should be performed on the final, merged GDB. Ensure correct snapping-horizontal (x,y) and vertical (z)-between all production blocks.
Pass	Check entire dataset for missing features that were not captured, but should be to meet baseline specifications or for consistency. Features should be collected consistently across tile bounds. Check that the horizontal placement of breaklines is correct. Breaklines should be compared to full point cloud intensity imagery and terrains
Pass	Breaklines are correctly edge-matched to adjoining datasets in completion, coding, and horizontal placement.
Pass	Using a terrain created from LiDAR ground (all ground including 2 and 10) and water points (class 9), compare breakline Z values to interpolated LiDAR elevations.
Pass	Perform all Topology and Data Integrity Checks
N/A	Perform hydro-flattening and hydro-enforcement checks including monotonicity and flatness from bank to bank on linear hydrographic features and flatness of water bodies. Tidal waters should preserve as much ground as possible and can include variations or be non-monotonic.

Table 12-A subset of the high-level steps from Dewberry's Production and QA/QC checklist performed for this project.

## DATA DICTIONARY

The following data dictionary was used for this project.

### Horizontal and Vertical Datum

The horizontal datum shall be North American Datum of 1983 (2011), Units in Meters. The vertical datum shall be referenced to the North American Vertical Datum of 1988 (NAVD 88), Units in Meters. Geoid12B shall be used to convert ellipsoidal heights to orthometric heights.

### Coordinate System and Projection

All data shall be projected to UTM Zone 10 and UTM Zone 11, Horizontal Units in Meters and Vertical Units in Meters.

### Tidal Waters

**Feature Dataset:** BREAKLINES  
**Feature Type:** Polygon  
**Contains Z Values:** Yes  
**XY Resolution:** Accept Default Setting  
**XY Tolerance:** 0.003

**Feature Class:** TIDAL\_WATERS  
**Contains M Values:** No  
**Annotation Subclass:** None  
**Z Resolution:** Accept Default Setting  
**Z Tolerance:** 0.001

### Description

This polygon feature class will outline the land / water interface at the time of LiDAR acquisition.

**Table Definition**

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

**Feature Definition**

Description	Definition	Capture Rules
TIDAL_WATERS	<p>The coastal breakline will delineate the land water interface using LiDAR data as reference. In flight line boundary areas with tidal variation the coastal shoreline may show stair stepping as no feathering is allowed. Stair stepping is allowed to show as much ground as the collected data permits.</p>	<p>The feature shall be extracted at the apparent land/water interface, as determined by the LiDAR intensity data, to the extent of the tile boundaries. Differences caused by tidal variation are acceptable and breaklines delineated should reflect that change with no feathering.</p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding LiDAR points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water's edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p> <p>Breaklines shall snap and merge seamlessly with linear hydrographic features.</p>

**Beneath Bridge Breaklines**

**Feature Dataset:** BREAKLINES  
**Feature Type:** Polyline  
**Contains Z Values:** Yes  
**XY Resolution:** Accept Default Setting  
**XY Tolerance:** 0.003

**Feature Class:** Bridge\_Breaklines  
**Contains M Values:** No  
**Annotation Subclass:** None  
**Z Resolution:** Accept Default Setting  
**Z Tolerance:** 0.001

## Description

This polyline feature class is used to enforce terrain beneath bridge decks where ground data may not have been acquired. Enforcing the terrain beneath bridge decks prevents bridge saddles.

## Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software

## Feature Definition

Description	Definition	Capture Rules
Bridge Breaklines	Bridge Breaklines should be used where necessary to enforce terrain beneath bridge decks and to prevent bridge saddles in the bare earth DEMs.	<p>Bridge breaklines should be collected beneath bridges where bridge saddles exist or are likely to exist in the bare earth DEMs.</p> <p>Bridge breaklines should be collected perpendicular to the bridge deck so that the endpoints are on either side of the bridge deck. Typically two bridge breaklines are collected per bridge deck, one at either end of the bridge deck to enforce the terrain under the full bridge deck.</p> <p>The endpoints of the bridge breaklines will match the elevation of the ground at their xy position to enforce the ground/bare earth elevations beneath the bridge deck and prevent bridge saddles from forming.</p>

## DEM Production & Qualitative Assessment

### DEM PRODUCTION METHODOLOGY

Dewberry utilized ESRI software and Global Mapper for the DEM production and QC process. ArcGIS software is used to generate the products and the QC is performed in both ArcGIS and Global Mapper. The figure below shows the entire process necessary for bare earth DEM production, starting from the LiDAR swath processing.

The final bare-earth LiDAR points are used to create a terrain. The final 3D breaklines collected for the project are also enforced in the terrain. As this is a research project focusing on the land/water interface and beach areas, tidal waters were not hydro-flattened in the terrains. Not enforcing tidal water breaklines in terrain preserves as much information as possible in the coastal areas. Bridge breaklines were enforced in the terrain. The terrain is then converted to raster format using linear interpolation. For most projects, a single terrain/DEM can be created for the whole project. For very large projects, multiple terrains/DEMs may be created. The DEM(s) is reviewed for any issues requiring corrections, including remaining LiDAR mis-



classifications, erroneous breakline elevations, and processing artifacts. After corrections are applied, the DEM(s) is then split into individual tiles following the project tiling scheme. The tiles are verified for final formatting and then loaded into Global Mapper to ensure no missing or corrupt tiles and to ensure seamlessness across tile boundaries.



Figure 21-DEM Production Workflow

## DEM QUALITATIVE ASSESSMENT

Dewberry performed a comprehensive qualitative assessment of the bare earth DEM deliverables to ensure that all tiled DEM products were delivered with the proper extents, were free of processing artifacts, and contained the proper referencing information. This process was performed in ArcGIS software with the use of a tool set Dewberry has developed to verify that the raster extents match those of the tile grid and contain the correct projection information. The DEM data was reviewed at a scale of 1:5000 to review for artifacts caused by the DEM generation process. To perform this review Dewberry creates HillShade models and overlays a partially transparent colored elevation model to review for these issues. All corrections are completed using Dewberry's proprietary correction workflow. Upon completion of the corrections, the DEM data is loaded into Global Mapper for its second review and to verify corrections. Once the DEMs are tiled out, the final tiles are again loaded into Global Mapper to ensure coverage, extents, and that the final tiles are seamless.

The images below show an example of a bare earth DEM.




Figure 22-Tiles 10TCN37354740, 10TCN37504740. The image above is of the bare earth DEM




Figure 23- Tiles 10TCN37354740, 10TCN37504740. 3D Profile view of the bare earth DEM

### DEM VERTICAL ACCURACY RESULTS

The same 92 checkpoints that were used to test the vertical accuracy of the LiDAR were used to validate the vertical accuracy of the final DEM products as well. Accuracy results may vary between the source LiDAR and final DEM deliverable. DEMs are created by averaging several LiDAR points within each pixel which may result in slightly different elevation values at each survey checkpoint when compared to the source LAS, which does not average several LiDAR points together but may interpolate (linearly) between two or three points to derive an elevation value. The vertical accuracy of the DEM is tested by extracting the elevation of the pixel that contains the x/y coordinates of the checkpoint and comparing these DEM elevations to the surveyed elevations. Dewberry typically uses LP360 software to test the swath LIDAR vertical accuracy, Terrascan software to test the classified LiDAR vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project.

Table 13 summarizes the tested vertical accuracy results from a comparison of the surveyed checkpoints to the elevation values present within the final DEM dataset.

Land Cover Category	# of Points	NVA – Non-vegetated Vertical Accuracy (RMSE <sub>z</sub> x 1.9600) Spec=19.6 cm	VVA – Vegetated Vertical Accuracy (95th Percentile) Spec=29.4 cm
NVA	50	11.6	
VVA	42		20.4

Table 13 – DEM tested NVA and VVA

This DEM dataset was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm RMSE<sub>z</sub> Vertical Accuracy Class. Actual NVA accuracy was found to be RMSE<sub>z</sub> =5.9 cm, equating to +/- 11.6 cm at 95% confidence level. Actual VVA accuracy was found to be +/- 20.4 cm at the 95th percentile.

Table 14 lists the 5% outliers that are larger than the VVA 95<sup>th</sup> percentile.

Point ID	NAD83 UTM Zone 10 and Zone 11		NAVD88 (Geoid 12B)	DEM Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
CP57	375915.297	4735419.350	20.549	20.005	-0.544	0.544
CP80	393891.755	5284758.814	35.312	35.559	0.247	0.247

Table 14 – 5% Outliers

Table 15 provides overall descriptive statistics.

100 % of Totals	# of Points	RMSE <sub>z</sub> (m) NVA Spec=0.1 m	Mean (m)	Median (m)	Skew	Std Dev (m)	Kurtosis	Min (m)	Max (m)
NVA	50	0.059	-0.012	-0.003	-0.095	0.059	0.445	-0.173	0.127
VVA	42	N/A	0.027	0.032	-2.279	0.124	10.097	-0.544	0.247

Table 15 – Overall Descriptive Statistics

**Based on the vertical accuracy testing conducted by Dewberry, the DEM dataset for the West Coast El Nino LiDAR Project satisfies the project’s pre-defined vertical accuracy criteria.**

### DEM CHECKLIST

The following table represents a portion of the high-level steps in Dewberry’s bare earth DEM Production and QA/QC checklist that were performed for this project.

Pass/Fail	Validation Step
Pass	Masspoints (LAS to multipoint) are created from ground and tidal water points only (class 2 ground, Class 9 Water, class 10 ignored ground points)
Pass	Create a terrain for each production block using the final bare earth LiDAR points and final breaklines.
Pass	Convert terrains to rasters using project specifications for grid type, formatting, and cell size
Pass	Create hillshades for all DEMs

Pass	Manually review bare-earth DEMs in ArcMap with hillshades to check for issues
Pass	DEMs should not be hydro-flattened or hydro-enforced as required by project specifications
Pass	DEMs should be seamless across tile boundaries
N/A	Water should be flowing downhill without excessive water artifacts present
N/A	Water features should NOT be floating above surrounding
Pass	Bridges should NOT be present in bare-earth DEMs.
Pass	Any remaining bridge saddles where below bridge breaklines were not used need to be fixed by adding below bridge breaklines and re-processing.
Pass	All qualitative issues present in the DEMs as a result of LiDAR processing and editing issues must be marked for corrections in the LiDAR. These DEMs will need to be recreated after the LiDAR has been corrected.
Pass	Calculate DEM Vertical Accuracy including NVA, VVA, and other statistics
Pass	Split the DEMs into tiles according to the project tiling scheme
Pass	Verify all properties of the tiled DEMs, including coordinate reference system information, cell size, cell extents, and that compression has not been applied to the tiled DEMs
Pass	Load all tiled DEMs into Global Mapper to verify complete coverage to the (buffered) project boundary and that no tiles are corrupt.

**Table 16-A subset of the high-level steps from Dewberry's bare earth DEM Production and QA/QC checklist performed for this project.**

## Appendix A: Survey Report

### 1.1 Project Summary

Dewberry is under contract to the United States Geological Survey to provide surveyed control points for the above referenced USGS Task Order. Towill, Inc. was subcontracted by Dewberry to complete this task. The control points will be used to validate the newly acquired lidar and generate both Non-vegetated Vertical Accuracy (NVA) and Vegetated Vertical Accuracy (VVA) reports.

The ground survey was conducted during periods in April and May, 2016. The exclusive source of control for this Lidar campaign and Control survey consisted of Continuously Operating Reference Stations operated by the Plate Boundary Observatory (PBO) branch of UNAVCO (<http://www.unavco.org/projects/major-projects/pbo/pbo.html>). The western coastal and coast mountain ranges of the United States include hundreds of the PBO CORS that are publically funded and, with coordination in advance, can be operated at a high collection rate (1-hertz) and the data obtained via simple File Transfer Protocol.

The horizontal datum for this project is the latest realization of NAD83, namely NAD83(2011), epoch of 2010.0. The datum is realized by the published horizontal coordinates of the PBO CORS. These values were obtained via the National Geodetic Survey (NGS - [www.ngs.noaa.gov/CORS](http://www.ngs.noaa.gov/CORS)) and the Scripps Orbit and permanent Array Center (SOPAC - [sopac.ucsd.edu/processing](http://sopac.ucsd.edu/processing)). See Table 1 for a list of the published coordinate values.

The vertical datum for this project is NAVD88. The datum is realized by the published ellipsoid heights of the PBO CORS and the absolute application of the geoid model GEOID12B. These heights were obtained via the National Geodetic Survey (NGS - [www.ngs.noaa.gov/CORS](http://www.ngs.noaa.gov/CORS)) and the Scripps Orbit and permanent Array Center (SOPAC - [sopac.ucsd.edu/processing](http://sopac.ucsd.edu/processing)). See Table 1 for a list of the published ellipsoid heights.

### 1.2 Points of Contact

Questions regarding the technical aspects of this report should be addressed to:

**Towill, Inc.**

Keith Kirkby, PE

Survey Engineer

7222 Commerce Center Dr.


Suite 230


Colorado Springs, CO 80924

(719) 243-5990


### 1.3 Project Area


The project boundary falls along an approximately 500 meter wide corridor on the coastline between Tijuana, Mexico and Port Townsend, WA as depicted below:



















### **2.1 Survey Equipment**

All GPS observations were accomplished using Trimble Navigation R7 dual frequency GPS receivers and accompanying Trimble Zephyr Geodetic antennae. Instrument heights were measured twice in units of feet and meters and the values reduced and compared in the field prior to leaving each station.

Control point observation data were logged for a minimum of 45 minutes and as much as 60 minutes depending on proximity to operating PBO/CORS.

### **2.2 Survey Point Detail**

Ninety-two control points were established along the coastline. The control points were marked with either 12” spikes or PK nails and consisted of a combination of bare-earth, bare-earth/photo-identifiable, and low vegetation ground cover classes. Relative static GPS observation and processing techniques were used for all survey measurements.

The Ground Control Point locations are detailed in section 4 of this document, “Ground Control Point Documentation Reports”.

### **2.3 Network Design**

A primary geodetic network consisting of 55 PBO/CORS stations was established by downloading several 24-hour data files for each station for multiple days and post-processing the resulting baselines. The resulting network comprises 107 baselines of a minimum 24-hour duration each. Ninety-two new control points were established and subsequently tied into two of the PBO/CORS stations by downloading the appropriate 24-hour RINEX files and post-processing the static observation in Trimble Business Center. The project diagrams above illustrate the primary network connections and the new control point locations.

### **2.4 Data Post-processing and Analysis**

Observed relative GPS baselines were processed in Trimble Business Center. All processed observations consist of quasi-independent baselines (i.e. in accordance with the “n-1 baselines” rule where n = number of receivers in a given ‘session’). The International GPS Service for Geodynamics (IGS) rapid precise orbits (igr) were used in the processing of all baseline vectors. The ‘igr’ orbits are published with a latency of approximately 30 hours. These orbits are globally accurate to within ~5cm and are particularly important when processing long baselines.

One temporary base station point (in addition to the PBO/CORS) was established at the Florence Municipal Airport in Florence, OR. This point was tied into two local PBO stations via static GPS data acquired during the campaign.

It is well known that the Earth's crust deforms over time. The geometric variations of the Earth's surface over time must be taken into account for the realization of terrestrial reference systems. It is for this reason that there is inherent inconsistency between the 'published' coordinates of the PBO/CORS and the current survey campaign.

For the purpose of the new control survey, the methodology employed by Towill was to transform the published control coordinates to the mid-epoch of the GPS survey using the National Geodetic Survey software HTDP (Horizontal Time Dependent Positioning) software. The software employs crustal motion models that incorporate both continuous and episodic components of crustal motion. These models assume that points on the Earth's surface move with constant horizontal velocities. This is a generally accepted approach, except for years following the accelerated motion of the plates associated with large earthquakes. The episodic motion (created by earthquakes) is modeled by dislocation theory. The Northridge Earthquake of 1994 is an example. It is modeled by dislocation theory and is incorporated into the HTDP software.

The published geodetic coordinates of the PBO/CORS were transformed using HTDP from the published values (NAD83[2011], epoch 2010.0), to the datum and epoch associated with the new surveys, viz., NAD83[2011], epoch 2016.35. This ensures compatibility between the GPS observations (vectors), and the coordinates used as constraints in the final network adjustment.

## **2.5 Adjustments**

A minimally constrained, primary network adjustment was executed to verify the internal integrity of the baseline computations and to derive appropriate a-priori baseline observation weighting factors. In the resulting adjustment, the estimated variance factor ( $\sigma_{02} = 1.0002$ ) passed the  $\chi^2$ -test. This indicates appropriate *a priori* estimates of the accuracy of the GPS baseline vectors. None of the 321 vector component residuals or associated standardized residuals were flagged for possible rejection under the  $\tau$ -max test at the 95 percent level of confidence. The relative horizontal accuracy of the network can be assessed by reviewing the relative 95 percent confidence regions (ellipses) of the adjustment. All station pairings meet the Federal Geodetic Control Subcommittee (FGCS) relative positioning standard for Order B surveys (8mm + 8ppm).

The HTDP-translated latitude and longitude of each PBO/CORS and the published ellipsoid height on the GRS80 ellipsoid were held as weighted observations in a fully constrained primary network adjustment. The estimated variance factor ( $\sigma_{02} = 0.9868$ ) passed the  $\chi^2$ -test at the 95 percent level of confidence. This indicates that network was not being unduly distorted by the imposition of constraints. No residuals were flagged for possible rejection. Ninety-two control points were established and tied into two of the PBO/CORS stations by downloading the appropriate 24-hour RINEX files and post-processing the static observation in Trimble Business Center. These processed vectors were incorporated into a third least-squares adjustment to derive final coordinates and elevations of each of the newly established control points. The adjusted final coordinates were then run through HTDP to translate the values back to 2010.0 from the mid-epoch of the survey. **2.6**

## **Published PBO Coordinates / Adjustment Constraints**

The published coordinates of the PBO / CORS stations that were used as control for this survey and, ultimately, constraints (following the HTDP process described above) in the



network adjustments is tabulated below:

**PBO / CORS Published Coordinates and Ellipsoid Heights**

Horizontal Datum: NAD83(2011)  
 Epoch: 2010.0  
 Linear Unit: International Meter

Point	Latitude			Longitude			Ellipsoid Height		
	°	'	"	°	'	"			
<i>NGS Published Coordinates</i>									
CABL	N	42	50	09.94308	W	124	33	47.98620	38.286
CHZZ	N	45	29	11.44093	W	123	58	41.18376	51.161
LFLO	N	43	59	00.96713	W	124	06	27.69084	-6.042
NEAH	N	48	17	52.26367	W	124	37	29.60004	460.245
P059	N	38	55	42.03419	W	123	43	34.25628	-10.822
P067	N	35	33	06.29824	W	121	00	10.60668	107.594
P157	N	40	14	51.15527	W	124	18	29.00880	696.236
P172	N	36	13	41.05535	W	121	46	02.02944	313.190
P173	N	35	56	44.56712	W	121	17	25.15020	339.828
P181	N	37	54	52.34987	W	122	22	36.26760	72.732
P185	N	39	15	40.67993	W	123	44	57.55488	146.834
P188	N	38	40	04.27069	W	123	13	46.37496	209.358
P210	N	36	48	58.08233	W	121	43	54.58008	3.600
P231	N	36	37	18.02341	W	121	54	19.42416	-25.764
P316	N	41	33	32.86577	W	124	05	10.06188	235.389
P415	N	46	39	21.55259	W	123	43	47.45496	-15.081
P472	N	32	53	21.13976	W	117	06	16.85412	138.603
P474	N	33	21	18.68098	W	117	14	55.24188	183.653
P475	N	32	39	59.01142	W	117	14	38.11776	-24.285
P523	N	35	18	16.00618	W	120	51	36.93060	41.984
P534	N	37	03	40.41997	W	122	14	15.34524	204.804
PABH	N	47	12	46.06456	W	124	12	16.43148	13.277
PTSG	N	41	46	57.85558	W	124	15	18.66132	-9.794

Point	Latitude				Longitude				Ellipsoid Height
	°	'	"		°	'	"		
SBCC	N	33	33	10.78852	W	117	39	41.30280	89.406
TJRN	N	34	29	00.49571	W	120	07	57.17748	157.816
TRND	N	41	03	13.97729	W	124	09	03.06396	78.680
VNDP	N	34	33	22.71092	W	120	36	59.17428	-9.147
<i>SOPAC SECTOR Published Coordinates</i>									
CIRX	N	34	06	34.38086	W	118	56	14.21628	488.885
P161	N	40	38	14.49384	W	124	12	47.05236	32.868
P177	N	37	31	41.39000	W	122	29	42.13464	72.321
P182	N	38	29	42.04021	W	123	10	52.43052	397.293
P193	N	38	07	22.55902	W	122	54	29.25540	67.104
P312	N	39	31	45.03011	W	123	41	54.09492	255.394
P315	N	39	51	48.88562	W	123	43	00.77268	258.381
P364	N	43	05	25.16694	W	124	24	33.38532	6.807
P365	N	43	23	43.85245	W	124	15	12.47796	27.467
P366	N	43	36	51.50484	W	123	58	46.47828	529.468
P367	N	44	35	06.87286	W	124	03	41.59584	23.277
P395	N	45	01	20.19122	W	123	51	27.03708	53.385
P396	N	45	18	34.23391	W	123	49	22.36332	54.908
P397	N	46	25	17.81465	W	123	47	56.91588	566.625
P398	N	46	55	32.81066	W	123	54	58.05864	23.811
P401	N	47	56	13.86182	W	124	33	25.20540	36.486
P402	N	47	45	58.38217	W	124	18	21.16656	24.010
P403	N	48	03	44.34448	W	124	08	27.08628	284.951
P407	N	45	57	16.72355	W	123	55	51.55968	-12.778
P435	N	48	03	34.36160	W	123	30	11.73996	287.623
P436	N	48	02	43.07377	W	123	08	03.59016	191.191
P437	N	48	00	06.49840	W	122	27	32.90436	12.789
P525	N	35	25	32.74939	W	120	48	29.25720	271.978

Point	Latitude			Longitude			Ellipsoid Height		
	°	'	"	°	'	"			
P548	N	34	28	00.48986	W	119	30	14.14980	1135.502
P733	N	42	26	31.24331	W	124	24	47.81268	184.951
P734	N	42	04	35.87203	W	124	17	35.66652	113.718
PVRS	N	33	46	25.89424	W	118	19	14.07036	60.538
VIMT	N	34	07	35.19970	W	118	30	51.84000	554.389
VNCO	N	34	16	32.74244	W	119	14	15.56124	26.345

**Notes:** Ellipsoid heights are to the Antenna Reference Point (ARP) for the respective PBO/CORS antenna.

### **2.7 Station Reoccupation Comparison**

The allowable tolerance of  $\pm 5$ cm within the 95% confidence level was specified for the survey accuracy. Forty-six of the control points were occupied a second time at least 4 hours, and in most cases several hours or days, after the initial occupation.

The computed coordinate values and elevations of the re-occupations were compared with those of the initial occupations to evaluate the accuracy of the survey effort. The RMS of the difference in coordinates is 0.007, 0.006 and 0.020 meters for each of northing, easting, and elevation, respectively. The reoccupation results are tabulated below:

**Dewberry**  
 El Nino Lidar Campaign Control  
**RE-OCCUPATION COMPARISON**

<b>Point Name</b>	<b>Re-occupation Name</b>	<b>dNorthing (Meter)</b>	<b>dEasting (Meter)</b>	<b>dElev (Meter)</b>
CP01	CP01_R	0.003	0.009	-0.016
CP03	CP03_R	-0.008	0.000	-0.028
CP05	CP05_R	-0.007	0.001	-0.021
CP06	CP06_R	0.000	0.000	-0.019
CP09	CP09_R	-0.002	0.000	-0.015
CP11	CP11_R	-0.010	0.001	0.019
CP13	CP13_R	0.007	-0.009	0.011
CP15	CP15_R	0.003	0.000	0.001
CP18	CP18_R	0.004	0.000	-0.008
CP20	CP20_R	0.010	0.009	-0.005
CP22	CP22_R	-0.002	0.009	-0.003
CP24	CP24_R	0.008	-0.018	0.019
CP26	CP26_R	0.002	-0.001	-0.011
CP28	CP28_R	-0.003	0.000	0.004
CP30	CP30_R	-0.007	0.009	-0.018
CP32	CP32_R	0.001	0.009	-0.002
CP34	CP34_R	0.013	0.000	-0.015
CP35	CP35_R	0.005	-0.009	0.004
CP38	CP38_R	-0.005	0.000	-0.011
CP40	CP40_R	0.010	0.000	0.023
CP42	CP42_R	-0.009	-0.008	0.000
CP44	CP44_R	0.007	0.009	0.024
CP45	CP45_R	0.004	-0.009	0.024

Point Name	Re-occupation Name	dNorthing (Meter)	dEasting (Meter)	dElev (Meter)
CP48	CP48_R	-0.005	0.009	0.024
CP50	CP50_R	0.001	0.000	0.001
CP51	CP51_R	0.001	0.000	-0.001
CP55	CP55_R	0.003	0.000	0.007
CP57	CP57_R	-0.003	0.000	0.006
CP59	CP59_R	0.002	-0.008	0.007
CP61	CP61_R	0.001	0.000	0.003
CP63	CP63_R	-0.004	0.000	0.044
CP65	CP65_R	0.001	0.000	0.013
CP67	CP67_R	0.002	-0.007	0.005
CP69	CP69_R	-0.002	0.000	0.008
CP71	CP71_R	-0.005	0.000	-0.015
CP73	CP73_R	0.003	-0.007	-0.006
CP75	CP75_R	-0.006	0.000	-0.008
CP77	CP77_R	0.001	-0.007	0.011
CP79	CP79_R	0.005	-0.007	-0.041
CP81	CP81_R	0.014	0.001	-0.037
CP83	CP83_R	0.003	0.000	0.018
CP85	CP85_R	0.013	0.000	-0.038
CP87	CP87_R	0.010	0.000	0.017
CP89	CP89_R	-0.020	-0.007	0.035
CP90	CP90_R	0.021	0.000	0.044

## Appendix B: Complete List of Delivered Tiles

10SGD73203813	10SEG54754146	10TCL39754518	10TDR42455013	10UDU41405343
10SGD73353813	10SEG54904146	10TCL39904518	10TDR42305014	10UDU37205344
10SGD73053814	10SEG54754147	10TCL39904519	10TDR42455014	10UDU37355344
10SGD73203814	10SEG54904147	10TDL40054519	10TDR42305016	10UDU37505344
10SGD73353814	10SEG54304149	10TCL39904521	10TDR42455016	10UDU40205344
10SGD73503814	10SEG54454149	10TDL40054521	10TDR42305017	10UDU40355344
10SGD73653814	10SEG54604149	10TDL40054522	10TDR42455017	10UDU40505344
10SGD73803814	10SEG54754149	10TDL40204522	10TDR42305019	10UDU40655344
10SGD73953814	10SEG54154150	10TDL40054524	10TDR42455019	10UDU40805344
10SGD74103814	10SEG54304150	10TDL40204524	10TDR42005020	10UDU40955344
10SGD74253814	10SEG54454150	10TDL40054525	10TDR42155020	10UDU41105344
10SGD73053816	10SEG54604150	10TDL40204525	10TDR42305020	10UDU37355346
10SGD73203816	10SEG54754150	10TDL40204527	10TDR42155022	10UDU37505346
10SGD73653816	10SEG54154152	10TDL40354527	10TDR42305022	10UDU39905346
10SGD73803816	10SEG54304152	10TDL40204528	10TDR42305023	10UDU40055346
10SGD73953816	10SEG54154153	10TDL40354528	10TDR42455023	10UDU40205346
10SGD74103816	10SEG54304153	10TDL40354530	10TDR42305025	10UDU40355346
10SGD74253816	10SEG54154155	10TDL40354531	10TDR42455025	10UDU40655346
10SGD74403816	10SEG54304155	10TDL40504531	10TDR42305026	10UDU40805346
10SGD74553816	10SEG54154156	10TDL40354533	10TDR42455026	10UDU37355347
10SGD74703816	10SEG54304156	10TDL40504533	10TDR42305028	10UDU37505347
10SGD74853816	10SEG54154158	10TDL40354534	10TDR42455028	10UDU39605347
10SGD75003816	10SEG54304158	10TDL40504534	10TDR42305029	10UDU39755347
10SGD75153816	10SEG54154159	10TDL40504536	10TDR42455029	10UDU39905347
10SGD75303816	10SEG54304159	10TDL40504537	10TDR42305031	10UDU40055347
10SGD76503816	10SEG54154161	10TDL40654537	10TDR42455031	10UDU40205347
10SGD76653816	10SEG54304161	10TDL40504539	10TDR42305032	10UDU37355349
10SGD76803816	10SEG54454161	10TDL40654539	10TDR42455032	10UDU37505349
10SGD76953816	10SEG54304162	10TDL40504540	10TDR42305034	10UDU37655349
10SGD77103816	10SEG54454162	10TDL40654540	10TDR42455034	10UDU39455349
10SGD77253816	10SEG54304164	10TDL40504542	10TDR42305035	10UDU39605349
10SGD77403816	10SEG54454164	10TDL40654542	10TDR42455035	10UDU39755349
10SGD73053817	10SEG54304165	10TDL40204543	10TDR42305037	10UDU39905349
10SGD73203817	10SEG54454165	10TDL40354543	10TDR42455037	10UDU37355350
10SGD74553817	10SEG54304167	10TDL40504543	10TDR42305038	10UDU37505350
10SGD74703817	10SEG54454167	10TDL40204545	10TDR42455038	10UDU37655350
10SGD74853817	10SEG54304168	10TDL40354545	10TDR42455040	10UDU39155350
10SGD75003817	10SEG54454168	10TDL40504545	10TDR42455041	10UDU39305350
0SGD75153817	10SEG54304170	10TDL40204546	10TDR42455043	10UDU39455350
10SGD75303817	10SEG54454170	10TDL40354546	10TDR42605043	10UDU37505352
10SGD75453817	10SEG54304171	10TDL40204548	10TDR42455044	10UDU37655352

10SGD75603817	10SEG54454171	10TDL40204549	10TDR42605044	10UDU39005352
10SGD75753817	10SEG54304173	10TDL40204551	10TDR42455046	10UDU39155352
10SGD75903817	10SEG54454173	10TDL40204552	10TDR42605046	10UDU39305352
10SGD76053817	10SEG54304174	10TDL40204554	10TDR42455047	10UDU37505353
10SGD76203817	10SEG54304176	10TDL40354554	10TDR42605047	10UDU37655353
10SGD76353817	10SEG54154177	10TDL40354555	10TDR42455049	10UDU38705353
10SGD76503817	10SEG54304177	10TDL40354557	10TDR42605049	10UDU38855353
10SGD76653817	10SEG54154179	10TDL40504557	10TDR42455050	10UDU39005353
10SGD76803817	10SEG54304179	10TDL40504558	10TDR42605050	10UDU37355355
10SGD76953817	10SEG54154180	10TDL40504560	10TDR42455052	10UDU37505355
10SGD77103817	10SEG54304180	10TDL40504561	10TDR42605052	10UDU37655355
10SGD77253817	10SEG54454180	10TDL40654561	10TDR42605053	10UDU38405355
10SGD77403817	10SEG54154182	10TDL40654563	10TDR42605055	10UDU38555355
10SGD72903819	10SEG54304182	10TDL40654564	10TDR42605056	10UDU38705355
10SGD73053819	10SEG54454182	10TDL40654566	10TDR42605058	10UDU38855355
10SGD72753820	10SEG54604182	10TDL40804566	10TDR42605059	10UDU37205356
10SGD72903820	10SEG54454183	10TDL40654567	10TDR42605061	10UDU37355356
10SGD72603822	10SEG54604183	10TDL40804567	10TDR42605062	10UDU37955356
10SGD72753822	10SEG54004185	10TDL40654569	10TDR42455064	10UDU38105356
10SGD72903822	10SEG54154185	10TDL40804569	10TDR42605064	10UDU38255356
10SGD72303823	10SEG54304185	10TDL40804570	10TDR42455065	10UDU38405356
10SGD72453823	10SEG54454185	10TDL40804572	10TDR42605065	10UDU38555356
10SGD72603823	10SEG54604185	10TDL40804573	10TDR42305067	10UDU37055358
10SGD72753823	10SEG53854186	10TDL40954573	10TDR42455067	10UDU37205358
10SGD71703825	10SEG54004186	10TDL40804575	10TDR42305068	10UDU37355358
10SGD71853825	10SEG54154186	10TDL40954575	10TDR42455068	10UDU37805358
10SGD72003825	10SEG54304186	10TDL40804576	10TDR42305070	10UDU37955358
10SGD72153825	10SEG54454186	10TDL40954576	10TDR42455070	10UDU38105358
10SGD72303825	10SEG54604186	10TDL40954578	10TDR42305071	10UDU38255358
10SGD72453825	10SEG53704188	10TDL40954579	10TDR42455071	10UDU38405358
10SGD71553826	10SEG53854188	10TDL40954581	10TDR42455073	10UDU37055359
10SGD71703826	10SEG54004188	10TDL41104581	10TDR42455074	10UDU37205359
10SGD71853826	10SEG53554189	10TDL40954582	10TDR42455076	10UDU37355359
10SGD72003826	10SEG53704189	10TDL41104582	10TDR42455077	10UDU37505359
10SGD72153826	10SEG53854189	10TDL40954584	10TDR42455079	10UDU37655359
10SGD71403828	10SEG53254191	10TDL41104584	10TDR42455080	10UDU37805359
10SGD71553828	10SEG53404191	10TDL40954585	10TDR42455082	10UDU37955359
10SGD71553829	10SEG53554191	10TDL41104585	10TDR42305083	10UDU38105359
10SGD71553831	10SEG52504192	10TDL40954587	10TDR42455083	10UDU37205361
10SGD71703831	10SEG53104192	10TDL41104587	10TDR42305085	10UDU37355361
10SGD71553832	10SEG53254192	10TDL40954588	10TDR42455085	10UDU37505361
10SGD71703832	10SEG53404192	10TDL41104588	10TDR42155086	10UDU37655361

10SGD71553834	10SEG52354194	10TDL40954590	10TDR42305086	10UDU37805361
10SGD71703834	10SEG52504194	10TDL41104590	10TDR42455086	11SKU77553816
10SGD71703835	10SEG52654194	10TDL40954591	10TDR42155088	10SFE694539160
10SGD71853835	10SEG52804194	10TDL41104591	10TDR42305088	10SDH46354281
10SGD71703837	10SEG52954194	10TDL40954593	10TDR42455088	10TDQ421549952
10SGD71853837	10SEG53104194	10TDL40954594	10TDR42305089	11SMR48753598
10SGD71703838	10SEG52204195	10TDL40804596	10TDR42455089	11SMS48753600
10SGD71853838	10SEG52354195	10TDL40954596	10TDR42455091	11SMS48603601
10SGD71853840	10SEG52654195	10TDL40804597	10TDR42605091	11SMS48753601
10SGD71853841	10SEG52804195	10TDL40954597	10TDR42755091	11SMS48603603
10SGD72003841	10SEG52954195	10TDL40804599	10TDR42605092	11SMS48753603
10SGD71853843	10SEG52054197	10TDL40954599	10TDR42755092	11SMS48603604
10SGD72003843	10SEG52204197	10TDM40804600	10TDR42605094	11SMS48753604
10SGD71703844	10SEG52354197	10TDM40954600	10TDR42755094	11SMS48603606
10SGD71853844	10SEG51754198	10TDM40654602	10TDR42755095	11SMS48753606
10SGD71553846	10SEG51904198	10TDM40804602	10TDR42755097	11SMS48603607
10SGD71703846	10SEG52054198	10TDM40654603	10TDR42755098	11SMS48753607
10SGD71853846	10SEG52204198	10TDM40804603	10TDS42605100	11SMS48603609
10SGD71553847	10SEH51754200	10TDM40654605	10TDS42755100	11SMS48753609
10SGD71703847	10SEH51904200	10TDM40804605	10TDS42605101	11SMS48453610
10SGD71553849	10SEH51754201	10TDM40654606	10TDS42755101	11SMS48603610
10SGD71703849	10SEH51904201	10TDM40804606	10TDS42605103	11SMS48453612
10SGD71553850	10SEH51604203	10TDM40654608	10TDS42755103	11SMS48603612
10SGD71703850	10SEH51754203	10TDM40504609	10TDS42605104	11SMS47553613
10SGD71703852	10SDH49654204	10TDM40654609	10TDS42755104	11SMS47703613
10SGD71703853	10SDH49804204	10TDM40504611	10TDS42605106	11SMS48303613
10SGD71703855	10SDH49954204	10TDM40654611	10TDS42455107	11SMS48453613
10SGD71853855	10SEH50104204	10TDM40354612	10TDS42605107	11SMS47553615
10SGD71703856	10SEH50254204	10TDM40504612	10TDS42455109	11SMS47703615
10SGD71853856	10SEH51454204	10TDM40354614	10TDS42605109	11SMS47853615
10SGD71703858	10SEH51604204	10TDM40504614	10TDS42455110	11SMS48003615
10SGD71853858	10SDH49804206	10TDM40354615	10TDS42605110	11SMS48153615
10SGD71703859	10SDH49954206	10TDM40504615	10TDS42305112	11SMS48303615
10SGD71853859	10SEH50104206	10TDM40354617	10TDS42455112	11SMS48453615
10SGD71553861	10SEH51154206	10TDM40504617	10TDS42305113	11SMS47553616
10SGD71703861	10SEH51304206	10TDM40354618	10TDS42455113	11SMS47703616
10SGD71403862	10SEH51454206	10TDM40504618	10TDS42305115	11SMS47853616
10SGD71553862	10SDH49804207	10TCM39904620	10TDS42155116	11SMS48003616
10SGD71253864	10SDH49954207	10TDM40054620	10TDS42305116	11SMS48153616
10SGD71403864	10SEH50104207	10TDM40204620	10TDS42155118	11SMS47553618
10SGD71553864	10SEH50254207	10TDM40354620	10TDS42305118	11SMS47553619
10SGD71253865	10SEH50404207	10TCM39754621	10TDS41855119	11SMS47553621



10SGD71253867	10SEH50554207	10TCM39904621	10TDS42005119	11SMS47553622
10SGD71403867	10SEH50704207	10TDM40054621	10TDS42155119	11SMS47403624
10SGD71253868	10SEH50854207	10TDM40204621	10TDS41855121	11SMS47553624
10SGD71403868	10SEH51004207	10TDM40354621	10TDS42005121	11SMS47553625
10SGD71253870	10SEH51154207	10TCM39604623	10TDS41705122	11SMS47553627
10SGD71403870	10SEH51304207	10TCM39754623	10TDS41855122	11SMS47403628
10SGD71403871	10SDH49954209	10TCM39904623	10TDS41555124	11SMS47553628
10SGD71403873	10SEH50104209	10TDM40054623	10TDS41705124	11SMS47253630
10SGD71403874	10SEH50254209	10TCM39454624	10TDS41555125	11SMS47403630
10SGD71553874	10SEH50404209	10TCM39604624	10TDS41705125	11SMS47553630
10SGD71403876	10SEH50554209	10TCM39754624	10TDS41555127	11SMS47253631
10SGD71553876	10SEH50704209	10TCM39454626	10TDS41705127	11SMS47403631
10SGD71403877	10SEH50854209	10TCM39604626	10TDS41705128	11SMS47253633
10SGD71553877	10SEH51004209	10TCM39604627	10TDS41705130	11SMS47403633
10SGD71553879	10SDH49954210	10TCM39754627	10TDS41705131	11SMS47553633
10SGD71553880	10SEH50104210	10TCM39604629	10TDS41855131	11SMS47253634
10SGD71553882	10SEH50104212	10TCM39754629	10TDS41705133	11SMS47403634
10SGD71553883	10SEH50104213	10TCM39754630	10TDS41855133	11SMS47553634
10SGD71553885	10SEH50254213	10TCM39754632	10TDS41705134	11SMS47553636
10SGD71553886	10SEH50104215	10TCM39904632	10TDS41855134	11SMS47553637
10SGD71403888	10SEH50254215	10TCM39754633	10TDS41705136	11SMS47553639
10SGD71553888	10SEH50254216	10TCM39904633	10TDS41855136	11SMS47553640
10SGD71403889	10SEH50254218	10TCM39754635	10TDS41705137	11SMS47553642
10SGD71553889	10SEH50404218	10TCM39904635	10TDS41855137	11SMS47403643
10SGD71103891	10SEH50254219	10TCM39904636	10TDS41705139	11SMS47553643
10SGD71253891	10SEH50404219	10TCM39904638	10TDS41855139	11SMS47403645
10SGD71403891	10SEH50254221	10TCM39904639	10TDS41705140	11SMS47553645
10SGD70203892	10SEH50404221	10TDM40054639	10TDS41855140	11SMS47403646
10SGD70353892	10SEH50404222	10TCM39904641	10TDS41705142	11SMS47403648
10SGD70503892	10SEH50254224	10TDM40054641	10TDS41855142	11SMS47403649
10SGD70953892	10SEH50404224	10TCM39904642	10TDS41705143	11SMS47253651
10SGD71103892	10SEH50254225	10TDM40054642	10TDS41855143	11SMS47403651
10SGD71253892	10SEH50404225	10TCM39904644	10TDS41705145	11SMS47253652
10SFD69903894	10SEH50104227	10TDM40054644	10TDS41855145	11SMS47403652
10SGD70053894	10SEH50254227	10TCM39904645	10TDS41705146	11SMS47103654
10SGD70203894	10SEH50104228	10TCM39904647	10TDS41855146	11SMS47253654
10SGD70353894	10SEH50254228	10TCM39904648	10TDS41705148	11SMS47103655
10SGD70503894	10SDH49954230	10TCM39754650	10TDS41855148	11SMS47253655
10SGD70653894	10SEH50104230	10TCM39904650	10TDS41705149	11SMS47103657
10SGD70803894	10SEH50254230	10TCM39604651	10TDS41855149	11SMS46953658
10SGD70953894	10SDH49954231	10TCM39754651	10TDS41705151	11SMS47103658
10SFD69603895	10SEH50104231	10TCM39904651	10TDS41855151	11SMS46953660

10SFD69753895	10SEH50254231	10TCM39454653	10TDS41705152	11SMS47103660
10SFD69903895	10SEH50104233	10TCM39604653	10TDS41855152	11SMS46953661
10SGD70053895	10SEH50254233	10TCM39754653	10TDS41705154	11SMS46803663
10SGD70353895	10SEH50104234	10TCM39154654	10TDS41855154	11SMS46953663
10SGD70503895	10SEH50254234	10TCM39304654	10TDS41705155	11SMS46803664
10SGD70653895	10SDH49954236	10TCM39454654	10TDS41855155	11SMS46953664
10SFD69453897	10SEH50104236	10TCM39604654	10TDS41705157	11SMS46653666
10SFD69603897	10SDH49354237	10TCM39154656	10TDS41855157	11SMS46803666
10SFD69753897	10SDH49504237	10TCM39304656	10TDS41705158	11SMS46653667
10SFD69303898	10SDH49804237	10TCM39454656	10TDS41855158	11SMS46803667
10SFD69453898	10SDH49954237	10TCM39004657	10TDS41705160	11SMS46503669
10SFE69153900	10SDH49354239	10TCM39154657	10TDS41855160	11SMS46653669
10SFE69303900	10SDH49504239	10TCM38854659	10TDS41705161	11SMS46353670
10SFE69003901	10SDH49654239	10TCM39004659	10TDS41855161	11SMS46503670
10SFE69153901	10SDH49804239	10TCM38704660	10TDS41705163	11SMS46353672
10SFE69003903	10SDH49954239	10TCM38854660	10TDS41855163	11SMS46503672
10SFE69153903	10SDH49204240	10TCM39004660	10TDS41705164	11SMS46203673
10SFE69003904	10SDH49354240	10TCM38704662	10TDS41855164	11SMS46353673
10SFE69153904	10SDH49504240	10TCM38854662	10TDS41705166	11SMS46053675
10SFE69153906	10SDH49654240	10TCM38704663	10TDS41855166	11SMS46203675
10SFE69303906	10SDH49804240	10TCM38854663	10TDS41705167	11SMS45903676
10SFE69153907	10SDH49354242	10TCM38704665	10TDS41855167	11SMS46053676
10SFE69303907	10SDH49354243	10TCM38854665	10TDS41705169	11SMS46203676
10SFE69303909	10SDH49354245	10TCM38704666	10TDS41705170	11SMS45903678
10SFE69303910	10SDH49204246	10TCM38554668	10TDS41705172	11SMS46053678
10SFE69303912	10SDH49354246	10TCM38704668	10TDS41555173	11SMS45753679
10SFE69453912	10SDH49054248	10TCM38704669	10TDS41705173	11SMS45903679
10SFE69303913	10SDH49204248	10TCM38554671	10TDS41555175	11SMS45603681
10SFE69453913	10SDH49054249	10TCM38704671	10TDS41705175	11SMS45753681
10SFE69303915	10SDH49204249	10TCM38554672	10TDS41555176	11SMS45603682
10SFE69453915	10SDH48904251	10TCM38554674	10TDS41705176	11SMS45753682
10SFE69303916	10SDH49054251	10TCM38404675	10TDS41405178	11SMS45453684
10SFE69303918	10SDH48904252	10TCM38554675	10TDS41555178	11SMS45603684
10SFE69153919	10SDH49054252	10TCM38254677	10TDS41405179	11SMS45303685
10SFE69303919	10SDH48754254	10TCM38404677	10TDS41555179	11SMS45453685
10SFE69153921	10SDH48904254	10TCM38254678	10TDS41405181	11SMS45153687
10SFE69303921	10SDH48604255	10TCM38404678	10TDS41555181	11SMS45303687
10SFE69003922	10SDH48754255	10TCM38254680	10TDS41555182	11SMS45453687
10SFE69153922	10SDH48904255	10TCM38404680	10TDS41405184	11SMS45003688
10SFE68403924	10SDH48454257	10TCM38254681	10TDS41555184	11SMS45153688
10SFE68553924	10SDH48604257	10TCM38404681	10TDS41405185	11SMS45303688
10SFE68703924	10SDH48754257	10TCM38254683	10TDS41555185	11SMS44853690

10SFE68853924	10SDH48304258	10TCM38404683	10TDS41405187	11SMS45003690
10SFE69003924	10SDH48454258	10TCM38254684	10TDS41555187	11SMS45153690
10SFE69153924	10SDH48604258	10TCM38404684	10TDS41405188	11SMS44553691
10SFE67953925	10SDH47854260	10TCM38104686	10TDS41555188	11SMS44703691
10SFE68103925	10SDH48004260	10TCM38254686	10TDS41405190	11SMS44853691
10SFE68253925	10SDH48154260	10TCM38104687	10TDS41255191	11SMS45003691
10SFE68403925	10SDH48304260	10TCM38254687	10TDS41405191	11SMS444403693
10SFE68553925	10SDH47704261	10TCM38104689	10TDS41255193	11SMS44553693
10SFE67803927	10SDH47854261	10TCM38254689	10TDS41405193	11SMS44703693
10SFE67953927	10SDH48004261	10TCM38104690	10TDS41105194	11SMS44253694
10SFE67653928	10SDH48154261	10TCM38254690	10TDS41255194	11SMS444403694
10SFE67803928	10SDH47554263	10TCM38104692	10TDS41405194	11SMS44253696
10SFE67953928	10SDH47704263	10TCM38254692	10TDS40955196	11SMS444403696
10SFE67503930	10SDH47854263	10TCM38254693	10TDS41105196	11SMS44103697
10SFE67653930	10SDH47404264	10TCM38104695	10TDS41255196	11SMS44253697
10SFE67353931	10SDH47554264	10TCM38254695	10TDS40955197	11SMS43953699
10SFE67503931	10SDH47704264	10TCM38104696	10TDS41105197	11SMS44103699
10SFE67203933	10SDH47254266	10TCM38254696	10TDS40955199	11SMT43353700
10SFE67353933	10SDH47404266	10TCM38104698	10TDT40955200	11SMT43503700
10SFE67053934	10SDH46954267	10TCM38254698	10TDT41105200	11SMT43653700
10SFE67203934	10SDH47104267	10TCM38104699	10TDT40955202	11SMT43803700
10SFE67353934	10SDH47254267	10TCM38254699	10TDT41105202	11SMT43953700
10SFE67053936	10SDH46954269	10TCN38104701	10TDT40955203	11SMT43203702
10SFE67203936	10SDH47104269	10TCN38254701	10TDT41105203	11SMT43353702
10SFE66903937	10SDH46804270	10TCN38254702	10TDT40955205	11SMT43503702
10SFE67053937	10SDH46954270	10TCN38254704	10TDT41105205	11SMT43653702
10SFE66903939	10SDH47104270	10TCN38254705	10TDT40955206	11SMT43803702
10SFE67053939	10SDH46654272	10TCN38404705	10TDT41105206	11SMT43203703
10SFE66753940	10SDH46804272	10TCN38254707	10TDT40955208	11SMT43353703
10SFE66903940	10SDH46954272	10TCN38404707	10TDT41105208	11SMT43053705
10SFE66603942	10SDH46654273	10TCN38404708	10TDT40955209	11SMT43203705
10SFE66753942	10SDH46804273	10TCN38404710	10TDT41105209	11SMT42903706
10SFE66303943	10SDH46504275	10TCN38554710	10TDT40955211	11SMT43053706
10SFE66453943	10SDH46654275	10TCN38404711	10TDT41105211	11SMT42753708
10SFE66603943	10SDH46354276	10TCN38554711	10TDT40955212	11SMT42903708
10SFE66753943	10SDH46504276	10TCN38554713	10TDT41105212	11SMT43053708
10SFE66003945	10SDH46354278	10TCN38404714	10TDT40955214	11SMT42603709
10SFE66153945	10SDH46504278	10TCN38554714	10TDT41105214	11SMT42753709
10SFE66303945	10SDH46204279	10TCN38404716	10TDT40955215	11SMT42903709
10SFE66453945	10SDH46354279	10TCN38554716	10TDT41105215	11SMT42453711
10SFE66603945	10SDH46054281	10TCN38404717	10TDT40955217	11SMT42603711
10SFE65403946	10SDH46204281	10TCN38554717	10TDT40955218	11SMT42753711

10SFE65553946	10SDH46054282	10TCN38404719	10TDT40955220	11SMT42303712
10SFE65703946	10SDH46204282	10TCN38554719	10TDT40805221	11SMT42453712
10SFE65853946	10SDH45904284	10TCN38404720	10TDT40955221	11SMT42003714
10SFE66003946	10SDH46054284	10TCN38404722	10TDT40805223	11SMT42153714
10SFE66153946	10SDH45604285	10TCN38254723	10TDT40955223	11SMT42303714
10SFE65403948	10SDH45754285	10TCN38404723	10TDT40805224	11SMT41703715
10SFE65553948	10SDH45904285	10TCN37954725	10TDT40955224	11SMT41853715
10SFE65703948	10SDH45454287	10TCN38104725	10TDT40805226	11SMT42003715
10SFE65403949	10SDH45604287	10TCN38254725	10TDT40955226	11SMT42153715
10SFE65553949	10SDH45754287	10TCN37954726	10TDT40805227	11SMT41403717
10SFE65253951	10SDH45304288	10TCN38104726	10TDT40655229	11SMT41553717
10SFE65403951	10SDH45454288	10TCN37954728	10TDT40805229	11SMT41703717
10SFE65103952	10SDH45304290	10TCN38104728	10TDT40655230	11SMT41853717
10SFE65253952	10SDH45454290	10TCN37954729	10TDT40805230	11SMT41253718
10SFE65103954	10SDH45004291	10TCN37504731	10TDT40655232	11SMT41403718
10SFE65253954	10SDH45154291	10TCN37654731	10TDT40805232	11SMT41553718
10SFE65103955	10SDH45304291	10TCN37804731	10TDT40655233	11SMT40953720
10SFE65253955	10SDH44854293	10TCN37954731	10TDT40805233	11SMT41103720
10SFE65103957	10SDH45004293	10TCN37504732	10TDT40505235	11SMT41253720
10SFE65253957	10SDH45154293	10TCN37654732	10TDT40655235	11SMT40803721
10SFE65103958	10SDH44704294	10TCN37804732	10TDT40505236	11SMT40953721
10SFE65253958	10SDH44854294	10TCN37504734	10TDT40655236	11SMT41103721
10SFE64953960	10SDH45004294	10TCN37654734	10TDT40205238	11SMT40653723
10SFE65103960	10SDH44554296	10TCN37504735	10TDT40355238	11SMT40803723
10SFE64803961	10SDH44704296	10TCN37504737	10TDT40505238	11SMT40953723
10SFE64953961	10SDH44404297	10TCN37354738	10TDT40655238	11SMT40503724
10SFE65103961	10SDH44554297	10TCN37504738	10TDT40205239	11SMT40653724
10SFE64653963	10SDH44704297	10TCN37354740	10TDT40355239	11SMT40353726
10SFE64803963	10SDH44254299	10TCN37504740	10TDT40505239	11SMT40503726
10SFE64503964	10SDH44404299	10TCN37204741	10TDT40205241	11SMT40203727
10SFE64653964	10SDH44554299	10TCN37354741	10TDT40355241	11SMT40353727
10SFE64353966	10SDJ44254300	10TCN37054743	10TDT40205242	11SLT37953729
10SFE64503966	10SDJ44404300	10TCN37204743	10TDU39905244	11SLT38103729
10SFE64203967	10SDJ44104302	10TCN37354743	10TDT40055244	11SMT40053729
10SFE64353967	10SDJ44254302	10TCN37054744	10TDT40205244	11SMT40203729
10SFE64053969	10SDJ43954303	10TCN37204744	10TDU39905245	11SLT37503730
10SFE64203969	10SDJ44104303	10TCN37354744	10TDT40055245	11SLT37653730
10SFE64353969	10SDJ44254303	10TCN37354746	10TDU39905247	11SLT37803730
10SFE63903970	10SDJ43804305	10TCN37504746	10TDU39905248	11SLT37953730
10SFE64053970	10SDJ43954305	10TCN37354747	10TDU39905250	11SLT38103730
10SFE63753972	10SDJ43654306	10TCN37504747	10TDU39755251	11SLT38253730
10SFE63903972	10SDJ43804306	10TCN37504749	10TDU39905251	11SLT38403730

10SFE63753973	10SDJ43654308	10TCN37654749	10TDU39755253	11SLT39903730
10SFE63903973	10SDJ43804308	10TCN37504750	10TDU39905253	11SMT40053730
10SFE63753975	10SDJ43504309	10TCN37654750	10TDU39755254	11SLT37353732
10SFE63603976	10SDJ43654309	10TCN37654752	10TDU39905254	11SLT37503732
10SFE63753976	10SDJ43504311	10TCN37804752	10TDU39755256	11SLT37653732
10SFE63603978	10SDJ43654311	10TCN37654753	10TDU39905256	11SLT38103732
10SFE63753978	10SDJ43654312	10TCN37804753	10TDU39755257	11SLT38253732
10SFE63603979	10SDJ43804312	10TCN37804755	10TDU39905257	11SLT38403732
10SFE63753979	10SDJ43654314	10TCN37954755	10TDU39755259	11SLT38553732
10SFE63603981	10SDJ43804314	10TCN37804756	10TDU39905259	11SLT38853732
10SFE63453982	10SDJ43804315	10TCN37954756	10TDU39755260	11SLT39003732
10SFE63603982	10SDJ43954315	10TCN37954758	10TDU39905260	11SLT39603732
10SFE63303984	10SDJ43804317	10TCN37954759	10TDU39755262	11SLT39753732
10SFE63453984	10SDJ43954317	10TCN38104759	10TDU39755263	11SLT39903732
10SFE62853985	10SDJ43954318	10TCN37954761	10TDU39755265	11SMT40053732
10SFE63003985	10SDJ43954320	10TCN38104761	10TDU39755266	11SLT36753733
10SFE63153985	10SDJ43954321	10TCN37954762	10TDU39605268	11SLT36903733
10SFE63303985	10SDJ43804323	10TCN38104762	10TDU39755268	11SLT37053733
10SFE63453985	10SDJ43954323	10TCN38104764	10TDU39605269	11SLT37203733
10SFE62703987	10SDJ43804324	10TCN38104765	10TDU39755269	11SLT37353733
10SFE62853987	10SDJ43954324	10TCN38254765	10TDU39605271	11SLT38403733
10SFE63003987	10SDJ43804326	10TCN38104767	10TDU39605272	11SLT38553733
10SFE63153987	10SDJ43654327	10TCN38254767	10TDU39605274	11SLT38703733
10SFE62703988	10SDJ43804327	10TCN38254768	10TDU39455275	11SLT38853733
10SFE62853988	10SDJ43654329	10TCN38254770	10TDU39605275	11SLT39003733
10SFE62553990	10SDJ43804329	10TCN38254771	10TDU39455277	11SLT39453733
10SFE62703990	10SDJ43654330	10TCN38254773	10TDU39605277	11SLT39603733
10SFE62403991	10SDJ43804330	10TCN38254774	10TDU39455278	11SLT39753733
10SFE62553991	10SDJ43504332	10TCN38404774	10TDU39305280	11SLT39903733
10SFE62703991	10SDJ43654332	10TCN38254776	10TDU39455280	11SLT36753735
10SFE62403993	10SDJ43804332	10TCN38404776	10TDU39305281	11SLT36903735
10SFE62553993	10SDJ43504333	10TCN38404777	10TDU39455281	11SLT38703735
10SFE62253994	10SDJ43654333	10TCN38404779	10TDU39305283	11SLT38853735
10SFE62403994	10SDJ43354335	10TCN38554779	10TDU39305284	11SLT39003735
10SFE62253996	10SDJ43504335	10TCN38404780	10TDU39305286	11SLT39153735
10SFE62403996	10SDJ43654335	10TCN38554780	10TDU39155287	11SLT39303735
10SFE62103997	10SDJ43354336	10TCN38554782	10TDU39305287	11SLT39453735
10SFE62253997	10SDJ43504336	10TCN38554783	10TDU39005289	11SLT39603735
10SFE61953999	10SDJ43204338	10TCN38554785	10TDU39155289	11SLT36753736
10SFE62103999	10SDJ43354338	10TCN38554786	10TDU39305289	11SLT36903736
10SFE62253999	10SDJ43204339	10TCN38704786	10TDU38855290	11SLT39003736
10SFF61804000	10SDJ43354339	10TCN38554788	10TDU39005290	11SLT39153736

10SFF61954000	10SDJ43204341	10TCN38704788	10TDU39155290	11SLT39303736
10SFF62104000	10SDJ43354341	10TCN38704789	10TDU38855292	11SLT36753738
10SFF61654002	10SDJ43204342	10TCN38704791	10TDU38855293	11SLT36903738
10SFF61804002	10SDJ43354342	10TCN38704792	10TDU38855295	11SLT36753739
10SFF61954002	10SDJ43054344	10TCN38554794	10TDU38555296	11SLT36903739
10SFF61504003	10SDJ43204344	10TCN38704794	10TDU38705296	11SLT37053739
10SFF61654003	10SDJ43054345	10TCN38554795	10TDU38855296	11SLT36903741
10SFF61804003	10SDJ43204345	10TCN38704795	10TDU38405298	11SLT37053741
10SFF61354005	10SDJ43054347	10TCN38554797	10TDU38555298	11SLT37053742
10SFF61504005	10SDJ43204347	10TCN38704797	10TDU38705298	11SLT37053744
10SFF61654005	10SDJ42904348	10TCN38854797	10TDU38255299	11SLT36903745
10SFF61054006	10SDJ43054348	10TCN38704798	10TDU38405299	11SLT37053745
10SFF61204006	10SDJ42904350	10TCN38854798	10TDU38105301	11SLT36903747
10SFF61354006	10SDJ43054350	10TCN39004798	10TDU38255301	11SLT37053747
10SFF61504006	10SDJ42904351	10TCP38704800	10TDU38405301	11SLT36903748
10SFF60904008	10SDJ43054351	10TCP38854800	10TDU37805302	11SLT36753750
10SFF61054008	10SDJ42904353	10TCP39004800	10TDU37955302	11SLT36903750
10SFF61204008	10SDJ43054353	10TCP39154800	10TDU38105302	11SLT36753751
10SFF61354008	10SDJ42754354	10TCP39004801	10TDU38255302	11SLT36903751
10SFF60604009	10SDJ42904354	10TCP39154801	10TDU37655304	11SLT36603753
10SFF60754009	10SDJ42754356	10TCP39154803	10TDU37805304	11SLT36753753
10SFF60904009	10SDJ42904356	10TCP39304803	10TDU37955304	11SLT36603754
10SFF61054009	10SDJ42754357	10TCP39304804	10TDU38105304	11SLT36753754
10SFF60304011	10SDJ42904357	10TCP39304806	10TDU37655305	11SLT36603756
10SFF60454011	10SDJ42904359	10TCP39454806	10TDU37805305	11SLT36453757
10SFF60604011	10SDJ42904360	10TCP39454807	10TDU37655307	11SLT36603757
10SFF60754011	10SDJ42904362	10TCP39454809	10TDU37805307	11SLT36303759
10SFF60304012	10SDJ42904363	10TCP39604809	10TDU37655308	11SLT36453759
10SFF60454012	10SDJ43054363	10TCP39454810	10TDU37505310	11SLT36303760
10SFF60154014	10SDJ42904365	10TCP39604810	10TDU37655310	11SLT36453760
10SFF60304014	10SDJ43054365	10TCP39604812	10TDU37505311	11SLT36153762
10SFF60004015	10SDJ42904366	10TCP39604813	10TDU37655311	11SLT36303762
10SFF60154015	10SDJ43054366	10TCP39754813	10TDU37355313	11SLT33153763
10SFF60304015	10SDJ42904368	10TCP39754815	10TDU37505313	11SLT33303763
10SEF59704017	10SDJ43054368	10TCP39754816	10TDU37355314	11SLT33453763
10SEF59854017	10SDJ42904369	10TCP39904816	10TDU37505314	11SLT36003763
10SFF60004017	10SDJ43054369	10TCP39754818	10TDU37355316	11SLT36153763
10SEF59704018	10SDJ43054371	10TCP39904818	10TDU37505316	11SLT33003765
10SEF59854018	10SDJ43204371	10TCP39754819	10TDU37355317	11SLT33153765
10SEF59854020	10SDJ43054372	10TCP39904819	10TDU37505317	11SLT33303765
10SEF59854021	10SDJ43204372	10TCP39904821	10UDU37355319	11SLT33453765
10SEF59704023	10SDJ43204374	10TCP39904822	10UDU37505319	11SLT33603765

10SEF59854023	10SDJ43204375	10TDP40054822	10UDU37355320	11SLT33753765
10SEF59704024	10SDJ43354375	10TCP39904824	10UEU50705320	11SLT35853765
10SEF59854024	10SDJ43204377	10TDP40054824	10UDU37355322	11SLT36003765
10SEF59704026	10SDJ43354377	10TDP40054825	10UEU50405322	11SLT36153765
10SEF59854026	10SDJ43204378	10TDP40054827	10UEU50555322	11SLT32403766
10SEF59704027	10SDJ43354378	10TDP40054828	10UEU50705322	11SLT32553766
10SEF59854027	10SDJ43204380	10TDP40204828	10UDU37355323	11SLT32703766
10SEF59554029	10SDJ43354380	10TDP40054830	10UDU49655323	11SLT32853766
10SEF59704029	10SDJ43204381	10TDP40204830	10UDU49805323	11SLT33003766
10SEF59554030	10SDJ43354381	10TDP40054831	10UEU50405323	11SLT33453766
10SEF59704030	10SDJ43054383	10TDP40204831	10UEU50555323	11SLT33603766
10SEF59554032	10SDJ43204383	10TDP40204833	10UEU50705323	11SLT33753766
10SEF59704032	10SDJ43204384	10TDP40204834	10UEU50855323	11SLT33903766
10SEF59554033	10SDJ43204386	10TDP40204836	10UDU37205325	11SLT34053766
10SEF59404035	10SDJ43204387	10TDP40354836	10UDU37355325	11SLT34203766
10SEF59554035	10SDJ43204389	10TDP40204837	10UDU49505325	11SLT34353766
10SEF59404036	10SDJ43054390	10TDP40354837	10UDU49655325	11SLT34503766
10SEF59554036	10SDJ43204390	10TDP40204839	10UDU49805325	11SLT34653766
10SEF59404038	10SDJ43054392	10TDP40354839	10UDU49955325	11SLT34803766
10SEF59404039	10SDJ43204392	10TDP40354840	10UEU50105325	11SLT34953766
10SEF59554039	10SDJ43054393	10TDP40354842	10UEU50255325	11SLT35103766
10SEF59254041	10SDJ43204393	10TDP40354843	10UEU50405325	11SLT35253766
10SEF59404041	10SDJ42904395	10TDP40504843	10UEU50555325	11SLT35403766
10SEF59554041	10SDJ43054395	10TDP40354845	10UEU50705325	11SLT35553766
10SEF59254042	10SDJ42754396	10TDP40504845	10UEU50855325	11SLT35703766
10SEF59404042	10SDJ42904396	10TDP40354846	10UDU37355326	11SLT35853766
10SEF59554042	10SDJ43054396	10TDP40504846	10UDU49505326	11SLT31803768
10SEF59404044	10SDJ42754398	10TDP40504848	10UDU49655326	11SLT31953768
10SEF59554044	10SDJ42904398	10TDP40504849	10UDU49955326	11SLT32103768
10SEF59254045	10SDJ42754399	10TDP40504851	10UEU50105326	11SLT32253768
10SEF59404045	10SDJ42904399	10TDP40504852	10UEU50255326	11SLT32403768
10SEF59554045	10SDK42754401	10TDP40654852	10UEU50405326	11SLT32553768
10SEF59104047	10SDK42754402	10TDP40504854	10UEU50555326	11SLT32703768
10SEF59254047	10SDK42754404	10TDP40654854	10UEU50705326	11SLT32853768
10SEF59404047	10SDK42604405	10TDP40504855	10UEU50855326	11SLT34503768
10SEF59554047	10SDK42754405	10TDP40654855	10UDU37355328	11SLT34653768
10SEF59104048	10SDK42604407	10TDP40654857	10UDU46655328	11SLT34803768
10SEF59254048	10SDK42754407	10TDP40654858	10UDU46805328	11SLT35103768
10SEF59104050	10SDK42604408	10TDP40654860	10UDU46955328	11SLT35253768
10SEF59254050	10SDK42754408	10TDP40654861	10UDU47105328	11SLT35403768
10SEF59704050	10SDK42304410	10TDP40654863	10UDU47255328	11SLT35553768
10SEF59854050	10SDK42454410	10TDP40804863	10UDU47405328	11SLT31503769

10SFF60004050	10SDK42604410	10TDP40654864	10UDU47555328	11SLT31653769
10SFF60154050	10SDK42154411	10TDP40804864	10UDU47705328	11SLT31803769
10SEF59254051	10SDK42304411	10TDP40654866	10UDU47855328	11SLT31953769
10SEF59404051	10SDK42454411	10TDP40804866	10UDU48005328	11SLT31203771
10SEF59704051	10SDK42154413	10TDP40654867	10UDU48155328	11SLT31353771
10SEF59854051	10SDK42004414	10TDP40804867	10UDU48305328	11SLT31503771
10SFF60004051	10SDK42154414	10TDP40804869	10UDU49355328	11SLT31653771
10SFF60154051	10SDK42004416	10TDP40804870	10UDU49505328	11SLT30753772
10SFF60304051	10SDK42154416	10TDP40804872	10UEU50255328	11SLT30903772
10SEF59404053	10SDK41854417	10TDP40804873	10UEU50405328	11SLT31053772
10SEF59554053	10SDK42004417	10TDP40804875	10UEU50705328	11SLT31203772
10SEF59704053	10SDK41704419	10TDP40804876	10UEU50855328	11SLT31353772
10SFF60154053	10SDK41854419	10TDP40954876	10UEU51005328	11SLT30303774
10SFF60304053	10SDK41704420	10TDP40804878	10UDU37205329	11SLT30453774
10SEF59404054	10SDK41554422	10TDP40954878	10UDU37355329	11SLT30603774
10SEF59554054	10SDK41704422	10TDP40804879	10UDU46055329	11SLT30753774
10SFF60304054	10SDK41404423	10TDP40954879	10UDU46205329	11SLT30903774
10SFF60454054	10SDK41554423	10TDP40804881	10UDU46355329	11SLT30003775
10SFF60304056	10SDK41704423	10TDP40954881	10UDU46505329	11SLT30153775
10SFF60454056	10SDK41404425	10TDP40954882	10UDU46655329	11SLT30303775
10SFF60454057	10SDK41554425	10TDP40954884	10UDU46805329	11SKT29853777
10SFF60454059	10SDK41254426	10TDP40954885	10UDU46955329	11SLT30003777
10SFF60604059	10SDK41404426	10TDP40954887	10UDU47255329	11SLT30153777
10SFF60454060	10SDK41104428	10TDP40954888	10UDU47405329	11SKT29703778
10SFF60604060	10SDK41254428	10TDP40954890	10UDU47705329	11SKT29853778
10SFF60604062	10TDK40804429	10TDP41104890	10UDU47855329	11SLT30003778
10SFF60604063	10TDK40954429	10TDP40954891	10UDU48005329	11SKT29403780
10SFF60604065	10TDK41104429	10TDP40954893	10UDU48155329	11SKT29553780
10SFF60604066	10TDK40654431	10TDP41104893	10UDU48305329	11SKT29703780
10SFF60604068	10TDK40804431	10TDP40954894	10UDU48455329	11SKT29253781
10SFF60604069	10TDK40954431	10TDP41104894	10UDU49205329	11SKT29403781
10SFF60754069	10TDK40654432	10TDP40954896	10UDU49355329	11SKT29553781
10SFF60604071	10TDK40804432	10TDP41104896	10UDU49505329	11SKT29253783
10SFF60754071	10TDK40654434	10TDP40954897	10UEU50255329	11SKT29403783
10SFF60754072	10TDK40804434	10TDP41104897	10UEU50405329	11SKT29253784
10SFF60604074	10TDK40654435	10TDP40954899	10UEU50555329	11SKT29403784
10SFF60754074	10TDK40804435	10TDP41104899	10UEU50855329	11SKT29103786
10SFF60604075	10TDK40504437	10TDQ41104900	10UEU51005329	11SKT29253786
10SFF60754075	10TDK40654437	10TDQ40954902	10UEU51155329	11SKT29103787
10SFF60604077	10TDK40354438	10TDQ41104902	10UEU51305329	11SKT29253787
10SFF60454078	10TDK40504438	10TDQ40954903	10UDU37205331	11SKT29103789
10SFF60604078	10TDK40654438	10TDQ41104903	10UDU37355331	11SKT28953790







10SFF60454080	10TDK40054440	10TDQ41104905	10UDU45155331	11SKT29103790
10SFF60304081	10TDK40204440	10TDQ41104906	10UDU45305331	11SKT28953792
10SFF60454081	10TDK40354440	10TDQ41104908	10UDU45455331	11SKT29103792
10SFF60154083	10TDK40504440	10TDQ41254908	10UDU45605331	11SKT28653793
10SFF60304083	10TCK39754441	10TDQ41104909	10UDU45755331	11SKT28803793
10SFF60454083	10TCK39904441	10TDQ41254909	10UDU45905331	11SKT28953793
10SFF60154084	10TDK40054441	10TDQ41104911	10UDU46055331	11SKT29103793
10SFF60304084	10TDK40204441	10TDQ41254911	10UDU46205331	11SKT28503795
10SFF60004086	10TCK39604443	10TDQ41254912	10UDU46355331	11SKT28653795
10SFF60154086	10TCK39754443	10TDQ41254914	10UDU46505331	11SKT28803795
10SFF60004087	10TCK39904443	10TDQ41254915	10UDU46655331	11SKT28953795
10SFF60154087	10TCK39604444	10TDQ41254917	10UDU46805331	11SKT28353796
10SEF57904089	10TCK39754444	10TDQ41254918	10UDU46955331	11SKT28503796
10SEF58054089	10TCK39454446	10TDQ41404918	10UDU48305331	11SKT28203798
10SEF58204089	10TCK39604446	10TDQ41254920	10UDU48455331	11SKT28353798
10SEF58354089	10TCK39154447	10TDQ41404920	10UDU48605331	11SKT27903799
10SEF58504089	10TCK39304447	10TDQ41254921	10UDU49055331	11SKT28053799
10SEF58654089	10TCK39454447	10TDQ41404921	10UDU49205331	11SKT28203799
10SEF58954089	10TCK39004449	10TDQ41254923	10UEU50405331	11SKU27753801
10SEF59104089	10TCK39154449	10TDQ41404923	10UEU50555331	11SKU27903801
10SEF59854089	10TCK39304449	10TDQ41254924	10UEU51155331	11SKU27603802
10SFF60004089	10TCK38854450	10TDQ41404924	10UEU51305331	11SKU27753802
10SEF57604090	10TCK39004450	10TDQ41254926	10UEU51455331	11SKU27303804
10SEF57754090	10TCK39154450	10TDQ41404926	10UEU51605331	11SKU27453804
10SEF57904090	10TCK38704452	10TDQ41254927	10UEU51755331	11SKU27603804
10SEF58054090	10TCK38854452	10TDQ41404927	10UDU37055332	11SKU27153805
10SEF58504090	10TCK39004452	10TDQ41254929	10UDU37205332	11SKU27303805
10SEF58654090	10TCK38554453	10TDQ41404929	10UDU43055332	11SKU27453805
10SEF58804090	10TCK38704453	10TDQ41404930	10UDU43205332	11SKU26703807
10SEF58954090	10TCK38854453	10TDQ41404932	10UDU43355332	11SKU26853807
10SEF59104090	10TCK38404455	10TDQ41404933	10UDU43505332	11SKU27003807
10SEF59254090	10TCK38554455	10TDQ41404935	10UDU43655332	11SKU27153807
10SEF59554090	10TCK38704455	10TDQ41404936	10UDU43805332	11SKU27303807
10SEF59704090	10TCK38254456	10TDQ41404938	10UDU43955332	11SKU24753808
10SEF59854090	10TCK38404456	10TDQ41554938	10UDU44105332	11SKU24903808
10SEF57304092	10TCK38254458	10TDQ41404939	10UDU44255332	11SKU25053808
10SEF57454092	10TCK38404458	10TDQ41554939	10UDU44405332	11SKU25203808
10SEF57604092	10TCK38254459	10TDQ41404941	10UDU44555332	11SKU26553808
10SEF59104092	10TCK38404459	10TDQ41554941	10UDU44705332	11SKU26703808
10SEF59254092	10TCK38404461	10TDQ41404942	10UDU44855332	11SKU26853808
10SEF59404092	10TCK38404462	10TDQ41554942	10UDU45005332	11SKU23403810
10SEF59554092	10TCK38554462	10TDQ41554944	10UDU45155332	11SKU23553810

10SEF59704092	10TCK38404464	10TDQ41554945	10UDU45605332	11SKU23703810
10SEF57154093	10TCK38554464	10TDQ41404947	10UDU45755332	11SKU23853810
10SEF57304093	10TCK38404465	10TDQ41554947	10UDU45905332	11SKU24303810
10SEF57454093	10TCK38254467	10TDQ41404948	10UDU46055332	11SKU24453810
10SEF57004095	10TCK38404467	10TDQ41554948	10UDU48455332	11SKU24603810
10SEF57154095	10TCK38254468	10TDQ41554950	10UDU48605332	11SKU24753810
10SEF57304095	10TCK38404468	10TDQ41554951	10UDU48755332	11SKU25053810
10SEF56854096	10TCK38254470	10TDQ41554953	10UDU48905332	11SKU25203810
10SEF57004096	10TCK38404470	10TDQ41404954	10UDU49055332	11SKU25353810
10SEF57154096	10TCK38254471	10TDQ41554954	10UDU49205332	11SKU25503810
10SEF56704098	10TCK38404471	10TDQ41404956	10UEU51605332	11SKU25653810
10SEF56854098	10TCK38104473	10TDQ41554956	10UEU51755332	11SKU25803810
10SEF57004098	10TCK38254473	10TDQ41404957	10UDU37055334	11SKU26103810
10SEF56554099	10TCK37954474	10TDQ41554957	10UDU37205334	11SKU26253810
10SEF56704099	10TCK38104474	10TDQ41404959	10UDU42305334	11SKU26403810
10SEF56854099	10TCK37954476	10TDQ41554959	10UDU42455334	11SKU26553810
10SEG56554101	10TCK38104476	10TDQ41404960	10UDU42605334	11SKU23253811
10SEG56704101	10TCK37954477	10TDQ41554960	10UDU42755334	11SKU23403811
10SEG56404102	10TCK38104477	10TDQ41404962	10UDU42905334	11SKU23553811
10SEG56554102	10TCK37954479	10TDQ41554962	10UDU43055334	11SKU23703811
10SEG56254104	10TCK38104479	10TDQ41404963	10UDU43205334	11SKU23853811
10SEG56404104	10TCK38104480	10TDQ41554963	10UDU43355334	11SKU24003811
10SEG56254105	10TCK38254480	10TDQ41554965	10UDU43505334	11SKU24153811
10SEG56404105	10TCK38104482	10TDQ41704965	10UDU43655334	11SKU24303811
10SEG55804107	10TCK38254482	10TDQ41554966	10UDU43805334	11SKU24453811
10SEG55954107	10TCK38104483	10TDQ41704966	10UDU43955334	11SKU25203811
10SEG56104107	10TCK38254483	10TDQ41704968	10UDU44105334	11SKU25353811
10SEG56254107	10TCK38104485	10TDQ41704969	10UDU44255334	11SKU25503811
10SEG55804108	10TCK38254485	10TDQ41704971	10UDU44405334	11SKU25653811
10SEG55954108	10TCK38254486	10TDQ41854971	10UDU44555334	11SKU25803811
10SEG56104108	10TCK38404486	10TDQ41704972	10UDU44705334	11SKU25953811
10SEG55654110	10TCK38254488	10TDQ41854972	10UDU44855334	11SKU26103811
10SEG55804110	10TCK38404488	10TDQ41704974	10UDU45005334	11SKU26253811
10SEG55654111	10TCK38404489	10TDQ41854974	10UDU45155334	11SKU26403811
10SEG55804111	10TCK38404491	10TDQ41854975	10UDU48605334	11SKU22653813
10SEG55504113	10TCK38554491	10TDQ41854977	10UDU48755334	11SKU22803813
10SEG55654113	10TCK38404492	10TDQ41854978	10UDU48905334	11SKU22953813
10SEG55204114	10TCK38554492	10TDQ41854980	10UDU37055335	11SKU23103813
10SEG55354114	10TCK38554494	10TDQ42004980	10UDU37205335	11SKU23253813
10SEG55504114	10TCK38704494	10TDQ41854981	10UDU42005335	11SKU22503814
10SEG55204116	10TCK38554495	10TDQ42004981	10UDU42155335	11SKU22653814
10SEG55354116	10TCK38704495	10TDQ41854983	10UDU42305335	11SKU22803814

10SEG55204117	10TCK38704497	10TDQ42004983	10UDU42455335	11SKU22953814
10SEG55054119	10TCK38854497	10TDQ42004984	10UDU42605335	11SKU23103814
10SEG55204119	10TCK38704498	10TDQ42004986	10UDU48755335	11SKU22353816
10SEG55054120	10TCK38854498	10TDQ41854987	10UDU48905335	11SKU22503816
10SEG55204120	10TCL38854500	10TDQ42004987	10UDU49055335	11SKU22653816
10SEG55054122	10TCL39004500	10TDQ41854989	10UDU49205335	11SMS47703622
10SEG55204122	10TCL38854501	10TDQ42004989	10UDU37055337	11SMS47703624
10SEG55054123	10TCL39004501	10TDQ41854990	10UDU37205337	11SLT39153730
10SEG55204123	10TCL39004503	10TDQ42004990	10UDU37355337	11SLT39303730
10SEG55054125	10TCL39154503	10TDQ42004992	10UDU41855337	11SLT39453730
10SEG55204125	10TCL39004504	10TDQ42154992	10UDU42005337	11SLT39603730
10SEG55204126	10TCL39154504	10TDQ42154993	10UDU42155337	11SLT39753730
10SEG55204128	10TCL39154506	10TDQ42154995	10UDU49205337	11SLT38253729
10SEG55204129	10TCL39304506	10TDQ42304995	10UDU37205338	11SLT38403729
10SEG55204131	10TCL39154507	10TDQ42154996	10UDU37355338	11SLT38553730
10SEG55204132	10TCL39304507	10TDQ42304996	10UDU41705338	11SLT38703730
10SEG55204134	10TCL39454507	10TDQ42154998	10UDU41855338	11SLT38853730
10SEG55054135	10TCL39304509	10TDQ42304998	10UDU37355340	11SLT39003730
10SEG55204135	10TCL39454509	10TDQ42304999	10UDU41405340	11SLT38703732
10SEG55054137	10TCL39304510	10TDR42305001	10UDU41555340	11SLT39153732
10SEG55204137	10TCL39454510	10TDR42305002	10UDU41705340	11SLT39303732
10SEG54904138	10TCL39604510	10TDR42305004	10UDU37355341	11SLT39453732
10SEG55054138	10TCL39454512	10TDR42305005	10UDU41255341	11SLT39153733
10SEG54904140	10TCL39604512	10TDR42155007	10UDU41405341	11SLT39303733
10SEG55054140	10TCL39454513	10TDR42305007	10UDU41555341	11SMS47703625
10SEG54904141	10TCL39604513	10TDR42305008	10UDU41705341	11SMS46203672
10SEG54754143	10TCL39754513	10TDR42305010	10UDU37205343	11SMT41703718
10SEG54904143	10TCL39604515	10TDR42305011	10UDU37355343	11SLT36603759
10SEG54754144	10TCL39754515	10TDR42455011	10UDU40955343	11SLT38853736
10SEG54904144	10TCL39754516	10TDR42305013	10UDU41105343	11SLT38703736
		10TCL39904516	10UDU41255343	11SMS47853613


## Appendix C: GPS Processing






Project Day0228


Crabbar v0.41.0110



Project Day0228

Crabbar v0.41.0110








Project Day066A

Crabtree v0.61.001.0


Project Day066A

Crabtree v0.61.001.0







Project Day07A      Cruise v0.43.2016



Project Day07A      Cruise v0.43.2016



**Combined - Map**





Project Day0278

Cruise no. 61264


Project Day0278



Cruise no. 61264






### Combined - Map


Geographic, UTM























Project: Day1048



Crabbar v0.41.2014


Project: Day1048

Crabbar v0.41.2014











Project Day107A


Crabbar v0.42.0614



Project Day107A


Crabbar v0.42.0614






Project Day107B

Crabtree v0.41.2014






Project Day107B


Crabtree v0.41.2014

























Project: Dey1885

Graphic v6.40.2016











Project Day 11A


CRS# 65421010



Project Day 11A

CRS# 65421010







Project Day1108

CRUISE 16-01-2016


Project Day1108



CRUISE 16-01-2016



Project: Dey110C


Graphic: v6.40.0410





Project: Dey111A

Graphic: v6.49.2410





Project Day11A


CRSAR 05/02/2016



Project Day11A

CRSAR 05/02/2016










Project: Dey 112A

Graphic: v6.40.2410






Project Day112A



CHIRAN VELAZQUEZ


Project Day112A

CHIRAN VELAZQUEZ











Project Day128

CHIRP 05-41-2016



Project Day128


CHIRP 05-41-2016








Project: Day 1 19A

Gridfile: v04012410









Project Day121A

Client USACE/DRS


Project Day121A

Client USACE/DRS




Project: Day121B


Gridfile: v64028410



Project: Day 121B GRANITE v6.40.0410




Project: Day 121B GRANITE v6.40.0410



Project: Day 121A

Granite v6.40.0410

### Combined - Map





Project Day121A

Graphix v6.40.0410

Project Day121A

Graphix v6.40.0410





Project Day121B

Graphix v6.40.0410


### Combined - Map

Geographic, UTM






Project: Day 1228 GrafNav v6.40.0410






Project Day126


Cruise W64L010



Project Day126

Cruise W64L010







Project: Day123A

CHIRAN 05.42.010


Project: Day123A

CHIRAN 05.42.010



Project: Dey183B

Graphics: v8.40.2410





Project: Day 123B

Grabber v0.40.0410


Project: Day 123B

Grabber v0.40.0410



Project: Day 123C

Grabber v0.40.0410






Project: Day122c

QID# 6643200

Project: Day123c


QID# 6643200






Page# Day127A

Chart# 0042,010



Page# Day127A


Chart# 0042,010





Project Day 190A

GridNet v0.40.0410






Project Day130A



CHIRAS 05.01.010

Project Day130A


CHIRAS 05.01.010








Project: Day 140A CIRRAS v6.43.0410




Project: Day140A

CUSTOM 16L4L2016




Project: Day140A

CUSTOM 16L4L2016



Project: Dey1403

Graphic: v64032410





Project: Day140B

Chart: v6.41.2410


Project: Day140B

Chart: v6.41.2410



Project: Day141B

Chart: v6.41.2410





Project: Day141B

GrainNet v6.41.0410

Project: Day141B

GrainNet v6.41.0410



Project: Day141C

GrainNet v6.41.0410

