

Everglades National Park Lidar

Report Produced for U.S. Geological Survey

USGS Contract: G16PC00020

Task Order: G16PD01224

Report Date: 08/30/2018

SUBMITTED BY:

Dewberry

1000 North Ashley Drive Suite 801
Tampa, FL 33602
813.225.1325

SUBMITTED TO:

U.S. Geological Survey

1400 Independence Road
Rolla, MO 65401
573.308.3810

Table of Contents

Executive Summary	4
The Project Team.....	4
Survey Area.....	4
Date of Survey.....	4
Coordinate Reference System	4
Lidar Vertical Accuracy	4
Project Deliverables.....	5
Project Tiling Footprint.....	5
Overview of Classification	6
Lidar Acquisition Report	7
Lidar Acquisition Details.....	7
Lidar System parameters.....	8
Acquisition Status Report and Flightlines	9
Lidar Control	9
Airborn GPS Kinematic	10
Generation and Calibration of Laser Points (raw data)	10
Boresight and Relative accuracy.....	11
Preliminary Vertical Accuracy Assessment.....	13
Lidar Processing & Qualitative Assessment	14
Initial Processing.....	14
Refraction Correction.....	15
Final Swath Vertical Accuracy Assessment.....	15
Inter-Swath (Between Swath) Relative Accuracy	16
Intra-Swath (Within a Single Swath) Relative Accuracy	18
Horizontal Alignment	18
Point Density and Spatial Distribution.....	19
Breakline Production & Qualitative Assessment Report.....	21
Breakline Production Methodology	21
Inland Water Voids	22
Land/Water Interface	23
Topobathy Voids	24
Breakline Checklist.....	24
Data Classification and Editing.....	25
GeoCue and Terrascan Processing.....	25
Submerged Objects	28

Temporal Changes	28
Lidar Qualitative Assessment	28
Visual Review	28
NIR Depressions	28
Excessive Vegetation	29
Bridge Removal Artifacts	30
Culverts and Bridges	31
Flight line Ridges	32
Formatting	33
Derivative Lidar Products	34
Intensity Imagery	34
Low-Confidence Polygons	34
Lidar Positional Accuracy	35
Background.....	35
Survey Vertical Accuracy Checkpoints	35
Vertical Accuracy Test Procedures	41
NVA	41
VVA	41
Vertical Accuracy Results	42
Horizontal Accuracy Test Procedures	48
Horizontal Accuracy Results	49
DEM Processing & Qualitative Assessment.....	49
DEM Generation.....	49
DEM Qualitative Review	49
DEM Quantitative Assessment.....	51
DEM Checklist.....	52
Optical Imagery	53
Imagery Processing	53
Metadata	54
Appendix A: Checkpoint Survey Report	55
Appendix B: Ground Control Survey Report.....	56
Appendix C: Complete List of Delivered Tiles.....	57
Appendix D: GPS Spatial Processing.....	73

Executive Summary

Dewberry was tasked with developing a consistent and accurate topographic and bathymetric (topobathymetric) elevation dataset derived from high-accuracy Light Detection and Ranging (lidar) technology for the USGS Everglades National Park (ENP) in Florida.

The lidar data were processed and classified according to project specifications. Topobathymetric Digital Elevation Models (DEMs) were produced for the project area. Data were formatted according to tiles with each tile covering an area of 1000 m by 1000 m. A total of 3,320 tiles were produced for the project encompassing an area of approximately 1,211 sq. miles.

THE PROJECT TEAM

Dewberry served as the prime contractor for the project. In addition to project management, Dewberry was responsible for acquisition, calibration, LAS classification, LAS refraction correction, all lidar products, breakline production, Digital Elevation Model (DEM) production, and quality assurance.

Dewberry's William D. Donley completed ground surveying for the project and delivered surveyed checkpoints. His task was to acquire surveyed checkpoints and ground control points for the project. Surveyed checkpoints were acquired to use in independent testing of the vertical accuracy of the lidar-derived model and surveyed ground control points were acquired to use for lidar calibration processes. He also verified the GPS base station coordinates used during lidar data acquisition to ensure that the base station coordinates were accurate. Please see Appendices A and B to view the separate Survey Reports that were created for this portion of the project.

SURVEY AREA

The project area addressed by this report falls within Florida Everglades National Park, located in the counties of Monroe and Miami-Dade.

DATE OF SURVEY

The lidar aerial acquisition was conducted from April 19, 2017 to June 12, 2017.

COORDINATE REFERENCE SYSTEM

Data produced for the project were produced in the following reference system.

Horizontal Datum: The horizontal datum for the project is North American Datum of 1983 with the 2011 Adjustment (NAD 83 (2011))

Vertical Datum: The Vertical datum for the project is North American Vertical Datum of 1988 (NAVD88)

Coordinate System: UTM Zone 17

Units: Horizontal units are in meters, Vertical units are in meters.

Geoid Model: Geoid12B (Geoid 12B was used to convert ellipsoid heights to orthometric heights).

LIDAR VERTICAL ACCURACY

For the Everglades National Park Lidar Project, the tested $RMSE_z$ of the classified lidar data for checkpoints in non-vegetated terrain equaled **3.6 cm** compared with the 10 cm specification;

and the NVA of the classified lidar data computed using $RMSE_z \times 1.9600$ was equal to **7 cm**, compared with the 19.6 cm specification.

For the Everglades National Park Lidar Project, the Bathymetric Vertical Accuracy of the classified lidar was not a testing requirement. Survey checkpoints identified as bathymetric were delivered for testing. Dewberry used these points for internal production processing, however the points were not survey grade and were not used for bathymetric vertical accuracy testing.

For the Everglades National Park Lidar Project, the tested VVA of the classified lidar data computed using the 95th percentile was equal to **35 cm**, compared with the 29.4 cm specification.

Additional accuracy information and statistics for the classified lidar data, raw swath data, and topobathymetric DEM data are found in the following sections of this report.

PROJECT DELIVERABLES

The deliverables for the project are listed below.

1. Project Extents, including buffered boundary, tile grid, and a shapefile derived from the lidar deliverable (Shapefiles)
2. Breakline Data (GDB and Shapefiles)
3. Classified Point Cloud Data (Tiled)
4. Bare Earth Surface Tiled Topobathymetric DEMs with voids enforced (IMG)
5. Digital Surface Models (IMG)
6. Intensity Images for Green Sensor Data and NIR Sensor Data (Tiled, GeoTIFF)
7. Low Confidence polygons (Shapefile)
8. Raw color imagery frames (GeoTIFF)
9. Independent Survey Checkpoint Data (Report, Photos, Point Shapefile, & Coordinates Spreadsheet)
10. Calibration Points (Report, Photos, Point Shapefile, & Coordinates Spreadsheet)
11. Metadata (XML)
12. Final Project Report (Acquisition, Processing, QC)

PROJECT TILING FOOTPRINT

Three thousand three hundred twenty (3,320) tiles were delivered for the project. Each tile's extent is 1,000 meters by 1,000 meters (see Appendix C for a complete listing of delivered tiles).

Florida Everglades National Park LiDAR Project




Figure 1 – Project Map

OVERVIEW OF CLASSIFICATION

The classification schema used during manual editing and also the schema used for the final LAS delivered to USGS as required by the project's scope of work in conjunction with ASPRS standards for bathymetric classification is listed below.

Lidar Classification – Manual Editing and Final Deliverables	
Class	Description
Class 1	Processed, but unclassified (includes buildings and vegetation)
Class 2	Bare-earth ground
Class 7	Low Noise
Class 9	Water
Class 17	Bridge Decks
Class 18	High Noise
Class 40	Bathymetric Bottom
Class 41	Water Surface
Class 45	No bathymetric bottom found (water column)

Table 1 - Final lidar classification schema

Lidar Acquisition Report

Dewberry elected to perform the lidar acquisition and calibration activities. Dewberry was responsible for performing lidar acquisition and calibration of lidar data files.

LIDAR ACQUISITION DETAILS

Dewberry planned 124 passes for the project area as a series of parallel flight lines with cross flightlines for the purposes of quality control. The flight plan included zigzag flight line collection as a result of the inherent IMU drift associated with all IMU systems. In order to reduce any margin for error in the flight plan, Dewberry followed FEMA’s Appendix A “guidelines” for flight planning and, at a minimum, includes the following criteria:

- A digital flight line layout using Riegl ALS flight design software for direct integration into the aircraft flight navigation system.
- Planned flight lines; flight line numbers; and coverage area.
- Lidar coverage extended by a predetermined margin beyond all project borders to ensure necessary over-edge coverage appropriate for specific task order deliverables.
- Local restrictions related to air space and any controlled areas have been investigated so that required permissions can be obtained in a timely manner with respect to schedule. Additionally, Dewberry will file our flight plans as required by local Air Traffic Control (ATC) prior to each mission.

Dewberry monitored weather and atmospheric conditions and conducted lidar missions only when no conditions exist below the sensor that will affect the collection of data. These conditions include leaf-off for hardwoods, no snow, rain, fog, smoke, mist and low clouds. Lidar systems are active sensors, not requiring light, thus missions may be conducted during night hours when weather restrictions do not prevent collection. Dewberry accesses reliable weather sites and indicators (webcams) to establish the highest probability for successful collection in order to position our sensors to maximize successful data acquisition. Due to flight restrictions in Everglades National Park, no missions were conducted during night hours.

Within 72-hours prior to the planned day(s) of acquisition, Dewberry closely monitored the weather, checking all sources for forecasts at least twice daily. As soon as weather conditions were conducive to acquisition, our aircraft mobilized to the project site to begin data collection. Once on site, the acquisition team took responsibility for weather analysis.

Dewberry lidar sensors are calibrated at a designated site in Kissimmee, Florida and are periodically checked and adjusted to minimize corrections at project sites.

LIDAR SYSTEM PARAMETERS

Dewberry operated a Navajo Aircraft (Tail # C-GKCN) outfitted with a Riegl VQ820G and Riegl LMS Q680i dual lidar system configuration during the collection of the study area. Table 2 illustrates Dewberry system parameters for lidar acquisition on this project.

Item	Parameter	Parameter
System	Riegl VQ820G	Riegl LMS Q680i
Altitude (AGL meters)	400	400
Approx. Flight Speed (knots)	130	130
Scanner Pulse Rate (kHz)	522	400
Scan Frequency (hz)	200	191
Pulse Duration of the Scanner (nanoseconds)	1.2	3
Pulse Width of the Scanner (m)	0.36	0.9
Swath width (m)	307	462
Central Wavelength of the Sensor Laser (nanometers)	532	1550
Did the Sensor Operate with Multiple Pulses in The Air? (yes/no)	Yes	Yes
Beam Divergence (milliradians)	1	1
Nominal Swath Width on the Ground (m)	307	462
Swath Overlap (%)	30	30
Total Sensor Scan Angle (degree)	60	60
Computed Down Track spacing (m) per beam	0.45	0.63
Computed Cross Track Spacing (m) per beam	0.25	0.18
Nominal Pulse Spacing (single swath), (m)	0.35	0.35
Nominal Pulse Density (single swath) (ppsm), (m)	8	8
Aggregate NPS (m) (if ANPS was designed to be met through single coverage, ANPS and NPS will be equal)	0.35	0.35
Aggregate NPD (m) (if ANPD was designed to be met through single coverage, ANPD and NPD will be equal)	8	8
Maximum Number of Returns per Pulse	Unlimited	Unlimited

Table 2 - Dewberry lidar system parameters

ACQUISITION STATUS REPORT AND FLIGHTLINES

Upon notification to proceed, the flight crew loaded the flight plans and validated the flight parameters. The Acquisition Manager contacted air traffic control and coordinated flight pattern requirements. Lidar acquisition began immediately upon notification that control base stations were in place. During flight operations, the flight crew monitored weather and atmospheric conditions. Lidar missions were flown only when no condition existed below the sensor that would affect the collection of data. The pilot constantly monitored the aircraft course, position, pitch, roll, and yaw of the aircraft. The sensor operator monitored the sensor, the status of PDOPs, and performed the first QA/QC review during acquisition. The flight crew constantly reviewed weather and cloud locations. Any flight lines impacted by unfavorable conditions were marked as invalid and re-flown immediately or at an optimal time.

Figure 2 shows the combined trajectory of the flightlines.




Figure 2: Trajectories as flown by Dewberry

LIDAR CONTROL

Dewberry deployed static GPS base stations during the acquisition of the Everglades National Park. Considerations were made for location access and clear visibility of the horizon. Additionally these static sessions were recorded at 1 Hz samples for the highest quality post processed solution. These static base sessions were then incorporated during the kinematic post-processing of aircraft position. These base stations were either set on existing control monumentation, or new benchmarks established. The coordinates of these base stations are provided in the table below. All control and calibration points are also provided in shapefile format as part of the final deliverables.

Name	NAD83 (2011) UTM 17		Ellipsoid Ht (NAD83 (2011), m)	Orthometric Ht (NAVD88 Geoid12B, m)
	Easting X (m)	Northing Y (m)		
7119	545250.45	2820522.10	-22.868	1.795
AC0526	518658.29	2849337.17	-20.758	3.405
Home	545211.71	2820507.07	-19.138	5.527

Table 3 – Base stations used to control lidar acquisition

AIRBORN GPS KINEMATIC

Airborne GPS data was processed using the PosPac kinematic On-The-Fly (OTF) software suite. Flights were flown with a minimum of 6 satellites in view (13° above the horizon) and with a PDOP of better than 4. Distances from base station to aircraft were kept to a maximum of 40 km.

For all flights, the GPS data can be classified as excellent, with GPS residuals of 3 cm average or better but no larger than 10 cm being recorded.

GPS processing reports for each mission are included in Appendix D.

GENERATION AND CALIBRATION OF LASER POINTS (RAW DATA)

The initial step of calibration is to verify availability and status of all needed GPS and Laser data against field notes and compile any data if not complete.

Subsequently the mission points are output using Riegl RiProcess, initially with default values from Riegl or the last mission calibrated for the system. The initial point generation for each mission calibration is verified within Microstation/Terrascan for calibration errors. If a calibration error greater than specification is observed within the mission, the roll, pitch and scanner scale corrections that need to be applied are calculated. The missions with the new calibration values are regenerated and validated internally once again to ensure quality.

Data collected by the lidar unit is reviewed for completeness, acceptable density and to make sure all data is captured without errors or corrupted values. In addition, all GPS, aircraft trajectory, mission information, and ground control files are reviewed and logged into a database.

On a project level, a supplementary coverage check is carried out to ensure no data voids unreported by Field Operations are present.



Figure 3 – Lidar swath output showing complete coverage.

BORESIGHT AND RELATIVE ACCURACY

The initial points for each mission calibration are inspected for flight line errors, flight line overlap, slivers or gaps in the data, point data minimums, or issues with the lidar unit or GPS. Roll, pitch and scanner scale are optimized during the calibration process until the relative accuracy is met.

Relative accuracy and internal quality are checked using at least 3 regularly spaced QC blocks in which points from all lines are loaded and inspected. Vertical differences between ground surfaces of each line are displayed. Color scale is adjusted so that errors greater than the specifications are flagged. Cross sections are visually inspected across each block to validate point to point, flight line to flight line and mission to mission agreement.

For this project the specifications used are as follow:
Relative accuracy ≤ 6 cm maximum difference within individual swaths and ≤ 8 cm RMSDz
between adjacent and overlapping swaths.




Figure 4 – Profile views showing correct roll and pitch adjustments.




Figure 5 – QC block colored by distance to ensure accuracy at swath edges.

A different set of QC blocks are generated for final review after all transformations have been applied.

PRELIMINARY VERTICAL ACCURACY ASSESSMENT

A preliminary RMSE_z error check is performed by Dewberry at this stage of the project life cycle in the raw lidar dataset against GPS static and kinematic data and compared to RMSE_z project specifications. The lidar data is examined in non-vegetated, flat areas away from breaks. Lidar ground points for each flight line generated by an automatic classification routine are used.

The elevation data was verified internally to ensure it met Non-vegetated Vertical Accuracy (NVA) requirements (RMSE_z ≤ 10 cm and Accuracy_z at the 95% confidence level ≤ 19.6 cm) when compared to static and kinematic GPS checkpoints. Below is a summary for the test:

The calibrated Everglades National Park lidar dataset was tested to 0.064 m vertical accuracy at 95% confidence level based on RMSE_z (0.10 m x 1.9600) when compared to 47 GPS static check points.

The following are the final statistics for the GPS static ground control points used by Dewberry to internally verify vertical accuracy.

Number	NAD83 (2011) UTM 17N		NAVD88 (Geoid 12B)	Laser Z (m)	Delta Z
	Easting X (m)	Northing Y (m)	Known Z (m)		
GCP-300	513849.390	2788034.780	1.100	1.060	-0.040
GCP-302	518915.380	2791439.940	1.050	1.010	-0.040
GCP-303	520299.670	2794732.580	0.900	0.920	0.020
GCP-304	520299.110	2798228.870	0.970	0.990	0.020
GCP-305	518645.760	2802768.080	1.030	1.030	0.000
GCP-306	518949.930	2807015.560	0.970	0.940	-0.030
GCP-307	521261.730	2809820.740	1.170	1.190	0.020
GCP-309	528070.620	2812364.740	0.810	0.850	0.040
GCP-311	534577.490	2809133.990	1.570	1.560	-0.010
GCP-312	539248.840	2807455.320	1.400	1.370	-0.030
GCP-313	541739.320	2808653.000	1.400	1.440	0.040
GCP-314	552212.710	2806533.260	1.300	1.310	0.010
GCP-315	541273.100	2811431.220	2.350	2.310	-0.040
GCP-316	541219.440	2816117.060	2.530	2.520	-0.010
GCP-317	542820.030	2820364.800	3.500	3.510	0.010
GCP-318	542771.510	2825889.070	3.520	3.550	0.030
GCP-320	542606.380	2833991.360	2.400	2.440	0.040
GCP-321	547852.700	2800345.880	0.780	0.770	-0.010
GCP-322	550992.590	2798878.540	1.050	1.020	-0.030
GCP-324	541989.340	2849188.480	2.180	2.160	-0.020
GCP-325	539660.340	2849260.110	2.490	2.510	0.020
GCP-326	537386.870	2849255.010	2.460	2.410	-0.050
GCP-327	535988.080	2849251.580	2.460	2.460	0.000
GCP-328	533629.880	2849246.620	2.450	2.490	0.040
GCP-330	523464.490	2849095.840	2.390	2.370	-0.020
GCP-333	522635.970	2849301.040	3.160	3.190	0.030

GCP-334	521065.030	2849215.860	2.800	2.720	-0.080
GCP-335	520419.130	2849316.390	3.890	3.890	0.000
GCP-336	519210.430	2849207.620	2.730	2.710	-0.020
GCP-338	517230.220	2849196.130	2.810	2.820	0.010
GCP-341	513797.780	2849175.990	2.610	2.590	-0.020
GCP-344	510105.450	2849252.510	2.150	2.220	0.070
GCP-345	508084.220	2849245.260	2.570	2.590	0.020
GCP-346	506542.610	2848187.160	2.100	2.120	0.020
GCP-347	504289.630	2847731.780	2.450	2.430	-0.020
GCP-348	499416.890	2849144.440	2.070	2.070	0.000
GCP-349	493187.810	2849145.990	1.880	1.860	-0.020
GCP-400	538008.760	2806640.440	0.710	0.770	0.060
GCP-401	547760.570	2807599.480	1.850	1.840	-0.010
GCP-405	551014.160	2802738.790	1.460	1.430	-0.030
GCP-406	550284.180	2840759.170	4.380	4.380	0.000
GCP-407	550420.700	2846100.710	4.630	4.600	-0.030
GCP-408	523526.740	2848815.620	2.720	2.680	-0.040
GCP-409	532830.820	2840670.720	3.540	3.590	0.050
GCP-410	532865.020	2845038.190	3.810	3.830	0.020
GCP-411	550298.640	2849283.860	2.930	3.000	0.070
GCP-412	496428.720	2846318.480	0.980	0.970	-0.010

Table 4 - Static GPS Ground Control Points

100 % of Totals	# of Points	RMSEz (m) NVA Spec=0.1 m	NVA at 95% Spec=0.196 m	Mean (m)	Std Dev (m)	Min (m)	Max (m)
Non-Vegetated Terrain	47	0.033	0.064	0.001	0.033	-0.080	0.070

Table 5 - Static GPS Ground Control Vertical Accuracy Results

Overall the calibrated lidar data products collected by Dewberry meet or exceed the requirements set out in the Statement of Work. The quality control requirements of Dewberry quality management program were adhered to throughout the acquisition stage for this project to ensure product quality.

Lidar Processing & Qualitative Assessment

INITIAL PROCESSING

As the acquisition provider, Dewberry applied the refraction correction. Dewberry then performed several validations on the dataset prior to starting full-scale production on the project. These validations include vertical accuracy of the swath data, inter-swath (between swath) relative accuracy validation, intra-swath (within a single swath) relative accuracy validation, verification of horizontal alignment between swaths, and confirmation of point density and spatial distribution. This initial assessment allows Dewberry to determine if the data are suitable for full-scale production. Addressing issues at this stage allows the data to be corrected while imposing the least disruption possible on the overall production workflow and overall schedule.

Refraction Correction

Bathymetric data must have a refraction correction applied, which corrects the horizontal and vertical (depth) positions of each data point by accounting for the change in direction and speed of light as it enters and travels through water. The refraction correction was performed by Dewberry using the proprietary tool Dewberry's Lidar Processor (DLP).

Final Swath Vertical Accuracy Assessment

Dewberry tested the vertical accuracy of the non-vegetated terrain swath data prior to additional processing. Dewberry tested the vertical accuracy of the swath data using the sixty (60) non-vegetated (open terrain and urban) independent survey check points. The vertical accuracy is tested by comparing survey checkpoints in non-vegetated terrain to a triangulated irregular network (TIN) that is created from the raw swath points. Only checkpoints in non-vegetated terrain can be tested against raw swath data because the data has not undergone classification techniques to remove vegetation, buildings, and other artifacts from the ground surface. Checkpoints are always compared to interpolated surfaces from the lidar point cloud because it is unlikely that a survey checkpoint will be located at the location of a discrete lidar point. Dewberry typically uses LP360 software to test the swath lidar vertical accuracy, Terrascan software to test the classified lidar vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project. Project specifications require a NVA of 19.6 cm based on the $RMSE_z$ (10 cm) x 1.96. The dataset for the Florida Everglades National Park Lidar Project satisfies this criteria. This raw lidar swath data set was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm $RMSE_z$ Vertical Accuracy Class. Actual NVA accuracy was found to be $RMSE_z = 4.3$ cm, equating to +/- 8.5 cm at 95% confidence level. The table below shows all calculated statistics for the raw swath data.

100 % of Totals	# of Points	RMSE _z NVA Spec=0.10 m	NVA –Non-vegetated Vertical Accuracy (RMSE _z x 1.9600) Spec=0.196 m	Mean (m)	Median (m)	Skew	Std Dev (m)	Min (m)	Max (m)	Kurtosis
Non-Vegetated Terrain	60	0.043	0.085	0.016	0.017	0.005	0.040	-0.084	0.104	-0.204

Table 6 - NVA at 95% Confidence Level for Raw Swaths

One checkpoint (NVA-151) was removed from the raw swath vertical accuracy testing due to its location underneath a parked vehicle. Only non-vegetated terrain checkpoints are used to test the raw swath data because the raw swath data has not been classified to remove vegetation, structures, and other above ground features from the ground classification. While NVA-151 is located in open terrain, the parked vehicle is modeled by the lidar point cloud. These high points caused erroneous high values during the swath vertical accuracy testing so this point was removed from the final calculations. Once the data underwent the classification process, the car was removed from the final ground classification and this point could be used in the final vertical accuracy testing for the fully classified lidar data. Table 7, below, provides the coordinates for this checkpoint and the vertical accuracy results from the raw swath data. Table 8, below, provides the usable vertical accuracy results of this checkpoint from the fully classified

lidar. The differences in the tables show how above ground features can cause erroneous vertical accuracy results in the raw swath data. Figure 6, below, shows a side profile of the lidar point cloud and the location of the checkpoint beneath the parked vehicle in the survey photo.

Point ID	NAD83 (2011) UTM Zone 17N		NAVD88 (Geoid 12B)	Lidar Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
NVA-151	544035.935	2849277.208	2.608	3.720	1.112	1.112

Table 7 - Checkpoint removed from raw swath vertical accuracy testing

Point ID	NAD83 (2011) UTM Zone 17N		NAVD88 (Geoid 12B)	Lidar Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
NVA-151	544035.935	2849277.208	2.608	2.580	-0.028	0.028

Table 8 - Final tested vertical accuracy for NVA-151 post ground classification



Figure 6 – Survey photo of NVA checkpoint 151 (left image) and profile view of the lidar with point location (right image). Checkpoint 151 is located underneath a parked vehicle. This point was removed from raw swath vertical accuracy testing because above ground features, including vehicles, have not been separated from the ground classification yet.

Inter-Swath (Between Swath) Relative Accuracy

Dewberry verified inter-swath or between swath relative accuracy of the dataset by creating Delta-Z (DZ) orthos. According to the SOW, USGS Lidar Base Specifications v1.2, and ASPRS Positional Accuracy Standards for Digital Geospatial Data, 10 cm Vertical Accuracy Class or QL1 data must meet inter-swath relative accuracy of 8 cm RMSDz or less with maximum differences less than 16 cm. These measurements are to be taken in non-vegetated and flat open terrain using single or only returns from all classes. Measurements are calculated in the DZ orthos on 1-meter pixels or cell sizes. Areas in the dataset where overlapping flight lines are within 8 cm of each other within each pixel are colored green, areas in the dataset where overlapping flight lines have elevation differences in each pixel between 8 cm to 16 cm are colored yellow, and areas in the dataset where overlapping flight lines have elevation differences in each pixel

greater than 16 cm are colored red. Pixels that do not contain points from overlapping flight lines are colored according to their intensity values. Areas of vegetation and steep slopes (slopes with 16 cm or more of valid elevation change across 1 linear meter) are expected to appear yellow or red in the DZ orthos. If the project area is heavily vegetated, Dewberry may also create DZ Orthos from the initial ground classification only, while keeping all other parameters consistent. This allows Dewberry to review the ground classification relative accuracy beneath vegetation and to ensure flight line ridges or other issues do not exist in the final classified data.

Flat, open areas are expected to be green in the DZ orthos. Bathymetric areas may be yellow or red due to varying elevations of returns within the water column. Large or continuous sections of yellow or red pixels following flight line patterns and not the terrain, vegetation, or bathymetric areas can indicate the data was not calibrated correctly or that there were issues during acquisition that could affect the usability of the data. The DZ orthos for Florida Everglades National Park Lidar Project are shown in the figure below; this project meets inter-swath relative accuracy specifications.




Figure 7 – Single return DZ Orthos (combined green and near infrared sensors) for the Florida Everglades National Park Lidar Project. Offsets between flight lines of 0-8 cm are green, 8-16 cm are yellow, and above 16 cm are red. Larger offsets in vegetated and bathymetric areas are expected as different returns from water column and vegetation can occur between different flight lines. Inter-swath relative accuracy passes specifications.

Intra-Swath (Within a Single Swath) Relative Accuracy

Dewberry verifies the intra-swath or within swath relative accuracy by using Quick Terrain Modeler (QTM) scripting and visual reviews. QTM scripting is used to calculate the maximum difference of all points within each 1-meter pixel/cell size of each swath. Dewberry analysts then identify planar surfaces acceptable for repeatability testing and analysts review the QTM results in those areas. According to the SOW, USGS Lidar Base Specifications v1.2, and ASPRS Positional Accuracy Standards for Digital Geospatial Data, 10 cm Vertical Accuracy Class or QL1 data must meet intra-swath relative accuracy of 6 cm maximum difference or less. The image below shows two examples of the intra-swath relative accuracy of Everglades National Park Lidar project; this project meets intra-swath relative accuracy specifications.




Figure 8 – Intra-swath relative accuracy. The left image shows a large portion of the dataset; flat, open areas are colored green as they are within 6 cm whereas sloped terrain is colored red because it exceeds 6 cm maximum difference, as expected, due to actual slope/terrain change. The right image is a close-up of a flat area. With the exception of tree islands (shown in red as the elevation/height difference in vegetated areas will exceed 6 cm) this open flat area is acceptable for repeatability testing. Intra-swath relative accuracy passes specifications.

Horizontal Alignment

To ensure horizontal alignment between adjacent or overlapping flight lines, Dewberry uses QTM scripting and visual reviews. QTM scripting is used to create files similar to DZ orthos for each swath but this process highlights planar surfaces, such as roof tops. In particular, horizontal shifts or misalignments between swaths on roof tops and other elevated planar surfaces are highlighted. Visual reviews of these features, including additional profile verifications, are used to confirm the results of this process. The image below shows an example of the horizontal alignment between swaths for the Everglades National Park project; no horizontal alignment issues were identified.




Figure 9 – Horizontal Alignment. Two separate flight lines differentiated by color (Teal/Purple) are shown in this profile. There is no visible offset between these two flight lines. No horizontal alignment issues were identified.

Point Density and Spatial Distribution

For topographic areas, the required Aggregate Nominal Point Spacing (ANPS) for this project is no greater than 0.35 meters, which equates to an Aggregate Nominal Point Density (ANPD) of 8 points per square meter or greater. Density calculations were performed using first return data only located in the geometrically usable center portion (typically ~90%) of each swath. By utilizing statistics, the project area was determined to have a combined topobathy ANPS of 0.22 meters or an ANPD of 21.15 points per square meter which satisfies the project requirements. A visual review of a 1-square meter density grid (figure below) shows that there are some 1-meter cells that do not contain 8 points per square meter (red areas) due to the irregular spacing of lidar point cloud data. Most 1-sqaure meter cells contain at least 8 points per square meter (green areas) and when density is viewed/analyzed by representative 1-square kilometer areas (to account for the irregular spacing of lidar point clouds), density passes with no issues.




Figure 10 – 1-square meter density grid. There are some 1-meter cells that do not contain 8 points per square meter (red areas) due to the irregular spacing of lidar point cloud data. Most 1-square meter cells contain at least 8 points per square meter (green areas) showing there are no systematic density issues. When density is viewed/analyzed by representative 1-square kilometer areas, density passes with no issues.

The spatial distribution of points must be uniform and free of clustering. This specification is tested by creating a grid with cell sizes equal to the design NPS^2 . ArcGIS tools are then used to calculate the number of first return points of each swath within each grid cell. At least 90% of the cells must contain 1 lidar point, excluding acceptable void areas such as low NIR reflectivity features, i.e. some asphalt and roof composition materials. This project passes spatial distribution requirements, as shown in the image below.




Figure 11 – Spatial Distribution. All cells (2*NPS cellsize) containing at least one lidar point are colored green. Cells that do not contain a lidar point are colored red. 99.5% of cells contain at least one lidar point.

Breakline Production & Qualitative Assessment Report

BREAKLINE PRODUCTION METHODOLOGY

Dewberry used 2D digitization to collect breaklines for this project. Green sensor intensity imagery, near infrared (NIR) intensity imagery, bare earth ground models, LAS datasets, and density models were produced to assist with breakline delineation. Breaklines were collected following USGS Base Specifications for collection – inland ponds and lakes 2 acres or greater surface area, and inland streams and rivers 100 feet nominal width.

Hydrologic features meeting collection size requirements were determined using the near infrared intensity imagery, which identifies wet features at the time of data collection. Green intensity imagery was used to determine where bathymetric data was present, along with drawing profiles using the lidar point cloud.

Refraction requirements were determined between Dewberry and the client. Hydrologic features meeting USGS collection size requirements and also containing bathymetric data deeper than 50

cm were refracted. Bathymetric data within locations of refraction follow the ASPRS topographic-bathymetric point classification schema.

Hydrographic breaklines are delivered in three feature classes/shapefiles. They are discussed below. Bridge saddle breaklines were also collected where necessary and are discussed in the DEM Qualitative Review section of this report.

Inland Water Voids

These polygons are located where no bathymetric data were found in the lidar. Any points within these polygons that were grounded by the initial grounding macro were reclassified to point class 9: water. In the final topobathy DEMs, these locations are represented as voids and set to No Data.




Figure 12 - Tiles 17RMJ980210 and 17RMJ980200. Near infrared intensity image and inland water void (pink) representing hydrologic feature where no bathymetric data were found (top image). The initial ground points were reclassified to class 9: water, and are represented as No Data voids in the topobathy DEMs (bottom image).

Land/Water Interface

These polygons are located where bathymetric data were found in the lidar that is deep enough to require refraction (i.e. deeper than 50 cm). Dewberry's internal refraction tool corrects the horizontal and vertical (depth) positions of each data point by accounting for the change in the speed of light as it travels through water and the change in angle or direction as light enters the water. The refraction tool is applied to the Green sensor data. Because the LAS is a combination of the NIR and Green sensor data, Dewberry applied a topobathy classification schema to the NIR points within these polygons so all lidar points within these polygons follow the ASPRS topobathy classification schema.

Class 40 – Bathymetric point (submerged topography)

Class 41 – Water Surface (distinct from point class 9, which is used in topographic-only lidar and only designates “water”, not “water surface”)

Class 45 – No-bottom-found-at (bathymetric lidar point for which no detectable bottom return was received)




Figure 13 - Tiles 17RNH210830 and 17RNH220830. Green intensity image and land/water interface breakline (green) representing hydrologic feature where refraction correction was performed on bathymetric data (top image). Basemap with land/water interface (bottom image).

Topobathy Voids

These polygons are located within the land/water interface breaklines used for refraction, and are located where no submerged bottom data were found in the lidar. Points within these polygons follow the same classification schema used in the land/water interface breaklines. In the final topobathy DEMs, these locations are represented as voids and set to No Data.




Figure 14 - Tile 17RNH400890. Green intensity image, land/water interface breakline (green), and topobathy voids (blue) representing hydrologic feature where refraction correction was performed on bathymetric data and locations with no bathymetric data were delineated as voids (left image). Locations where no bathymetric data are found are reclassified to class 45: no bottom found, and are represented as No Data voids in the topobathy DEMs (right image).

BREAKLINE CHECKLIST

The following table represents a portion of the high-level steps in Dewberry's Production and QA/QC checklist that were performed for this project.

Pass/Fail	Validation Step
Pass	Use lidar-derived data, which may include intensity imagery, stereo pairs, bare earth ground models, density models, slope models, and terrains, to collect breaklines according to project specifications.
Pass	In areas of heavy vegetation or where the exact shoreline is hard to delineate, it is better to err on placing the breakline <i>slightly</i> inside or seaward of the shoreline (breakline can be inside shoreline by 1x-2x NPS).
Pass	After each producer finishes breakline collection for a block, each producer must perform a completeness check and all automated checks on their block before calling that block complete and ready for the final merge and QC
Pass	After breaklines are completed for production blocks, all production blocks should be merged together and completeness and automated checks should be performed on the final, merged GDB. Ensure correct snapping-horizontal (x,y) between all production blocks.
Pass	Check entire dataset for missing features that were not captured, but should be to meet baseline specifications or for consistency. Features should be collected consistently across tile bounds. Check that the horizontal placement of breaklines is correct. Breaklines should be compared to full point cloud intensity imagery and terrains.

Pass	Breaklines are correctly edge-matched to adjoining datasets in completion, coding, and horizontal placement.
Pass	Perform all Topology and Data Integrity Checks

Table 9 - A subset of the high-level steps from Dewberry's Production and QA/QC checklist performed for this project.

DATA CLASSIFICATION AND EDITING

Once the calibration, absolute swath vertical accuracy, and relative accuracy of the data was confirmed, Dewberry utilized a variety of software suites for data processing. Data processing included breakline creation to define the land/water interface, automated and manual editing of the lidar tiles, QA/QC, and final formatting of the LAS files.

GeoCue and Terrascan Processing

Next is the setup of the GeoCue project, which is done by importing a project defined tile boundary index encompassing the entire project area. The acquired 3D laser point clouds, in LAS binary format, were imported into the GeoCue project and tiled according to the project tile grid. Once tiled, the laser points were classified using a proprietary routine in TerraScan to create the initial automated ground and bathy bottom classifications, using the final project classification schema.

This routine classifies any obvious low outliers in the dataset to class 7 and high outliers in the dataset to class 18. Points along flight line edges that are geometrically unusable are identified as withheld and classified to a separate class so that they will not be used in the initial ground algorithm. After points that could negatively affect the ground are removed from class 1, the ground layer is extracted from this remaining point cloud. The ground extraction process encompassed in this routine takes place by building an iterative surface model.

This surface model is generated using three main parameters: building size, iteration angle and iteration distance. The initial model is based on low points being selected by a "roaming window" with the assumption that these are the ground points. The size of this roaming window is determined by the building size parameter. The low points are triangulated and the remaining points are evaluated and subsequently added to the model if they meet the iteration angle and distance constraints. This process is repeated until no additional points are added within iterations. A second critical parameter is the maximum terrain angle constraint, which determines the maximum terrain angle allowed within the classification model.

The final breaklines defining the land/water interface are then used to perform refraction correction and classify "ground" points within the water breaklines as bathymetric bottom. The breaklines are also used as part of the classification routines to ensure water surface and water column points are classified correctly.

Each tile was then imported into Terrascan and a surface model was created to examine the ground (class 2) and bathy bottom (class 40) classification. Dewberry analysts employ 3D visualization techniques to view the point cloud at multiple angles and in profile to ensure that non-ground points are removed from the ground classification and that class 40 accurately represents submerged topography. Dewberry analysts visually reviewed the surface models and corrected errors in the ground classification such as vegetation, buildings, and bridges that were

present following the initial processing conducted by Dewberry. Common errors in the bathymetric classification that were corrected by Dewberry include some of the issues outlined below.

The lidar tiles were classified to the following classification schema:

- Class 1 = Unclassified, used for all other features that do not fit into the Classes 2, 7, 9, 10, 17, or 18, including vegetation, buildings, etc.
- Class 2 = Bare-Earth Ground
- Class 7 = Low Noise
- Class 9 = Water, points located within collected breaklines
- Class 10 = Ignored Ground due to breakline proximity
- Class 17 = Bridge Decks
- Class 18 = High Noise
- Class 40 = Bathymetric Bottom
- Class 41 = Water Surface
- Class 45 = No bathymetric bottom found (water column)

Special attention was given along shorelines or the land/water interface as no hard edges or seams should exist between ground and bathy bottom.






Figure 15 - The land water interface should be seamless with no hard edges or seamlines. The topobathy surface model is shown in the top image with a profile location overlaid. The LAS profile is shown in the bottom image where bathy bottom points are green, water surface points are blue, ground points are orange, and unclassified points are grey.

Areas of rapids or swift moving water may also need to be removed from the bathy bottom class as these may be surface or water column points and not bathy bottom points due to the water movement and stirring of sediment (increased turbidity). When possible, color orthos were used to help determine water clarity and likelihood of full penetration to the submerged bottom. Generally, editors looked for consistency in data, especially continuous topography (connecting the dots method to ensure channel geometry is reasonable).

Special attention was given in deeper areas where there may not be any true bathy bottom points, but the automated algorithm classified lower water column points as bathy bottom. When evaluating points to determine if they are low water column points or true bathy bottom, the following rules were used as guidelines to maintain accuracy and consistency:

1. Gradient consistency-if the points are part of consistent gradients or consistent channel geometry, they are more likely to be bathy bottom rather than low water column noise. Conversely, points that would cause abrupt changes or inconsistency in the overall gradient or channel geometry are less likely to be bathy bottom points, especially if the abrupt change would result in shallower (higher) bathy bottom points above lower bathy bottom points with a high confidence.




Figure 16 - Bathy Bottom points (green) are shown with water column (dark blue) and water surface points (light blue) in this profile. The four water column points circled in red would cause inconsistent and upward changes in the topobathy model if these points were classified to bathy bottom. These points should remain classified as water column.



Figure 17 - Bathy Bottom points (green) are shown with water column (dark blue) and water surface points (light blue) in this profile. The bathy bottom points circled in red are isolated, but maintain a consistent gradient with other bathy bottom points to the east. These points should remain classified as bathy bottom.

Bridge decks are classified to class 17 using bridge breaklines compiled by Dewberry. Overage points are then identified in Terrascan and GeoCue is used to set the overlap bit for the overage points and the withheld bit is set on the withheld points previously identified in Terrascan before the ground classification routine was performed.

After manual classification, the LAS tiles were peer reviewed and then underwent a final QA/QC. After the final QA/QC and corrections, all headers, appropriate point data records, and variable length records, including spatial reference information, are updated in GeoCue software and then verified using proprietary Dewberry tools.

Submerged Objects

No submerged objects were identified during editing and review of the lidar data, therefore no points were classified to class 43 or class 44.

Temporal Changes

Changes in the bathymetric bottom surface can result from differences between collection periods due to factors such as currents moving sediment. However, Dewberry did not identify any significant temporal changes in this project.

Lidar Qualitative Assessment

Dewberry's qualitative assessment utilizes a combination of statistical analysis and interpretative methodology or visualization to assess the quality of the data for a bare-earth digital terrain model (DTM). This includes creating pseudo image products such as lidar orthos produced from the intensity returns, Triangular Irregular Network (TIN)'s, Digital Elevation Models (DEM) and 3-dimensional models as well as reviewing the actual point cloud data. This process looks for anomalies in the data, areas where man-made structures or vegetation points may not have been classified properly to produce a bare-earth model, and other classification errors. This report will present representative examples where the lidar and post processing had issues as well as examples of where the lidar performed well.

VISUAL REVIEW

The following sections describe common types of issues identified in lidar data and the results of the visual review for the Everglades National Park lidar project.

NIR Depressions

Marsh areas within the project contain east-west strips of minimally "depressed" NIR data at nadir. The cause of these artifacts is due to incorrect range values due to highly reflective, extremely shallow water. This is evident in the NIR intensities – where this artifact occurs in the NIR intensity is very bright. This bright strip of nadir intensity is a typical signature of a wetter surface. Due to the extremely high intensity, the intensity based range corrections become less valid. Since the water has no depth, the green data is not lower than the NIR, thus the artifact

appears. Dewberry minimized these NIR depressions by filtering based on the scan angle and intensity properties, the relationship of the NIR below the green dataset, and its isolation within a single flightline's points. An example is shown below.




Figure 18 – Tile 17RNJ130080. NIR depressions originally identified in the initial ground DEMs (top image). These locations are represented by very bright strips in the NIR intensity imagery (middle image). Filtering methods resulted in minimized effects of the NIR depressions (bottom image).

Excessive Vegetation

Dewberry identified locations of very dense low-lying vegetation within the project area. These low lying features are extremely difficult for the automated algorithms to detect as non-ground and must be removed manually. The higher points were removed from ground and the lower points were left as ground due to the difficulty of delineating where the true ground ended and

the low-lying vegetation began. An example of this low-lying vegetation in the project area is shown below.






Figure 19 – Tile 17RNH340960. Bare earth topobathy DEM showing location of low-lying dense vegetation in Everglades National Park (top image). The LAS profile (bottom image) shows higher points were removed from ground and the lower points were left as ground in the final classification schema.

Bridge Removal Artifacts

The DEM surface models are created from TINs or Terrains. TIN and Terrain models create continuous surfaces from the inputs. Because a continuous surface is being created, the TIN or Terrain will use interpolation to continue the surface beneath the bridge where no lidar data was acquired. Locations where bridges were removed will generally contain less detail in the bare-earth surface because these areas are interpolated.






Figure 20 –Tile number 17RNJ390090. The DEM in the bottom view shows an area where a bridge has been removed from ground. The surface model must make a continuous model and in order to do so, points are connected through interpolation. This results in less detail where the surface must be interpolated. The profile in the top view shows the lidar points of this particular feature colored by class. All bridge points (green) have been removed from ground (orange) and are classified as bridge deck.

Culverts and Bridges

Bridges have been removed from the bare earth surface while culverts remain in the bare earth surface. In instances where it is difficult to determine if the feature is a culvert or bridge, such as with some small bridges, Dewberry erred on assuming they would be culverts especially if they are on secondary or tertiary roads. Below is an example of a culvert that has been left in the ground surface.






Figure 21 – Tile number 17RNJ390090. Profile with points colored by class (class 1=grey, class 2=orange) is shown in the top view and the DEM is shown in the bottom view. This culvert remains in the bare earth surface. Bridges have been removed from the bare earth surface and classified to class 17.

Flight line Ridges

Ridges occur when there is a difference between the elevations of adjoining flight lines or swaths. Some flight line ridges are visible in the final DEMs but they do not exceed the project specifications and the overall relative accuracy requirements for the project area have been met. An example of a visible ridge that is within tolerance is shown below.




Figure 22 – Tile number 17RNJ200070. The flight line ridge is less than 8 cm. Overall, the Florida Everglades National Park lidar data meets the project specifications for 8 cm RMSE relative accuracy.

Formatting

After the final QA/QC is performed and all corrections have been applied to the dataset, all lidar files are updated to the final format requirements and the final formatting, header information, point data records, and variable length records are verified using Dewberry proprietary tools. The table below lists some of the main lidar header fields that are updated and verified.

Classified Lidar Formatting		
Parameter	Requirement	Pass/Fail
LAS Version	1.4	Pass
Point Data Format	Format 6	Pass
Coordinate Reference System	NAD83 (2011) UTM Zone 17N, meters and NAVD88 (Geoid 12B), meters in WKT Format	Pass
Global Encoder Bit	Should be set to 17 for Adjusted GPS Time	Pass
Time Stamp	Adjusted GPS Time (unique timestamps)	Pass
System ID	Should be set to the processing system/software and is set to NIIRS10 for GeoCue software	Pass
Multiple Returns	The sensor shall be able to collect multiple returns per pulse and the return numbers are recorded	Pass
Intensity	16 bit intensity values are recorded for each pulse	Pass
Classification	Required Classes include: Class 1: Unclassified Class 2: Ground Class 7: Low Noise Class 9: Water Class 17: Bridge Deck Class 18: High Noise Class 40: Bathymetric Bottom Class 41: Water Surface Class 45: No bathymetric bottom found (water column)	Pass
Overlap and Withheld Points	Overlap (Overage) and Withheld points are set to the Overlap and Withheld bits	Pass
Scan Angle	Recorded for each pulse	Pass
XYZ Coordinates	Unique Easting, Northing, and Elevation coordinates are recorded for each pulse	Pass

Derivative Lidar Products

USGS required several derivative lidar products to be created. Each type of derived product is described below.

INTENSITY IMAGERY

Full point cloud intensity images were generated in the GeoCue software of both the Green sensor and the Near Infrared (NIR) sensor data. Each image contains a respective world file to georeference the raster map image. Intensity images are delivered in 8-bit, 256 color gray scale, and GeoTIFF format.

The NIR intensity imagery contains strips of data drop-outs in localized areas. An example of this is shown below. These data drop-outs do not impact the usability of the final lidar data as these data are present in the Green lidar data; the full point cloud consists of data from both the NIR and Green lidar sensors.



Figure 23 – The intensity imagery of the NIR sensor data contain small black strips in several localized areas. These strips are where drop-outs occurred during collection of the NIR data. This does not impact the coverage of the lidar and is only visible in the intensity imagery of the NIR sensor data. The Green sensor lidar data was combined with the NIR sensor lidar data to create complete coverage of the lidar point cloud. The combined data has been verified to meet project specifications. There are no detrimental effects to the DEM or any derivative products aside from the artifacts in the NIR intensity imagery.

LOW-CONFIDENCE POLYGONS

Low confidence polygons have been delivered with this dataset. These polygons represent areas where heavy vegetation greatly diminishes penetration of the lidar pulse, resulting in a bare earth surface that is potentially less accurate due to the lack of lidar returns from the ground beneath the vegetation. Low confidence polygons delineate areas where conformance to VVA standards may not be met. The low confidence polygons created for this dataset were delineated according to the criteria and assumptions outlined in the ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014). Low confidence areas are identified using a ground density raster. All areas with a Nominal Ground Point Density less than a specified threshold are

identified as low confidence cells in the ground density raster. The low confidence cells are exported to polygons and aggregated into larger shapes. Areas of expected low density in the ground, such as water or where buildings/structures have been removed, are deleted from the aggregated low confidence polygons. The size of all polygons are then calculated and polygons below the minimum size threshold are removed from the final low confidence polygon dataset.

Lidar Positional Accuracy

BACKGROUND

Dewberry quantitatively tested the dataset by testing the vertical accuracy of the lidar. The vertical accuracy is tested by comparing the discrete measurement of the survey checkpoints to that of the interpolated value within the three closest lidar points that constitute the vertices of a three-dimensional triangular face of the TIN. Therefore, the end result is that only a small sample of the lidar data is actually tested. However there is an increased level of confidence with lidar data due to the relative accuracy. This relative accuracy in turn is based on how well one lidar point "fits" in comparison to the next contiguous lidar measurement, and is verified as part of the initial processing. If the relative accuracy of a dataset is within specifications and the dataset passes vertical accuracy requirements at the location of survey checkpoints, the vertical accuracy results can be applied to the whole dataset with high confidence due to the passing relative accuracy. Dewberry typically uses LP360 software to test the swath lidar vertical accuracy, Terrascan software to test the classified lidar vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project.

Dewberry also tests the horizontal accuracy of lidar datasets when checkpoints are photo-identifiable in the intensity imagery. Photo-identifiable checkpoints in intensity imagery typically include checkpoints located at the ends of paint stripes on concrete or asphalt surfaces or checkpoints located at 90 degree corners of different reflectivity, e.g. a sidewalk corner adjoining a grass surface. The XY coordinates of checkpoints, as defined in the intensity imagery, are compared to surveyed XY coordinates for each photo-identifiable checkpoint. These differences are used to compute the tested horizontal accuracy of the lidar. As not all projects contain photo-identifiable checkpoints, the horizontal accuracy of the lidar cannot always be tested.

SURVEY VERTICAL ACCURACY CHECKPOINTS

For the vertical accuracy assessment, one hundred thirty eight (138) check points were surveyed for the project and are located within bare earth/open terrain, grass/weeds/crops, forested/fully grown, and submerged topography land cover categories. Please see appendix A to view the survey report which details and validates how the survey was completed for this project.

Checkpoints were evenly distributed throughout the project area so as to cover as many flight lines as possible using the "dispersed method" of placement.

All checkpoints surveyed for vertical accuracy testing purposes are listed in the following table.

Point ID	NAD83 (2011) UTM Zone 17N		NAVD88 (Geoid 12B)
	Easting X (m)	Northing Y (m)	Elevation (m)
100	543079.597	2836710.724	3.385

101	547314.001	2837248.061	1.607
102	546793.713	2835637.593	1.606
103	545750.175	2832407.957	2.17
104	542664.056	2832427.138	2.338
106	542756.182	2822474.292	3.203
107	542810.294	2817792.76	2.856
108	542866.728	2812729.445	1.818
118	520306.625	2800382.673	0.883
120	527594.236	2808089.378	0.34
122	533607.061	2808098.151	1.293
123	541002.767	2807498.292	0.887
124	543836.915	2805488.588	1.023
125	543714.578	2800572.493	1.19
126	547816.23	2804003.615	2.227
128	550898.076	2806522.064	1.086
129	553937.03	2806554.035	1.304
130	555680.231	2797122.754	0.655
131	550957.355	2799162.547	0.543
148	515034.473	2788702.555	0.862
150	520348.953	2793107.853	0.66
158	530381.44	2849373.802	3.25
161	523434.366	2837818.879	1.865
413	544411.242	2807928.587	2.233
414	546485.02	2806069.545	2.482
415	547771.676	2801713.161	2.099
417	538007.777	2806509.318	0.82
105	542686.165	2827526.839	2.288
109	543026.282	2809128.916	2.262
110	538851.84	2809933.277	1.318
111	535509.582	2811173.343	1.646
112	532162.45	2811832.531	1.669
113	528735.225	2813307.196	1.679
114	524791.751	2813000.11	1.27
115	523030.728	2812348.82	1.351
116	521825.291	2813724.038	1.082
117	518134.545	2805267.915	0.979
119	520171.164	2796284.377	0.952
121	531554.389	2806039.417	1.323
127	550179.266	2808610.684	0.809
132	514356.183	2849179.277	2.747
133	517304.704	2849334.301	4.19
134	519410.489	2849313.902	3.999
135	520397.028	2849187.798	2.967

136	522567.263	2849303.614	3.006
137	523518.875	2848795.892	3.015
143	506861.664	2848776.82	2.127
144	496434.481	2849026.74	2.45
145	500665.487	2849055.652	2.054
146	495246.924	2844988.406	0.798
147	512625.154	2787190.341	0.913
149	517775.761	2790677.638	0.951
151	544035.935	2849277.208	2.608
152	549985.732	2849319.656	2.931
153	525217.978	2849354.404	3.43
154	526026.249	2849358.576	3.372
155	527568.517	2849370.059	3.347
156	528720.247	2849370.459	3.373
157	529581.786	2849351.2	3.847
159	531651.615	2849371.261	3.774
160	532739.336	2849294.568	3.482
416	537995.121	2808117.983	1.811
138	512703.238	2843726.494	1.547
139	517995.585	2844025.513	1.771
140	521738.093	2843803.256	1.639
141	509960.513	2838598.562	0.797
142	514924.281	2838695.4	1.283
200	543237.474	2840111.177	1.381
201	550231.757	2840322.079	1.689
202	539299.42	2833878.331	1.422
203	534056.345	2831173.018	1.205
204	532428.572	2826333.015	1.193
205	538753.233	2826656.368	1.366
206	538665.872	2820200.088	1.058
207	534162.987	2819992.3	1.209
208	529540.564	2819935.575	0.936
209	523091.995	2819564.126	0.331
210	538659.449	2815534.591	1.168
211	520050.151	2808392.485	0.257
212	525060.416	2800464.228	0.045
213	529435.811	2800873.868	0.256
214	534339.091	2800656.344	-0.088
215	538619.367	2800661.432	0.119
216	548069.554	2796730.626	-0.382
217	543208.971	2795917.093	-0.383
218	537220.334	2794739.962	-0.324
219	531952.194	2794966.41	-0.46

Everglades National Park Lidar

TO# G16PD01224

August 30, 2018

Page 38 of 165

220	529450.003	2790382.642	-0.452
221	524870.159	2794754.582	-0.369
222	520378.161	2838820.216	1.388
223	508007.545	2833812.838	0.283
224	514368.828	2834083.566	1
225	518816.481	2833409.753	1.043
226	503114.788	2828624.583	-0.155
227	509064.102	2828621.425	0.39
228	515997.196	2828393.11	0.759
229	499924.975	2824548.14	-0.181
230	508657.9	2824597.494	0.15
231	515466.944	2824466.811	0.433
232	505811.959	2820918.29	-0.186
233	505010.513	2844273.373	1.208
234	503130.446	2838283.069	0.407
235	495637.561	2839248.012	0.092
236	489696.599	2840072.175	-0.296
237	495068.279	2834814.668	-0.29
238	513115.321	2787735.451	-0.16
239	520415.845	2792098.225	-0.405
240	537823.674	2790559.953	-0.56
241	551893.47	2794082.512	-0.276
242	537786.183	2846853.293	1.439
243	543006.735	2845977.712	1.448
244	497670.07	2828390.52	-0.148
245	484791.681	2840655.307	-0.339
246	524886.565	2841735.417	1.417
247	531701.478	2840691.659	1.426
248	523019.874	2834496.691	1.144
249	532535.427	2835048.148	1.404
250	520898.525	2828596.78	0.781
251	527135.739	2827894.78	0.976
252	512772.221	2817421.751	-0.044
253	511048.181	2808496.606	-0.248
500	539946.127	2809333.181	-0.101
501	539720.076	2809443.736	-0.423
502	539281.652	2809708.186	-0.154
503	539060.758	2809809.728	-0.142
504	522668.671	2812703.647	0.003
505	522392.072	2812835.414	-0.057
506	522042.29	2813105.88	-0.182
507	522506.886	2811759.157	-0.172
508	518380.972	2805881.605	-0.32

509	519662.323	2791919.961	-0.46
510	537914.168	2806302.845	-0.115
511	537843.535	2806091.929	-0.045
512	537595.323	2805784.184	-0.193
513	537508.596	2805542.112	-0.148
514	537325.004	2805257.624	-0.625
515	542942.854	2806822.562	-0.139
516	542940.397	2806294.073	-0.25

Table 10 - USGS FL Everglades National Park lidar surveyed accuracy checkpoints.

One hundred and thirty-eight checkpoints were surveyed for vertical accuracy testing. One checkpoint (NVA-413) was removed from testing due to its location outside of the project boundary.



Figure 24 – Checkpoint NVA-413 (green) was removed from accuracy testing because it was located outside of the project boundary (red).

Project specifications do not require bathymetric accuracy testing. Seventeen (17) points were surveyed for bathymetric accuracy testing (Point ID 500 – 516). Dewberry used these checkpoints for internal production processing, however these points were not survey grade and were not used for final bathymetric accuracy testing in the project area. An example of a bathymetric point removed from accuracy testing is shown below.



Figure 25 – Survey photos of bathy checkpoint 501 shown above. Bathymetric checkpoints 500 through 516 were removed from accuracy testing because they were determined to not be survey grade.

The figure below shows the location of the QA/QC checkpoints used to test the positional accuracy of the dataset.




Figure 26 – Location of QA/QC Checkpoints

VERTICAL ACCURACY TEST PROCEDURES

NVA (Non-vegetated Vertical Accuracy) is determined with check points located only in non-vegetated terrain, including open terrain (grass, dirt, sand, and/or rocks) and urban areas, where there is a very high probability that the lidar sensor will have detected the bare-earth ground surface and where random errors are expected to follow a normal error distribution. The NVA determines how well the calibrated lidar sensor performed. With a normal error distribution, the vertical accuracy at the 95% confidence level is computed as the vertical root mean square error ($RMSE_z$) of the checkpoints x 1.9600. For the Florida Everglades National Park lidar project, vertical accuracy must be 19.6 cm or less based on an $RMSE_z$ of 10 cm x 1.9600.

VVA (Vegetated Vertical Accuracy) is determined with all checkpoints in vegetated land cover categories, including tall grass, weeds, crops, brush and low trees, and fully forested areas, where there is a possibility that the lidar sensor and post-processing may yield elevation errors that do not follow a normal error distribution. VVA at the 95% confidence level equals the 95th

percentile error for all checkpoints in all vegetated land cover categories combined. The Florida Everglades National Park Lidar Project VVA standard is 29.4 cm based on the 95th percentile. The VVA is accompanied by a listing of the 5% outliers that are larger than the 95th percentile used to compute the VVA; these are always the largest outliers that may depart from a normal error distribution. Here, Accuracy_z differs from VVA because Accuracy_z assumes elevation errors follow a normal error distribution where RMSE procedures are valid, whereas VVA assumes lidar errors may not follow a normal error distribution in vegetated categories, making the RMSE process invalid.

The relevant testing criteria are summarized in Table 11.

Quantitative Criteria	Measure of Acceptability
Non-Vegetated Vertical Accuracy (NVA) in open terrain and urban land cover categories using RMSE _z *1.9600	19.6 cm (based on RMSE _z (10 cm) * 1.9600)
Vegetated Vertical Accuracy (VVA) in all vegetated land cover categories combined at the 95% confidence level	29.4 cm (based on combined 95 th percentile)

Table 11 – Acceptance Criteria

The primary QA/QC vertical accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry’s team surveyed QA/QC vertical checkpoints in accordance with the project’s specifications.
2. Next, Dewberry interpolated the topobathy lidar DEM to provide the z-value for every checkpoint.
3. Dewberry then computed the associated z-value differences between the interpolated z-value from the lidar data and the ground truth survey checkpoints and computed NVA and VVA accuracy and other statistics.
4. The data were analyzed by Dewberry to assess the accuracy of the data. The review process examined the various accuracy parameters as defined by the scope of work. The overall descriptive statistics of each dataset were computed to assess any trends or anomalies. This report provides tables, graphs and figures to summarize and illustrate data quality.

VERTICAL ACCURACY RESULTS

The table below summarizes the tested vertical accuracy resulting from a comparison of the surveyed checkpoints to the elevation values present within the fully classified lidar LAS files.

Land Cover Category	# of Points	NVA – Non-vegetated Vertical Accuracy (RMSE _z x 1.9600) Spec=19.6 cm	VVA – Vegetated Vertical Accuracy (95 th Percentile) Spec=29.4 cm
NVA	61	7	
VVA	59		35

Table 12 – Tested Vertical Accuracy

The topographic portion of this lidar dataset was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm RMSE_z Vertical Accuracy Class. Actual NVA accuracy was found to be RMSE_z = 3.6 cm, equating to +/- 7 cm at 95% confidence level. Actual VVA accuracy was found to be +/- 35 cm at the 95th percentile. The bathymetric portion of this lidar dataset was not tested.

As a result of the failing final VVA accuracy calculation of 35 cm, Dewberry did an in-depth analysis of the checkpoints. Five (5) VVA checkpoints had high Delta Z values when compared to all of the VVA checkpoint Delta Z values from the lidar accuracy testing. They are shown in the table below, as well as some of the survey field photos. The survey field photos show that neither light nor lidar pulses can penetrate through some of the dense vegetation.

Point ID	NAD83 (2011) UTM Zone 17N		NAVD88 (Geoid 12B)	Lidar Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
214	534339.091	2800656.344	-0.088	0.230	0.318	0.318
216	548069.554	2796730.626	-0.382	0.110	0.492	0.492
217	543208.971	2795971.093	-0.383	-0.030	0.353	0.353
238	513115.321	2787735.451	-0.160	0.190	0.350	0.350
239	520415.845	2792098.225	-0.405	0.090	0.495	0.495

Table 13 – VVA checkpoints with high Delta Z values.



Figure 27 – VVA Point 216. The top two images show the dense vegetation at the survey tripod location. The lidar profile (bottom image) shows the lidar could not penetrate through the dense vegetation to the location of point 216 (pink).



Figure 28 – VVA Point 238. The two images show the dense vegetation at the survey tripod location.



Figure 29 – VVA Point 239. The top two images show the dense vegetation at the survey tripod location. The lidar profile (bottom image) shows the lidar could not penetrate through the dense vegetation to the location of point 239 (pink).

The points identified above revealed a trend of points with high Delta Z values based on land cover type in Everglades National Park. Dewberry also performed a comparison of the topobathy raster elevations versus a plumb-bob survey covering the extents of the North AOI delivery. The plumb-bob survey points were provided by USGS and National Park Service. The results of this comparison also showed a trend of points with high Delta Z values based on land cover type. Further information can be found in the separate plumb-bob comparison report. Below is an image of the location of the plumb-bob survey points covering the extents of the North AOI.




Figure 30 – Screenshot from the NPS of their comparison between HAED points elevations and the elevations of the delivered Everglades North AOI DEMs. Differences (DZ) are shown in centimeters.

Below is a statistics summary table from the plumb-bob comparison report, showing various land cover types in the North AOI and the corresponding accuracy values of the topobathy raster/plumb-bob point comparison.

	Shark River Slough	Coastal Mangroves	All Points without Slough and Mangroves	All Points Combined
# of Points	2659	998	5360	9017
RMSE	0.258	0.407	0.182	0.240
Mean	0.202	0.361	0.132	0.178
Median	0.176	0.330	0.119	0.152
Skew	0.529	0.692	0.425	0.882
Std Dev	0.160	0.188	0.125	0.161
Min	-0.376	-0.290	-0.481	-0.481
Max	0.945	1.012	0.973	1.012
Kurtosis	0.563	0.849	1.714	1.924
NVA (AccuracyZ)	0.505	0.799	0.356	0.470
VVA (95th Percentile)	0.495	0.732	0.345	0.473

Table 14 – Statistics summary of point distribution (meters) in the North AOI of the Everglades project.

Dewberry understood when entering this lidar project that vegetation coverage and density would provide a challenge for lidar in the environment of Everglades National Park.

The green wavelength topobathymetric lidar sensor while capable of mapping topography, is optimized for bathymetric measurements. Due to its larger beam divergence / spot size and scan pattern, in some areas it may have difficulty recording ground measurements through dense

vegetation. The NIR topographic sensor is optimized for topographic surveying, and with its narrow beam divergence and multiple look angles is much more likely to penetrate dense vegetation. The combination of the two sensors leads to the ideal case of both recording shallow water bathymetric returns (where otherwise the NIR would record water surface elevation or no information at all), and penetrating dense vegetation.

The acquisition plan was optimized for bathymetric measurements. The above ground altitude (AGL) of 400m is not ideal for efficient broad area topographic collects due to the increased flight times, but it is optimal for achieving bathymetric results with the VQ-820G. Additionally this low altitude increases point densities for both scanners and thus increases the statistical likelihood of ground measurements.

Taking into account the sensor optimization parameters configured for the Florida Everglades National Lidar Project, the unique land cover types in the project area, and the VVA accuracy points with high Delta Z values, Dewberry determined the final VVA accuracy calculation of 35 cm to be justified. The NVA accuracy passes specifications for the project area, showing the usability of the lidar data is valid. The high Delta Z values are correlated to land cover types found in Everglades National Park. Dewberry plans to address the VVA accuracy by adjusting the standard operating procedures of the low-confidence polygons to account for these land cover types in the future. Further information on this discussion can be found in the separate plumb-bob comparison report.

The figure below illustrates the magnitude of the differences between the QA/QC checkpoints and lidar data. This shows that the majority of lidar elevations were within +/- 20 cm of the checkpoints elevations, but there were some outliers where lidar and checkpoint elevations differed by up to +50 cm. The line graph below also shows a clear separation between NVA and VVA checkpoints, further illustrating the dataset achieves good vertical accuracy in non-vegetated areas but that the lidar had poorer penetration in dense vegetated areas.




Figure 31 – Magnitude of elevation discrepancies per land cover category

Table 15 lists the 5% outliers that are larger than the VVA 95th percentile.

Point ID	NAD83 (2011) UTM Zone 17N		NAVD88 (Geoid 12B)	Lidar Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
216	548069.554	2796730.626	-0.382	0.110	0.492	0.492
217	543208.971	2795971.093	-0.383	-0.030	0.353	0.353
239	520415.845	2792098.225	-0.405	0.090	0.495	0.495

Table 15 – 5% Outliers

Table 16 provides overall descriptive statistics.

100 % of Totals	# of Points	RMSEz (m) Spec=0.10 m NVA	Mean (m)	Median (m)	Skew	Std Dev (m)	Kurtosis	Min (m)	Max (m)
NVA	61	0.036	-0.001	0.001	0.328	0.036	0.650	0.094	0.103
VVA	59	N/A	0.138	0.127	1.306	0.110	2.309	0.039	0.495

Table 16 – Overall Descriptive Statistics

The figure below illustrates a histogram of the associated elevation discrepancies between the QA/QC checkpoints and elevations interpolated from the lidar triangulated irregular network (TIN). The frequency shows the number of discrepancies within each band of elevation differences. Although the discrepancies vary between a low of -0.094 meters and a high of +0.495 meters, the histogram shows that the majority of the discrepancies are skewed on the positive side. The vast majority of points are within the ranges of -0.05 meters to +0.15 meters.




Figure 32 – Histogram of Elevation Discrepancies with errors in meters

Based on the vertical accuracy testing conducted by Dewberry, the lidar dataset for the USGS Florida Everglades National Park Lidar Project satisfies the project’s pre-defined vertical accuracy criteria for the NVA testing. However, the VVA testing does not meet the project’s pre-defined vertical accuracy criteria.

HORIZONTAL ACCURACY TEST PROCEDURES

Horizontal accuracy testing requires well-defined checkpoints that can be identified in the dataset. Elevation datasets, including lidar datasets, do not always contain well-defined checkpoints suitable for horizontal accuracy assessment. However, the ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) recommends at least half of the NVA vertical check points should be located at the ends of paint stripes or other point features visible on the lidar intensity image, allowing them to double as horizontal check points.

Dewberry reviews all NVA checkpoints to determine which, if any, of these checkpoints are located on photo-identifiable features in the intensity imagery. This subset of checkpoints are then used for horizontal accuracy testing.

The primary QA/QC horizontal accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry’s team surveyed QA/QC vertical checkpoints in accordance with the project’s specifications and tried to locate half of the NVA checkpoints on features photo-identifiable in the intensity imagery.

2. Next, Dewberry identified the well-defined features in the intensity imagery.
3. Dewberry then computed the associated xy-value differences between the coordinates of the well-defined feature in the lidar intensity imagery and the ground truth survey checkpoints.
4. The data were analyzed by Dewberry to assess the accuracy of the data. Horizontal accuracy was assessed using NSSDA methodology where horizontal accuracy is calculated at the 95% confidence level. This report provides the results of the horizontal accuracy testing.

HORIZONTAL ACCURACY RESULTS

No checkpoints were photo-identifiable in the intensity imagery, horizontal accuracy could not be tested on this dataset.

DEM Processing & Qualitative Assessment

The final topobathy DEMs are IMG format with 0.5 meter pixel cell size, tiled, named according to project specifications. Inland water voids and topobathy voids were enforced in the DEMs so that bathymetric areas where no bathymetry was collected are NoData in the DEMs.

DEM GENERATION

After the final void polygons (inland water voids and topobathy voids) are created and imported into the terrain GDB, a multipoint feature class was created from all lidar bathymetric bottom and bare earth ground points. Next, a terrain was created using the multipoint feature class and final void polygon layers. The void polygons are used in the terrain as “soft erase” features. This ensures that bathymetric areas where there are no bathymetric bottom points will be set as NoData in the DEM. After the terrain processed, the Arc tool Terrain to Raster was used to create the final topobathy DEM. The DEM is then split into individual tiles following the project tiling scheme.

The creation of first return DSMs follows a similar workflow as required for bare earth DEMs, except that void polygons are not applied to the first return terrain. Additionally, rather than ground only data, the first return of all point classes, except for low noise (class 7), high noise (class 18), bathy bottom (class 40), and water column (class 45), are used to create the multipoint file and subsequent terrain. Review of the DSMs includes looking for spikes, divots, or noise points not properly classified to the noise classes (class 7 and class 18), other lidar misclassifications, and processing artifacts. As void polygons are not used in DSMs, DSMs are interpolated across hydrologic features. After corrections are applied, the DSM is then split into individual tiles following the project tiling scheme. The tiles are verified for final formatting and then loaded into Global Mapper to ensure no missing or corrupt tiles and to ensure seamlessness across tile boundaries.

DEM QUALITATIVE REVIEW

Dewberry performed a comprehensive qualitative assessment of the topobathy DEM deliverables to ensure that all tiled DEM products were delivered with the proper extents, formatting, and contained the proper referencing information. This process was performed in ArcGIS software with the use of a tool set Dewberry has developed to verify that the raster extents match those of the tile grid, are formatted correctly, and contain the correct coordinate reference system information.

The final topobathy DEMs are then reviewed in Global Mapper at a 1:3000 scale. A review with the void polygons visible and another review without the void polygons visible was performed in order to ensure voids were enforced properly and there were no issues along the boundaries of the void layer. Special attention was given along the land/water interface to ensure there were no hard edges along the interface. Any remaining lidar issues and DEM artifacts were flagged by the reviewer and corrected by the editing team as necessary.

The images below show an example of a topobathy DEM and first return DSM of the same tile.




Figure 33 - Tile 17RNJ400070. The bare earth DEM is shown on the left while the first return DSM is shown on the right




Figure 34 - DEM tile 17RNH420900. An example of the land-water interface is shown. No hard edges along the interface were identified during DEM QA/QC.

When some bridges are removed from the ground surface, the distance from bridge abutment to bridge abutment is small enough that the DEM interpolates across the entire bridge opening,

forming 'bridge saddles.' Dewberry collected 3D bridge breaklines in locations where bridge saddles were present and enforced these breaklines in the final DEM creation to help mitigate the bridge saddle artifacts. The image below on the left shows a bridge saddle while the image below on the right shows the same bridge after bridge breaklines have been enforced.




Figure 35 – Tiles 17RNJ530060 and 17RNJ540060. The DEM on the left shows a bridge saddle artifact while the DEM on the right shows the same location after bridge breaklines have been enforced.

DEM QUANTITATIVE ASSESSMENT

The same 120 checkpoints that were used to test the vertical accuracy of the lidar were used to validate the vertical accuracy of the final DEM products as well. Accuracy results may vary between the source lidar and final DEM deliverable. DEMs are created by averaging several lidar points within each pixel which may result in slightly different elevation values at each survey checkpoint when compared to the source LAS, which does not average several lidar points together but may interpolate (linearly) between two or three points to derive an elevation value. The vertical accuracy of the DEM is tested by extracting the elevation of the pixel that contains the x/y coordinates of the checkpoint and comparing these DEM elevations to the surveyed elevations. Dewberry typically uses LP360 software to test the swath lidar vertical accuracy, Terrascan software to test the classified lidar vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project.

The survey checkpoints used to test this topobathymetric dataset are listed in the survey report included as Appendix A.

Table 17 summarizes the tested vertical accuracy results from a comparison of the surveyed checkpoints to the elevation values present within the final DEM dataset.

Land Cover Category	# of Points	NVA – Non-vegetated Vertical Accuracy (RMSE _z x 1.9600) Spec=19.6 cm	VVA – Vegetated Vertical Accuracy (95th Percentile) Spec=29.4 cm
NVA	61	6.8	
VVA	59		34.8

Table 17 – DEM tested NVA and VVA

The topographic portion of this DEM dataset was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm RMSE_z Vertical Accuracy Class. Actual NVA accuracy was found to be RMSE_z =3.5 cm, equating to +/- 6.8 cm at 95% confidence level. Actual VVA accuracy was found to be +/- 34.8 cm at the 95th percentile. The bathymetric portion of this DEM dataset was not tested. A more in-depth analysis of the VVA accuracy testing results can be found in the lidar vertical accuracy section of this report.

Table 18 lists the 5% outliers that are larger than the VVA 95th percentile.

Point ID	NAD83 (2011) UTM Zone 17N		NAVD88 (Geoid 12B)	DEM Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
216	548069.554	2796730.626	-0.382	0.101	0.483	0.483
244	543208.971	2795917.093	-0.383	-0.028	0.355	0.355
239	520415.845	2792098.225	-0.405	0.093	0.498	0.498

Table 18 – 5% Outliers

Table 19 provides overall descriptive statistics.

100 % of Totals	# of Points	RMSE _z (m) Spec=0.1 m NVA	Mean (m)	Median (m)	Skew	Std Dev (m)	Kurtosis	Min (m)	Max (m)
NVA	61	0.035	-0.002	-0.001	0.449	0.035	0.327	-0.079	0.095
VVA	59	N/A	0.144	0.122	1.172	0.112	1.671	-0.032	0.498

Table 19 – Overall Descriptive Statistics

Based on the vertical accuracy testing conducted by Dewberry, the DEM dataset for the USGS Florida Everglades National Park Lidar Project satisfies the project’s pre-defined vertical accuracy criteria for the NVA testing. However, the VVA testing does not meet the project’s pre-defined vertical accuracy criteria.

DEM CHECKLIST

The following table represents a portion of the high-level steps in Dewberry’s DEM Production and QA/QC checklist that were performed for this project.

Pass/Fail	Validation Step
Pass	Final void breakline polygons are created.
Pass	Masspoints (LAS to multipoint) are created from final ground and bathymetric bottom points.
Pass	Masspoints and void breakline polygons are used to create the final topobathymetric terrain.
Pass	Convert terrains to rasters using project specifications for grid type, formatting, and cell size.
Pass	Manually review topobathymetric DEMs to check for issues.
Pass	Special attention should be paid along the land/water interface.
Pass	DEMs should be seamless across tile boundaries.
Pass	Bridges should NOT be present in final topobathy DEMs.
Pass	Any remaining bridge saddles where below bridge breaklines were not used need to be fixed by adding below bridge breaklines and re-processing.
Pass	All qualitative issues present in the DEMs as a result of lidar processing and editing issues must be marked for corrections in the lidar. These DEMs will need to be recreated after the lidar has been corrected.
Pass	Calculate DEM Vertical Accuracy including NVA and VVA Vertical Accuracy and other statistics.
Pass	Split the DEMs into tiles according to the project tiling scheme.
Pass	Verify all properties of the tiled DEMs, including coordinate reference system information, cell size, cell extents, and that compression has not been applied to the tiled DEMs.
Pass	Load all tiled DEMs into Global Mapper to verify complete coverage to the (buffered) project boundary and that no tiles are corrupt.

Table 20 - A subset of the high-level steps from Dewberry's bare earth DEM Production and QA/QC checklist performed for this project.

Optical Imagery

During acquisition of the lidar data, Dewberry acquired optical imagery of the area of interest using a Nikon three-band (Red, Green, and Blue channels) D810 camera when possible throughout the project area. Dewberry performed the aerotriangulation, georeferencing, and conversion to Geotiff format. Dewberry and the client agreed to deliver usable optical imagery collected during acquisition in Geotiff format.

IMAGERY PROCESSING

Dewberry used Geomedia software to convert the image frames from their native sensor format to Geotiff format and to georeference the image frames. The three-band (RGB) imagery has the same coordinate reference system as the lidar data:

Horizontal Datum: The horizontal datum for the project is North American Datum of 1983 with the 2011 Adjustment (NAD 83 (2011))

Coordinate System: UTM Zone 17N

Units: Horizontal units are in meters.

Once Dewberry generated the image frames and world files, photo-center shapefiles were created and all images were verified to load correctly. Image frames found to be unusable after processing are not provided to the client. Below is an example of a set of usable Geotiff image frames for the Florida Everglades National Park Lidar Project.



Figure 36 – A set of usable Geotiff imagery frames collected during acquisition of the project area.

Metadata

Project level metadata files were delivered in XML format for all project deliverables including lidar, DEMs, breaklines, and intensity imagery. All metadata files are FGDC compliant and were verified to be error-free according to the USGS MetaParser.

Appendix A: Checkpoint Survey Report

Please see the report included with this deliverable:
Appendix_A_Checkpoint_Survey_Report

Appendix B: Ground Control Survey Report

Please see the report included with this deliverable:

Appendix_B_Ground_Control_Survey_Report

Appendix C: Complete List of Delivered Tiles

17RNH250800	17RNH320830	17RNH280850	17RNH170870	17RNH300880
17RNH260800	17RNH120840	17RNH290850	17RNH180870	17RNH310880
17RNH270800	17RNH130840	17RNH300850	17RNH190870	17RNH320880
17RNH240810	17RNH140840	17RNH310850	17RNH200870	17RNH330880
17RNH250810	17RNH150840	17RNH320850	17RNH210870	17RNH340880
17RNH260810	17RNH160840	17RNH330850	17RNH220870	17RNH350880
17RNH270810	17RNH170840	17RNH340850	17RNH230870	17RNH360880
17RNH280810	17RNH180840	17RNH350850	17RNH240870	17RNH370880
17RNH290810	17RNH190840	17RNH120860	17RNH250870	17RNH380880
17RNH170820	17RNH200840	17RNH130860	17RNH260870	17RNH120890
17RNH180820	17RNH210840	17RNH140860	17RNH270870	17RNH130890
17RNH200820	17RNH220840	17RNH150860	17RNH280870	17RNH140890
17RNH210820	17RNH230840	17RNH160860	17RNH290870	17RNH150890
17RNH220820	17RNH240840	17RNH170860	17RNH300870	17RNH160890
17RNH230820	17RNH250840	17RNH180860	17RNH310870	17RNH170890
17RNH240820	17RNH260840	17RNH190860	17RNH320870	17RNH180890
17RNH250820	17RNH270840	17RNH200860	17RNH330870	17RNH190890
17RNH260820	17RNH280840	17RNH210860	17RNH340870	17RNH200890
17RNH270820	17RNH290840	17RNH220860	17RNH350870	17RNH210890
17RNH280820	17RNH300840	17RNH230860	17RNH360870	17RNH220890
17RNH290820	17RNH310840	17RNH240860	17RNH370870	17RNH230890
17RNH300820	17RNH320840	17RNH250860	17RNH120880	17RNH240890
17RNH120830	17RNH330840	17RNH260860	17RNH130880	17RNH250890
17RNH160830	17RNH120850	17RNH270860	17RNH140880	17RNH260890
17RNH170830	17RNH130850	17RNH280860	17RNH150880	17RNH270890
17RNH180830	17RNH140850	17RNH290860	17RNH160880	17RNH280890
17RNH190830	17RNH150850	17RNH300860	17RNH170880	17RNH290890
17RNH200830	17RNH160850	17RNH310860	17RNH180880	17RNH300890
17RNH210830	17RNH170850	17RNH320860	17RNH190880	17RNH310890
17RNH220830	17RNH180850	17RNH330860	17RNH200880	17RNH320890
17RNH230830	17RNH190850	17RNH340860	17RNH210880	17RNH330890
17RNH240830	17RNH200850	17RNH350860	17RNH220880	17RNH340890
17RNH250830	17RNH210850	17RNH360860	17RNH230880	17RNH350890
17RNH260830	17RNH220850	17RNH370860	17RNH240880	17RNH360890
17RNH270830	17RNH230850	17RNH120870	17RNH250880	17RNH370890
17RNH280830	17RNH240850	17RNH130870	17RNH260880	17RNH380890
17RNH290830	17RNH250850	17RNH140870	17RNH270880	17RNH390890
17RNH300830	17RNH260850	17RNH150870	17RNH280880	17RNH400890
17RNH310830	17RNH270850	17RNH160870	17RNH290880	17RNH410890

17RNH480890	17RNH140910	17RNH130920	17RNH550920	17RNH530930
17RNH120900	17RNH150910	17RNH140920	17RNH120930	17RNH540930
17RNH130900	17RNH160910	17RNH150920	17RNH130930	17RNH550930
17RNH140900	17RNH170910	17RNH160920	17RNH140930	17RNH560930
17RNH150900	17RNH180910	17RNH170920	17RNH150930	17RNH120940
17RNH160900	17RNH190910	17RNH180920	17RNH160930	17RNH130940
17RNH170900	17RNH200910	17RNH190920	17RNH170930	17RNH140940
17RNH180900	17RNH210910	17RNH200920	17RNH180930	17RNH150940
17RNH190900	17RNH220910	17RNH210920	17RNH190930	17RNH160940
17RNH200900	17RNH230910	17RNH220920	17RNH200930	17RNH170940
17RNH210900	17RNH240910	17RNH230920	17RNH210930	17RNH180940
17RNH220900	17RNH250910	17RNH240920	17RNH220930	17RNH190940
17RNH230900	17RNH260910	17RNH250920	17RNH230930	17RNH200940
17RNH240900	17RNH270910	17RNH260920	17RNH240930	17RNH210940
17RNH250900	17RNH280910	17RNH270920	17RNH250930	17RNH220940
17RNH260900	17RNH290910	17RNH280920	17RNH260930	17RNH230940
17RNH270900	17RNH300910	17RNH290920	17RNH270930	17RNH240940
17RNH280900	17RNH310910	17RNH300920	17RNH280930	17RNH250940
17RNH290900	17RNH320910	17RNH310920	17RNH290930	17RNH260940
17RNH300900	17RNH330910	17RNH320920	17RNH300930	17RNH270940
17RNH310900	17RNH340910	17RNH330920	17RNH310930	17RNH280940
17RNH320900	17RNH350910	17RNH340920	17RNH320930	17RNH290940
17RNH330900	17RNH360910	17RNH350920	17RNH330930	17RNH300940
17RNH340900	17RNH370910	17RNH360920	17RNH340930	17RNH310940
17RNH350900	17RNH380910	17RNH370920	17RNH350930	17RNH320940
17RNH360900	17RNH390910	17RNH380920	17RNH360930	17RNH330940
17RNH370900	17RNH400910	17RNH390920	17RNH370930	17RNH340940
17RNH380900	17RNH410910	17RNH400920	17RNH380930	17RNH350940
17RNH390900	17RNH420910	17RNH410920	17RNH390930	17RNH360940
17RNH400900	17RNH430910	17RNH420920	17RNH400930	17RNH370940
17RNH410900	17RNH440910	17RNH430920	17RNH410930	17RNH380940
17RNH420900	17RNH450910	17RNH440920	17RNH420930	17RNH390940
17RNH460900	17RNH460910	17RNH450920	17RNH430930	17RNH400940
17RNH470900	17RNH470910	17RNH460920	17RNH440930	17RNH410940
17RNH480900	17RNH480910	17RNH470920	17RNH450930	17RNH420940
17RNH490900	17RNH490910	17RNH480920	17RNH460930	17RNH430940
17RNH500900	17RNH500910	17RNH490920	17RNH470930	17RNH440940
17RNH510900	17RNH510910	17RNH500920	17RNH480930	17RNH450940
17RNH520900	17RNH520910	17RNH510920	17RNH490930	17RNH460940
17RNH530900	17RNH530910	17RNH520920	17RNH500930	17RNH470940
17RNH120910	17RNH540910	17RNH530920	17RNH510930	17RNH480940
17RNH130910	17RNH120920	17RNH540920	17RNH520930	17RNH490940

17RNH500940	17RNH470950	17RNH440960	17RNH410970	17RNH390980
17RNH510940	17RNH480950	17RNH450960	17RNH420970	17RNH400980
17RNH520940	17RNH490950	17RNH460960	17RNH430970	17RNH410980
17RNH530940	17RNH500950	17RNH470960	17RNH440970	17RNH420980
17RNH540940	17RNH510950	17RNH480960	17RNH450970	17RNH430980
17RNH550940	17RNH520950	17RNH490960	17RNH460970	17RNH440980
17RNH560940	17RNH530950	17RNH500960	17RNH470970	17RNH450980
17RNH120950	17RNH540950	17RNH510960	17RNH480970	17RNH460980
17RNH130950	17RNH550950	17RNH520960	17RNH490970	17RNH470980
17RNH140950	17RNH560950	17RNH530960	17RNH500970	17RNH480980
17RNH150950	17RNH120960	17RNH540960	17RNH510970	17RNH490980
17RNH160950	17RNH130960	17RNH550960	17RNH520970	17RNH500980
17RNH170950	17RNH140960	17RNH560960	17RNH530970	17RNH510980
17RNH180950	17RNH150960	17RNH120970	17RNH540970	17RNH520980
17RNH190950	17RNH160960	17RNH130970	17RNH550970	17RNH530980
17RNH200950	17RNH170960	17RNH140970	17RNH120980	17RNH540980
17RNH210950	17RNH180960	17RNH150970	17RNH130980	17RNH550980
17RNH220950	17RNH190960	17RNH160970	17RNH140980	17RNH120990
17RNH230950	17RNH200960	17RNH170970	17RNH150980	17RNH130990
17RNH240950	17RNH210960	17RNH180970	17RNH160980	17RNH140990
17RNH250950	17RNH220960	17RNH190970	17RNH170980	17RNH150990
17RNH260950	17RNH230960	17RNH200970	17RNH180980	17RNH160990
17RNH270950	17RNH240960	17RNH210970	17RNH190980	17RNH170990
17RNH280950	17RNH250960	17RNH220970	17RNH200980	17RNH180990
17RNH290950	17RNH260960	17RNH230970	17RNH210980	17RNH190990
17RNH300950	17RNH270960	17RNH240970	17RNH220980	17RNH200990
17RNH310950	17RNH280960	17RNH250970	17RNH230980	17RNH210990
17RNH320950	17RNH290960	17RNH260970	17RNH240980	17RNH220990
17RNH330950	17RNH300960	17RNH270970	17RNH250980	17RNH230990
17RNH340950	17RNH310960	17RNH280970	17RNH260980	17RNH240990
17RNH350950	17RNH320960	17RNH290970	17RNH270980	17RNH250990
17RNH360950	17RNH330960	17RNH300970	17RNH280980	17RNH260990
17RNH370950	17RNH340960	17RNH310970	17RNH290980	17RNH270990
17RNH380950	17RNH350960	17RNH320970	17RNH300980	17RNH280990
17RNH390950	17RNH360960	17RNH330970	17RNH310980	17RNH290990
17RNH400950	17RNH370960	17RNH340970	17RNH320980	17RNH300990
17RNH410950	17RNH380960	17RNH350970	17RNH330980	17RNH310990
17RNH420950	17RNH390960	17RNH360970	17RNH340980	17RNH320990
17RNH430950	17RNH400960	17RNH370970	17RNH350980	17RNH330990
17RNH440950	17RNH410960	17RNH380970	17RNH360980	17RNH340990
17RNH450950	17RNH420960	17RNH390970	17RNH370980	17RNH350990
17RNH460950	17RNH430960	17RNH400970	17RNH380980	17RNH360990

Everglades National Park Lidar

TO# G16PD01224

August 30, 2018

Page 60 of 165

17RNH370990	17RNJ350000	17RNJ330010	17RNJ310020	17RNJ290030
17RNH380990	17RNH360000	17RNJ340010	17RNJ320020	17RNJ300030
17RNH390990	17RNJ370000	17RNJ350010	17RNJ330020	17RNJ310030
17RNH400990	17RNH380000	17RNJ360010	17RNJ340020	17RNJ320030
17RNH410990	17RNJ390000	17RNJ370010	17RNJ350020	17RNJ330030
17RNH420990	17RNH400000	17RNJ380010	17RNJ360020	17RNJ340030
17RNH430990	17RNH410000	17RNJ390010	17RNJ370020	17RNJ350030
17RNH440990	17RNH420000	17RNJ400010	17RNJ380020	17RNJ360030
17RNH450990	17RNJ430000	17RNJ410010	17RNJ390020	17RNJ370030
17RNH460990	17RNJ440000	17RNJ420010	17RNJ400020	17RNJ380030
17RNH470990	17RNJ450000	17RNJ430010	17RNJ410020	17RNJ390030
17RNH480990	17RNH460000	17RNJ440010	17RNJ420020	17RNJ400030
17RNH490990	17RNJ470000	17RNJ450010	17RNJ430020	17RNJ410030
17RNH500990	17RNJ480000	17RNJ460010	17RNJ440020	17RNJ420030
17RNH510990	17RNH490000	17RNJ470010	17RNJ450020	17RNJ430030
17RNH520990	17RNJ500000	17RNJ480010	17RNJ460020	17RNJ440030
17RNH530990	17RNJ510000	17RNJ490010	17RNJ470020	17RNJ450030
17RNH540990	17RNJ520000	17RNJ500010	17RNJ480020	17RNJ460030
17RNH550990	17RNJ530000	17RNJ510010	17RNJ490020	17RNJ470030
17RNJ120000	17RNJ540000	17RNJ520010	17RNJ500020	17RNJ480030
17RNJ130000	17RNJ550000	17RNJ530010	17RNJ510020	17RNJ490030
17RNJ140000	17RNJ120010	17RNJ540010	17RNJ520020	17RNJ500030
17RNJ150000	17RNJ130010	17RNJ550010	17RNJ530020	17RNJ510030
17RNJ160000	17RNJ140010	17RNJ120020	17RNJ540020	17RNJ520030
17RNJ170000	17RNJ150010	17RNJ130020	17RNJ110030	17RNJ530030
17RNH180000	17RNJ160010	17RNJ140020	17RNJ120030	17RNJ540030
17RNJ190000	17RNJ170010	17RNJ150020	17RNJ130030	17RNJ090040
17RNJ200000	17RNJ180010	17RNJ160020	17RNJ140030	17RNJ100040
17RNJ210000	17RNJ190010	17RNJ170020	17RNJ150030	17RNJ110040
17RNJ220000	17RNJ200010	17RNJ180020	17RNJ160030	17RNJ120040
17RNH230000	17RNJ210010	17RNJ190020	17RNJ170030	17RNJ130040
17RNH240000	17RNJ220010	17RNJ200020	17RNJ180030	17RNJ140040
17RNJ250000	17RNJ230010	17RNJ210020	17RNJ190030	17RNJ150040
17RNJ260000	17RNJ240010	17RNJ220020	17RNJ200030	17RNJ160040
17RNJ270000	17RNJ250010	17RNJ230020	17RNJ210030	17RNJ170040
17RNH280000	17RNJ260010	17RNJ240020	17RNJ220030	17RNJ180040
17RNJ290000	17RNJ270010	17RNJ250020	17RNJ230030	17RNJ190040
17RNH300000	17RNJ280010	17RNJ260020	17RNJ240030	17RNJ200040
17RNH310000	17RNJ290010	17RNJ270020	17RNJ250030	17RNJ210040
17RNJ320000	17RNJ300010	17RNJ280020	17RNJ260030	17RNJ220040
17RNH330000	17RNJ310010	17RNJ290020	17RNJ270030	17RNJ230040
17RNH340000	17RNJ320010	17RNJ300020	17RNJ280030	17RNJ240040

17RNJ250040	17RNJ200050	17RNJ140060	17RNJ070070	17RNJ490070
17RNJ260040	17RNJ210050	17RNJ150060	17RNJ080070	17RNJ500070
17RNJ270040	17RNJ220050	17RNJ160060	17RNJ090070	17RNJ510070
17RNJ280040	17RNJ230050	17RNJ170060	17RNJ100070	17RNJ520070
17RNJ290040	17RNJ240050	17RNJ180060	17RNJ110070	17RNJ530070
17RNJ300040	17RNJ250050	17RNJ190060	17RNJ120070	17RNJ040080
17RNJ310040	17RNJ260050	17RNJ200060	17RNJ130070	17RNJ050080
17RNJ320040	17RNJ270050	17RNJ210060	17RNJ140070	17RNJ060080
17RNJ330040	17RNJ280050	17RNJ220060	17RNJ150070	17RNJ070080
17RNJ340040	17RNJ290050	17RNJ230060	17RNJ160070	17RNJ080080
17RNJ350040	17RNJ300050	17RNJ240060	17RNJ170070	17RNJ090080
17RNJ360040	17RNJ310050	17RNJ250060	17RNJ180070	17RNJ100080
17RNJ370040	17RNJ320050	17RNJ260060	17RNJ190070	17RNJ110080
17RNJ380040	17RNJ330050	17RNJ270060	17RNJ200070	17RNJ120080
17RNJ390040	17RNJ340050	17RNJ280060	17RNJ210070	17RNJ130080
17RNJ400040	17RNJ350050	17RNJ290060	17RNJ220070	17RNJ140080
17RNJ410040	17RNJ360050	17RNJ300060	17RNJ230070	17RNJ150080
17RNJ420040	17RNJ370050	17RNJ310060	17RNJ240070	17RNJ160080
17RNJ430040	17RNJ380050	17RNJ320060	17RNJ250070	17RNJ170080
17RNJ440040	17RNJ390050	17RNJ330060	17RNJ260070	17RNJ180080
17RNJ450040	17RNJ400050	17RNJ340060	17RNJ270070	17RNJ190080
17RNJ460040	17RNJ410050	17RNJ350060	17RNJ280070	17RNJ200080
17RNJ470040	17RNJ420050	17RNJ360060	17RNJ290070	17RNJ210080
17RNJ480040	17RNJ430050	17RNJ370060	17RNJ300070	17RNJ220080
17RNJ490040	17RNJ440050	17RNJ380060	17RNJ310070	17RNJ230080
17RNJ500040	17RNJ450050	17RNJ390060	17RNJ320070	17RNJ240080
17RNJ510040	17RNJ460050	17RNJ400060	17RNJ330070	17RNJ250080
17RNJ520040	17RNJ470050	17RNJ410060	17RNJ340070	17RNJ260080
17RNJ530040	17RNJ480050	17RNJ420060	17RNJ350070	17RNJ270080
17RNJ540040	17RNJ490050	17RNJ430060	17RNJ360070	17RNJ280080
17RNJ080050	17RNJ500050	17RNJ440060	17RNJ370070	17RNJ290080
17RNJ090050	17RNJ510050	17RNJ450060	17RNJ380070	17RNJ300080
17RNJ100050	17RNJ520050	17RNJ460060	17RNJ390070	17RNJ310080
17RNJ110050	17RNJ530050	17RNJ470060	17RNJ400070	17RNJ320080
17RNJ120050	17RNJ540050	17RNJ480060	17RNJ410070	17RNJ330080
17RNJ130050	17RNJ070060	17RNJ490060	17RNJ420070	17RNJ340080
17RNJ140050	17RNJ080060	17RNJ500060	17RNJ430070	17RNJ350080
17RNJ150050	17RNJ090060	17RNJ510060	17RNJ440070	17RNJ360080
17RNJ160050	17RNJ100060	17RNJ520060	17RNJ450070	17RNJ370080
17RNJ170050	17RNJ110060	17RNJ530060	17RNJ460070	17RNJ380080
17RNJ180050	17RNJ120060	17RNJ540060	17RNJ470070	17RNJ390080
17RNJ190050	17RNJ130060	17RNJ060070	17RNJ480070	17RNJ400080

17RNJ410080	17RNJ320090	17RNJ260100	17RNJ220110	17RNJ190120
17RNJ420080	17RNJ330090	17RNJ270100	17RNJ230110	17RNJ200120
17RNJ430080	17RNJ340090	17RNJ280100	17RNJ240110	17RNJ210120
17RNJ440080	17RNJ350090	17RNJ290100	17RNJ250110	17RNJ220120
17RNJ450080	17RNJ360090	17RNJ300100	17RNJ260110	17RNJ230120
17RNJ460080	17RNJ370090	17RNJ310100	17RNJ270110	17RNJ240120
17RNJ470080	17RNJ380090	17RNJ320100	17RNJ280110	17RNJ250120
17RNJ480080	17RNJ390090	17RNJ330100	17RNJ290110	17RNJ260120
17RNJ490080	17RNJ400090	17RNJ340100	17RNJ300110	17RNJ270120
17RNJ500080	17RNJ410090	17RNJ350100	17RNJ310110	17RNJ280120
17RNJ510080	17RNJ420090	17RNJ360100	17RNJ320110	17RNJ290120
17RNJ520080	17RNJ430090	17RNJ370100	17RNJ330110	17RNJ300120
17RNJ530080	17RNJ480090	17RNJ380100	17RNJ340110	17RNJ310120
17RNJ030090	17RNJ490090	17RNJ390100	17RNJ350110	17RNJ320120
17RNJ040090	17RNJ500090	17RNJ400100	17RNJ360110	17RNJ330120
17RNJ050090	17RNJ510090	17RNJ410100	17RNJ370110	17RNJ340120
17RNJ060090	17RNJ520090	17RNJ420100	17RNJ380110	17RNJ350120
17RNJ070090	17RNJ530090	17RNJ430100	17RNJ390110	17RNJ360120
17RNJ080090	17RNJ020100	17RNJ510100	17RNJ400110	17RNJ370120
17RNJ090090	17RNJ030100	17RNJ520100	17RNJ410110	17RNJ380120
17RNJ100090	17RNJ040100	17RNJ530100	17RNJ420110	17RNJ390120
17RNJ110090	17RNJ050100	17RNJ010110	17RNJ430110	17RNJ400120
17RNJ120090	17RNJ060100	17RNJ020110	17RMJ990120	17RNJ410120
17RNJ130090	17RNJ070100	17RNJ030110	17RMJ000120	17RNJ420120
17RNJ140090	17RNJ080100	17RNJ040110	17RNJ010120	17RMJ980130
17RNJ150090	17RNJ090100	17RNJ050110	17RNJ020120	17RMJ990130
17RNJ160090	17RNJ100100	17RNJ060110	17RNJ030120	17RMJ000130
17RNJ170090	17RNJ110100	17RNJ070110	17RNJ040120	17RNJ010130
17RNJ180090	17RNJ120100	17RNJ080110	17RNJ050120	17RNJ020130
17RNJ190090	17RNJ130100	17RNJ090110	17RNJ060120	17RNJ030130
17RNJ200090	17RNJ140100	17RNJ100110	17RNJ070120	17RNJ040130
17RNJ210090	17RNJ150100	17RNJ110110	17RNJ080120	17RNJ050130
17RNJ220090	17RNJ160100	17RNJ120110	17RNJ090120	17RNJ060130
17RNJ230090	17RNJ170100	17RNJ130110	17RNJ100120	17RNJ070130
17RNJ240090	17RNJ180100	17RNJ140110	17RNJ110120	17RNJ080130
17RNJ250090	17RNJ190100	17RNJ150110	17RNJ120120	17RNJ090130
17RNJ260090	17RNJ200100	17RNJ160110	17RNJ130120	17RNJ100130
17RNJ270090	17RNJ210100	17RNJ170110	17RNJ140120	17RNJ110130
17RNJ280090	17RNJ220100	17RNJ180110	17RNJ150120	17RNJ120130
17RNJ290090	17RNJ230100	17RNJ190110	17RNJ160120	17RNJ130130
17RNJ300090	17RNJ240100	17RNJ200110	17RNJ170120	17RNJ140130
17RNJ310090	17RNJ250100	17RNJ210110	17RNJ180120	17RNJ150130

17RNJ160130	17RNJ120140	17RNJ080150	17RNJ040160	17RNJ010170
17RNJ170130	17RNJ130140	17RNJ090150	17RNJ050160	17RNJ020170
17RNJ180130	17RNJ140140	17RNJ100150	17RNJ060160	17RNJ030170
17RNJ190130	17RNJ150140	17RNJ110150	17RNJ070160	17RNJ040170
17RNJ200130	17RNJ160140	17RNJ120150	17RNJ080160	17RNJ050170
17RNJ210130	17RNJ170140	17RNJ130150	17RNJ090160	17RNJ060170
17RNJ220130	17RNJ180140	17RNJ140150	17RNJ100160	17RNJ070170
17RNJ230130	17RNJ190140	17RNJ150150	17RNJ110160	17RNJ080170
17RNJ240130	17RNJ200140	17RNJ160150	17RNJ120160	17RNJ090170
17RNJ250130	17RNJ210140	17RNJ170150	17RNJ130160	17RNJ100170
17RNJ260130	17RNJ220140	17RNJ180150	17RNJ140160	17RNJ110170
17RNJ270130	17RNJ230140	17RNJ190150	17RNJ150160	17RNJ120170
17RNJ280130	17RNJ240140	17RNJ200150	17RNJ160160	17RNJ130170
17RNJ290130	17RNJ250140	17RNJ210150	17RNJ170160	17RNJ140170
17RNJ300130	17RNJ260140	17RNJ220150	17RNJ180160	17RNJ150170
17RNJ310130	17RNJ270140	17RNJ230150	17RNJ190160	17RNJ160170
17RNJ320130	17RNJ280140	17RNJ240150	17RNJ200160	17RNJ170170
17RNJ330130	17RNJ290140	17RNJ250150	17RNJ210160	17RNJ180170
17RNJ340130	17RNJ300140	17RNJ260150	17RNJ220160	17RNJ190170
17RNJ350130	17RNJ310140	17RNJ270150	17RNJ230160	17RNJ200170
17RNJ360130	17RNJ320140	17RNJ280150	17RNJ240160	17RNJ210170
17RNJ370130	17RNJ330140	17RNJ290150	17RNJ250160	17RNJ220170
17RNJ380130	17RNJ340140	17RNJ300150	17RNJ260160	17RNJ230170
17RNJ390130	17RNJ350140	17RNJ310150	17RNJ270160	17RNJ240170
17RNJ400130	17RNJ360140	17RNJ320150	17RNJ280160	17RNJ250170
17RNJ410130	17RNJ370140	17RNJ330150	17RNJ290160	17RNJ260170
17RNJ420130	17RNJ380140	17RNJ340150	17RNJ300160	17RNJ270170
17RMJ970140	17RNJ390140	17RNJ350150	17RNJ310160	17RNJ280170
17RMJ980140	17RNJ400140	17RNJ360150	17RNJ320160	17RNJ290170
17RMJ990140	17RNJ410140	17RNJ370150	17RNJ330160	17RNJ300170
17RMJ000140	17RNJ420140	17RNJ380150	17RNJ340160	17RNJ310170
17RNJ010140	17RMJ970150	17RNJ390150	17RNJ350160	17RNJ320170
17RNJ020140	17RMJ980150	17RNJ400150	17RNJ360160	17RNJ330170
17RNJ030140	17RMJ990150	17RNJ410150	17RNJ370160	17RNJ340170
17RNJ040140	17RMJ000150	17RNJ420150	17RNJ380160	17RNJ350170
17RNJ050140	17RNJ010150	17RMJ970160	17RNJ390160	17RNJ360170
17RNJ060140	17RNJ020150	17RMJ980160	17RNJ400160	17RNJ370170
17RNJ070140	17RNJ030150	17RMJ990160	17RNJ410160	17RNJ380170
17RNJ080140	17RNJ040150	17RMJ000160	17RNJ420160	17RNJ390170
17RNJ090140	17RNJ050150	17RNJ010160	17RMJ980170	17RNJ400170
17RNJ100140	17RNJ060150	17RNJ020160	17RMJ990170	17RNJ410170
17RNJ110140	17RNJ070150	17RNJ030160	17RMJ000170	17RNJ420170

17RNJ430170	17RNJ380180	17RNJ330190	17RNJ280200	17RNJ230210
17RMJ970180	17RNJ390180	17RNJ340190	17RNJ290200	17RNJ240210
17RMJ980180	17RNJ400180	17RNJ350190	17RNJ300200	17RNJ250210
17RMJ990180	17RNJ410180	17RNJ360190	17RNJ310200	17RNJ260210
17RMJ000180	17RNJ420180	17RNJ370190	17RNJ320200	17RNJ270210
17RNJ010180	17RNJ430180	17RNJ380190	17RNJ330200	17RNJ280210
17RNJ020180	17RMJ970190	17RNJ390190	17RNJ340200	17RNJ290210
17RNJ030180	17RMJ980190	17RNJ400190	17RNJ350200	17RNJ300210
17RNJ040180	17RMJ990190	17RNJ410190	17RNJ360200	17RNJ310210
17RNJ050180	17RMJ000190	17RNJ420190	17RNJ370200	17RNJ320210
17RNJ060180	17RNJ010190	17RNJ430190	17RNJ380200	17RNJ330210
17RNJ070180	17RNJ020190	17RMJ970200	17RNJ390200	17RNJ340210
17RNJ080180	17RNJ030190	17RMJ980200	17RNJ400200	17RNJ350210
17RNJ090180	17RNJ040190	17RMJ990200	17RNJ410200	17RNJ360210
17RNJ100180	17RNJ050190	17RMJ000200	17RNJ420200	17RNJ370210
17RNJ110180	17RNJ060190	17RNJ010200	17RNJ430200	17RNJ380210
17RNJ120180	17RNJ070190	17RNJ020200	17RMJ970210	17RNJ390210
17RNJ130180	17RNJ080190	17RNJ030200	17RMJ980210	17RNJ400210
17RNJ140180	17RNJ090190	17RNJ040200	17RMJ990210	17RNJ410210
17RNJ150180	17RNJ100190	17RNJ050200	17RMJ000210	17RNJ420210
17RNJ160180	17RNJ110190	17RNJ060200	17RNJ010210	17RNJ430210
17RNJ170180	17RNJ120190	17RNJ070200	17RNJ020210	17RMJ970220
17RNJ180180	17RNJ130190	17RNJ080200	17RNJ030210	17RMJ980220
17RNJ190180	17RNJ140190	17RNJ090200	17RNJ040210	17RMJ990220
17RNJ200180	17RNJ150190	17RNJ100200	17RNJ050210	17RMJ000220
17RNJ210180	17RNJ160190	17RNJ110200	17RNJ060210	17RNJ010220
17RNJ220180	17RNJ170190	17RNJ120200	17RNJ070210	17RNJ020220
17RNJ230180	17RNJ180190	17RNJ130200	17RNJ080210	17RNJ030220
17RNJ240180	17RNJ190190	17RNJ140200	17RNJ090210	17RNJ040220
17RNJ250180	17RNJ200190	17RNJ150200	17RNJ100210	17RNJ050220
17RNJ260180	17RNJ210190	17RNJ160200	17RNJ110210	17RNJ060220
17RNJ270180	17RNJ220190	17RNJ170200	17RNJ120210	17RNJ070220
17RNJ280180	17RNJ230190	17RNJ180200	17RNJ130210	17RNJ080220
17RNJ290180	17RNJ240190	17RNJ190200	17RNJ140210	17RNJ090220
17RNJ300180	17RNJ250190	17RNJ200200	17RNJ150210	17RNJ100220
17RNJ310180	17RNJ260190	17RNJ210200	17RNJ160210	17RNJ110220
17RNJ320180	17RNJ270190	17RNJ220200	17RNJ170210	17RNJ120220
17RNJ330180	17RNJ280190	17RNJ230200	17RNJ180210	17RNJ130220
17RNJ340180	17RNJ290190	17RNJ240200	17RNJ190210	17RNJ140220
17RNJ350180	17RNJ300190	17RNJ250200	17RNJ200210	17RNJ150220
17RNJ360180	17RNJ310190	17RNJ260200	17RNJ210210	17RNJ160220
17RNJ370180	17RNJ320190	17RNJ270200	17RNJ220210	17RNJ170220

17RNJ180220	17RNJ140230	17RNJ090240	17RNJ020250	17RNJ440250
17RNJ190220	17RNJ150230	17RNJ100240	17RNJ030250	17RMJ930260
17RNJ200220	17RNJ160230	17RNJ110240	17RNJ040250	17RMJ940260
17RNJ210220	17RNJ170230	17RNJ120240	17RNJ050250	17RMJ950260
17RNJ220220	17RNJ180230	17RNJ130240	17RNJ060250	17RMJ960260
17RNJ230220	17RNJ190230	17RNJ140240	17RNJ070250	17RMJ970260
17RNJ240220	17RNJ200230	17RNJ150240	17RNJ080250	17RMJ980260
17RNJ250220	17RNJ210230	17RNJ160240	17RNJ090250	17RMJ990260
17RNJ260220	17RNJ220230	17RNJ170240	17RNJ100250	17RMJ000260
17RNJ270220	17RNJ230230	17RNJ180240	17RNJ110250	17RNJ010260
17RNJ280220	17RNJ240230	17RNJ190240	17RNJ120250	17RNJ020260
17RNJ290220	17RNJ250230	17RNJ200240	17RNJ130250	17RNJ030260
17RNJ300220	17RNJ260230	17RNJ210240	17RNJ140250	17RNJ040260
17RNJ310220	17RNJ270230	17RNJ220240	17RNJ150250	17RNJ050260
17RNJ320220	17RNJ280230	17RNJ230240	17RNJ160250	17RNJ060260
17RNJ330220	17RNJ290230	17RNJ240240	17RNJ170250	17RNJ070260
17RNJ340220	17RNJ300230	17RNJ250240	17RNJ180250	17RNJ080260
17RNJ350220	17RNJ310230	17RNJ260240	17RNJ190250	17RNJ090260
17RNJ360220	17RNJ320230	17RNJ270240	17RNJ200250	17RNJ100260
17RNJ370220	17RNJ330230	17RNJ280240	17RNJ210250	17RNJ110260
17RNJ380220	17RNJ340230	17RNJ290240	17RNJ220250	17RNJ120260
17RNJ390220	17RNJ350230	17RNJ300240	17RNJ230250	17RNJ130260
17RNJ400220	17RNJ360230	17RNJ310240	17RNJ240250	17RNJ140260
17RNJ410220	17RNJ370230	17RNJ320240	17RNJ250250	17RNJ150260
17RNJ420220	17RNJ380230	17RNJ330240	17RNJ260250	17RNJ160260
17RNJ430220	17RNJ390230	17RNJ340240	17RNJ270250	17RNJ170260
17RMJ980230	17RNJ400230	17RNJ350240	17RNJ280250	17RNJ180260
17RMJ990230	17RNJ410230	17RNJ360240	17RNJ290250	17RNJ190260
17RMJ000230	17RNJ420230	17RNJ370240	17RNJ300250	17RNJ200260
17RNJ010230	17RNJ430230	17RNJ380240	17RNJ310250	17RNJ210260
17RNJ020230	17RMJ970240	17RNJ390240	17RNJ320250	17RNJ220260
17RNJ030230	17RMJ980240	17RNJ400240	17RNJ330250	17RNJ230260
17RNJ040230	17RMJ990240	17RNJ410240	17RNJ340250	17RNJ240260
17RNJ050230	17RMJ000240	17RNJ420240	17RNJ350250	17RNJ250260
17RNJ060230	17RNJ010240	17RNJ430240	17RNJ360250	17RNJ260260
17RNJ070230	17RNJ020240	17RMJ950250	17RNJ370250	17RNJ270260
17RNJ080230	17RNJ030240	17RMJ960250	17RNJ380250	17RNJ280260
17RNJ090230	17RNJ040240	17RMJ970250	17RNJ390250	17RNJ290260
17RNJ100230	17RNJ050240	17RMJ980250	17RNJ400250	17RNJ300260
17RNJ110230	17RNJ060240	17RMJ990250	17RNJ410250	17RNJ310260
17RNJ120230	17RNJ070240	17RMJ000250	17RNJ420250	17RNJ320260
17RNJ130230	17RNJ080240	17RNJ010250	17RNJ430250	17RNJ330260

17RNJ340260	17RNJ220270	17RNJ070280	17RMJ910290	17RNJ330290
17RNJ350260	17RNJ230270	17RNJ080280	17RMJ920290	17RNJ340290
17RNJ360260	17RNJ240270	17RNJ090280	17RMJ930290	17RNJ350290
17RNJ370260	17RNJ250270	17RNJ100280	17RMJ940290	17RNJ360290
17RNJ380260	17RNJ260270	17RNJ110280	17RMJ950290	17RNJ370290
17RNJ390260	17RNJ270270	17RNJ120280	17RMJ960290	17RNJ380290
17RNJ400260	17RNJ280270	17RNJ130280	17RMJ970290	17RNJ390290
17RNJ410260	17RNJ290270	17RNJ140280	17RMJ980290	17RNJ400290
17RNJ420260	17RNJ300270	17RNJ150280	17RMJ990290	17RNJ410290
17RNJ430260	17RNJ310270	17RNJ160280	17RMJ000290	17RNJ420290
17RNJ440260	17RNJ320270	17RNJ170280	17RNJ010290	17RNJ430290
17RMJ910270	17RNJ330270	17RNJ180280	17RNJ020290	17RNJ440290
17RMJ920270	17RNJ340270	17RNJ190280	17RNJ030290	17RNJ450290
17RMJ930270	17RNJ350270	17RNJ200280	17RNJ040290	17RMJ880300
17RMJ940270	17RNJ360270	17RNJ210280	17RNJ050290	17RMJ890300
17RMJ950270	17RNJ370270	17RNJ220280	17RNJ060290	17RMJ900300
17RMJ960270	17RNJ380270	17RNJ230280	17RNJ070290	17RMJ910300
17RMJ970270	17RNJ390270	17RNJ240280	17RNJ080290	17RMJ920300
17RMJ980270	17RNJ400270	17RNJ250280	17RNJ090290	17RMJ930300
17RMJ990270	17RNJ410270	17RNJ260280	17RNJ100290	17RMJ940300
17RMJ000270	17RNJ420270	17RNJ270280	17RNJ110290	17RMJ950300
17RNJ010270	17RNJ430270	17RNJ280280	17RNJ120290	17RMJ960300
17RNJ020270	17RNJ440270	17RNJ290280	17RNJ130290	17RMJ970300
17RNJ030270	17RNJ450270	17RNJ300280	17RNJ140290	17RMJ980300
17RNJ040270	17RMJ890280	17RNJ310280	17RNJ150290	17RMJ990300
17RNJ050270	17RMJ900280	17RNJ320280	17RNJ160290	17RMJ000300
17RNJ060270	17RMJ910280	17RNJ330280	17RNJ170290	17RNJ010300
17RNJ070270	17RMJ920280	17RNJ340280	17RNJ180290	17RNJ020300
17RNJ080270	17RMJ930280	17RNJ350280	17RNJ190290	17RNJ030300
17RNJ090270	17RMJ940280	17RNJ360280	17RNJ200290	17RNJ040300
17RNJ100270	17RMJ950280	17RNJ370280	17RNJ210290	17RNJ050300
17RNJ110270	17RMJ960280	17RNJ380280	17RNJ220290	17RNJ060300
17RNJ120270	17RMJ970280	17RNJ390280	17RNJ230290	17RNJ070300
17RNJ130270	17RMJ980280	17RNJ400280	17RNJ240290	17RNJ080300
17RNJ140270	17RMJ990280	17RNJ410280	17RNJ250290	17RNJ090300
17RNJ150270	17RMJ000280	17RNJ420280	17RNJ260290	17RNJ100300
17RNJ160270	17RNJ010280	17RNJ430280	17RNJ270290	17RNJ110300
17RNJ170270	17RNJ020280	17RNJ440280	17RNJ280290	17RNJ120300
17RNJ180270	17RNJ030280	17RNJ450280	17RNJ290290	17RNJ130300
17RNJ190270	17RNJ040280	17RMJ880290	17RNJ300290	17RNJ140300
17RNJ200270	17RNJ050280	17RMJ890290	17RNJ310290	17RNJ150300
17RNJ210270	17RNJ060280	17RMJ900290	17RNJ320290	17RNJ160300

17RNJ170300	17RMJ000310	17RNJ420310	17RNJ240320	17RNJ040330
17RNJ180300	17RNJ010310	17RNJ430310	17RNJ250320	17RNJ050330
17RNJ190300	17RNJ020310	17RNJ440310	17RNJ260320	17RNJ060330
17RNJ200300	17RNJ030310	17RNJ450310	17RNJ270320	17RNJ070330
17RNJ210300	17RNJ040310	17RMJ860320	17RNJ280320	17RNJ080330
17RNJ220300	17RNJ050310	17RMJ870320	17RNJ290320	17RNJ090330
17RNJ230300	17RNJ060310	17RMJ880320	17RNJ300320	17RNJ100330
17RNJ240300	17RNJ070310	17RMJ890320	17RNJ310320	17RNJ110330
17RNJ250300	17RNJ080310	17RMJ900320	17RNJ320320	17RNJ120330
17RNJ260300	17RNJ090310	17RMJ910320	17RNJ330320	17RNJ130330
17RNJ270300	17RNJ100310	17RMJ920320	17RNJ340320	17RNJ140330
17RNJ280300	17RNJ110310	17RMJ930320	17RNJ350320	17RNJ150330
17RNJ290300	17RNJ120310	17RMJ940320	17RNJ360320	17RNJ160330
17RNJ300300	17RNJ130310	17RMJ950320	17RNJ370320	17RNJ170330
17RNJ310300	17RNJ140310	17RMJ960320	17RNJ380320	17RNJ180330
17RNJ320300	17RNJ150310	17RMJ970320	17RNJ390320	17RNJ190330
17RNJ330300	17RNJ160310	17RMJ980320	17RNJ400320	17RNJ200330
17RNJ340300	17RNJ170310	17RMJ990320	17RNJ410320	17RNJ210330
17RNJ350300	17RNJ180310	17RMJ000320	17RNJ420320	17RNJ220330
17RNJ360300	17RNJ190310	17RNJ010320	17RNJ430320	17RNJ230330
17RNJ370300	17RNJ200310	17RNJ020320	17RNJ440320	17RNJ240330
17RNJ380300	17RNJ210310	17RNJ030320	17RNJ450320	17RNJ250330
17RNJ390300	17RNJ220310	17RNJ040320	17RNJ460320	17RNJ260330
17RNJ400300	17RNJ230310	17RNJ050320	17RMJ850330	17RNJ270330
17RNJ410300	17RNJ240310	17RNJ060320	17RMJ860330	17RNJ280330
17RNJ420300	17RNJ250310	17RNJ070320	17RMJ870330	17RNJ290330
17RNJ430300	17RNJ260310	17RNJ080320	17RMJ880330	17RNJ300330
17RNJ440300	17RNJ270310	17RNJ090320	17RMJ890330	17RNJ310330
17RNJ450300	17RNJ280310	17RNJ100320	17RMJ900330	17RNJ320330
17RMJ870310	17RNJ290310	17RNJ110320	17RMJ910330	17RNJ330330
17RMJ880310	17RNJ300310	17RNJ120320	17RMJ920330	17RNJ340330
17RMJ890310	17RNJ310310	17RNJ130320	17RMJ930330	17RNJ350330
17RMJ900310	17RNJ320310	17RNJ140320	17RMJ940330	17RNJ360330
17RMJ910310	17RNJ330310	17RNJ150320	17RMJ950330	17RNJ370330
17RMJ920310	17RNJ340310	17RNJ160320	17RMJ960330	17RNJ380330
17RMJ930310	17RNJ350310	17RNJ170320	17RMJ970330	17RNJ390330
17RMJ940310	17RNJ360310	17RNJ180320	17RMJ980330	17RNJ400330
17RMJ950310	17RNJ370310	17RNJ190320	17RMJ990330	17RNJ410330
17RMJ960310	17RNJ380310	17RNJ200320	17RMJ000330	17RNJ420330
17RMJ970310	17RNJ390310	17RNJ210320	17RNJ010330	17RNJ430330
17RMJ980310	17RNJ400310	17RNJ220320	17RNJ020330	17RNJ440330
17RMJ990310	17RNJ410310	17RNJ230320	17RNJ030330	17RNJ450330

17RNJ460330	17RNJ260340	17RNJ060350	17RMJ840360	17RNJ260360
17RMJ850340	17RNJ270340	17RNJ070350	17RMJ850360	17RNJ270360
17RMJ860340	17RNJ280340	17RNJ080350	17RMJ860360	17RNJ280360
17RMJ870340	17RNJ290340	17RNJ090350	17RMJ870360	17RNJ290360
17RMJ880340	17RNJ300340	17RNJ100350	17RMJ880360	17RNJ300360
17RMJ890340	17RNJ310340	17RNJ110350	17RMJ890360	17RNJ310360
17RMJ900340	17RNJ320340	17RNJ120350	17RMJ900360	17RNJ320360
17RMJ910340	17RNJ330340	17RNJ130350	17RMJ910360	17RNJ330360
17RMJ920340	17RNJ340340	17RNJ140350	17RMJ920360	17RNJ340360
17RMJ930340	17RNJ350340	17RNJ150350	17RMJ930360	17RNJ350360
17RMJ940340	17RNJ360340	17RNJ160350	17RMJ940360	17RNJ360360
17RMJ950340	17RNJ370340	17RNJ170350	17RMJ950360	17RNJ370360
17RMJ960340	17RNJ380340	17RNJ180350	17RMJ960360	17RNJ380360
17RMJ970340	17RNJ390340	17RNJ190350	17RMJ970360	17RNJ390360
17RMJ980340	17RNJ400340	17RNJ200350	17RMJ980360	17RNJ400360
17RMJ990340	17RNJ410340	17RNJ210350	17RMJ990360	17RNJ410360
17RMJ000340	17RNJ420340	17RNJ220350	17RMJ000360	17RNJ420360
17RNJ010340	17RNJ430340	17RNJ230350	17RNJ010360	17RNJ430360
17RNJ020340	17RNJ440340	17RNJ240350	17RNJ020360	17RNJ440360
17RNJ030340	17RNJ450340	17RNJ250350	17RNJ030360	17RNJ450360
17RNJ040340	17RNJ460340	17RNJ260350	17RNJ040360	17RNJ460360
17RNJ050340	17RMJ850350	17RNJ270350	17RNJ050360	17RNJ470360
17RNJ060340	17RMJ860350	17RNJ280350	17RNJ060360	17RMJ840370
17RNJ070340	17RMJ870350	17RNJ290350	17RNJ070360	17RMJ850370
17RNJ080340	17RMJ880350	17RNJ300350	17RNJ080360	17RMJ860370
17RNJ090340	17RMJ890350	17RNJ310350	17RNJ090360	17RMJ870370
17RNJ100340	17RMJ900350	17RNJ320350	17RNJ100360	17RMJ880370
17RNJ110340	17RMJ910350	17RNJ330350	17RNJ110360	17RMJ890370
17RNJ120340	17RMJ920350	17RNJ340350	17RNJ120360	17RMJ900370
17RNJ130340	17RMJ930350	17RNJ350350	17RNJ130360	17RMJ910370
17RNJ140340	17RMJ940350	17RNJ360350	17RNJ140360	17RMJ920370
17RNJ150340	17RMJ950350	17RNJ370350	17RNJ150360	17RMJ930370
17RNJ160340	17RMJ960350	17RNJ380350	17RNJ160360	17RMJ940370
17RNJ170340	17RMJ970350	17RNJ390350	17RNJ170360	17RMJ950370
17RNJ180340	17RMJ980350	17RNJ400350	17RNJ180360	17RMJ960370
17RNJ190340	17RMJ990350	17RNJ410350	17RNJ190360	17RMJ970370
17RNJ200340	17RMJ000350	17RNJ420350	17RNJ200360	17RMJ980370
17RNJ210340	17RNJ010350	17RNJ430350	17RNJ210360	17RMJ990370
17RNJ220340	17RNJ020350	17RNJ440350	17RNJ220360	17RMJ000370
17RNJ230340	17RNJ030350	17RNJ450350	17RNJ230360	17RNJ010370
17RNJ240340	17RNJ040350	17RNJ460350	17RNJ240360	17RNJ020370
17RNJ250340	17RNJ050350	17RNJ470350	17RNJ250360	17RNJ030370

17RNJ040370	17RNJ460370	17RNJ220380	17RMJ970390	17RNJ390390
17RNJ050370	17RNJ470370	17RNJ230380	17RMJ980390	17RNJ400390
17RNJ060370	17RNJ480370	17RNJ240380	17RMJ990390	17RNJ410390
17RNJ070370	17RMJ830380	17RNJ250380	17RMJ000390	17RNJ420390
17RNJ080370	17RMJ840380	17RNJ260380	17RNJ010390	17RNJ430390
17RNJ090370	17RMJ850380	17RNJ270380	17RNJ020390	17RNJ440390
17RNJ100370	17RMJ860380	17RNJ280380	17RNJ030390	17RNJ450390
17RNJ110370	17RMJ870380	17RNJ290380	17RNJ040390	17RNJ460390
17RNJ120370	17RMJ880380	17RNJ300380	17RNJ050390	17RNJ470390
17RNJ130370	17RMJ890380	17RNJ310380	17RNJ060390	17RNJ480390
17RNJ140370	17RMJ900380	17RNJ320380	17RNJ070390	17RNJ490390
17RNJ150370	17RMJ910380	17RNJ330380	17RNJ080390	17RNJ500390
17RNJ160370	17RMJ920380	17RNJ340380	17RNJ090390	17RMJ830400
17RNJ170370	17RMJ930380	17RNJ350380	17RNJ100390	17RMJ840400
17RNJ180370	17RMJ940380	17RNJ360380	17RNJ110390	17RMJ850400
17RNJ190370	17RMJ950380	17RNJ370380	17RNJ120390	17RMJ860400
17RNJ200370	17RMJ960380	17RNJ380380	17RNJ130390	17RMJ870400
17RNJ210370	17RMJ970380	17RNJ390380	17RNJ140390	17RMJ880400
17RNJ220370	17RMJ980380	17RNJ400380	17RNJ150390	17RMJ890400
17RNJ230370	17RMJ990380	17RNJ410380	17RNJ160390	17RMJ900400
17RNJ240370	17RMJ000380	17RNJ420380	17RNJ170390	17RMJ910400
17RNJ250370	17RNJ010380	17RNJ430380	17RNJ180390	17RMJ920400
17RNJ260370	17RNJ020380	17RNJ440380	17RNJ190390	17RMJ930400
17RNJ270370	17RNJ030380	17RNJ450380	17RNJ200390	17RMJ940400
17RNJ280370	17RNJ040380	17RNJ460380	17RNJ210390	17RMJ950400
17RNJ290370	17RNJ050380	17RNJ470380	17RNJ220390	17RMJ960400
17RNJ300370	17RNJ060380	17RNJ480380	17RNJ230390	17RMJ970400
17RNJ310370	17RNJ070380	17RNJ490380	17RNJ240390	17RMJ980400
17RNJ320370	17RNJ080380	17RMJ830390	17RNJ250390	17RMJ990400
17RNJ330370	17RNJ090380	17RMJ840390	17RNJ260390	17RMJ000400
17RNJ340370	17RNJ100380	17RMJ850390	17RNJ270390	17RNJ010400
17RNJ350370	17RNJ110380	17RMJ860390	17RNJ280390	17RNJ020400
17RNJ360370	17RNJ120380	17RMJ870390	17RNJ290390	17RNJ030400
17RNJ370370	17RNJ130380	17RMJ880390	17RNJ300390	17RNJ040400
17RNJ380370	17RNJ140380	17RMJ890390	17RNJ310390	17RNJ050400
17RNJ390370	17RNJ150380	17RMJ900390	17RNJ320390	17RNJ060400
17RNJ400370	17RNJ160380	17RMJ910390	17RNJ330390	17RNJ070400
17RNJ410370	17RNJ170380	17RMJ920390	17RNJ340390	17RNJ080400
17RNJ420370	17RNJ180380	17RMJ930390	17RNJ350390	17RNJ090400
17RNJ430370	17RNJ190380	17RMJ940390	17RNJ360390	17RNJ100400
17RNJ440370	17RNJ200380	17RMJ950390	17RNJ370390	17RNJ110400
17RNJ450370	17RNJ210380	17RMJ960390	17RNJ380390	17RNJ120400

17RNJ130400	17RMJ880410	17RNJ300410	17RNJ060420	17RNJ480420
17RNJ140400	17RMJ890410	17RNJ310410	17RNJ070420	17RNJ490420
17RNJ150400	17RMJ900410	17RNJ320410	17RNJ080420	17RNJ500420
17RNJ160400	17RMJ910410	17RNJ330410	17RNJ090420	17RMJ860430
17RNJ170400	17RMJ920410	17RNJ340410	17RNJ100420	17RMJ870430
17RNJ180400	17RMJ930410	17RNJ350410	17RNJ110420	17RMJ880430
17RNJ190400	17RMJ940410	17RNJ360410	17RNJ120420	17RMJ890430
17RNJ200400	17RMJ950410	17RNJ370410	17RNJ130420	17RMJ900430
17RNJ210400	17RMJ960410	17RNJ380410	17RNJ140420	17RMJ910430
17RNJ220400	17RMJ970410	17RNJ390410	17RNJ150420	17RMJ920430
17RNJ230400	17RMJ980410	17RNJ400410	17RNJ160420	17RMJ930430
17RNJ240400	17RMJ990410	17RNJ410410	17RNJ170420	17RMJ940430
17RNJ250400	17RMJ000410	17RNJ420410	17RNJ180420	17RMJ950430
17RNJ260400	17RNJ010410	17RNJ430410	17RNJ190420	17RMJ960430
17RNJ270400	17RNJ020410	17RNJ440410	17RNJ200420	17RMJ970430
17RNJ280400	17RNJ030410	17RNJ450410	17RNJ210420	17RMJ980430
17RNJ290400	17RNJ040410	17RNJ460410	17RNJ220420	17RMJ990430
17RNJ300400	17RNJ050410	17RNJ470410	17RNJ230420	17RMJ000430
17RNJ310400	17RNJ060410	17RNJ480410	17RNJ240420	17RNJ010430
17RNJ320400	17RNJ070410	17RNJ490410	17RNJ250420	17RNJ020430
17RNJ330400	17RNJ080410	17RNJ500410	17RNJ260420	17RNJ030430
17RNJ340400	17RNJ090410	17RMJ850420	17RNJ270420	17RNJ040430
17RNJ350400	17RNJ100410	17RMJ860420	17RNJ280420	17RNJ050430
17RNJ360400	17RNJ110410	17RMJ870420	17RNJ290420	17RNJ060430
17RNJ370400	17RNJ120410	17RMJ880420	17RNJ300420	17RNJ070430
17RNJ380400	17RNJ130410	17RMJ890420	17RNJ310420	17RNJ080430
17RNJ390400	17RNJ140410	17RMJ900420	17RNJ320420	17RNJ090430
17RNJ400400	17RNJ150410	17RMJ910420	17RNJ330420	17RNJ100430
17RNJ410400	17RNJ160410	17RMJ920420	17RNJ340420	17RNJ110430
17RNJ420400	17RNJ170410	17RMJ930420	17RNJ350420	17RNJ120430
17RNJ430400	17RNJ180410	17RMJ940420	17RNJ360420	17RNJ130430
17RNJ440400	17RNJ190410	17RMJ950420	17RNJ370420	17RNJ140430
17RNJ450400	17RNJ200410	17RMJ960420	17RNJ380420	17RNJ150430
17RNJ460400	17RNJ210410	17RMJ970420	17RNJ390420	17RNJ160430
17RNJ470400	17RNJ220410	17RMJ980420	17RNJ400420	17RNJ170430
17RNJ480400	17RNJ230410	17RMJ990420	17RNJ410420	17RNJ180430
17RNJ490400	17RNJ240410	17RMJ000420	17RNJ420420	17RNJ190430
17RNJ500400	17RNJ250410	17RNJ010420	17RNJ430420	17RNJ200430
17RMJ840410	17RNJ260410	17RNJ020420	17RNJ440420	17RNJ210430
17RMJ850410	17RNJ270410	17RNJ030420	17RNJ450420	17RNJ220430
17RMJ860410	17RNJ280410	17RNJ040420	17RNJ460420	17RNJ230430
17RMJ870410	17RNJ290410	17RNJ050420	17RNJ470420	17RNJ240430


17RNJ250430	17RNJ030440	17RNJ450440	17RNJ240450	17RNJ040460
17RNJ260430	17RNJ040440	17RNJ460440	17RNJ250450	17RNJ050460
17RNJ270430	17RNJ050440	17RNJ470440	17RNJ260450	17RNJ060460
17RNJ280430	17RNJ060440	17RNJ480440	17RNJ270450	17RNJ070460
17RNJ290430	17RNJ070440	17RNJ490440	17RNJ280450	17RNJ080460
17RNJ300430	17RNJ080440	17RNJ500440	17RNJ290450	17RNJ090460
17RNJ310430	17RNJ090440	17RMJ880450	17RNJ300450	17RNJ100460
17RNJ320430	17RNJ100440	17RMJ890450	17RNJ310450	17RNJ110460
17RNJ330430	17RNJ110440	17RMJ900450	17RNJ320450	17RNJ120460
17RNJ340430	17RNJ120440	17RMJ910450	17RNJ330450	17RNJ130460
17RNJ350430	17RNJ130440	17RMJ920450	17RNJ340450	17RNJ140460
17RNJ360430	17RNJ140440	17RMJ930450	17RNJ350450	17RNJ150460
17RNJ370430	17RNJ150440	17RMJ940450	17RNJ360450	17RNJ160460
17RNJ380430	17RNJ160440	17RMJ950450	17RNJ370450	17RNJ170460
17RNJ390430	17RNJ170440	17RMJ960450	17RNJ380450	17RNJ180460
17RNJ400430	17RNJ180440	17RMJ970450	17RNJ390450	17RNJ190460
17RNJ410430	17RNJ190440	17RMJ980450	17RNJ400450	17RNJ200460
17RNJ420430	17RNJ200440	17RMJ990450	17RNJ410450	17RNJ210460
17RNJ430430	17RNJ210440	17RMJ000450	17RNJ420450	17RNJ220460
17RNJ440430	17RNJ220440	17RNJ010450	17RNJ430450	17RNJ230460
17RNJ450430	17RNJ230440	17RNJ020450	17RNJ440450	17RNJ240460
17RNJ460430	17RNJ240440	17RNJ030450	17RNJ450450	17RNJ250460
17RNJ470430	17RNJ250440	17RNJ040450	17RNJ460450	17RNJ260460
17RNJ480430	17RNJ260440	17RNJ050450	17RNJ470450	17RNJ270460
17RNJ490430	17RNJ270440	17RNJ060450	17RNJ480450	17RNJ280460
17RNJ500430	17RNJ280440	17RNJ070450	17RNJ490450	17RNJ290460
17RMJ870440	17RNJ290440	17RNJ080450	17RNJ500450	17RNJ300460
17RMJ880440	17RNJ300440	17RNJ090450	17RMJ890460	17RNJ310460
17RMJ890440	17RNJ310440	17RNJ100450	17RMJ900460	17RNJ320460
17RMJ900440	17RNJ320440	17RNJ110450	17RMJ910460	17RNJ330460
17RMJ910440	17RNJ330440	17RNJ120450	17RMJ920460	17RNJ340460
17RMJ920440	17RNJ340440	17RNJ130450	17RMJ930460	17RNJ350460
17RMJ930440	17RNJ350440	17RNJ140450	17RMJ940460	17RNJ360460
17RMJ940440	17RNJ360440	17RNJ150450	17RMJ950460	17RNJ370460
17RMJ950440	17RNJ370440	17RNJ160450	17RMJ960460	17RNJ380460
17RMJ960440	17RNJ380440	17RNJ170450	17RMJ970460	17RNJ390460
17RMJ970440	17RNJ390440	17RNJ180450	17RMJ980460	17RNJ400460
17RMJ980440	17RNJ400440	17RNJ190450	17RMJ990460	17RNJ410460
17RMJ990440	17RNJ410440	17RNJ200450	17RMJ000460	17RNJ420460
17RMJ000440	17RNJ420440	17RNJ210450	17RNJ010460	17RNJ430460
17RNJ010440	17RNJ430440	17RNJ220450	17RNJ020460	17RNJ440460
17RNJ020440	17RNJ440440	17RNJ230450	17RNJ030460	17RNJ450460

17RNJ460460	17RNJ230470	17RNJ010480	17RNJ390480	17RNJ180490
17RNJ470460	17RNJ240470	17RNJ020480	17RNJ400480	17RNJ190490
17RNJ480460	17RNJ250470	17RNJ030480	17RNJ410480	17RNJ200490
17RNJ490460	17RNJ260470	17RNJ040480	17RNJ420480	17RNJ210490
17RNJ500460	17RNJ270470	17RNJ050480	17RNJ430480	17RNJ220490
17RMJ900470	17RNJ280470	17RNJ060480	17RNJ440480	17RNJ230490
17RMJ910470	17RNJ290470	17RNJ070480	17RNJ450480	17RNJ240490
17RMJ920470	17RNJ300470	17RNJ080480	17RNJ460480	17RNJ250490
17RMJ930470	17RNJ310470	17RNJ090480	17RNJ470480	17RNJ260490
17RMJ940470	17RNJ320470	17RNJ100480	17RNJ480480	17RNJ270490
17RMJ950470	17RNJ330470	17RNJ110480	17RNJ490480	17RNJ280490
17RMJ960470	17RNJ340470	17RNJ120480	17RNJ500480	17RNJ290490
17RMJ970470	17RNJ350470	17RNJ130480	17RMJ920490	17RNJ300490
17RMJ980470	17RNJ360470	17RNJ140480	17RMJ930490	17RNJ310490
17RMJ990470	17RNJ370470	17RNJ150480	17RMJ940490	17RNJ320490
17RMJ000470	17RNJ380470	17RNJ160480	17RMJ950490	17RNJ330490
17RNJ010470	17RNJ390470	17RNJ170480	17RMJ960490	17RNJ340490
17RNJ020470	17RNJ400470	17RNJ180480	17RMJ970490	17RNJ350490
17RNJ030470	17RNJ410470	17RNJ190480	17RMJ980490	17RNJ360490
17RNJ040470	17RNJ420470	17RNJ200480	17RMJ990490	17RNJ370490
17RNJ050470	17RNJ430470	17RNJ210480	17RMJ000490	17RNJ380490
17RNJ060470	17RNJ440470	17RNJ220480	17RNJ010490	17RNJ390490
17RNJ070470	17RNJ450470	17RNJ230480	17RNJ020490	17RNJ400490
17RNJ080470	17RNJ460470	17RNJ240480	17RNJ030490	17RNJ410490
17RNJ090470	17RNJ470470	17RNJ250480	17RNJ040490	17RNJ420490
17RNJ100470	17RNJ480470	17RNJ260480	17RNJ050490	17RNJ430490
17RNJ110470	17RNJ490470	17RNJ270480	17RNJ060490	17RNJ440490
17RNJ120470	17RNJ500470	17RNJ280480	17RNJ070490	17RNJ450490
17RNJ130470	17RMJ910480	17RNJ290480	17RNJ080490	17RNJ460490
17RNJ140470	17RMJ920480	17RNJ300480	17RNJ090490	17RNJ470490
17RNJ150470	17RMJ930480	17RNJ310480	17RNJ100490	17RNJ480490
17RNJ160470	17RMJ940480	17RNJ320480	17RNJ110490	17RNJ490490
17RNJ170470	17RMJ950480	17RNJ330480	17RNJ120490	17RNJ500490
17RNJ180470	17RMJ960480	17RNJ340480	17RNJ130490	
17RNJ190470	17RMJ970480	17RNJ350480	17RNJ140490	
17RNJ200470	17RMJ980480	17RNJ360480	17RNJ150490	
17RNJ210470	17RMJ990480	17RNJ370480	17RNJ160490	
17RNJ220470	17RMJ000480	17RNJ380480	17RNJ170490	


Appendix D: GPS Spatial Processing

Mission: 20170419_A


Mission Trajectory




Smoothed Performance Metrics




PDOP




Satellite Lock and Elevation




Baseline Length




SBET IAKAR Separation






Mission:20170419_B
Trajectory:



Smoothed Performance Metrics








SBET IAKAR Separation






Mission: 20170420_A


Trajectory



Smoothed Performance Metrics









SBET IAKAR Separation




Mission: 20170420_B




Smoothed Performance Metrics




PDOP



L1 Satellite Lock/Elevation






SBET IAKAR Separation




Mission: 20170421_A


Trajectory





Smoothed Performance Metrics



PDOP







SBET IAKAR Separation






20170421_B Trajectory



Smoothed Performance Metrics








SBET IAKAR Separation




20170421_C


Trajectory





Smoothed Performance Metrics




PDOP






SBET IAKAR Separation




Mission: 20170424_A


Trajectory





Smoothed Performance Metrics




PDOP







SBET IAKAR Separation




Mission:
20170425_A
Trajectory





Smoothed Performance Metrics



PDOP






SBET IAKAR Separation




Mission: 20170425_B


Trajectory






Smoothed Performance Metrics



PDOP









Mission:20170427_A


Trajectory





Smoothed Performance Metrics



PDOP






SBET IAKAR Separation




Mission: 20170428_A


Trajectory





Smoothed Performance Metrics




PDOP






SBET IAKAR Separation




Mission: 20170428_B


Trajectory





Smoothed Performance Metrics




PDOP






SBET IAKAR Separation






Mission: 20170429

Trajectory




Smoothed Performance Metrics







SBET IAKAR Separation




Mission: 20170522_A Trajectory





Smoothed Performance Metrics




PDOP






SBET IAKAR Separation




Mission: 20170522_B


Trajectory





Smoothed Performance Metrics




PDOP









Mission: 20170523_A



Smoothed Performance Metrics








SBET IAKAR Separation







Mission: 20170523_B

Trajectory




Smoothed Performance Metrics







SBET IAKAR Separation




Mission: 20170524_A Trajectory





Smoothed Performance Metrics




PDOP






SBET IAKAR Separation




Mission: 20170524_B


Trajectory





Smoothed Performance Metrics




PDOP







SBET IAKAR Separation






Mission: 20170526
Trajectory



Smoothed Performance Metrics







SBET IAKAR Separation




Mission: 20170527 Trajectory





Smoothed Performance Metrics




PDOP






SBET IAKAR Separation




Mission: 20170529_A


Trajectory





Smoothed Performance Metrics




PDOP







SBET IAKAR




Mission: 20170529_B
Trajectory





Smoothed Performance Metrics




PDOP






SBET IAKAR Separation




Mission: 20170529_C


Trajectory





Smoothed Performance Metrics




PDOP








SBET IAKAR Separation





Mission: 20170530_A Trajectory




Smoothed Performance Metrics







SBET IAKAR Separation




Mission: 20170530_B Trajectory






Smoothed Performance Metrics




PDOP










Mission: 20170612_A
Trajectory







PDOP



Baseline Length (m)





Program: POSGPS
Version: 4.30.3108
Project: G:\Projects\Dewberry\AR\12085a\pos\GPS\08512a.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 176637
No processed position: 160557
Missing Fwd or Rev: 4
With bad C/A code: 0
With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0163 (m)
C/A Code: 0.93 (m)
L1 Doppler: 0.016 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.010 (m)
North: 0.008 (m)
Height: 0.022 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (16074 occurrences):

East: 0.009 (m)
North: 0.004 (m)
Height: 0.021 (m)

Quality Number Percentages:

Everglades National Park Lidar
TO# G16PDO1224
August 30, 2018
Page 159 of 165

Q 1: 100.0 %
Q 2: 0.0 %
Q 3: 0.0 %
Q 4: 0.0 %
Q 5: 0.0 %
Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 100.0 %
0.10 - 0.30 m: 0.0 %
0.30 - 1.00 m: 0.0 %
1.00 - 5.00 m: 0.0 %
5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 0.0 %

Baseline Distances:

Maximum: 45.062 (km)
Minimum: 1.438 (km)
Average: 23.646 (km)
First Epoch: 41.528 (km)
Last Epoch: 45.062 (km)

Sensor Errors

