



Accuracy Report - LiDAR

ND_3DEPProcessing_6_D22 | ND

Contract: 140G0221D0010 | May 23, 2023

Version 01

Prepared for: USGS

Tnm_help@usgs.gov



Document Control

Document Information


Project Title	ND_3DEPProcessing_6_D22_300235
Document Title	Accuracy Report - LiDAR
Fugro Project No.	00210589
Fugro Document No.	Contract: 140G0221D0010
Issue Number	140G0221D0010
Issue Status	Version 01

Client Information

Client	Prepared for: USGS
--------	--------------------

Initials	Name	Role
RR	Rob Rombough	Project Manager
TW	Tian Wang	Project Lead

ND_3DEPProcessing_6_D22 – LiDAR GCP and Check Points



1. Accuracy reporting

Data collected under this Task Order meets the National Standard for Spatial Database Accuracy (NSSDA) accuracy standards. The NSSDA standards specify that vertical accuracy be reported at the 95 percent confidence level for data tested by an independent source of higher accuracy.

1.1 Positional Accuracy

Before classification and development of derivative products from the point cloud, the absolute and relative vertical accuracies of the point cloud were verified.

1.2 Horizontal Accuracy

This data set was produced to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 21.8 (cm) RMSE_x / RMSE_y Horizontal Accuracy Class which equates to Positional Horizontal Accuracy = +/- 53.5 cm at a 95% confidence level."

1.3 Absolute Vertical Accuracy

Bare Earth Surface: The accuracy (ACCZ) of the derived DEM and classified lidar data was calculated and is being reported in three (3) ways:

1. **RMSEZ (Non-Vegetated):** The required RMSEZ is ≤ 10 cm.
2. **Non-Vegetated Vertical Accuracy (NVA):** The required NVA is: ≤ 19.6 cm at a 95% confidence level, derived according to NSSDA, i.e., based on RMSEZ of 10 cm in the "open terrain" and/or "Urban" land cover categories. This is a required accuracy.
3. **Vegetated Vertical Accuracy (VVA):** The required VVA is: ≤ 29.4 cm at a 95th percentile level, derived according to ASPRS Guidelines, Vertical Accuracy for Reporting LiDAR Data, i.e. based on the 95th percentile error in Vegetated land cover categories combined (Tall Grass, Brush, Forested Areas). This is a required accuracy.

Please refer to the tables below for the achieved accuracies.

LAS	RMSEz (non-vegetated)	NVA at 95-percent confidence level	VVA at 95th percentiles
Specification (cm)	≤ 10	≤ 19.6	≤ 29.4
Calculated Values (cm)	4.4	8.7	21.6
Specification (m)	≤ 0.100	≤ 0.196	≤ 0.294
Calculated Values (m)	0.044	0.087	0.216
Number of points	227	227	99


DEM	RMSEz (non-vegetated)	NVA at 95-percent confidence level	VVA at 95th percentiles
Specification (cm)	≤ 10	≤ 19.6	≤ 29.4
Calculated Values (cm)	5.0	9.0	21.4
Specification (m)	≤ 0.100	≤ 0.196	≤ 0.294
Calculated Values (m)	0.05	0.09	0.214
Number of points	227	227	99

1.4 Relative Accuracy

Swath Separation Rasters are created at 1m resolution using 8cm threshold to show how the individual flightlines agree to one another in areas of overlap. Pixel color was based on vertical difference of swaths using the following breaks:

- 0-8 cm: GREEN;
- 8-16 cm: YELLOW;
- 16 cm or > last additional color ramp bin value: RED (for example, addition of ORANGE pixels for the range of 16-24 cm would require red pixels to represent > 24 cm).

An overview can be seen below.



The individual rasters are found in the spatial metadata folder of the deliverables.