

USGS Norfolk, VA LiDAR

Report Produced for U.S. Geological Survey

USGS Contract: G10PC00013

Task Order: G13PD00279

Report Date: 1/29/2014

SUBMITTED BY:

Dewberry

1000 North Ashley Drive Suite 801
Tampa, FL 33602
813.225.1325

SUBMITTED TO:

U.S. Geological Survey

1400 Independence Road
Rolla, MO 65401
573.308.3810

Table of Contents

Executive Summary	6
The Project Team	6
Survey Area.....	6
Date of Survey	6
Datum Reference.....	6
LiDAR Vertical Accuracy	7
Project Deliverables	7
Project Tiling Footprint	8
LiDAR Acquisition Report	9
Acquisition Equipment.....	9
LiDAR System parameters	10
Datum Reference.....	11
Atlantic LiDAR Acquisition Details	11
Acquisition Flight Logs, Dates, and Flightlines	12
LMSI LiDAR Acquisition Details	15
Acquisition Dates and Flightlines	16
Generation and Calibration of Laser Points (raw data)	17
Combined Swath Vertical Accuracy Assessment	18
LiDAR Processing & Qualitative Assessment	19
Data Classification and Editing.....	19
Qualitative Assessment.....	21
Analysis.....	23
Derivative LiDAR Products	34
Building Footprint Shapefiles	34
Vegetation Shapefiles	37
Survey Vertical Accuracy Checkpoints.....	37
LiDAR Vertical Accuracy Statistics & Analysis.....	40
Background.....	40
Vertical Accuracy Test Procedures.....	40
FVA	40
CVA.....	40
SVA	40
Vertical Accuracy Testing Steps	41
Vertical Accuracy Results	43
Breakline Production & Qualitative Assessment Report	46

Breakline Production Methodology46
 Breakline Qualitative Assessment.....46
 Breakline Topology Rules46
 Breakline QA/QC Checklist47
 Data Dictionary 51
 Horizontal and Vertical Datum 51
 Coordinate System and Projection..... 51
 Inland Streams and Rivers 51
 Description 51
 Table Definition 51
 Feature Definition..... 51
 Inland Ponds and Lakes53
 Description53
 Table Definition53
 Feature Definition.....53
 Tidal Waters55
 Description55
 Table Definition55
 Feature Definition.....55
 2D Buildings56
 Description56
 Table Definition56
 Feature Definition.....56
 3D Buildings57
 Description57
 Table Definition57
 Feature Definition.....58
 Forest Polygons59
 Description59
 Table Definition59
 Feature Definition.....59
 Tree Points..... 60
 Description 60
 Table Definition 60
 Feature Definition..... 60
 DEM Production & Qualitative Assessment 60

DEM Production Methodology 60

DEM Qualitative Assessment.....62

DEM Vertical Accuracy Results63

DEM QA/QC Checklist64

Appendix A: Survey Report.....66

INTRODUCTION66

 Project Summary66

 Points of Contact.....66

 1.3 Project Area 68

Project Details69

 Survey Equipment69

 Survey Point Detail69

 Network Design69

 Field Survey Procedures and Analysis69

 Data Processing Procedures.....70

Final Coordinates70

GPS Observations.....73

Point Comparison76

Appendix B: Complete List of Delivered Tiles78

 UTM Tiles (1,457):.....78

 SPCS Tiles (388):87

Appendix C: GPS Processing Reports for Each Mission..... 90

 Laser Mapping Specialists (LMSI)..... 90

 The Atlantic Group..... 152

Output Results for JD13087_1 152

 Figure 1: Trajectory Map 152

 Figure 2: Position and Standard Deviation..... 153

 Figure 3: Velocity and Standard Deviation 154

 Figure 4: Forward/Reverse or Combined Separation Plot 155

 Figure 5: Attitude and Standard Deviation..... 156

 Figure 6: Position Accuracy and PDOP 157

 Figure 7: Accelerometer Bias Estimation..... 158

 Figure 8: Kalman Filter Residuals and Position Accuracy 159

 Figure 9: Gyro Bias Estimation.....160

Output Result for JD13088_1 161

Executive Summary

The primary purpose of this project was to develop a consistent and accurate surface elevation dataset derived from high-accuracy Light Detection and Ranging (LiDAR) technology for the USGS Norfolk, Virginia Project Area.

The LiDAR data were processed to a bare-earth digital terrain model (DTM). Detailed breaklines, 3D buildings, 2D buildings, forest polygons, tree points, bare-earth digital elevation models (DEMs), first return digital surface models, and last return digital surface models were produced for the project area. Deliverables were produced in both UTM and State Plane coordinates. Data was formatted according to tiles with each UTM tile covering an area of 1,500 meters by 1,500 meters and each State Plane tile covering an area of 10,000 feet by 10,000 feet. A total of 1,457 UTM tiles and 388 State Plane tiles were produced for the project encompassing an area of approximately 1,130 sq. miles.

THE PROJECT TEAM

Dewberry served as the prime contractor for the project. In addition to project management, Dewberry was responsible for, all LiDAR products including; LAS classification, breakline production, Digital Elevation Model (DEM) production, and quality assurance.

Dewberry's Matthew Rudolph completed ground surveying for the project and delivered surveyed checkpoints. His task was to acquire surveyed checkpoints for the project to use in independent testing of the vertical accuracy of the LiDAR-derived surface model. He also verified the GPS base station coordinates used during LiDAR data acquisition to ensure that the base station coordinates were accurate. Please see Appendix A to view the separate Survey Report that was created for this portion of the project.

Laser Mapping Specialist, Inc (LMSI) and The Atlantic Group (Atlantic) completed LiDAR data acquisition and data calibration for the project area.

SURVEY AREA

The project area addressed by this report falls within the Virginia counties of Chesapeake, Hampton, James City, Newport News, Norfolk, Poquoson City, Portsmouth, Suffolk, Virginia Beach, Williamsburg, and York as well as portions of the North Carolina counties of Camden and Currituck.

DATE OF SURVEY

The LiDAR aerial acquisition for the Southern portion of the project was conducted from March 25, 2013 thru April 5, 2013. The LiDAR aerial acquisition for the Northern portion of the project was conducted from March 21, 2013 thru March 31, 2013.

DATUM REFERENCE

Data produced for the project were delivered in both of the following reference systems.

Horizontal Datum: The horizontal datum for the project is North American Datum of 1983 (NAD 83)

Vertical Datum: The Vertical datum for the project is North American Vertical Datum of 1988 (NAVD88)

Coordinate System: UTM Zone 18

Units: Horizontal units are in meters, Vertical units are in meters.

Geoid Model: Geoid12A

Horizontal Datum: North American Datum of 1983 HARN (NAD83 HARN)

Vertical Datum: North American Vertical Datum of 1988 (NAVD88)

Coordinate System: Virginia State Plane South

Units: Horizontal units are in U.S. Survey feet, Vertical units are in feet.

Geoid Model: Geoid12A

LIDAR VERTICAL ACCURACY

For the Norfolk, Virginia LiDAR Project, the tested RMSE_z of the classified LiDAR data for checkpoints in open terrain equaled **0.066 m** compared with the 0.092 m specification; and the FVA of the classified LiDAR data computed using RMSE_z x 1.9600 was equal to **0.129 m**, compared with the 0.181 m specification.

For the Norfolk, Virginia LiDAR Project, the tested CVA of the classified LiDAR data computed using the 95th percentile was equal to **0.194 m**, compared with the 0.269 m specification.

Additional accuracy information and statistics for the classified LiDAR data, raw swath data, and bare earth DEM data are found in the following sections of this report.

PROJECT DELIVERABLES

The deliverables for the project are listed below.

1. Raw Point Cloud Data (Swaths) in UTM coordinates
2. Control & Accuracy Checkpoint Report & Points in UTM coordinates
3. Project Report (Acquisition, Processing, QC)
4. Classified Point Cloud Data (Tiled) in both UTM and State Plane coordinates
5. First Return Surface (Raster DSM – IMG Format) in both UTM and State Plane coordinates
6. Last Return Surface (Raster DSM – IMG Format) in both UTM and State Plane coordinates
7. Bare Earth Surface (Raster DEM – IMG Format) in both UTM and State Plane coordinates
8. Intensity Images (8-bit gray scale, tiled, GeoTIFF format) in both UTM and State Plane coordinates
9. Breakline Data (File GDB) in both UTM and State Plane coordinates
10. 3D and 2D buildings (File GDB) in both UTM and State Plane coordinates
11. Forest polygons (File GDB) in both UTM and State Plane coordinates
12. Tree points (File GDB) in both UTM and State Plane coordinates
13. Metadata
14. Project Extents in both UTM and State Plane coordinates, including a shapefile derived from the LiDAR Deliverable

PROJECT TILING FOOTPRINT

One thousand four hundred and fifty eight (1,457) UTM tiles were delivered for the project. Each UTM tile's extent is 1,500 meters by 1,500 meters. Three hundred and eighty eight (388) State Plane tiles were delivered for the project. Each State plane tiles extent is 10,000 ft by 10,000 ft (see Appendix B for a complete listing of delivered tiles).

Norfolk, VA LiDAR Project




Figure 1 - Project Map

LiDAR Acquisition Report

Dewberry elected to subcontract the LiDAR Acquisition and Calibration activities to The Atlantic Group (Atlantic) and Laser Mapping Specialist Inc (LMSI). Atlantic and LMSI were responsible for providing LiDAR acquisition, calibration and delivery of LiDAR data files to Dewberry.

Dewberry received high accuracy, calibrated multiple return swath data from Atlantic on May 21, 2013 and from LMSI on June 5, 2013. Data was collected and delivered in compliance with the “U.S. Geological Survey National Geospatial Program Base LiDAR Specifications, Version 13 – ILMF 2010.”

ACQUISITION EQUIPMENT

Atlantic operated a Cessna T-210 (Tail # N732JE) outfitted with a LEICA ALS70-HP LiDAR system during the collection of the Southern portion of the study area. Table 1 represents a list of the features and characteristics for the LEICA ALS70-HP LiDAR system:

Leica ALS70-HP		
Manufacturer	Leica	
Model	ALS70 - HP	
Platform	Fixed-wing	
Scan Pattern	sine, triangle, raster	
Maximum Scan rate (Hz)	sine	200
	triangle	158
	raster	120
Field of view (°)	0 - 75 (full angle, user adjustable)	
Maximum Pulse rate (kHz)	500	
Maximum Flying height (m AGL)	3500	
Number of returns	unlimited	
Number of intensity measurements	3 (first, second, third)	
Roll stabilization (automatic adaptive, °)	75 - active FOV	
Storage media	removable 500 GB SSD	
Storage capacity (hours @ max pulse rate)	6	
size (cm)	Scanner	37 W x 68 L x 26 H
	Control Electronics	45 W x 47 D x 36 H
Weight (kg)	Scanner	43
	Control Electronics	45
Operating Temperature	0 - 40 °C	
Flight Management	FCMS	
Power Consumption	927 W @ 22.0 - 30.3 VDC	

Table 1: Atlantic’s LEICA Sensor Characteristic

LMSI operated an Optech 3100 EA LiDAR system during the collection of the Northern portion of the study area. Table 2 represents a list of the features and characteristics for the Optech 3100 EA LiDAR system:

Optech 3100 EA		
Manufacturer	Optech	
Model	3100EA	
Platform	Fixed-wing	
Maximum Scan rate (Hz)	0 to 70 Hz (>70 Hz optional)	
Field of view (°)	0 - 75 (full angle, user adjustable)	
Maximum Pulse rate (kHz)	100	
Maximum Flying height (m AGL)	3500	
Number of returns	Up to 4 range measurements, including 1 st , 2 nd , 3 rd , last returns	
Number of intensity measurements	12-bit dynamic range. Measurements for all recorded returns, including last return.	
Roll stabilization (automatic adaptive, °)	±5°; more compensation available if FOV reduced. Programmable in ±1° increments	
Storage media	Ruggedized removable SCSI hard disks	
size (cm)	Scanner	26cm W x 19cm L x 57 cm H
	Control Electronics	65 cm W x 59 cm D x 49 cm H
Weight (kg)	Scanner	23.4 kg
	Control Electronics	53.2 kg
Operating Temperature	Control rack: +10°C to 35 °C Sensor head: -10 °C to +35 °C	
Power Consumption	28 V 35 A (peak)	

Table 2: LMSI's Optech Sensor Characteristic

LIDAR SYSTEM PARAMETERS

Table 3 illustrates Atlantic's system parameters for LiDAR acquisition on this project.

Item	Parameter
System	Leica ALS-70 HP
Altitude (AGL meters)	1700
Approx. Ground Speed (kts)	120
Laser Firing Rate (kHz)	316.2
Scan Frequency (hz)	42.3
Swath width (m)	1237
Swath Overlap (%)	15%
Line Spacing (m)	858
Pass heading (degree)	164

Item	Parameter
Field of View (degree)	40
Computed Down Track spacing (m) per beam	0.73
Computed Cross Track Spacing (m) per beam	0.73
Average point spacing (m) per beam	0.7
Point Spacing density at Nadir	3.8
Points per meter ² (m)	2.4
Gain up/Down	3
Scan Pattern	Triangle

Table 3: Atlantics LiDAR System Parameters

Table 4 illustrates LMSI's system parameters for LiDAR acquisition on this project.

Item	Parameter
System	Optech 3100 EA
Altitude (AGL meters)	880
Approx. Ground Speed (kts)	110
Laser Firing Rate (kHz)	70
Scan Frequency (hz)	40
Swath width (m)	612
Swath Overlap (%)	25%
Line Spacing (m)	275
Field of View (degree)	38
Computed Down Track spacing (m)	0.5
Computed Cross Track Spacing (m)	0.5
Points per meter ² (m)	2

Table 4: LMSI's LiDAR System Parameters

DATUM REFERENCE

Horizontal Datum: The horizontal datum for the project is North American Datum of 1983 (NAD 83)

Vertical Datum: The Vertical datum for the project is North American Vertical Datum of 1988 (NAVD88)

Coordinate System: UTM Zone 18

Units: Horizontal units are in meters, Vertical units are in meters.

Geoid Model: Geoid12A

ATLANTIC LIDAR ACQUISITION DETAILS

Atlantic planned 64 passes for the Southern portion of the project area as a series of parallel flight lines with cross flightlines for the purposes of quality control. The flight plan included zigzag flight line collection as a result of the inherent IMU drift associated with all IMU systems. In order to reduce any margin for error in the flight plan, Atlantic followed FEMA's Appendix A "guidelines" for flight planning and, at a minimum, includes the following criteria:

- A digital flight line layout using LEICA MISSION PRO flight design software for direct integration into the aircraft flight navigation system.

- Planned flight lines; flight line numbers; and coverage area.
- LiDAR coverage extended by a predetermined margin beyond all project borders to ensure necessary over-edge coverage appropriate for specific task order deliverables.
- Local restrictions related to air space and any controlled areas have been investigated so that required permissions can be obtained in a timely manner with respect to schedule. Additionally, Atlantic Group will file our flight plans as required by local Air Traffic Control (ATC) prior to each mission.

Atlantic monitored weather and atmospheric conditions and conducted LiDAR missions only when no conditions exist below the sensor that will affect the collection of data. These conditions include leaf-off for hardwoods, no snow, rain, fog, smoke, mist and low clouds. LiDAR systems are active sensors, not requiring light, thus missions may be conducted during night hours when weather restrictions do not prevent collection. Atlantic accesses reliable weather sites and indicators (webcams) to establish the highest probability for successful collection in order to position our sensor to maximize successful data acquisition. Within 72-hours prior to the planned day(s) of acquisition, Atlantic closely monitored the weather, checking all sources for forecasts at least twice daily. As soon as weather conditions were conducive to acquisition, our aircraft mobilized to the project site to begin data collection. Once on site, the acquisition team took responsibility for weather analysis. Atlantic LiDAR sensors are calibrated at a designated site located at the Lawrence County Airport in Courtland, Alabama and are periodically checked and adjusted to minimize corrections at project sites.

ACQUISITION FLIGHT LOGS, DATES, AND FLIGHTLINES

Upon notification to proceed, the flight crew loaded the flight plans and validated the flight parameters. The Acquisition Manager contacted air traffic control and coordinated flight pattern requirements. LiDAR acquisition began immediately upon notification that control base stations were in place. During flight operations, the flight crew monitored weather and atmospheric conditions. LiDAR missions were flown only when no condition existed below the sensor that would affect the collection of data. The pilot constantly monitored the aircraft course, position, pitch, roll, and yaw of the aircraft. The sensor operator monitored the sensor, the status of PDOPs, and performed the first Q/C review during acquisition. The flight crew constantly reviewed weather and cloud locations. Any flight lines impacted by unfavorable conditions were marked as invalid and re-flown immediately or at an optimal time.

The table below shows the flight missions to acquire the laser data including flight dates, daily missions, number of lines, tidal information, and comments for each flight.

Date	Mission #	Lines Flown
3/25/13 to 3/29/13	5	1-43
3/31/13 to 4/5/13	5	44-66

Table 5: Flight Lines and Acquisition Dates

The figure below illustrates Atlantic’s final trajectories.




Figure 2: Trajectories as flown by Atlantic LiDAR Control

All surveys were performed to Federal Geodetic Control Subcommittee (FGCS) FGCS guidelines. Atlantic Group maximized existing NGS control and the ALDOT CORS stations to provide the control network, designed with proper redundancies, session occupation times, and time between sessions according to the applicable NOS technical standards. GPS observations were conducted using Federal Geodetic Control Committee (FGCC) approved dual frequency GPS receivers. A minimum of two fixed-height tripods were used as ground base stations running at a one (1.0) second epoch collection rate during every mission, typically at a minimum of four hours. The control locations are planned to ensure a 28km baseline distance from the furthest flight line distance. All mission collections were conducted with a PDOP of 3.2 or lower. Also, the KP index is considered prior to mission collection and no collection occurred when the KP index was at or above 4. During acquisition the following ground control points were used.

Station	Latitude	Longitude	Northing	Easting	Elevation	PID
CEM1	36 44 42.01674	76 06 26.52957	4067157.092	401140.823	5.000m	
CPK1	36 39 56.13139	76 19 19.36753	4058590.483	381853.335	4.185m	DN7636

Table 6 – Base Stations used to control LiDAR acquisition

Station	Julian Day	Receiver Model	Antenna Model	Height (m)	Start Date/Time	Stop Date/Time
CPK1	87	TOPCON	TPSHIPER_V	1.374	3/28/13 22:20	3/28/13 15:00
CEM1	88	TOPCON	TPSHIPER_V	1.391	3/29/13 11:15	3/29/13 11:43
CPK1	88	TOPCON	TPSHIPER_V	1.374	3/29/13	3/29/13

					2:30	17:33
CEM1	89	TOPCON	TPSHIPER_V	1.389	3/30/13 11:20	3/30/13 22:38
CPK1	89	TOPCON	TPSHIPER_V	1.374	3/30/13 15:22	3/30/13 20:02
CEM1	90	TOPCON	TPSHIPER_V	1.389	3/31/13 10:45	3/30/13 11:30
CPK1	90	TOPCON	TPSHIPER_V	1.374	3/31/13 4:15	3/31/13 8:30
CEM1	91	TOPCON	TPSHIPER_V	1.390	4/1/13 11:45	4/1/13 24:00
CPK1	91	TOPCON	TPSHIPER_V	1.373	4/1/13 5:15	4/1/13 20:30

Table 7 – Site Observations

Airborn GPS Kinematic

LEICA IPAS TC was used to post process the airborne solutions for the mission. IGS08 (EPOCH:2013.1011) coordinates from the OPUS solutions was used in the post processing.

Generation and Calibration of Laser Points (raw data)

Data collected by the LiDAR unit is reviewed for completeness, acceptable density and to make sure all data is captured without errors or corrupted values. In addition, all GPS, aircraft trajectory, mission information, and ground control files are reviewed and logged into a database.

On a project level, a supplementary coverage check is carried out to ensure no data voids are present.



Figure 3 – LiDAR Swath output showing complete coverage. Boresight and Relative accuracy

The initial points for each mission calibration are inspected for flight line errors, flight line overlap, slivers or gaps in the data, point data minimums, or issues with the LiDAR unit or GPS. Roll, pitch and scanner scale are optimized during the calibration process until the relative accuracy is met.

Relative accuracy and internal quality are checked using at least 3 regularly spaced QC blocks in which points from all lines are loaded and inspected. Vertical differences between ground surfaces of each line are displayed. Color scale is adjusted so that errors greater than the specifications are flagged. Cross sections are visually inspected across each block to validate point to point, flight line to flight line and mission to mission agreement.

LMSI LIDAR ACQUISITION DETAILS

LMSI planned 90 passes for the Northern portion of the project area as a series of parallel flight lines with cross flightlines for the purposes of quality control. The flight plan included zigzag flight line collection as a result of the inherent IMU drift associated with all IMU systems. In order to reduce any margin for error in the flight plan, LMSI followed FEMA's Appendix A "guidelines" for flight planning and, at a minimum, includes the following criteria:

- A digital flight line layout using ALTM-NAV flight management software for direct integration into the aircraft flight navigation system.
- Planned flight lines; flight line numbers; and coverage area.
- LiDAR coverage extended by a predetermined margin beyond all project borders to ensure necessary over-edge coverage appropriate for specific task order deliverables.
- Local restrictions related to air space and any controlled areas have been investigated so that required permissions can be obtained in a timely manner with respect to schedule. Additionally LMSI will file our flight plans as required by local Air Traffic Control (ATC) prior to each mission.

LMSI monitored weather and atmospheric conditions and conducted LiDAR missions only when no conditions exist below the sensor that will affect the collection of data. These conditions include leaf-off for hardwoods, no snow, rain, fog, smoke, mist and low clouds. LiDAR systems are active sensors, not requiring light, thus missions may be conducted during night hours when weather restrictions do not prevent collection. LMSI accesses reliable weather sites and indicators (webcams) to establish the highest probability for successful collection in order to position our sensor to maximize successful data acquisition.

Within 72-hours prior to the planned day(s) of acquisition, LMSI closely monitored the weather, checking all sources for forecasts at least twice daily. As soon as weather conditions were conducive to acquisition, our aircraft mobilized to the project site to begin data collection. Once on site, the acquisition team took responsibility for weather analysis.

ACQUISITION DATES AND FLIGHTLINES

Table 8 shows the flight missions to acquire the laser data including flight dates, daily missions, number of lines, tidal information, and comments for each flight.

Date	Mission #	Lines Flown	Mission Time	Tidal Window	Mission Notes
3/21/13	1	1-18	10:23-1:30	9:36-1:36	
3/22/13	2	19-23, 23-25	11:21-12:33, 1:34-2:22	10:22-2:22	Had mechanical issue, fixed, went back up
3/23/13	0				Laser maint/ground control
3/24/13	0				Weather/ground control
3/25/13	0				Weather/ground control
3/26/13	0				Ground Control/laser maint
3/27/13	0				Ground Control
3/28/13	1	26-31	4:55-6:25	2:41-6:41	
3/29/13	2	32-54	3:37-7:10a, 3:57-7:16p	3:18-7:18a, 3:26-7:16p	
3/30/13	2	55-90	4:20-8:05am, 4:16-6:23p	4:07-8:07a, 4:13-8:13p	
3/31/13	1	26-31	5:05-6:41a	4:58-8:58a	reflights

Table 8: Flight Lines and Acquisition Dates

The figure below illustrates LMSI's final trajectories.




Figure 4: Trajectories as flown by LMSI LiDAR Control

Two base stations were utilized. The base station coordinates are set forth below.

Latitude	Longitude	Elevation
37 11 46.65724	76 29 28.13126	-18.135m
37 07 27.35080	76 25 12.73298	-33.312m

Table 9 – Base Stations used to control LiDAR acquisition Airborne GPS Kinematic

All airborne GPS trajectories were processed and checked on site. All trajectories were very high quality with forward/reverse separation between 2cm-5cm.

GENERATION AND CALIBRATION OF LASER POINTS (RAW DATA)

The initial step of calibration is to verify availability and status of all needed GPS and Laser data against field notes and compile any data if not complete.

If a calibration error greater than specification is observed within the mission, the roll, pitch and scanner scale corrections that need to be applied are calculated. The missions with the new calibration values are regenerated and validated internally once again to ensure quality.

Data collected by the LiDAR unit is reviewed for completeness, acceptable density and to make sure all data is captured without errors or corrupted values. In addition, all GPS, aircraft trajectory, mission information, and ground control files are reviewed and logged into a database.

On a project level, a supplementary coverage check is carried out to ensure no data voids unreported by Field Operations are present.




Figure 5 – LiDAR Swath output showing complete coverage. Boresight and Relative accuracy

The initial points for each mission calibration are inspected for flight line errors, flight line overlap, slivers or gaps in the data, point data minimums, or issues with the LiDAR unit or GPS. Roll, pitch and scanner scale are optimized during the calibration process until the relative accuracy is met.

Relative accuracy and internal quality are checked using at least 3 regularly spaced QC blocks in which points from all lines are loaded and inspected. Vertical differences between ground surfaces of each line are displayed. Color scale is adjusted so that errors greater than the specifications are flagged. Cross sections are visually inspected across each block to validate point to point, flight line to flight line and mission to mission agreement.

COMBINED SWATH VERTICAL ACCURACY ASSESSMENT

Dewberry tested the vertical accuracy of the open terrain swath data upon receipt of the calibrated data from Atlantic and LMSI. Dewberry tested the vertical accuracy of the swath data using the eighteen open terrain independent survey check points. The vertical accuracy is tested by comparing survey checkpoints in open terrain to a triangulated irregular network (TIN) that is created from the raw swath points. Only checkpoints in open terrain can be tested against raw swath data because the data has not undergone classification techniques to remove vegetation,

buildings, and other artifacts from the ground surface. Checkpoints are always compared to interpolated surfaces from the LiDAR point cloud because it is unlikely that a survey checkpoint will be located at the location of a discrete LiDAR point. Project specifications require a FVA of 0.181 m based on the $RMSE_z$ (0.0925 m) x 1.96. The dataset for the Norfolk, VA LiDAR Project satisfies these criteria. The raw LiDAR swath data tested 0.163 m vertical accuracy at 95% confidence level in open terrain, based on $RMSE_z$ (0.083m) x 1.9600. The table below shows all calculated statistics for the raw swath data.

100 % of Totals	$RMSE_z$ (m) Open Terrain Spec=0.0925m	FVA – Fundamental Vertical Accuracy ($RMSE_z$ x 1.9600) Spec=0.181m	Mean (m)	Median (m)	Skew	Std Dev (m)	# of Points	Min (m)	Max (m)
Open Terrain	0.083	0.163	0.058	0.025	0.963	0.077	18	-0.109	0.248

Table 10: FVA at 95% Confidence Level for Raw Swaths

Based on the initial vertical accuracy testing conducted by Dewberry, the calibrated data received from Atlantic and LMSI for the Norfolk, VA LiDAR Project satisfies the project’s pre-defined vertical accuracy criteria.

LiDAR Processing & Qualitative Assessment

DATA CLASSIFICATION AND EDITING

LiDAR mass points were produced to LAS 1.2 specifications, including the following LAS classification codes:

- Class 1 = Unclassified, used for all other features that do not fit into the Classes 2, 7, 9, 10, or 11, including vegetation, buildings, etc.
- Class 2 = Bare-Earth Ground
- Class 7 = Noise, low and high points
- Class 9 = Water, points located within collected breaklines
- Class 10 = Ignored Ground due to breakline proximity.
- Class 11 = Withheld, Points with scan angles exceeding +/- 20 degrees.

The data was processed using GeoCue and TerraScan software. The initial step is the setup of the GeoCue project, which is done by importing a project defined tile boundary index encompassing the entire project area. The acquired 3D laser point clouds, in LAS binary format, were imported into the GeoCue project and tiled according to the project tile grid. Once tiled, the laser points were classified using a proprietary routine in TerraScan. This routine classifies any obvious outliers in the dataset to class 7 and points with scan angles exceeding +/- 20 degrees to class 11. After points that could negatively affect the ground are removed from class

1, the ground layer is extracted from this remaining point cloud. The ground extraction process encompassed in this routine takes place by building an iterative surface model.

This surface model is generated using three main parameters: building size, iteration angle and iteration distance. The initial model is based on low points being selected by a "roaming window" with the assumption that these are the ground points. The size of this roaming window is determined by the building size parameter. The low points are triangulated and the remaining points are evaluated and subsequently added to the model if they meet the iteration angle and distance constraints. This process is repeated until no additional points are added within iterations. A second critical parameter is the maximum terrain angle constraint, which determines the maximum terrain angle allowed within the classification model.

The following fields within the LAS files are populated to the following precision: GPS Time (0.000001 second precision), Easting (0.003 meter precision), Northing (0.003 meter precision), Elevation (0.003 meter precision), Intensity (integer value - 12 bit dynamic range), Number of Returns (integer - range of 1-4), Return number (integer range of 1-4), Scan Direction Flag (integer - range 0-1), Classification (integer), Scan Angle Rank (integer), Edge of flight line (integer, range 0-1), User bit field (integer - flight line information encoded). The LAS file also contains a Variable length record in the file header that defines the projection, datums, and units.

Once the initial ground routine has been performed on the data, Dewberry creates Delta Z (DZ) orthos to check the relative accuracy of the LiDAR data. These orthos compare the elevations of LiDAR points from overlapping flight lines on a 1 meter pixel cell size basis. If the elevations of points within each pixel are within 10 cm of each other, the pixel is colored green. If the elevations of points within each pixel are between 10 cm and 20 cm of each other, the pixel is colored yellow, and if the elevations of points within each pixel are greater than 20 cm in difference, the pixel is colored red. Pixels that do not contain points from overlapping flight lines are colored according to their intensity values. DZ orthos can be created using the full point cloud or ground only points and are used to review and verify the calibration of the data is acceptable. Some areas are expected to show sections or portions of red, including terrain variations, slope changes, and vegetated areas or buildings if the full point cloud is used. However, large or continuous sections of yellow or red pixels can indicate the data was not calibrated correctly or that there were issues during acquisition that could affect the usability of the data. The DZ orthos for Norfolk, VA showed that the data was calibrated correctly with no issues that would affect its usability. The figure below shows an example of the DZ orthos.




Figure 6 - DZ orthos created from the full point cloud. Some red pixels are visible along embankments, sloped terrain, on buildings, and in vegetated land cover, as expected. Open, flat areas are green indicating the calibration and relative accuracy of the data is acceptable.

Once the calibration and relative accuracy of the data was confirmed, Dewberry utilized a variety of software suites for data processing. The LAS dataset was imported into GeoCue task management software for processing in Terrascan. Each tile was imported into Terrascan and a surface model was created to examine the ground classification. Dewberry analysts visually reviewed the ground surface model and corrected errors in the ground classification such as vegetation, buildings, and bridges that were present following the initial processing conducted by Dewberry. Dewberry analysts employ 3D visualization techniques to view the point cloud at multiple angles and in profile to ensure that non-ground points are removed from the ground classification. After the ground classification corrections were completed, the dataset was processed through a water classification routine that utilizes breaklines compiled by Dewberry to automatically classify hydro features. The water classification routine selects ground points within the breakline polygons and automatically classifies them as class 9, water. The final classification routine applied to the dataset selects ground points within a specified distance of the water breaklines and classifies them as class 10, ignored ground due to breakline proximity.

QUALITATIVE ASSESSMENT

Dewberry's qualitative assessment utilizes a combination of statistical analysis and interpretative methodology to assess the quality of the data for a bare-earth digital terrain model (DTM). This process looks for anomalies in the data and also identifies areas where man-made structures or vegetation points may not have been classified properly to produce a bare-earth model.

Within this review of the LiDAR data, two fundamental questions were addressed:

- Did the LiDAR system perform to specifications?
- Did the vegetation removal process yield desirable results for the intended bare-earth terrain product?

Mapping standards today address the quality of data by quantitative methods. If the data are tested and found to be within the desired accuracy standard, then the data set is typically accepted. Now with the proliferation of LiDAR, new issues arise due to the vast amount of data. Unlike photogrammetrically-derived DEMs where point spacing can be eight meters or more, LiDAR nominal point spacing for this project is 1 point per 0.7 square meters. The end result is that millions of elevation points are measured to a level of accuracy previously unseen for traditional elevation mapping technologies and vegetated areas are measured that would be nearly impossible to survey by other means. The downside is that with millions of points, the dataset is statistically bound to have some errors both in the measurement process and in the artifact removal process.

As previously stated, the quantitative analysis addresses the quality of the data based on absolute accuracy. This accuracy is directly tied to the comparison of the discreet measurement of the survey checkpoints and that of the interpolated value within the three closest LiDAR points that constitute the vertices of a three-dimensional triangular face of the TIN. Therefore, the end result is that only a small sample of the LiDAR data is actually tested. However there is an increased level of confidence with LiDAR data due to the relative accuracy. This relative accuracy in turn is based on how well one LiDAR point "fits" in comparison to the next contiguous LiDAR measurement, and is verified with DZ orthos. Once the absolute and relative accuracy has been ascertained, the next stage is to address the cleanliness of the data for a bare-earth DTM.

By using survey checkpoints to compare the data, the absolute accuracy is verified, but this also allows us to understand if the artifact removal process was performed correctly. To reiterate the quantitative approach, if the LiDAR sensor operated correctly over open terrain areas, then it most likely operated correctly over the vegetated areas. This does not mean that the entire bare-earth was measured; only that the elevations surveyed are most likely accurate (including elevations of treetops, rooftops, etc.). In the event that the LiDAR pulse filtered through the vegetation and was able to measure the true surface (as well as measurements on the surrounding vegetation) then the level of accuracy of the vegetation removal process can be tested as a by-product.

To fully address the data for overall accuracy and quality, the level of cleanliness (or removal of above-ground artifacts) is paramount. Since there are currently no effective automated testing procedures to measure cleanliness, Dewberry employs a combination of statistical and visualization processes. This includes creating pseudo image products such as LiDAR orthos produced from the intensity returns, Triangular Irregular Network (TIN)'s, Digital Elevation Models (DEM) and 3-dimensional models. By creating multiple images and using overlay techniques, not only can potential errors be found, but Dewberry can also find where the data meets and exceeds expectations. This report will present representative examples where the LiDAR and post processing had issues as well as examples of where the LiDAR performed well.

ANALYSIS

Dewberry utilizes GeoCue software as the primary geospatial process management system. GeoCue is a three tier, multi-user architecture that uses .NET technology from Microsoft. .NET technology provides the real-time notification system that updates users with real-time project status, regardless of who makes changes to project entities. GeoCue uses database technology for sorting project metadata. Dewberry uses Microsoft SQL Server as the database of choice. Specific analysis is conducted in Terrascan and QT Modeler environments.

Following the completion of LiDAR point classification, the Dewberry qualitative assessment process flow for the Norfolk, VA LiDAR project incorporated the following reviews:

1. *Format*: The LAS files are verified to meet project specifications. The LAS files for the Norfolk, VA LiDAR project conform to the specifications outlined below.
 - Format, Echos, Intensity
 - o LAS format 1.2
 - o Point data record format 1
 - o Multiple returns (echos) per pulse
 - o Intensity values populated for each point
 - ASPRS classification scheme
 - o Class 1 – unclassified
 - o Class 2 – Bare-earth ground
 - o Class 7 – Noise
 - o Class 9 – Water
 - o Class 10 – Ignored Ground due to breakline proximity
 - o Class 11 – Withheld due to scan angles exceeding +/- 20 degrees
 - Projections
 - o Datum – North American Datum 1983
 - o Projected Coordinate System – UTM Zone 18
 - o Linear Units – Meters
 - o Vertical Datum – North American Vertical Datum 1988, Geoid 12A
 - o Vertical Units – Meters
 - o Datum – North American Datum 1983 HARN (NAD83 HARN)
 - o Projected Coordinate System – Virginia State Place South
 - o Linear Units – U.S. Survey Feet
 - o Vertical Datum – North American Vertical Datum 1988, Geoid 12A
 - o Vertical Units – Feet
 - LAS header information:
 - o Class (Integer)
 - o Adjusted GPS Time (0.0001 seconds)
 - o Easting (0.003 meters)
 - o Northing (0.003 meters)
 - o Elevation (0.003 meters)
 - o Echo Number (Integer 1 to 4)
 - o Echo (Integer 1 to 4)

- Intensity (8 bit integer)
 - Flight Line (Integer)
 - Scan Angle (Integer degree)
2. *Data density, data voids:* The LAS files are used to produce Digital Elevation Models using the commercial software package “QT Modeler” which creates a 3-dimensional data model derived from Class 2 (ground points) in the LAS files. Grid spacing is based on the project density deliverable requirement for un-obscured areas. For the Norfolk, VA LiDAR project it is stipulated that the minimum post spacing in un-obscured areas should be 1 point per 0.7 square meters.
- a. Acceptable voids (areas with no LiDAR returns in the LAS files) that are present in the majority of LiDAR projects include voids caused by bodies of water. These are considered to be acceptable voids. No unacceptable voids are present in the Norfolk, VA LiDAR project.

3. *Bare earth quality:* Dewberry reviewed the cleanliness of the bare earth to ensure the ground has correct definition, meets the project requirements, there is correct classification of points, and there are less than 5% residual artifacts.

- a. *Artifacts:* Artifacts are caused by the misclassification of ground points and usually represent vegetation and/or man-made structures. The artifacts identified are usually low lying structures, such as porches or low vegetation used as landscaping in neighborhoods and other developed areas. These low lying features are extremely difficult for the automated algorithms to detect as non-ground and must be removed manually. The vast majority of these features have been removed but a small number of these features are still in the ground classification. The limited numbers of features remaining in the ground are usually 0.3 meters or less above the actual ground surface, and should not negatively impact the usability of the dataset.




Figure 7 – Tile number 18SVF020755. Profile with points colored by class (class 1=white, class 2=orange) is shown in the top view and a model of the surface is shown in the bottom view. The arrow identifies low structure or vegetation points. A limited number of these small features are still classified as ground but do not impact the usability of the dataset.

- b. *Bridge Removal Artifacts:* The DEM surface models are created from TINs or Terrains. TIN and Terrain models create continuous surfaces from the inputs. Because a continuous surface is being created, the TIN or Terrain will use interpolation to triangulate across a bridge opening from legitimate ground points on either side of the actual bridge. This can cause visual artifacts or “saddles.” These “artifacts” are only visual and do not exist in the LiDAR points or breaklines.




Figure 8 – Tile number 18SUF840770. The DEM in the bottom left view shows visual artifacts because the surface model is interpolated from the ground points on the slope leading from the tops of the overpasses and bridges to the lower ground points on either side of the overpasses and bridges. The surface model must make a continuous model and in order to do so, points are connected through interpolation. This can cause visual artifacts when there are features with large elevation differences. The profiles in the top two views show the LiDAR points of this particular feature colored by class. All overpass and bridge points have been removed from ground (orange) and are unclassified (white). There are no ground points that can be modified to correct these visual artifacts.

- c. *Culverts and Bridges:* Bridges have been removed from the bare earth surface while culverts remain in the bare earth surface. In instances where it is difficult to determine if the feature is a culvert or bridge, such as with some small bridges, Dewberry erred on assuming they would be culverts especially if they are on secondary or tertiary roads. Below is an example of a culvert that has been left in the ground surface.




Figure 9– Tile number 18SUF885725. Profile with points colored by class (class 1=white, class 2=orange, class 9=blue) is shown in the top view and the DEM is shown in the bottom view. This culvert remains in the bare earth surface. Bridges have been removed from the bare earth surface and classified to class 1.

- d. *In Ground Structures:* In ground structures exist within the project area. These types of structures occur mainly on military bases and in facilities designed for munitions testing and storage. These features are correctly included in the ground classification.




Figure 10 – Tile 18SUG555265. Profile with the points colored by class (class 1=white, class 2=orange) is shown in the top view and a DEM of the surface is shown in the bottom view. These features are correctly included in the ground classification.




Figure 11 – Tiles 18SUG570220. Profile with the points colored by class (class 1=white, class 2=orange) is shown in the top view and a DEM of the surface is shown in the bottom view. These features are correctly included in the ground classification.

- e. *Dirt Mounds*: Irregularities in the natural ground exist and may be misinterpreted as artifacts that should be removed. Small hills and dirt mounds are present throughout the project area. These features are correctly included in the ground.




Figure 12 - Tile 18SUG585070. Profile with the points colored by class (class 1=white, class 2=orange) is shown in the top view and a DEM of the surface is shown in the bottom view. These features are correctly included in the ground classification.

- f. *Elevation Change Within Breaklines:* While water bodies are flattened in the final DEMs, other features such as linear hydrographic features can have significant changes in elevation within a small distance. In linear hydrographic features, this is often due to the presence of a structure that affects flow such as a dam or spillway. Significant changes in elevation are also present in tidally influenced areas which are located throughout the Norfolk, VA Project area. Dewberry has reviewed the DEMs to ensure that changes in elevation are shown from bank to bank. These changes are often shown as steps to reduce the presence of artifacts while ensuring consistent downhill flow. An example is shown below.




Figure 13 – Tile number 18SVF050500. Significant drops in elevation occur in the tidally influenced areas. Elevation change has been stair stepped. The steps are flat from bank to bank and flow consistently downhill.

- g. *Shipyards and Dry Docks*: Large dry docks are located throughout the Norfolk, VA project area. Newport News Shipbuilding is one of the largest in the world and has dry docks that can hold over 100 million gallons of water when flooded. Large vessels such as aircraft carriers were being actively constructed within most of the dry docks during the time of acquisition. Other dry docks were empty resulting in large crater like artifacts in the final bare earth DEMs. There are no ground points that can be modified to correct these visual artifacts. Examples are shown below.




Figure 14– Tile 18SUF705950 in the top view and tile 18SUF840755 in the bottom view. The DEMs show visual artifacts because the surface model is interpolated from the ground points on the slope leading from the tops of the dry docks to the lower ground points within the dry docks. The surface model must make a continuous model and in order to do so, points are connected through interpolation. This can cause visual artifacts when there are features with large elevation differences.

- h. Canal Locks:* Great Bridge Lock, often closed by the Army Corp. due to flooding, was open at the time of acquisition. Dewberry collected it as a water body and it was hydro flattened along with the rest of the hydro mask in the final DEMs. Examples are shown below.




Figure 15 – Tile 18SUF885635. Great Bridge Lock was open and full of water at the time of acquisition. Dewberry included the lock in the hydro mask to avoid artifacts in the final DEM model shown above in the bottom view.

- i. *Flight line Ridges:* Ridges occur when there is a difference between the elevations of adjoining flight lines or swaths. Some flight line ridges are visible in the final DEMs but they do not exceed the project specifications and the overall relative accuracy requirements for the project area have been met. An example of a visible ridge that is within tolerance is shown below.




Figure 16– Tile number 18SUF780515. The flight line ridge is less than 8 cm. Overall, the FEMA Norfolk, VA LiDAR data meets the project specifications for 10 cm RMSE relative accuracy.

DERIVATIVE LIDAR PRODUCTS

Building Footprint Shapefiles

Dewberry generated 2D and 3D building footprints through the use of a semi-automated approach. This approach is semi automated in that the initial development of the features is conducted through the automated processing of the LiDAR data using proprietary tools and completed through manual review and editing of the features to ensure that the product meets the specifications.

Dewberry developed an automated processing algorithm that identified the planar surfaces in the LiDAR data and generated polygons from the identified areas. Once the surfaces were identified and the initial polygons had been extracted, a secondary process performed a best-fit line surrounding the initial polygons to square and finish the buildings.

While the automated portion of the process successfully extracts the majority of features, there are instances where features will not be accurately captured. Dewberry identified and manually added features that were visible in the LiDAR but were missed by the automated collect, separated buildings that were collected as a single footprint due to proximity, and reshaped complex features in the final processing steps.

- a. *Missed or Inaccurately Generated Features:* The automated building footprints are based on LiDAR points that were classified based on size, elevation and angular relationships between the points. Occasionally, features were missed or inaccurately generated due to tree cover or certain properties not meeting the automated classification parameters. Dewberry added or modified these features as needed during the manual portion of the process. Examples are shown below.




Figure 17 – Tiles 18SUF795950 and 18SUF795965. The top image shows the automated portion of the process missed a feature and did not accurately capture a second feature. Dewberry corrected these types of errors during the manual review as shown in the bottom image.




Figure 19 – Tile 18SUF795725. The top image shows the automated portion of the process did not accurately capture and separate individual features that were in close proximity. Dewberry corrected these types of errors during the manual review as shown in the bottom image.

Dewberry completed the buildings by programmatically adding the attributes for length, width, area, building top elevation, building base elevation, median height of building, and rooftop.

The positional accuracy of the features are equal to 1.5 meters relative to the LiDAR data. This accuracy allows for the fact that the roof line will not be completely accurate due to the density of points on the feature.

Vegetation Shapefiles

Forest polygons were developed using automated processes in eCognition software. This software allowed the input of the surface models and intensity imagery to determine vegetation stands as well as individual points. Upon completion of the automated extraction buildings and hydrographic features were erased from the vegetation polygons as required in the specifications.

Dewberry determined the predominant height of the stand, the average stem spacing, and the type of tree using GIS tools. Stand height was calculated using the mean surface model elevation for each tree stand. Average stem spacing was calculated using the mean Euclidean distance of the tree points within each stand. Tree type was assigned by first correlating forest landcover types from NOAA's Coastal Change Analysis Program (C-CAP) 2006 landcover dataset to coincident forest polygons. Then, the remaining forest polygons that were not coincident to the C-CAP forest landcover were classified manually.

Along with the forest polygons, Dewberry generated point records for each tree within the project area that exceeds the 4 meter height requirement. Trees were collected both inside and outside of the vegetation polygons. Dewberry used eCognition to segment the intensity and surface models into likely candidates for individual trees. These segments were converted to a centroid and attributed as a tree point. Dewberry performed a review of the dataset to ensure that no significant errors are present. However, it should be noted that the individual tree points will be best estimates for the trees and not necessarily the absolute location of an individual tree.

Survey Vertical Accuracy Checkpoints

All checkpoints surveyed for vertical accuracy testing purposes are listed in the following table. A total of one hundred (100) checkpoints were surveyed for the USGS Norfolk, VA LiDAR Project.

Point ID	NAD83 UTM Zone 18		NAVD88
	Easting X (m)	Northing Y (m)	Elevation (m)
BLT	351760.734	4127850.10	18.183
BLT	381578.163	4078664.26	0.747
BLT	393248.624	4072438.86	5.015
BLT	402227.485	4071563.33	3.332
BLT	392360.215	4067495.23	4.073
BLT	381270.904	4060371.47	4.561
BLT	400675.21	4061689.79	3.101
BLT	418260.165	4058718.15	0.336
BLT	381142.027	4051271.05	0.508
BLT	391753.707	4051529.69	3.966
BLT	410587.042	4049846.41	0.215
BLT	354157.693	4124969.35	26.867

BLT	393929.901	4045956.46	1.760
BLT	374985.334	4116934.63	1.681
BLT	377113.574	4112722.61	1.301
BLT	363984.403	4105501.27	5.313
BLT	376746.304	4101703.52	3.508
BLT	387491.887	4091258.47	0.708
BLT	376730.499	4083420.21	5.063
BLT	409359.513	4083180.74	1.461
FO	370349.672	4073223.38	6.550
FO	372583.785	4071595.18	5.275
FO	415396.475	4067053.56	0.702
FO	397607.018	4068185.83	2.955
FO	376505.026	4067499.95	4.395
FO	395910.233	4060914.70	2.597
FO	410438.562	4055125.18	0.440
FO	380102.698	4056043.02	4.959
FO	396807.306	4049602.58	2.637
FO	403948.268	4045614.94	2.244
FO	350327.179	4136365.61	24.911
FO	391454.574	4046723.48	4.048
FO	360028.768	4126241.51	9.111
FO	366402.057	4118875.45	16.648
FO	372250.758	4112572.97	4.076
FO	362705.508	4108269.85	9.253
FO	381648.883	4101531.90	2.403
FO	372274.821	4096033.45	5.794
FO	399373.443	4084210.27	5.089
FO	400375.322	4078421.85	3.415
GWC	393746.948	4078316.06	1.982
GWC	375676.882	4072545.39	4.983
GWC	409067.175	4073011.62	5.377
GWC	403954.911	4067042.59	4.174
GWC	377981.16	4066255.19	3.710
GWC	392212.252	4061512.70	6.443
GWC	402351.116	4055382.32	2.440
GWC	386220.44	4056359.55	5.163
GWC	386712.905	4049194.93	3.966
GWC	409971.276	4046257.13	2.111
GWC	344779.087	4134125.52	35.999
GWC	376541.932	4046741.63	4.160
GWC	360405.124	4118838.76	13.727
GWC	373059.394	4119343.90	1.280
GWC	381475.24	4109732.52	0.319
GWC	376178.523	4107208.36	2.294
GWC	376137.546	4096625.80	4.989
GWC	365940.986	4114829.51	17.938
GWC	393786.442	4082613.86	6.043

GWC	404973.792	4084165.95	4.738
OT	348684.803	4133416.99	25.196
OT	387312	4078657.57	2.843
OT	387581.462	4072616.49	5.679
OT	409482.049	4066448.20	2.486
OT	381818.542	4067562.41	2.601
OT	378660.721	4061599.98	4.475
OT	409784.125	4060963.64	1.461
OT	397899.773	4055461.44	3.726
OT	376373.978	4051531.89	5.106
OT	385337.999	4049989.79	4.067
OT	399629.715	4045755.10	2.509
OT	365374.175	4120908.93	19.117
OT	389710.031	4046832.73	3.427
OT	360651.125	4113702.12	10.775
OT	385773.135	4105404.72	1.142
OT	365920.251	4107753.53	9.598
OT	371637.805	4101773.55	6.314
OT	382129.104	4097123.06	2.298
OT	383472.444	4086525.63	3.377
OT	404011.498	4078298.89	4.043
UT	350036.421	4130867.11	21.875
UT	376920.293	4079299.32	3.214
UT	381584.308	4073036.02	3.282
UT	398962.242	4072060.25	3.235
UT	387116.242	4067549.67	5.267
UT	386392.045	4061538.34	5.179
UT	417183.163	4061728.53	0.768
UT	407222.046	4055014.76	3.243
UT	392295.391	4055820.66	5.854
UT	403094.607	4049572.58	2.671
UT	407107.901	4049321.39	3.256
UT	386772.849	4046143.79	5.127
UT	366296.531	4122275.22	1.749
UT	365989.527	4112855.29	16.213
UT	360182.785	4110977.45	9.528
UT	371528.482	4107289.80	8.882
UT	365947.433	4102065.18	9.063
UT	375440.462	4094026.89	1.167
UT	388018.935	4084249.17	3.177
UT	410043.225	4077444.67	4.977

Table 11: Norfolk, VA LiDAR surveyed accuracy checkpoints

LiDAR Vertical Accuracy Statistics & Analysis

BACKGROUND

Dewberry tests and reviews project data both quantitatively (for accuracy) and qualitatively (for usability).

For quantitative assessment (i.e. vertical accuracy assessment), one hundred (100) check points were surveyed for the project and are located within bare earth/open terrain, urban, grass/weeds/crops, brush lands/tress, and forested/fully grown land cover categories. The checkpoints were surveyed for the project using RTK survey methods. Please see appendix A to view the survey report which details and validates how the survey was completed for this project.

Checkpoints were evenly distributed throughout the project area so as to cover as many flight lines as possible using the “dispersed method” of placement.

VERTICAL ACCURACY TEST PROCEDURES

FVA (Fundamental Vertical Accuracy) is determined with check points located only in the open terrain (grass, dirt, sand, and/or rocks) land cover category, where there is a very high probability that the LiDAR sensor will have detected the bare-earth ground surface and where random errors are expected to follow a normal error distribution. The FVA determines how well the calibrated LiDAR sensor performed. With a normal error distribution, the vertical accuracy at the 95% confidence level is computed as the vertical root mean square error ($RMSE_z$) of the checkpoints x 1.9600. For the Norfolk, VA LiDAR project, vertical accuracy must be 0.181 meters or less based on an $RMSE_z$ of 0.0925 meters x 1.9600.

CVA (Consolidated Vertical Accuracy) is determined with all checkpoints in all land cover categories combined where there is a possibility that the LiDAR sensor and post-processing may yield elevation errors that do not follow a normal error distribution. CVA at the 95% confidence level equals the 95th percentile error for all checkpoints in all land cover categories combined. The Norfolk, VA LiDAR Project CVA standard is 0.269 meters based on the 95th percentile. The CVA is accompanied by a listing of the 5% outliers that are larger than the 95th percentile used to compute the CVA; these are always the largest outliers that may depart from a normal error distribution. Here, $Accuracy_z$ differs from CVA because $Accuracy_z$ assumes elevation errors follow a normal error distribution where RMSE procedures are valid, whereas CVA assumes LiDAR errors may not follow a normal error distribution in vegetated categories, making the RMSE process invalid.

SVA (Supplemental Vertical Accuracy) is determined for each land cover category other than open terrain. SVA at the 95% confidence level equals the 95th percentile error for all checkpoints in each land cover category. The Norfolk, VA LiDAR Project SVA target is 0.269 meters based on the 95th percentile. Target specifications are given for SVA's as one individual land cover category may exceed this target value as long as the overall CVA is within specified tolerances. Again, $Accuracy_z$ differs from SVA because $Accuracy_z$ assumes elevation errors follow a normal error distribution where RMSE procedures are valid, whereas SVA assumes LiDAR errors may not follow a normal error distribution in vegetated categories, making the RMSE process invalid.

The relevant testing criteria are summarized in the table below.

Quantitative Criteria	Measure of Acceptability
Fundamental Vertical Accuracy (FVA) in open terrain only using RMSE _z *1.9600	0.181 meters (based on RMSE _z (0.0925 meters) * 1.9600)
Consolidated Vertical Accuracy (CVA) in all land cover categories combined at the 95% confidence level	0.269 meters (based on combined 95 th percentile)
Supplemental Vertical Accuracy (SVA) in each land cover category separately at the 95% confidence level	0.269 meters (based on 95 th percentile for each land cover category)

Table 12 – Acceptance Criteria

VERTICAL ACCURACY TESTING STEPS

The primary QA/QC vertical accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry’s team surveyed QA/QC vertical checkpoints in accordance with the project’s specifications.
2. Next, Dewberry interpolated the bare-earth LiDAR DTM to provide the z-value for every checkpoint.
3. Dewberry then computed the associated z-value differences between the interpolated z-value from the LiDAR data and the ground truth survey checkpoints and computed FVA, CVA, and SVA values.
4. The data were analyzed by Dewberry to assess the accuracy of the data. The review process examined the various accuracy parameters as defined by the scope of work. The overall descriptive statistics of each dataset were computed to assess any trends or anomalies. This report provides tables, graphs and figures to summarize and illustrate data quality.

The figure below shows the location of the QA/QC checkpoints within the project area.

Norfolk, VA Checkpoint Locations




Figure 20 – Location of QA/QC Checkpoints

VERTICAL ACCURACY RESULTS

The table below summarizes the tested vertical accuracy resulting from a comparison of the surveyed checkpoints to the elevation values present within the fully classified LiDAR LAS files.

Land Cover Category	# of Points	FVA – Fundamental Vertical Accuracy (RMSE _z x 1.9600) Spec=0.181 m	CVA – Consolidated Vertical Accuracy (95th Percentile) Spec=0.269 m	SVA – Supplemental Vertical Accuracy (95th Percentile) Target=0.269 m
Consolidated	100		0.194	
Bare Earth-Open Terrain	20	0.129		
Grass, Weeds and Crops	20			0.198
Forest	20			0.163
Urban	20			0.196
Brush Land and Trees	20			0.196

Table 13 – FVA, CVA, and SVA Vertical Accuracy at 95% Confidence Level

The RMSE_z for checkpoints in open terrain only tested 0.066 meters, within the target criteria of 0.092 meters. Compared with the 0.181 meters specification, the FVA tested 0.129 meters at the 95% confidence level based on RMSE_z x 1.9600.

Compared with the 0.269 meters specification, CVA for all checkpoints in all land cover categories combined tested 0.194 meters based on the 95th percentile.

Compared with the target 0.269 meters specification, SVA for checkpoints in the urban land cover category tested 0.196 meters based on the 95th percentile, checkpoints in the grass, weeds and crops land cover category tested 0.198 meters based on the 95th percentile, checkpoints in the forested land cover category tested 0.163 meters based on the 95th percentile, and checkpoints in the brush land and trees land cover category tested 0.196 meters based on the 95th percentile.

The figure below illustrates the magnitude of the differences between the QA/QC checkpoints and LiDAR data. This shows that the majority of LiDAR elevations were within +/- 0.15 meters of the checkpoints elevations, but there were some outliers where LiDAR and checkpoint elevations differed by up to +0.23 meters.




Figure 21 – Magnitude of elevation discrepancies per land cover category

Table 14 lists the 5% outliers that are larger than the 95th percentile.

Point ID	NAD83 UTM Zone 18		NAVD88	LiDAR Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
BLT	410587.042	4049846.41	0.215	0.4522	0.24	0.24
FO	376505.026	4067499.95	4.395	4.1936	-0.20	0.20
GWC	409067.175	4073011.62	5.377	5.5738	0.20	0.20
GWC	344779.087	4134125.52	35.999	36.2148	0.22	0.22
UT	417183.163	4061728.53	0.768	1.0002	0.23	0.23

Table 14 – 5% Outliers

Table 15 provides overall descriptive statistics.

100 % of Totals	RMSE _Z (m) Open Terrain Spec=0.0925m	Mean (m)	Median (m)	Skew	Std Dev (m)	# of Points	Min (m)	Max (m)
Consolidated		0.050	0.053	-0.197	0.088	100	-0.201	0.237
Open Terrain	0.066	0.023	0.008	-0.428	0.064	20	-0.117	0.119
Grass, Weeds and Crops		0.059	0.056	-0.256	0.095	20	-0.201	0.216
Forest		0.008	0.014	-0.884	0.086	20	-0.201	0.130
Urban		0.068	0.061	-0.005	0.089	20	-0.106	0.232
Brush land and Trees		0.093	0.104	-0.349	0.085	20	-0.063	0.237

Table 15 – Overall Descriptive Statistics

The figure below illustrates a histogram of the associated elevation discrepancies between the QA/QC checkpoints and elevations interpolated from the LiDAR triangulated irregular network (TIN). The frequency shows the number of discrepancies within each band of elevation differences. Although the discrepancies vary between a low of -0.201 meters and a high of +0.237 meters, the histogram shows that the majority of the discrepancies are skewed on the positive side. The vast majority of points are within the ranges of -0.15 meters to +0.15 meters.




Figure 22 – Histogram of Elevation Discrepancies with errors in meters

Based on the vertical accuracy testing conducted by Dewberry, the LiDAR dataset for the Norfolk, VA LiDAR Project satisfies the project's pre-defined vertical accuracy criteria.

Breakline Production & Qualitative Assessment Report


BREAKLINE PRODUCTION METHODOLOGY

Dewberry used GeoCue software to develop LiDAR stereo models of the Norfolk, VA LiDAR Project area so the LiDAR derived data could be viewed in 3-D stereo using Socet Set softcopy photogrammetric software. Using LiDARgrammetry procedures with LiDAR intensity imagery, Dewberry used the stereo models developed by Dewberry to stereo-compile the three types of hard breaklines in accordance with the project's Data Dictionary.

All drainage breaklines are monotonically enforced to show downhill flow. Water bodies are reviewed in stereo and the lowest elevation is applied to the entire waterbody.

BREAKLINE QUALITATIVE ASSESSMENT

Dewberry completed breakline qualitative assessments according to a defined workflow. The following workflow diagram represents the steps taken by Dewberry to provide a thorough qualitative assessment of the breakline data.



BREAKLINE TOPOLOGY RULES

Automated checks are applied on hydro features to validate the 3D connectivity of the feature and the monotonicity of the hydrographic breaklines. Dewberry's major concern was that the hydrographic breaklines have a continuous flow downhill and that breaklines do not undulate. Error points are generated at each vertex not complying with the tested rules and these potential edit calls are then visually validated during the visual evaluation of the data. This step also helped validate that breakline vertices did not have excessive minimum or maximum elevations and that elevations are consistent with adjacent vertex elevations.

The next step is to compare the elevation of the breakline vertices against the elevation extracted from the ESRI Terrain built from the LiDAR ground points, keeping in mind that a discrepancy is expected because of the hydro-enforcement applied to the breaklines and because of the interpolated imagery used to acquire the breaklines. A given tolerance is used to validate if the elevations differ too much from the LiDAR.

Dewberry's final check for the breaklines was to perform a full qualitative analysis. Dewberry compared the breaklines against LiDAR intensity images to ensure breaklines were captured in the required locations. The quality control steps taken by Dewberry are outlined in the QA Checklist below.

BREAKLINE QA/QC CHECKLIST

Project Number/Description: TO G13PD00279 USGS Norfolk, VA LiDAR

Date: _____ **1/29/2014** _____

Overview

- All Feature Classes are present in GDB
- All features have been loaded into the geodatabase correctly. Ensure feature classes with subtypes are domained correctly.
- The breakline topology inside of the geodatabase has been validated. See Data Dictionary for specific rules
- Projection/coordinate system of GDB is accurate with project specifications

Perform Completeness check on breaklines using either intensity or ortho imagery

- Check entire dataset for missing features that were not captured, but should be to meet baseline specifications or for consistency (See Data Dictionary for specific collection rules). Features should be collected consistently across tile bounds within a dataset as well as be collected consistently between datasets.
- Check to make sure breaklines are compiled to correct tile grid boundary and there is full coverage without overlap
- Check to make sure breaklines are correctly edge-matched to adjoining datasets if applicable. Ensure breaklines from one dataset join breaklines from another dataset that are coded the same and all connecting vertices between the two datasets match in X,Y, and Z (elevation). There should be no breaklines abruptly ending at dataset boundaries and no discrepancies of Z-elevation in overlapping vertices between datasets.

Compare Breakline Z elevations to LiDAR elevations

- ☒ Using a terrain created from LiDAR ground points and water points, drape breaklines on terrain to compare Z values. Breakline elevations should be at or below the elevations of the immediately surrounding terrain. This should be performed before other breakline checks are completed.

Perform automated data checks using ESRI's Data Reviewer

The following data checks are performed utilizing ESRI's Data Reviewer extension. These checks allow automated validation of 100% of the data. Error records can either be written to a table for future correction, or browsed for immediate correction. Data Reviewer checks should always be performed on the full dataset.

- ☒ Perform "adjacent vertex elevation change check" on the Inland Ponds feature class (Elevation Difference Tolerance=.001 meters). This check will return Waterbodies whose vertices are not all identical. This tool is found under "Z Value Checks."
- ☒ Perform "unnecessary polygon boundaries check" on Inland Ponds and Lakes, Tidal Waters, and Islands (if delivered as a separate feature class) feature classes. This tool is found under "Topology Checks."
- ☒ Perform "different Z-Value at intersection check" (Inland Streams and Rivers to Inland Streams and Rivers), (Ponds and Lakes to Ponds and Lakes), (Tidal Waters to Tidal Waters), (Streams and Rivers to Ponds and Lakes), (Streams and Rivers to Tidal Waters), (Ponds and Lakes to Tidal Waters), (Island to Inland Ponds and Lakes), (Island to Tidal Waters), (Island to Island),and (Islands to Inland Streams and Rivers) (Elevation Difference Tolerance= .01 meters Minimum, 200 meters Maximum, Touches). This tool is found under "Z Value Checks." [Please note that polygon feature classes will need to be converted to lines for this check.](#)
- ☒ Perform "duplicate geometry check" on (Inland Streams and Rivers to Inland Streams and Rivers), (Inland Ponds and Lakes to Inland Ponds and Lakes), (Tidal Waters to Tidal Waters), (Islands to Islands-if delivered as a separate shapefile), (Inland Streams and Rivers to Inland Ponds and Lakes), (Inland Streams and Rivers to Tidal Waters), (Inland Ponds and Lakes to Tidal Waters), (Islands to Tidal Waters), and (Islands to Inland Ponds and Lakes). Attributes do not need to be checked during this tool. This tool is found under "Duplicate Geometry Checks."
- ☒ Perform "geometry on geometry check" (Inland Streams and Rivers to Inland Ponds and Lakes), (Inland Streams and Rivers to Tidal Waters), (Inland Ponds and Lakes to Tidal Waters), (Inland Streams and Rivers to Inland Streams and Rivers), (Inland Ponds and Lakes to Inland Ponds and Lakes), (Tidal waters to Tidal waters), (Islands to Tidal Waters), and (Islands to Inland Ponds and Lakes), (Islands to Islands). Spatial relationship is crosses, attributes do not need to be checked. This tool is found under "Feature on Feature Checks." [Please note that "crosses" only works with line feature](#)

classes and not polygons. If the inputs are polygons, they will need to be converted to a line prior to running this tool.

- Perform “geometry on geometry check (Tidal Waters to Islands), and (Inland Ponds and Lakes to Islands), (Inland Streams and Rivers to Islands). Spatial relationship is contains, attributes do not need to be checked. This tool is found under “Feature on Feature Checks.”
- Perform “geometry on geometry check” (Inland Streams and Rivers to Inland Ponds and Lakes), (Inland Streams and Rivers to Tidal Waters), (Inland Ponds and Lakes to Tidal Waters), (Inland Streams and Rivers to Inland Streams and Rivers), (Inland Ponds and Lakes to Inland Ponds and Lakes), (Tidal waters to Tidal waters), (Islands to Tidal Waters), and (Islands to Inland Ponds and Lakes), (Islands to Islands). Spatial relationship is intersect, attributes do not need to be checked. This tool is found under “Feature on Feature Checks.” Please note that false positives may be returned with this tool but that this tool may identify issues not found with “crosses.”
- Perform “polygon overlap/gap is sliver check” on (Tidal Waters to Tidal Waters), (Island to Island), (Island to Inland Ponds and Lakes) and (Inland Ponds and Lakes to Inland Ponds and Lakes), (Inland Ponds and Lakes to Tidal Waters). Maximum Polygon Area is not required. This tool is found under “Feature on Feature Checks.”

Perform Dewberry Proprietary Tool Checks

- Perform monotonicity check on (Inland Streams and Rivers) and (Tidal Waters to Tidal Waters if they are not a constant elevation) using “A3_checkMonotonicityStreamLines.” This tool looks at line direction as well as elevation. Features in the output shapefile attributed with a “d” are correct monotonically, but were compiled from low elevation to high elevation. These features are ok and can be ignored. Features in the output shapefile attributed with an “m” are not correct monotonically and need elevations to be corrected. Input features for this tool need to be in a geodatabase and must be a line. If features are a polygon they will need to be converted to a line feature. Z tolerance is 0.01 meters.
- Perform connectivity check between (Inland Streams and Rivers to Inland Streams and Rivers), (Ponds and Lakes to Ponds and Lakes), (Tidal Waters to Tidal Waters), (Streams and Rivers to Ponds and Lakes), (Streams and Rivers to Tidal Waters), (Ponds and Lakes to Tidal Waters), (Island to Inland Ponds and Lakes), (Island to Tidal Waters), (Island to Island), and (Islands to Inland Streams and Rivers) using the tool “07_CheckConnectivityForHydro.” The input for this tool needs to be in a geodatabase. The output is a shapefile showing the location of overlapping vertices from the polygon features and polyline features that are at different Z-elevation.

Metadata

- Each XML file (1 per feature class) is error free as determined by the USGS MP tool
- Metadata content contains sufficient detail and all pertinent information regarding source materials, projections, datums, processing steps, etc. Content should be consistent across all feature classes.

Completion Comments: Complete – Approved

Data Dictionary

HORIZONTAL AND VERTICAL DATUM

The horizontal datum shall be North American Datum of 1983, Units in Meters. The vertical datum shall be referenced to the North American Vertical Datum of 1988 (NAVD 88), Units in Meters. Geoid12A shall be used to convert ellipsoidal heights to orthometric heights.

COORDINATE SYSTEM AND PROJECTION

All data shall be projected to UTM Zone 18, Horizontal Units in Meters and Vertical Units in Meters.

INLAND STREAMS AND RIVERS

Feature Dataset: BREAKLINES
Feature Type: Polygon
Contains Z Values: Yes
XY Resolution: Accept Default Setting
XY Tolerance: 0.003

Feature Class: STREAMS_AND_RIVERS
Contains M Values: No
Annotation Subclass: None
Z Resolution: Accept Default Setting
Z Tolerance: 0.001

Description

This polygon feature class will depict linear hydrographic features with a width greater than 100 feet.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

Feature Definition

Description	Definition	Capture Rules
Streams and Rivers	Linear hydrographic features such as streams, rivers, canals, etc. with an average width greater than 100 feet. In the case of embankments, if the feature forms a natural dual line channel, then capture it consistent with the capture rules. Other natural or manmade embankments will not qualify for this project.	<p>Capture features showing dual line (one on each side of the feature). Average width shall be greater than 100 feet to show as a double line. Each vertex placed should maintain vertical integrity. Generally both banks shall be collected to show consistent downhill flow. There are exceptions to this rule where a small branch or offshoot of the stream or river is present.</p> <p>The banks of the stream must be captured at the same elevation to ensure flatness of the water feature. If the elevation of the banks appears to be different see the task manager or PM for further guidance.</p>

		<p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding LiDAR points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>These instructions are only for docks or piers that follow the coastline or water's edge, not for docks or piers that extend perpendicular from the land into the water. If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water's edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p> <p>Every effort should be made to avoid breaking a stream or river into segments.</p> <p>Dual line features shall break at road crossings (culverts). In areas where a bridge is present the dual line feature shall continue through the bridge.</p> <p>Islands: The double line stream shall be captured around an island if the island is greater than 1/2 acre. In this case a segmented polygon shall be used around the island in order to allow for the island feature to remain as a "hole" in the feature.</p>
--	--	---

INLAND PONDS AND LAKES

Feature Dataset: BREAKLINES
Feature Type: Polygon
Contains Z Values: Yes
XY Resolution: Accept Default Setting
XY Tolerance: 0.003

Feature Class: PONDS_AND_LAKES
Contains M Values: No
Annotation Subclass: None
Z Resolution: Accept Default Setting
Z Tolerance: 0.001

Description

This polygon feature class will depict closed water body features that are at a constant elevation.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

Feature Definition

Description	Definition	Capture Rules
Ponds and Lakes	<p>Land/Water boundaries of constant elevation water bodies such as lakes, reservoirs, ponds, etc. Features shall be defined as closed polygons and contain an elevation value that reflects the best estimate of the water elevation at the time of data capture. Water body features will be captured for features 2 acres in size or greater.</p> <p>“Donuts” will exist where there are islands within a closed water body feature.</p>	<p>Water bodies shall be captured as closed polygons with the water feature to the right. <u>The compiler shall take care to ensure that the z-value remains consistent for all vertices placed on the water body.</u></p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding LiDAR points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>An Island within a Closed Water Body Feature that is 1/2 acre in size or greater will also have a “donut polygon” compiled.</p> <p>These instructions are only for docks or piers that follow the coastline or water’s edge, not for docks or piers that extend perpendicular from the land into the water. If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the</p>

		water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water's edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.
--	--	--

TIDAL WATERS

Feature Dataset: BREAKLINES
Feature Type: Polygon
Contains Z Values: Yes
XY Resolution: Accept Default Setting
XY Tolerance: 0.003

Feature Class: TIDAL_WATERS
Contains M Values: No
Annotation Subclass: None
Z Resolution: Accept Default Setting
Z Tolerance: 0.001

Description

This polygon feature class will outline the land / water interface at the time of LiDAR acquisition.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

Feature Definition

Description	Definition	Capture Rules
TIDAL_WATERS	<p>The coastal breakline will delineate the land water interface using LiDAR data as reference. In flight line boundary areas with tidal variation the coastal shoreline may show stair stepping as no feathering is allowed. Stair stepping is allowed to show as much ground as the collected data permits.</p>	<p>The feature shall be extracted at the apparent land/water interface, as determined by the LiDAR intensity data, to the extent of the tile boundaries. Differences caused by tidal variation are acceptable and breaklines delineated should reflect that change with no feathering.</p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding LiDAR points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water's edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p> <p>Breaklines shall snap and merge seamlessly with linear hydrographic features.</p>

2D BUILDINGS

Feature Dataset: Buildings
Feature Type: Polygon
Contains Z Values: No
XY Resolution: Accept Default Setting
XY Tolerance: 0.003

Feature Class: Buildings_2D
Contains M Values: No
Annotation Subclass: None
Z Resolution: Accept Default Setting
Z Tolerance: 0.001

Description

This 2D polygon feature class will depict at least 98% of all buildings larger than 200 square meters and at least 95% of all buildings larger than 100 square meters. The positional accuracy of the collected features will be equal to 1.5 meters relative to the LiDAR data.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
Id	Double	Yes						Polygon ID number for the building substructure assigned by user
ARA2d	Double	Yes						Area of the 2D sub structure calculated by software
LEN2d	Double	Yes						Length of the 2D polygon calculated by software
WID2d	Double	Yes						Width of the 2D polygon calculated by software
HGT2d	Double	Yes						Median height of the building substructure above ground level based on the difference between the DSM and the Bare Earth model calculated by software.
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

Feature Definition

Description	Definition	Capture Rules
2D Buildings	2D buildings will include the majority of structures larger than 100 square meters. The positional accuracy of the collected features will be equal to 1.5 meters relative to the LiDAR data.	<p>The roofs of some buildings or structures may be offset from the true footprint in the imagery. Care should be taken to collect the actual or true footprint of each structure by collecting the base of the structure.</p> <p>All building footprints should be captured in 2D, but should still show correct topology.</p>

3D BUILDINGS

Feature Dataset: Buildings
Feature Type: Polygon
Contains Z Values: No
XY Resolution: Accept Default Setting
XY Tolerance: 0.003

Feature Class: Buildings_3D
Contains M Values: No
Annotation Subclass: None
Z Resolution: Accept Default Setting
Z Tolerance: 0.001

Description

This 3D polygon feature class will depict at least 98% of all buildings larger than 200 square meters and at least 95% of all buildings larger than 100 square meters. The positional accuracy of the collected features will be equal to 1.5 meters relative to the LiDAR data.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
Id	Double	Yes						Polygon ID number for the building substructure assigned by user
BldgId	Double	Yes						ID number of the entire building footprint assigned by user
TopElev3D	Double	Yes						Elevation of the top of the building subsection. This is the arithmetic median of all LiDAR points within the polygon calculated by software
BaseElev3D	Double	Yes						Base elevation of the building subsection. This is the arithmetic minimum of all bare earth elevation points within the polygon calculated by software
ARA3D	Double	Yes						Area of the 3D substructure calculated by software
LEN3D	Double	Yes						Length of the 3D polygon calculated by software
WID3D	Double	Yes						Width of the 3D polygon calculated by software
HGT3D	Double	Yes						Median height of building substructure above ground level based on the difference between

								the DSM and the bare earth model calculated by software
SSR	Double	Yes						Classified roof type identified in the NGA FACC coding schema. Flat=41, pitched=42 and complex(other)=999 assigned by user
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

Feature Definition

Description	Definition	Capture Rules
3D Buildings	3D buildings will include the majority of structures larger than 100 square meters. The positional accuracy of the collected features will be equal to 1.5 meters relative to the LiDAR data.	<p>The roofs of some buildings or structures may be offset from the true footprint in the imagery. Care should be taken to collect the actual or true footprint of each structure by collecting the base of the structure.</p> <p>All building footprints should correct topology.</p>

FOREST POLYGONS

Feature Dataset: Vegetation
Feature Type: Polygon
Contains Z Values: No
XY Resolution: Accept Default Setting
XY Tolerance: 0.003

Feature Class: Forest_Polygons
Contains M Values: No
Annotation Subclass: None
Z Resolution: Accept Default Setting
Z Tolerance: 0.001

Description

This 2D polygon feature class will be delineated in areas where vegetation greater than 2m in height is predominant over a contiguous area 5,000 square meters or larger. Forests shall be de-conflicted from identifiable open water greater than 15 meters wide.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
Id	Double	Yes						Polygon ID number assigned by user
ARA	Double	Yes						Area calculated by software
PHT	Double	Yes						Predominant height of stand calculated by software
TSC	Double	Yes						Average stem spacing distance for stand, in decimeters calculated by software
Type	Double	Yes						Tree type (deciduous or coniferous) assigned by user
SHAPE_LENGTH	Double	Yes						Calculated by Software
SHAPE_AREA	Double	Yes						Calculated by Software

Feature Definition

Description	Definition	Capture Rules
Forest polygons	Areas of vegetation greater than 2m in height that are predominant over a contiguous area 5,000 square meters or larger will be included in the collect. Forests shall be de-conflicted from identifiable open water greater than 15 meters wide.	All polygons should have the correct topology.

TREE POINTS

Feature Dataset: Vegetation
Feature Type: Point
Contains Z Values: No
XY Resolution: Accept Default Setting
XY Tolerance: 0.003

Feature Class: Tree_points
Contains M Values: No
Annotation Subclass: None
Z Resolution: Accept Default Setting
Z Tolerance: 0.001

Description

This point feature class will be extracted from identified vegetated areas that exceed 4 meters in height relative to the bare earth model.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
Id	Double	Yes						Point ID number assigned by user
HGT	Double	Yes						The height of the tree calculated by software
BaseElev	Double	Yes						Base height of the tree calculated by software
Type	Double	Yes						Tree type (deciduous or coniferous) assigned by user
SHAPE_LENGTH	Double	Yes						Calculated by Software
SHAPE_AREA	Double	Yes						Calculated by Software

Feature Definition


Description	Definition	Capture Rules
Tree Points	This point feature class will be extracted from identified vegetated areas that exceed 4 meters in height relative to the bare earth model.	All points should have the correct topology.

DEM Production & Qualitative Assessment

DEM PRODUCTION METHODOLOGY

Dewberry utilized ESRI software and Global Mapper for the DEM production and QC process. ArcGIS software is used to generate the products and the QC is performed in both ArcGIS and Global Mapper.

Dewberry Hydro-Flattening Workflow



1. **Classify Water Points:** LAS point falling within hydrographic breaklines shall be classified to ASPRS class 9 using TerraScan. Breaklines must be prepared correctly prior to performing this task.
2. **Classify Ignored Ground Points:** Classify points in close proximity to the breaklines from Ground to class 10 (Ignored Ground). Close proximity will be defined as no more than 1x the nominal point spacing on the landward side of the breakline.
3. **Terrain Processing:** A Terrain will be generated using the Breaklines and LAS data that has been imported into Arc as a Multipoint File.
4. **Create DEM Zones for Processing:** Create DEM Zones that are buffered around the edges. Zones should be created in a logical manner to minimize the number of zones without creating zones too large for processing. Dewberry will make zones no larger than 200 square miles (taking into account that a DEM will fill in the entire extent not just where LiDAR is present). Once the first zone is created it must be verified against the tile grid to ensure that the cells line up perfectly with the tile grid edge.
5. **Convert Terrain to Raster:** Convert Terrain to raster using the DEM Zones created in step 4. In the environmental properties set the extents of the raster to the buffered Zone. For each subsequent zone, the first DEM will be utilized as the snap raster to ensure that zones consistently snap to one another.
6. **Perform Initial QAQC on Zones:** During the initial QA process anomalies will be identified and corrective polygons will be created.

7. Correct Issues on Zones: Dewberry will perform corrections on zones following Dewberry's correction process.
8. Extract Individual Tiles: Dewberry will extract individual tiles from the zones utilizing a Dewberry proprietary tool.
9. Final QA: Final QA will be performed on the dataset to ensure that tile boundaries are seamless.

The creation of first and last return DSMs follow a similar workflow as outlined above, except that breaklines are not used to enforce the first and last return terrains. Additionally, rather than ground only data, the first or last return of all point classes, except for noise-class 7, are used to create the multipoint files and subsequent terrains.

DEM QUALITATIVE ASSESSMENT

Dewberry performed a comprehensive qualitative assessment of the bare earth DEM deliverables to ensure that all tiled DEM products were delivered with the proper extents, were free of processing artifacts, and contained the proper referencing information. This process was performed in ArcGIS software with the use of a tool set Dewberry has developed to verify that the raster extents match those of the tile grid and contain the correct projection information. The DEM data was reviewed at a scale of 1:5000 to review for artifacts caused by the DEM generation process and to review the hydro-flattened features. To perform this review Dewberry creates HillShade models and overlays a partially transparent colored elevation model to review for these issues. All corrections are completed using Dewberry's proprietary correction workflow. Upon completion of the corrections, the DEM data is loaded into Global Mapper for its second review and to verify corrections. Once the DEMs are tiled out, the final tiles are again loaded into Global Mapper to ensure coverage, extents, and that the final tiles are seamless.

The images below show an example of a bare earth DEM and first return DSM of the same tile.




Figure 21-Tile 18SUG480340. The bare earth DEM is shown on the left while the first return DSM is shown on the right

DEM VERTICAL ACCURACY RESULTS

The same 100 checkpoints that were used to test the vertical accuracy of the LiDAR were used to validate the vertical accuracy of the final DEM products as well. Accuracy results may vary between the source LiDAR and final DEM deliverable. DEMs are created by averaging several LiDAR points within each pixel which may result in slightly different elevation values at each survey checkpoint when compared to the source LAS, which does not average several LiDAR points together but may interpolate (linearly) between two or three points to derive an elevation value.

Table 16 summarizes the tested vertical accuracy results from a comparison of the surveyed checkpoints to the elevation values present within the final DEM dataset.

Land Cover Category	# of Points	FVA – Fundamental Vertical Accuracy (RMSE _z x 1.9600) Spec=0.181 m	CVA – Consolidated Vertical Accuracy (95th Percentile) Spec=0.269 m	SVA – Supplemental Vertical Accuracy (95th Percentile) Target=0.269 m
Consolidated	100		0.197	
Bare Earth-Open Terrain	20	0.135		
Grass Weeds and Crops	20			0.194
Forest	20			0.168
Urban	20			0.216
Brush Land and Trees	20			0.211

Table 16 – FVA, CVA, and SVA Vertical Accuracy at 95% Confidence Level

The RMSE_z for checkpoints in open terrain only tested 0.069 meters, within the target criteria of 0.092 meters. Compared with the 0.181 meters specification, the FVA tested 0.135 meters at the 95% confidence level based on RMSE_z x 1.9600.

Compared with the 0.269 meters specification, CVA for all checkpoints in all land cover categories combined tested 0.197 meters based on the 95th percentile.

Compared with the target 0.269 meters specification, SVA for checkpoints in the grass weeds and crops land cover category tested 0.194 meters based on the 95th percentile, checkpoints in the forested and fully grown land cover category tested 0.168 meters based on the 95th percentile, checkpoints in the brush and small trees land cover category tested 0.211 meters based on the 95th percentile, and checkpoints in the urban land cover category tested 0.216 meters based on the 95th percentile.

Table 17 lists the 5% outliers that are larger than the 95th percentile.

Point ID	NAD83 UTM Zone 18		NAVD88	DEM Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
BLT_17	381142.027	4051271.05	0.508	0.718	0.21	0.21
BLT_19	410587.042	4049846.41	0.215	0.432	0.22	0.22

FO_14B	376505.026	4067499.95	4.395	4.199	-0.20	0.20
GWC_1CHK	344779.087	4134125.52	35.999	36.215	0.22	0.22
UT_15CHK	417183.163	4061728.53	0.768	1.016	0.25	0.25

Table 17 – 5% Outliers

Table 18 provides overall descriptive statistics.

100 % of Totals	RMSE _z (m) Open Terrain Spec=0.092m	Mean (m)	Median (m)	Skew	Std Dev (m)	# of Points	Min (m)	Max (m)
Consolidated		0.051	0.059	-0.224	0.089	100	-0.196	0.248
Open Terrain	0.069	0.021	0.032	-0.880	0.067	20	-0.155	0.119
Grass, Weeds and Crops		0.062	0.065	-0.186	0.090	20	-0.196	0.216
Forest		0.011	0.013	-0.862	0.089	20	-0.196	0.125
Urban		0.068	0.071	0.141	0.091	20	-0.099	0.248
Brush Land and Trees		0.092	0.095	-0.386	0.085	20	-0.069	0.217

Table 18 – Overall Descriptive Statistics

DEM QA/QC CHECKLIST

Project Number/Description: TO G13PD00279 USGS Norfolk, VA LiDAR

Date: 1/29/2014

Overview

- Correct number of files are delivered and all files are in ERDAS IMG format
- Verify Raster Extents
- Verify Projection/Coordinate System

Review

- Manually review bare-earth DEMs in Arc with a hillshade to check for issues with the hydro-flattening process or any general anomalies that may be present. Specifically, water should be flowing downhill, water features should NOT be floating above surrounding terrain and bridges should NOT be present in bare-earth DEM. Hydrologic breaklines should be overlaid during review of DEMs.
- Manually review first return DSMs with a hillshade to check for processing issues or coverage issues.
- Manually review last return DSMs with a hillshade to check for processing issues or coverage issues.
- DEM cell size is 1 meter
- Perform all necessary corrections in Arc using Dewberry's proprietary correction workflow.
- Review all corrections in Global Mapper
- Perform final overview on tiled data in Global Mapper to ensure seamless product.

Metadata

- Project level DEM metadata XML file is error free as determined by the USGS MP tool
- Metadata content contains sufficient detail and all pertinent information regarding source materials, projections, datums, processing steps, etc.

Completion Comments: Complete – Approved

Appendix A: Survey Report

Check Point Survey Report
“Norfolk, VA LiDAR Task Order”
USGS Contract: G10PC00013
Task Order Number: G13PD000279

Prepared by:

Dewberry Engineers Inc.
Charlotte, North Carolina, 282269
Phone: 704.509.9918
Fax: 704.509.9937

INTRODUCTION

Project Summary

Dewberry Engineers Inc. is under contract to United States Geodetic Survey to provide 100 QA Check Points for 933 square miles in Chesapeake, Hampton, Newport News, Norfolk, Poquoson, Portsmouth, Virginia Beach, and York Counties in Virginia. Under the above USGS Task Order, Dewberry is tasked to complete the quality assurance of high resolution LiDAR-derived elevation products. As a part of this work Dewberry staff will complete checkpoint surveys that will be used to evaluate vertical accuracy on the bare-earth terrain derived from the LiDAR. Existing NGC Control Points were located and surveyed to check the accuracy of the RTK/GPS survey equipment with the results shown in section 2.4 of this report. As an internal QA/QC procedure and to verify that the Check Points meet the 95% confidence level approximately 50% of the points were re-observed and are shown in section 5 in this report. Final horizontal coordinates are referenced to UTM Zone 18 North, NAD83, in meters. Final Vertical elevations are referenced to NAVD88, in meters.

Points of Contact

Questions regarding the technical aspects of this report should be addressed to:

Norfolk, VA LiDAR
TO# G13PD00279
January 29, 2014
Page 67 of 232


Dewberry Engineers Inc.
Matthew Rudolph
6135 Lakeview Road
Suite 150
Charlotte, NC 20269
(704)264-1257direct
(704)509-9937




1.3 Project Area



Norfolk, VA LiDAR

0.7m NPS/9.25cm VRMSEz with tide coordination (+/- 2hrs predicted low tide)



-  Total_Proposed_AOI_2012 (933 sq mi landr)
-  NGA_AOI_Norfolk-1 (603 sq mi landmass)
-  NGA_AOI_Norfolk-2 (14 sq mi)

PROJECT DETAILS

Survey Equipment

In performing the GPS observations, Trimble R-8 GNSS receiver/antenna attached to a 2 meter fixed height pole with a Trimble TSC2 Data Collector to collect GPS raw data were used to perform the field surveys.

Survey Point Detail

The 100 Check Points were well distributed throughout the project area so as to cover as many flight lines as possible using “dispersed method” of placement.

A “Ground Control Point Documentation Report” sheet was used to show the placement of the nail and a sketch for each of the points surveyed.

Network Design

The GPS survey performed by Dewberry Engineers Inc. located in Charlotte,NC was tied to a Real Time Network (RTN) managed by KeyNetGPS inc. KeyNetGPS is a series of continuously operating, high precision GNSS reference stations. These reference stations have all been linked together using Trimble VRS3Net App software, creating a Virtual Reference Station System (VRS).

Field Survey Procedures and Analysis

Dewberry Engineers Inc. used Trimble R-8 GNSS receivers, which is a geodetic quality dual frequency GPS receiver, to collect data at each surveyed location.

All locations were occupied once with approximately 50% of the locations being re-observed. All re-observations matched the initially derived station positions within the allowable tolerances of 5cm or within the 95% confidence level. Each occupation which utilized the VRS network was occupied for approximately three (3) minutes in duration and measured to at least 180 epochs.

Field GPS observations are detailed on the” Ground Control Point Documentation Reports” submitted as part of this report.

Ten existing NGS monuments listed in the NSRS database were located as an additional QA/QC method to check the accuracy of the VRS network. Some of these monuments were used as Horizontal and Vertical control checks. Some monuments were used as Horizontal or Vertical checks only as shown in the table below.

NGS PT. ID	AS SURVEYED(m)			AS PUBLISHED(m)						CHK TYPE
	NORTHING	EASTING	ELEV	NORTHING	EASTING	ELEV	Δ N	Δ E	Δ ELEV	
DOUGLAS CHK	4075440.488	380599.04	3.73	4,075,440.59	380,599.12	3.75	-0.103	-0.084	-0.020	VERT.
STATION 509	4100627.566	384554.955	2.124	4,100,627.56	384,554.95	2.3	0.010	0.007	X	HORIZ.
STATION 537	4098672.971	376462.99	3.503	4,098,672.96	376,463.00	4	0.008	-0.006	X	HORIZ.
STATION 538	4097985.036	375769.747	2.108	4,097,985.03	375,769.74	2	0.004	0.007	X	HORIZ.

F-455	4096857.383	376079.277	3.927	X	X	3.957	X	X	-0.030	VERT.
MON 007	4135651.82	349236.942	23.259	4,135,651.79	349,236.96	23.5	0.031	-0.022	X	HORIZ.
124	4107886.234	372228.771	8.579	4,107,886.28	372,228.77	8.7	-0.048	0.003	X	HORIZ.
PASCALE	4071366.848	371222.946	5.515	4,071,366.85	371,222.94	5.6	-0.003	0.009	X	HORIZ.
PEAKE	4094521.001	376414.781	2.479	4,094,520.99	376,414.77	2.5	0.008	0.013	-0.021	VERT.
D 470	4076051.123	3999352.192	3.401	X	X	3.447	X	X	-0.046	VERT.

The above results indicate that the VRS network is providing positional values within the 5cm parameters for this survey.

Data Processing Procedures

After field data is collected the information is downloaded from the data collectors into the office software. The software programs used Trimble Business Center and Arc Map 10.

Downloaded data is run through the Trimble Business Center program to obtain the following reports; points report, point comparison, and a point detail report. The reports are reviewed for point accuracy and precision.

After review of the point data an "ASCII" or "txt" file is created. Point files are loaded into Arc Map 10(GIS software) to make a visual check of the point data to make sure it also checks with the "Ground Control Point Documentation Report" sketch and description as well as the Pt#, Coordinates, and Elevation.

FINAL COORDINATES

The final coordinate system for checkpoints is as follows:

Coord System = UTM
 UTM Zone = Zone 18
 Horiz Datum = NAD83
 Vert Datum = NAVD88
 Units = both in Meters
 Geoid Model = GEOID12A

BRUSHLAND and LOW TREES			
BLT-1	4127850.095	351760.734	18.183
BLT-2	4124969.354	354157.693	26.867
BLT-3	4116934.625	374985.334	1.681
BLT-4	4112722.605	377113.574	1.301
BLT-5	4105501.265	363984.403	5.313
BLT-6	4101703.518	376746.304	3.508
BLT-7	4091258.47	387491.887	0.708
BLT-8	4083420.214	376730.499	5.063
BLT-9	4083180.738	409359.513	1.461
BLT-10	4078664.264	381578.163	0.747

BLT-11	4072438.855	393248.624	5.015
BLT-12	4071563.329	402227.485	3.332
BLT-13	4067495.229	392360.215	4.073
BLT-14	4060371.467	381270.904	4.561
BLT-15	4061689.787	400675.21	3.101
BLT-16	4058718.15	418260.165	0.336
BLT-17	4051271.046	381142.027	0.508
BLT-18	4051529.692	391753.707	3.966
BLT-19	4049846.406	410587.042	0.215
BLT-20	4045956.462	393929.901	1.76
FORESTED			
FO-1	4136323.776	350228.113	23.871
FO-2	4126211.091	360014.272	8.932
FO-3	4118875.446	366402.057	16.648
FO-4	4112572.968	372250.758	4.076
FO-5	4108269.849	362705.508	9.253
FO-6	4101531.898	381648.883	2.403
FO-7	4096033.448	372274.821	5.794
FO-8	4084210.274	399373.443	5.089
FO-9	4078442.28	400259.407	3.628
FO-10	4073199.529	370329.394	6.472
FO-11	4071580.897	372624.23	4.829
FO-12	4067053.555	415396.475	0.702
FO-13	4068198.754	397579.131	2.607
FO-14	4067550.12	376314.026	4.690
FO-15	4060962.236	395885.204	2.266
FO-16	4055125.178	410438.562	0.44
FO-17	4056004.221	380058.909	4.986
FO-18	4049656.47	396892.944	2.857
FO-19	4045705.789	403974.708	1.817
FO-20	4046751.378	391556.197	3.545
GRASS, WEEDS, and CROPS			
GWC-1	4134125.481	344779.064	35.965
GWC-2	4118838.763	360405.124	13.727
GWC-3	4119343.897	373059.394	1.28
GWC-4	4109732.524	381475.24	0.319
GWC-5	4107208.362	376178.523	2.294
GWC-6	4096625.795	376137.546	4.989
GWC-7	4114829.507	365940.986	17.938
GWC-8	4082613.859	393786.442	6.043

GWC-9	4084165.948	404973.792	4.738
GWC-10	4078316.06	393746.948	1.982
GWC-11	4072545.385	375676.882	4.983
GWC-12	4073011.615	409067.175	5.377
GWC-13	4067042.59	403954.911	4.174
GWC-14	4066255.187	377981.16	3.71
GWC-15	4061512.702	392212.252	6.443
GWC-16	4055382.316	402351.116	2.44
GWC-17	4056359.548	386220.44	5.163
GWC-18	4049194.933	386712.905	3.966
GWC-19	4046257.13	409971.276	2.111
GWC-20	4046741.634	376541.932	4.16
OPEN			
OT-1	4133416.989	348684.803	25.196
OT-2	4120908.932	365374.175	19.117
OT-3	4113702.121	360651.125	10.775
OT-4	4105404.702	385773.144	1.138
OT-5	4107753.528	365920.254	9.605
OT-6	4101773.558	371637.824	6.304
OT-7	4097123.061	382129.104	2.298
OT-8	4086525.625	383472.444	3.377
OT-9	4078298.891	404011.498	4.043
OT-10	4078657.569	387312	2.843
OT-11	4072616.492	387581.48	5.668
OT-12	4066448.202	409482.049	2.486
OT-13	4067562.414	381818.542	2.601
OT-14	4061599.984	378660.721	4.475
OT-15	4060963.643	409784.125	1.461
OT-16	4055461.44	397899.773	3.726
OT-17	4051531.896	376373.966	5.115
OT-18	4049989.779	385337.991	4.057
OT-19	4045755.088	399629.718	2.501
OT-20	4046832.726	389710.031	3.427
URBAN			
UT-1	4130867.113	350036.421	21.875
UT-2	4122275.214	366296.536	1.73
UT-3	4112855.286	365989.516	16.203
UT-4	4110977.445	360182.785	9.528
UT-5	4107289.791	371528.47	8.849
UT-6	4102065.181	365947.433	9.063

UT-7	4094026.888	375440.462	1.167
UT-8	4046143.784	386772.856	5.124
UT-9	4046143.784	386772.856	5.124
UT-10	4046143.784	386772.856	5.124
UT-11	4046143.784	386772.856	5.124
UT-12	4046143.784	386772.856	5.124
UT-13	4046143.784	386772.856	5.124
UT-14	4046143.784	386772.856	5.124
UT-15	4046143.784	386772.856	5.124
UT-16	4046143.784	386772.856	5.124
UT-17	4046143.784	386772.856	5.124
UT-18	4046143.784	386772.856	5.124
UT-19	4046143.784	386772.856	5.124
UT-20	4046143.784	386772.856	5.124

GPS OBSERVATIONS

NORFOLK, VA LiDAR 2013					
POINT ID	OBSERV. DATE	JULIAN DATE	TIME OF DAY	RE-OBSERV. DATE	RE-OBSERV TIME
BRUSHLANDS AND LOW TREES					
BLT-1	5/6/2013	239	8:13	N/A	N/A
BLT-2	5/5/2013	240	12:15	N/A	N/A
BLT-3	5/5/2013	240	10:14	N/A	N/A
BLT-4	5/5/2013	240	8:58	N/A	N/A
BLT-5	5/4/2013	241	13:42	N/A	N/A
BLT-6	5/4/2013	241	11:22	N/A	N/A
BLT-7	5/4/2013	241	7:22	N/A	N/A
BLT-8	5/2/2013	243	14:53	N/A	N/A
BLT-9	5/3/2013	242	12:29	N/A	N/A
BLT-10	5/2/2013	243	15:28	N/A	N/A
BLT-11	5/2/2013	243	10:52	N/A	N/A
BLT-12	5/2/2013	243	19:30	N/A	N/A
BLT-13	5/1/2013	244	12:52	N/A	N/A
BLT-14	5/1/2013	244	16:45	5/22/2013	12:03
BLT-15	5/1/2013	244	11:15	N/A	N/A
BLT-16	4/30/2013	245	17:18	N/A	N/A
BLT-17	4/29/2013	246	12:18	N/A	N/A
BLT-18	4/29/2013	246	15:32	N/A	N/A

BLT-19	4/30/2013	245	12:07	N/A	N/A
BLT-20	4/29/2013	246	15:07	N/A	N/A
FORESTED					
FO-1	5/6/2013	239	9:35	N/A	N/A
FO-2	5/5/2013	240	13:43	N/A	N/A
FO-3	5/5/2013	240	11:00	N/A	N/A
FO-4	5/5/2013	240	9:26	N/A	N/A
FO-5	5/4/2013	241	14:05	N/A	N/A
FO-6	5/4/2013	241	9:54	N/A	N/A
FO-7	5/4/2013	241	11:55	N/A	N/A
FO-8	5/3/2013	242	15:08	N/A	N/A
FO-9	5/3/2013	242	14:19	N/A	N/A
FO-10	5/2/2013	243	13:16	N/A	N/A
FO-11	5/2/2013	243	12:32	N/A	N/A
FO-12	4/30/2013	245	16:14	N/A	N/A
FO-13	5/1/2013	244	12:01	N/A	N/A
FO-14	5/1/2013	244	15:28	N/A	N/A
FO-15	5/1/2013	244	9:57	N/A	N/A
FO-16	4/30/2013	245	12:36	N/A	N/A
FO-17	4/29/2013	246	17:47	N/A	N/A
FO-18	4/30/2013	245	7:23	N/A	N/A
FO-19	4/30/2013	245	9:41	N/A	N/A
FO-20	4/29/2013	246	14:25	N/A	N/A
GRASS, WEEDS, and CROPS					
GWC-1	5/6/2013	239	9:08	5/6/2013	10:42
GWC-2	5/5/2013	240	14:38	5/22/2013	17:15
GWC-3	5/5/2013	240	10:34	5/5/2013	17:53
GWC-4	5/5/2013	240	8:27	N/A	N/A
GWC-5	5/4/2013	241	15:31	N/A	N/A
GWC-6	5/4/2013	241	8:49	N/A	N/A
GWC-7	5/5/2013	240	16:04	5/22/2013	16:50
GWC-8	5/2/2013	243	18:02	5/3/2013	10:24
GWC-9	5/3/2013	242	13:09	5/22/2013	7:30
GWC-10	5/2/2013	243	18:26	N/A	N/A
GWC-11	5/2/2013	243	12:01	5/3/2013	7:52
GWC-12	5/3/2013	242	11:24	5/3/2013	17:04
GWC-13	5/1/2013	244	11:39	5/22/2013	8:36

GWC-14	5/1/2013	244	15:08	5/22/2013	12:40
GWC-15	5/1/2301	244	19:21	N/A	N/A
GWC-16	4/30/2013	245	10:51	N/A	N/A
GWC-17	4/29/2013	246	16:10	5/22/2013	11:31
GWC-18	4/29/2013	246	12:52	N/A	N/A
GWC-19	4/30/2013	245	11:25	N/A	N/A
GWC-20	4/29/2013	246	11:52	4/29/2013	17:20
OPEN					
OT-1	5/6/2013	239	10:31	5/22/2013	17:40
OT-2	5/5/2013	240	13:15	5/5/2013	17:24
OT-3	5/5/2013	240	14:58	5/22/2013	16:22
OT-4	5/4/2013	241	10:50	5/4/2013	17:48
OT-5	5/4/2013	241	14:44	5/22/2013	15:10
OT-6	5/4/2013	241	12:39	5/4/2013	16:46
OT-7	5/4/2013	241	9:37	5/4/2013	18:07
OT-8	5/2/2013	243	16:57	5/3/2013	9:59
OT-9	5/3/2013	242	14:01	5/22/2013	7:58
OT-10	5/2/2013	243	16:16	5/3/2013	9:27
OT-11	5/2/2013	243	11:16	5/3/2013	9:07
OT-12	4/30/2013	245	15:52	5/22/2013	9:02
OT-13	5/1/2013	244	14:44	5/2/2013	8:51
OT-14	5/1/2013	244	16:18	5/22/2013	12:23
OT-15	4/30/2013	245	15:36	5/1/2031	8:05
OT-16	4/30/2013	245	18:49	5/1/2013	9:28
OT-17	4/29/2013	246	11:25	4/29/2013	17:30
OT-18	4/29/2013	246	12:35	4/29/2013	17:03
OT-19	4/30/2013	245	8:53	N/A	N/A
OT-20	4/29/2013	246	14:04	5/22/2013	10:49
URBAN					
UT-1	5/6/2013	239	8:38	N/A	N/A
UT-2	5/5/2013	240	11:45	5/5/2013	17:34
UT-3	5/5/2013	240	15:43	5/6/2013	11:41
UT-4	5/5/2013	240	15:23	5/22/2013	15:48
UT-5	5/4/2013	241	15:08	5/6/2013	12:53
UT-6	5/4/2013	241	13:15	5/22/2013	14:35
UT-7	5/4/2013	241	8:04	5/4/2013	17:15

UT-8	5/2/2013	243	17:24	5/3/2013	9:43
UT-9	5/3/2013	242	11:51	5/3/2013	16:45
UT-10	5/2/2013	243	14:14	5/3/2013	8:18
UT-11	5/2/2013	243	11:38	5/3/2013	8:43
UT-12	5/2/2013	243	19:02	5/3/2013	10:54
UT-13	5/1/2013	244	14:18	5/2/2013	8:26
UT-14	5/1/2013	244	13:46	5/2/2013	9:11
UT-15	4/30/2013	245	17:01	5/22/2013	9:27
UT-16	4/30/2013	245	13:26	5/1/2013	8:27
UT-17	4/29/2013	246	15:47	5/6/2013	16:30
UT-18	4/30/2013	245	9:25	5/1/2013	7:10
UT-19	4/30/2013	245	11:43	5/1/2013	8:46
UT-20	4/29/2013	246	13:40	4/29/2013	13:45

POINT COMPARISON

LiDAR QA				
PT ID	CHK PT	DELTA N	DELTA E	DELTA EL
BLT-14	BLT-14CHK3	0.007	-0.002	0.022
GWC-1	GWC-1CHK	-0.036	-0.023	-0.034
GWC-2	GWC-2CHK2	-0.018	0.021	-0.029
GWC-3	GWC-3CHK	-0.013	-0.007	0.051
GWC-7	GWC-7CHK2	-0.008	-0.031	0.002
GWC-8	GWC-8CHK	0.02	0.018	-0.001
GWC-9	GWC-9CHK2	-0.024	0.005	0.016
GWC-11	GWC-11CHK	-0.023	0.022	0.004
GWC-12	GWC-12CHK	0.001	-0.016	0.002
GWC-13	GWC-13CHK	0.012	-0.028	-0.026
GWC-14	GWC-14CHK2	-0.009	0.006	0.012
GWC-17	GWC-17CHK2	0.021	-0.024	0.016
GWC-20	GWC-20CHK	0	0.002	-0.008
OT-1	OT-1CHK2	-0.008	-0.015	0.017
OT-2	OT-2CHK	0.003	0.002	-0.012
OT-3	OT-3CHK2	-0.022	0.003	-0.045
OT-4	OT-4CHK	-0.019	0.009	-0.004
OT-5	OT-5CHK2	-0.014	-0.011	-0.043
OT-6	OT-6CHK	0.007	0.004	0.002
OT-7	OT-7CHK	-0.042	0.016	0.07
OT-8	OT-8CHK	-0.001	0.011	-0.008

OT-9	OT-9CHK2	-0.008	0.006	-0.007
OT-10	OT-10CHK	-0.002	0.001	-0.015
OT-11	OT-11CHK	-0.002	0.018	-0.011
OT-12	OT-12CHK2	-0.018	0.007	0.006
OT-13	OT-13CHK	-0.012	0.014	-0.007
OT-14	OT-14CHK2	0.002	0.026	0.025
OT-15	OT-15CHK	0.005	0.007	0.007
OT-16	OT-16CHK	-0.009	-0.007	0.072
OT-17	OT-17CHK	0.003	-0.012	0.009
OT-18	OT-18CHK	-0.01	-0.008	-0.01
OT-19	OT-19CHK	-0.012	0.003	-0.008
OT-20	OT-20CHK	0	-0.002	0.041
UT-2	UT-2CHK	-0.003	0.005	-0.019
UT-3	UT-3CHK2	-0.007	-0.011	-0.01
UT-4	UT-4CHK2	-0.018	-0.034	-0.047
UT-5	UT-5CHK2	-0.007	-0.012	-0.033
UT-6	UT-6CHK2	0.011	0.012	-0.046
UT-7	UT-7CHK	-0.015	-0.008	0.019
UT-8	UT-8CHK	0.003	-0.004	0.005
UT-9	UT-9CHK	-0.012	-0.004	0.011
UT-10	UT-10CHK	0.007	0	-0.021
UT-11	UT-11CHK	0.001	0.023	0.012
UT-12	UT-12CHK	0.013	-0.023	0.031
UT-13	UT-13CHK	-0.012	0.007	0.001
UT-14	UT-14CHK	-0.015	-0.002	0.027
UT-15	UT-15CHK2	0.01	0.007	-0.011
UT-16	UT-16CHK	-0.003	0.01	0.019
UT-17	UT-17CHK2	-0.038	0.006	-0.004
UT-18	UT-18CHK	0.007	0.009	-0.016
UT-19	UT-19CHK	0.009	0.02	0.03
UT-20	UT-20CHK	-0.004	0.007	-0.003

Appendix B: Complete List of Delivered Tiles

UTM TILES (1,457):

18SUF825425	18SVF110575	18SUF780755	18SUG720025
18SUF840425	18SVF125575	18SUF795755	18SUG735025
18SUF855425	18SVF140575	18SUF810755	18SUG750025
18SUF870425	18SVF155575	18SUF825755	18SUG765025
18SUF885425	18SVF170575	18SUF840755	18SUG780025
18SUF900425	18SVF185575	18SUF855755	18SUG795025
18SUF660440	18SUF675590	18SUF870755	18SUG810025
18SUF675440	18SUF690590	18SUF885755	18SUG825025
18SUF690440	18SUF705590	18SUF900755	18SUG840025
18SUF705440	18SUF720590	18SUF915755	18SUG855025
18SUF720440	18SUF735590	18SUF930755	18SUG870025
18SUF735440	18SUF750590	18SUF945755	18SUG885040
18SUF750440	18SUF765590	18SUF960755	18SUG900040
18SUF765440	18SUF780590	18SUF975755	18SUG915040
18SUF780440	18SUF795590	18SUF990755	18SUG930040
18SUF795440	18SUF810590	18SVF005755	18SUG945040
18SUF810440	18SUF825590	18SVF020755	18SUG960040
18SUF825440	18SUF840590	18SVF035755	18SUG975040
18SUF840440	18SUF855590	18SVF050755	18SUG990040
18SUF855440	18SUF870590	18SVF065755	18SUG005040
18SUF870440	18SUF885590	18SVF080755	18SUG020040
18SUF885440	18SUF900590	18SVF095755	18SUG035040
18SUF900440	18SUF915590	18SVF110755	18SUG050040
18SUF915440	18SUF930590	18SVF125755	18SUG065040
18SUF930440	18SUF945590	18SVF140755	18SUG080040
18SUF945440	18SUF960590	18SUF690770	18SUG095040
18SUF960440	18SUF975590	18SUF705770	18SUG110040
18SUF975440	18SUF990590	18SUF720770	18SUG125040
18SUF990440	18SVF005590	18SUF735770	18SUG140040
18SVF005440	18SVF020590	18SUF750770	18SUG155040
18SVF020440	18SVF035590	18SUF765770	18SUG170040
18SVF035440	18SVF050590	18SUF780770	18SUG185055
18SVF050440	18SVF065590	18SUF795770	18SUG200055
18SVF065440	18SVF080590	18SUF810770	18SUG215055
18SVF080440	18SVF095590	18SUF825770	18SUG230055
18SVF095440	18SVF110590	18SUF840770	18SUG245055
18SVF110440	18SVF125590	18SUF855770	18SUG260055
18SVF125440	18SVF140590	18SUF870770	18SUG275055
18SVF140440	18SVF155590	18SUF885770	18SUG290055

18SVF155440	18SVF170590	18SUF900770	18SUG690055
18SVF170440	18SVF185590	18SUF915770	18SUG705055
18SVF185440	18SUF675605	18SUF930770	18SUG720055
18SVF200440	18SUF690605	18SUF945770	18SUG735055
18SVF215440	18SUF705605	18SUF960770	18SUG750055
18SUF660455	18SUF720605	18SUF975770	18SUG765055
18SUF675455	18SUF735605	18SUF990770	18SUG780055
18SUF690455	18SUF750605	18SVF005770	18SUG795055
18SUF705455	18SUF765605	18SVF020770	18SUG810055
18SUF720455	18SUF780605	18SVF035770	18SUG825055
18SUF735455	18SUF795605	18SVF050770	18SUG840055
18SUF750455	18SUF810605	18SVF065770	18SUG855055
18SUF765455	18SUF825605	18SVF080770	18SUG870055
18SUF780455	18SUF840605	18SVF095770	18SUG555070
18SUF795455	18SUF855605	18SVF110770	18SUG570070
18SUF810455	18SUF870605	18SVF125770	18SUG585070
18SUF825455	18SUF885605	18SUF690785	18SUG600070
18SUF840455	18SUF900605	18SUF705785	18SUG615070
18SUF855455	18SUF915605	18SUF720785	18SUG630070
18SUF870455	18SUF930605	18SUF735785	18SUG645070
18SUF885455	18SUF945605	18SUF750785	18SUG660070
18SUF900455	18SUF960605	18SUF765785	18SUG675070
18SUF915455	18SUF975605	18SUF780785	18SUG690070
18SUF930455	18SUF990605	18SUF795785	18SUG705070
18SUF945455	18SVF005605	18SUF810785	18SUG720070
18SUF960455	18SVF020605	18SUF825785	18SUG735070
18SUF975455	18SVF035605	18SUF840785	18SUG750070
18SUF990455	18SVF050605	18SUF855785	18SUG765070
18SVF005455	18SVF065605	18SUF870785	18SUG780070
18SVF020455	18SVF080605	18SUF885785	18SUG795070
18SVF035455	18SVF095605	18SUF900785	18SUG810070
18SVF050455	18SVF110605	18SUF915785	18SUG825070
18SVF065455	18SVF125605	18SUF930785	18SUG840070
18SVF080455	18SVF140605	18SUF945785	18SUG855070
18SVF095455	18SVF155605	18SUF960785	18SUG540085
18SVF110455	18SVF170605	18SUF975785	18SUG555085
18SVF125455	18SUF675620	18SUF990785	18SUG570085
18SVF140455	18SUF690620	18SVF005785	18SUG585085
18SVF155455	18SUF705620	18SVF020785	18SUG600085
18SVF170455	18SUF720620	18SVF035785	18SUG615085
18SVF185455	18SUF735620	18SVF050785	18SUG630085
18SVF200455	18SUF750620	18SVF065785	18SUG645085

18SVF215455	18SUF765620	18SVF080785	18SUG660085
18SUF660470	18SUF780620	18SVF095785	18SUG675085
18SUF675470	18SUF795620	18SVF110785	18SUG690085
18SUF690470	18SUF810620	18SVF125785	18SUG705085
18SUF705470	18SUF825620	18SUF690800	18SUG720085
18SUF720470	18SUF840620	18SUF705800	18SUG735085
18SUF735470	18SUF855620	18SUF720800	18SUG750085
18SUF750470	18SUF870620	18SUF735800	18SUG765085
18SUF765470	18SUF885620	18SUF750800	18SUG780085
18SUF780470	18SUF900620	18SUF765800	18SUG795085
18SUF795470	18SUF915620	18SUF780800	18SUG810085
18SUF810470	18SUF930620	18SUF795800	18SUG825085
18SUF825470	18SUF945620	18SUF810800	18SUG840085
18SUF840470	18SUF960620	18SUF825800	18SUG855085
18SUF855470	18SUF975620	18SUF840800	18SUG540100
18SUF870470	18SUF990620	18SUF855800	18SUG555100
18SUF885470	18SVF005620	18SUF870800	18SUG570100
18SUF900470	18SVF020620	18SUF885800	18SUG585100
18SUF915470	18SVF035620	18SUF900800	18SUG600100
18SUF930470	18SVF050620	18SUF915800	18SUG615100
18SUF945470	18SVF065620	18SUF930800	18SUG630100
18SUF960470	18SVF080620	18SUF945800	18SUG645100
18SUF975470	18SVF095620	18SUF960800	18SUG660100
18SUF990470	18SVF110620	18SUF975800	18SUG675100
18SVF005470	18SVF125620	18SUF990800	18SUG690100
18SVF020470	18SVF140620	18SVF005800	18SUG705100
18SVF035470	18SVF155620	18SVF020800	18SUG720100
18SVF050470	18SVF170620	18SVF035800	18SUG735100
18SVF065470	18SUF675635	18SVF050800	18SUG750100
18SVF080470	18SUF690635	18SVF065800	18SUG765100
18SVF095470	18SUF705635	18SVF080800	18SUG780100
18SVF110470	18SUF720635	18SVF095800	18SUG795100
18SVF125470	18SUF735635	18SVF110800	18SUG810100
18SVF140470	18SUF750635	18SVF125800	18SUG825100
18SVF155470	18SUF765635	18SUF690815	18SUG840100
18SVF170470	18SUF780635	18SUF705815	18SUG555115
18SVF185470	18SUF795635	18SUF720815	18SUG570115
18SVF200470	18SUF810635	18SUF735815	18SUG585115
18SVF215470	18SUF825635	18SUF750815	18SUG600115
18SUF660485	18SUF840635	18SUF765815	18SUG615115
18SUF675485	18SUF855635	18SUF780815	18SUG630115
18SUF690485	18SUF870635	18SUF795815	18SUG645115

18SUF705485	18SUF885635	18SUF810815	18SUG660115
18SUF720485	18SUF900635	18SUF825815	18SUG675115
18SUF735485	18SUF915635	18SUF840815	18SUG690115
18SUF750485	18SUF930635	18SUF855815	18SUG705115
18SUF765485	18SUF945635	18SUF870815	18SUG720115
18SUF780485	18SUF960635	18SUF885815	18SUG735115
18SUF795485	18SUF975635	18SUF900815	18SUG750115
18SUF810485	18SUF990635	18SUF915815	18SUG765115
18SUF825485	18SVF005635	18SUF930815	18SUG780115
18SUF840485	18SVF020635	18SUF945815	18SUG795115
18SUF855485	18SVF035635	18SUF960815	18SUG810115
18SUF870485	18SVF050635	18SUF975815	18SUG825115
18SUF885485	18SVF065635	18SUF990815	18SUG555130
18SUF900485	18SVF080635	18SVF005815	18SUG570130
18SUF915485	18SVF095635	18SVF020815	18SUG585130
18SUF930485	18SVF110635	18SVF035815	18SUG600130
18SUF945485	18SVF125635	18SVF050815	18SUG615130
18SUF960485	18SVF140635	18SVF065815	18SUG630130
18SUF975485	18SVF155635	18SVF080815	18SUG645130
18SUF990485	18SVF170635	18SVF095815	18SUG660130
18SVF005485	18SUF675650	18SVF110815	18SUG675130
18SVF020485	18SUF690650	18SVF125815	18SUG690130
18SVF035485	18SUF705650	18SUF690830	18SUG705130
18SVF050485	18SUF720650	18SUF705830	18SUG720130
18SVF065485	18SUF735650	18SUF720830	18SUG735130
18SVF080485	18SUF750650	18SUF735830	18SUG750130
18SVF095485	18SUF765650	18SUF750830	18SUG765130
18SVF110485	18SUF780650	18SUF765830	18SUG780130
18SVF125485	18SUF795650	18SUF780830	18SUG795130
18SVF140485	18SUF810650	18SUF795830	18SUG810130
18SVF155485	18SUF825650	18SUF810830	18SUG555145
18SVF170485	18SUF840650	18SUF825830	18SUG570145
18SVF185485	18SUF855650	18SUF840830	18SUG585145
18SVF200485	18SUF870650	18SUF855830	18SUG600145
18SVF215485	18SUF885650	18SUF870830	18SUG615145
18SUF660500	18SUF900650	18SUF885830	18SUG630145
18SUF675500	18SUF915650	18SUF900830	18SUG645145
18SUF690500	18SUF930650	18SUF915830	18SUG660145
18SUF705500	18SUF945650	18SUF930830	18SUG675145
18SUF720500	18SUF960650	18SUF945830	18SUG690145
18SUF735500	18SUF975650	18SUF960830	18SUG705145
18SUF750500	18SUF990650	18SUF975830	18SUG720145

18SUF765500	18SVF005650	18SUF990830	18SUG735145
18SUF780500	18SVF020650	18SVF005830	18SUG750145
18SUF795500	18SVF035650	18SVF020830	18SUG765145
18SUF810500	18SVF050650	18SVF035830	18SUG780145
18SUF825500	18SVF065650	18SVF050830	18SUG795145
18SUF840500	18SVF080650	18SVF065830	18SUG810145
18SUF855500	18SVF095650	18SVF080830	18SUG570160
18SUF870500	18SVF110650	18SVF095830	18SUG585160
18SUF885500	18SVF125650	18SVF110830	18SUG600160
18SUF900500	18SVF140650	18SUF690845	18SUG615160
18SUF915500	18SVF155650	18SUF705845	18SUG630160
18SUF930500	18SUF675665	18SUF720845	18SUG645160
18SUF945500	18SUF690665	18SUF735845	18SUG660160
18SUF960500	18SUF705665	18SUF750845	18SUG675160
18SUF975500	18SUF720665	18SUF765845	18SUG690160
18SUF990500	18SUF735665	18SUF780845	18SUG705160
18SVF005500	18SUF750665	18SUF795845	18SUG720160
18SVF020500	18SUF765665	18SUF810845	18SUG735160
18SVF035500	18SUF780665	18SUF825845	18SUG750160
18SVF050500	18SUF795665	18SUF840845	18SUG765160
18SVF065500	18SUF810665	18SUF855845	18SUG780160
18SVF080500	18SUF825665	18SUF870845	18SUG570175
18SVF095500	18SUF840665	18SUF885845	18SUG585175
18SVF110500	18SUF855665	18SUF900845	18SUG600175
18SVF125500	18SUF870665	18SUF915845	18SUG615175
18SVF140500	18SUF885665	18SUF930845	18SUG630175
18SVF155500	18SUF900665	18SUF945845	18SUG645175
18SVF170500	18SUF915665	18SUF960845	18SUG660175
18SVF185500	18SUF930665	18SUF975845	18SUG675175
18SVF200500	18SUF945665	18SUF990845	18SUG690175
18SVF215500	18SUF960665	18SVF005845	18SUG705175
18SUF660515	18SUF975665	18SVF020845	18SUG720175
18SUF675515	18SUF990665	18SVF035845	18SUG735175
18SUF690515	18SVF005665	18SVF050845	18SUG750175
18SUF705515	18SVF020665	18SVF065845	18SUG765175
18SUF720515	18SVF035665	18SVF080845	18SUG570190
18SUF735515	18SVF050665	18SVF095845	18SUG585190
18SUF750515	18SVF065665	18SVF110845	18SUG600190
18SUF765515	18SVF080665	18SUF690860	18SUG615190
18SUF780515	18SVF095665	18SUF705860	18SUG630190
18SUF795515	18SVF110665	18SUF720860	18SUG645190
18SUF810515	18SVF125665	18SUF735860	18SUG660190

18SUF825515	18SVF140665	18SUF750860	18SUG675190
18SUF840515	18SVF155665	18SUF765860	18SUG690190
18SUF855515	18SUF675680	18SUF780860	18SUG705190
18SUF870515	18SUF690680	18SUF795860	18SUG720190
18SUF885515	18SUF705680	18SUF810860	18SUG735190
18SUF900515	18SUF720680	18SUF825860	18SUG750190
18SUF915515	18SUF735680	18SUF840860	18SUG765190
18SUF930515	18SUF750680	18SUF855860	18SUG540205
18SUF945515	18SUF765680	18SUF870860	18SUG555205
18SUF960515	18SUF780680	18SUF885860	18SUG570205
18SUF975515	18SUF795680	18SUF900860	18SUG585205
18SUF990515	18SUF810680	18SUF915860	18SUG600205
18SVF005515	18SUF825680	18SUF930860	18SUG615205
18SVF020515	18SUF840680	18SUF945860	18SUG630205
18SVF035515	18SUF855680	18SUF960860	18SUG645205
18SVF050515	18SUF870680	18SUF975860	18SUG660205
18SVF065515	18SUF885680	18SUF990860	18SUG675205
18SVF080515	18SUF900680	18SVF005860	18SUG690205
18SVF095515	18SUF915680	18SVF020860	18SUG705205
18SVF110515	18SUF930680	18SVF035860	18SUG720205
18SVF125515	18SUF945680	18SVF050860	18SUG735205
18SVF140515	18SUF960680	18SVF065860	18SUG750205
18SVF155515	18SUF975680	18SVF080860	18SUG765205
18SVF170515	18SUF990680	18SVF095860	18SUG510220
18SVF185515	18SVF005680	18SVF110860	18SUG525220
18SVF200515	18SVF020680	18SUF750875	18SUG540220
18SUF660530	18SVF035680	18SUF765875	18SUG555220
18SUF675530	18SVF050680	18SUF780875	18SUG570220
18SUF690530	18SVF065680	18SUF795875	18SUG585220
18SUF705530	18SVF080680	18SUF810875	18SUG600220
18SUF720530	18SVF095680	18SUF825875	18SUG615220
18SUF735530	18SVF110680	18SUF840875	18SUG630220
18SUF750530	18SVF125680	18SUF855875	18SUG645220
18SUF765530	18SVF140680	18SUF870875	18SUG660220
18SUF780530	18SVF155680	18SUF885875	18SUG495235
18SUF795530	18SUF675695	18SUF900875	18SUG510235
18SUF810530	18SUF690695	18SUF915875	18SUG525235
18SUF825530	18SUF705695	18SUF930875	18SUG540235
18SUF840530	18SUF720695	18SUF945875	18SUG555235
18SUF855530	18SUF735695	18SUF960875	18SUG570235
18SUF870530	18SUF750695	18SUF975875	18SUG585235
18SUF885530	18SUF765695	18SVF050875	18SUG600235

18SUF900530	18SUF780695	18SVF065875	18SUG615235
18SUF915530	18SUF795695	18SVF080875	18SUG630235
18SUF930530	18SUF810695	18SVF095875	18SUG645235
18SUF945530	18SUF825695	18SVF110875	18SUG480250
18SUF960530	18SUF840695	18SUF795890	18SUG495250
18SUF975530	18SUF855695	18SUF810890	18SUG510250
18SUF990530	18SUF870695	18SUF825890	18SUG525250
18SVF005530	18SUF885695	18SUF840890	18SUG540250
18SVF020530	18SUF900695	18SUF855890	18SUG555250
18SVF035530	18SUF915695	18SUF870890	18SUG570250
18SVF050530	18SUF930695	18SUF885890	18SUG585250
18SVF065530	18SUF945695	18SUF900890	18SUG600250
18SVF080530	18SUF960695	18SUF915890	18SUG615250
18SVF095530	18SUF975695	18SUF930890	18SUG630250
18SVF110530	18SUF990695	18SUF945890	18SUG465265
18SVF125530	18SVF005695	18SUF720905	18SUG480265
18SVF140530	18SVF020695	18SUF735905	18SUG495265
18SVF155530	18SVF035695	18SUF750905	18SUG510265
18SVF170530	18SVF050695	18SUF795905	18SUG525265
18SVF185530	18SVF065695	18SUF810905	18SUG540265
18SVF200530	18SVF080695	18SUF825905	18SUG555265
18SUF660545	18SVF095695	18SUF840905	18SUG570265
18SUF675545	18SVF110695	18SUF855905	18SUG585265
18SUF690545	18SVF125695	18SUF870905	18SUG600265
18SUF705545	18SVF140695	18SUF885905	18SUG615265
18SUF720545	18SVF155695	18SUF900905	18SUG465280
18SUF735545	18SUF690710	18SUF705920	18SUG480280
18SUF750545	18SUF705710	18SUF720920	18SUG495280
18SUF765545	18SUF720710	18SUF735920	18SUG510280
18SUF780545	18SUF735710	18SUF750920	18SUG525280
18SUF795545	18SUF750710	18SUF795920	18SUG540280
18SUF810545	18SUF765710	18SUF810920	18SUG555280
18SUF825545	18SUF780710	18SUF825920	18SUG570280
18SUF840545	18SUF795710	18SUF840920	18SUG585280
18SUF855545	18SUF810710	18SUF855920	18SUG600280
18SUF870545	18SUF825710	18SUF870920	18SUG450295
18SUF885545	18SUF840710	18SUF885920	18SUG465295
18SUF900545	18SUF855710	18SUF690935	18SUG480295
18SUF915545	18SUF870710	18SUF705935	18SUG495295
18SUF930545	18SUF885710	18SUF720935	18SUG510295
18SUF945545	18SUF900710	18SUF735935	18SUG525295
18SUF960545	18SUF915710	18SUF750935	18SUG540295

18SUF975545	18SUF930710	18SUF765935	18SUG555295
18SUF990545	18SUF945710	18SUF810935	18SUG570295
18SVF005545	18SUF960710	18SUF825935	18SUG585295
18SVF020545	18SUF975710	18SUF840935	18SUG450310
18SVF035545	18SUF990710	18SUF855935	18SUG465310
18SVF050545	18SVF005710	18SUF675950	18SUG480310
18SVF065545	18SVF020710	18SUF690950	18SUG495310
18SVF080545	18SVF035710	18SUF705950	18SUG510310
18SVF095545	18SVF050710	18SUF720950	18SUG525310
18SVF110545	18SVF065710	18SUF735950	18SUG540310
18SVF125545	18SVF080710	18SUF750950	18SUG555310
18SVF140545	18SVF095710	18SUF765950	18SUG570310
18SVF155545	18SVF110710	18SUF780950	18SUG435325
18SVF170545	18SVF125710	18SUF795950	18SUG450325
18SVF185545	18SVF140710	18SUF810950	18SUG465325
18SVF200545	18SUF690725	18SUF825950	18SUG480325
18SUF660560	18SUF705725	18SUF840950	18SUG495325
18SUF675560	18SUF720725	18SUF660965	18SUG510325
18SUF690560	18SUF735725	18SUF675965	18SUG525325
18SUF705560	18SUF750725	18SUF690965	18SUG540325
18SUF720560	18SUF765725	18SUF705965	18SUG555325
18SUF735560	18SUF780725	18SUF720965	18SUG570325
18SUF750560	18SUF795725	18SUF735965	18SUG435340
18SUF765560	18SUF810725	18SUF750965	18SUG450340
18SUF780560	18SUF825725	18SUF765965	18SUG465340
18SUF795560	18SUF840725	18SUF780965	18SUG480340
18SUF810560	18SUF855725	18SUF795965	18SUG495340
18SUF825560	18SUF870725	18SUF810965	18SUG510340
18SUF840560	18SUF885725	18SUF825965	18SUG525340
18SUF855560	18SUF900725	18SUF840965	18SUG540340
18SUF870560	18SUF915725	18SUF645980	18SUG555340
18SUF885560	18SUF930725	18SUF660980	18SUG435355
18SUF900560	18SUF945725	18SUF675980	18SUG450355
18SUF915560	18SUF960725	18SUF690980	18SUG465355
18SUF930560	18SUF975725	18SUF705980	18SUG480355
18SUF945560	18SUF990725	18SUF720980	18SUG495355
18SUF960560	18SVF005725	18SUF735980	18SUG510355
18SUF975560	18SVF020725	18SUF750980	18SUG525355
18SUF990560	18SVF035725	18SUF765980	18SUG540355
18SVF005560	18SVF050725	18SUF780980	18SUG450370
18SVF020560	18SVF065725	18SUF795980	18SUG465370
18SVF035560	18SVF080725	18SUF810980	18SUG480370

18SVF050560	18SVF095725	18SUF825980	18SUG495370
18SVF065560	18SVF110725	18SUF840980	18SUG510370
18SVF080560	18SVF125725	18SUF855980	18SUG525370
18SVF095560	18SVF140725	18SUF645995	
18SVF110560	18SUF690740	18SUF660995	
18SVF125560	18SUF705740	18SUF675995	
18SVF140560	18SUF720740	18SUF690995	
18SVF155560	18SUF735740	18SUF705995	
18SVF170560	18SUF750740	18SUF720995	
18SVF185560	18SUF765740	18SUF735995	
18SVF200560	18SUF780740	18SUF750995	
18SUF675575	18SUF795740	18SUF765995	
18SUF690575	18SUF810740	18SUF780995	
18SUF705575	18SUF825740	18SUF795995	
18SUF720575	18SUF840740	18SUF810995	
18SUF735575	18SUF855740	18SUF825995	
18SUF750575	18SUF870740	18SUF840995	
18SUF765575	18SUF885740	18SUF855995	
18SUF780575	18SUF900740	18SUG630010	
18SUF795575	18SUF915740	18SUG645010	
18SUF810575	18SUF930740	18SUG660010	
18SUF825575	18SUF945740	18SUG675010	
18SUF840575	18SUF960740	18SUG690010	
18SUF855575	18SUF975740	18SUG705010	
18SUF870575	18SUF990740	18SUG720010	
18SUF885575	18SVF005740	18SUG735010	
18SUF900575	18SVF020740	18SUG750010	
18SUF915575	18SVF035740	18SUG765010	
18SUF930575	18SVF050740	18SUG780010	
18SUF945575	18SVF065740	18SUG795010	
18SUF960575	18SVF080740	18SUG810010	
18SUF975575	18SVF095740	18SUG825010	
18SUF990575	18SVF110740	18SUG840010	
18SVF005575	18SVF125740	18SUG855010	
18SVF020575	18SVF140740	18SUG615025	
18SVF035575	18SUF690755	18SUG630025	
18SVF050575	18SUF705755	18SUG645025	
18SVF065575	18SUF720755	18SUG660025	
18SVF080575	18SUF735755	18SUG675025	
18SVF095575	18SUF750755	18SUG690025	
	18SUF765755	18SUG705025	

SPCS TILES (388):

DO_S23_1387_00	DO_S23_0680_00	DO_S23_0377_00	DO_S23_1487_00
DO_S23_1493_00	DO_S23_0589_00	DO_S23_0483_00	DO_S23_1486_00
DO_S23_1492_00	DO_S23_0588_00	DO_S23_0482_00	DO_S23_1485_00
DO_S23_1491_00	DO_S23_0691_00	DO_S23_0481_00	DO_S23_1484_00
DO_S23_1490_00	DO_S23_0690_00	DO_S23_0480_00	DO_S23_1590_00
DO_S23_1399_00	DO_S23_0599_00	DO_S23_0389_00	DO_S23_1499_00
DO_S23_1398_00	DO_S23_0598_00	DO_S23_0388_00	DO_S23_1498_00
DO_S23_1397_00	DO_S23_1600_00	DO_S23_0387_00	DO_S23_1497_00
DO_S23_2403_00	DO_S23_1509_00	DO_S23_0493_00	DO_S23_1496_00
DO_S23_2402_00	DO_S23_1508_00	DO_S23_0492_00	DO_S23_1495_00
DO_S23_2401_00	DO_S23_1519_00	DO_S23_0491_00	DO_S23_1494_00
DO_S23_2400_00	DO_S23_1518_00	DO_S23_0490_00	DO_S23_2500_00
DO_S23_2309_00	DO_S23_0527_00	DO_S23_0399_00	DO_S23_2409_00
DO_S23_2308_00	DO_S23_0537_00	DO_S23_0398_00	DO_S23_2408_00
DO_S23_2307_00	DO_S23_0536_00	DO_S23_0397_00	DO_S23_2407_00
DO_S23_2413_00	DO_S23_0547_00	DO_S23_1403_00	DO_S23_2406_00
DO_S23_2412_00	DO_S23_0546_00	DO_S23_1402_00	DO_S23_2405_00
DO_S23_2411_00	DO_S23_0545_00	DO_S23_1401_00	DO_S23_2404_00
DO_S23_2410_00	DO_S23_0557_00	DO_S23_1400_00	DO_S23_2510_00
DO_S23_2319_00	DO_S23_0556_00	DO_S23_1309_00	DO_S23_2419_00
DO_S23_2318_00	DO_S23_0555_00	DO_S23_1308_00	DO_S23_2418_00
DO_S23_2317_00	DO_S23_0554_00	DO_S23_1307_00	DO_S23_2417_00
DO_S23_2423_00	DO_S23_0567_00	DO_S23_1413_00	DO_S23_2416_00
DO_S23_2422_00	DO_S23_0566_00	DO_S23_1412_00	DO_S23_2415_00
DO_S23_2421_00	DO_S23_0565_00	DO_S23_1411_00	DO_S23_2414_00
DO_S23_2420_00	DO_S23_0564_00	DO_S23_1410_00	DO_S23_2429_00
DO_S23_2329_00	DO_S23_0563_00	DO_S23_1319_00	DO_S23_2428_00
DO_S23_2328_00	DO_S23_0577_00	DO_S23_1318_00	DO_S23_2427_00
DO_S23_2327_00	DO_S23_0576_00	DO_S23_1317_00	DO_S23_2426_00
DO_S23_2433_00	DO_S23_0575_00	DO_S23_0376_00	DO_S23_2425_00
DO_S23_2432_00	DO_S23_0574_00	DO_S23_0386_00	DO_S23_2424_00
DO_S23_2431_00	DO_S23_0573_00	DO_S23_0396_00	DO_S23_2435_00
DO_S23_2430_00	DO_S23_0572_00	DO_S23_1306_00	DO_S23_2434_00
DO_S23_2339_00	DO_S23_0587_00	DO_S23_1316_00	DO_S23_1423_00
DO_S23_2338_00	DO_S23_0586_00	DO_S23_1528_00	DO_S23_1422_00
DO_S23_2337_00	DO_S23_0585_00	DO_S23_1527_00	DO_S23_1421_00
DO_S23_1326_00	DO_S23_0584_00	DO_S23_1526_00	DO_S23_1420_00
DO_S23_1336_00	DO_S23_0583_00	DO_S23_1525_00	DO_S23_1329_00
DO_S23_1346_00	DO_S23_0582_00	DO_S23_1524_00	DO_S23_1328_00
DO_S23_1356_00	DO_S23_0581_00	DO_S23_1523_00	DO_S23_1327_00
DO_S23_1366_00	DO_S23_0597_00	DO_S23_1522_00	DO_S23_1433_00


DO_S23_1376_00	DO_S23_0596_00	DO_S23_1521_00	DO_S23_1432_00
DO_S23_1386_00	DO_S23_0595_00	DO_S23_1537_00	DO_S23_1431_00
DO_S23_1396_00	DO_S23_0594_00	DO_S23_1536_00	DO_S23_1430_00
DO_S23_2306_00	DO_S23_0593_00	DO_S23_1535_00	DO_S23_1339_00
DO_S23_2316_00	DO_S23_0592_00	DO_S23_1534_00	DO_S23_1338_00
DO_S13_9685_00	DO_S23_0591_00	DO_S23_1532_00	DO_S23_1337_00
DO_S13_9696_00	DO_S23_1507_00	DO_S23_1531_00	DO_S23_1443_00
DO_S13_9695_00	DO_S23_1506_00	DO_S23_1541_00	DO_S23_1442_00
DO_S13_9694_00	DO_S23_1505_00	DO_S23_1551_00	DO_S23_1441_00
DO_S13_9693_00	DO_S23_1504_00	DO_S23_1561_00	DO_S23_1440_00
DO_S23_0606_00	DO_S23_1503_00	DO_S23_2501_00	DO_S23_1349_00
DO_S23_0605_00	DO_S23_1502_00	DO_S23_1520_00	DO_S23_1348_00
DO_S23_0616_00	DO_S23_1517_00	DO_S23_1429_00	DO_S23_1347_00
DO_S23_0615_00	DO_S23_1516_00	DO_S23_1428_00	DO_S23_1453_00
DO_S23_0626_00	DO_S23_1515_00	DO_S23_1427_00	DO_S23_1452_00
DO_S23_0625_00	DO_S23_1514_00	DO_S23_1426_00	DO_S23_1451_00
DO_S23_0635_00	DO_S23_1513_00	DO_S23_1425_00	DO_S23_1450_00
DO_S23_0604_00	DO_S23_1512_00	DO_S23_1424_00	DO_S23_1359_00
DO_S23_0603_00	DO_S23_1511_00	DO_S23_1530_00	DO_S23_1358_00
DO_S23_0602_00	DO_S23_0477_00	DO_S23_1439_00	DO_S23_1357_00
DO_S23_0614_00	DO_S23_0476_00	DO_S23_1438_00	DO_S23_1463_00
DO_S23_0613_00	DO_S23_0475_00	DO_S23_1437_00	DO_S23_1462_00
DO_S23_0612_00	DO_S23_0474_00	DO_S23_1436_00	DO_S23_1461_00
DO_S23_0611_00	DO_S23_0489_00	DO_S23_1435_00	DO_S23_1460_00
DO_S23_0624_00	DO_S23_0488_00	DO_S23_1434_00	DO_S23_1369_00
DO_S23_0623_00	DO_S23_0487_00	DO_S23_1540_00	DO_S23_1368_00
DO_S23_0622_00	DO_S23_0486_00	DO_S23_1449_00	DO_S23_1367_00
DO_S23_0621_00	DO_S23_0485_00	DO_S23_1448_00	DO_S23_1473_00
DO_S23_0528_00	DO_S23_0484_00	DO_S23_1447_00	DO_S23_1472_00
DO_S23_0634_00	DO_S23_0590_00	DO_S23_1446_00	DO_S23_1471_00
DO_S23_0633_00	DO_S23_0499_00	DO_S23_1445_00	DO_S23_1470_00
DO_S23_0632_00	DO_S23_0498_00	DO_S23_1444_00	DO_S23_1379_00
DO_S23_0631_00	DO_S23_0497_00	DO_S23_1550_00	DO_S23_1378_00
DO_S23_0630_00	DO_S23_0496_00	DO_S23_1459_00	DO_S23_1377_00
DO_S23_0539_00	DO_S23_0495_00	DO_S23_1458_00	DO_S23_1483_00
DO_S23_0538_00	DO_S23_0494_00	DO_S23_1457_00	DO_S23_1482_00
DO_S23_0643_00	DO_S23_1500_00	DO_S23_1456_00	DO_S23_1481_00
DO_S23_0642_00	DO_S23_1409_00	DO_S23_1455_00	DO_S23_1480_00
DO_S23_0641_00	DO_S23_1408_00	DO_S23_1454_00	DO_S23_1389_00
DO_S23_0640_00	DO_S23_1407_00	DO_S23_1560_00	DO_S23_1388_00
DO_S23_0549_00	DO_S23_1406_00	DO_S23_1469_00	DO_S23_2326_00
DO_S23_0548_00	DO_S23_1405_00	DO_S23_1468_00	DO_S23_2336_00


DO_S23_0652_00	DO_S23_1404_00	DO_S23_1467_00	DO_S23_2442_00
DO_S23_0651_00	DO_S23_1510_00	DO_S23_1466_00	DO_S23_2441_00
DO_S23_0650_00	DO_S23_1419_00	DO_S23_1465_00	DO_S23_2440_00
DO_S23_0559_00	DO_S23_1418_00	DO_S23_1464_00	DO_S23_2349_00
DO_S23_0558_00	DO_S23_1417_00	DO_S23_1570_00	DO_S23_2348_00
DO_S23_0661_00	DO_S23_1416_00	DO_S23_1479_00	DO_S23_2347_00
DO_S23_0660_00	DO_S23_1415_00	DO_S23_1478_00	DO_S23_2359_00
DO_S23_0569_00	DO_S23_1414_00	DO_S23_1477_00	DO_S23_2358_00
DO_S23_0568_00	DO_S23_0473_00	DO_S23_1476_00	DO_S23_2357_00
DO_S23_0671_00	DO_S23_0472_00	DO_S23_1475_00	DO_S23_2346_00
DO_S23_0670_00	DO_S23_0471_00	DO_S23_1474_00	DO_S23_2356_00
DO_S23_0579_00	DO_S23_0470_00	DO_S23_1580_00	DO_S23_1325_00
DO_S23_0578_00	DO_S23_0379_00	DO_S23_1489_00	DO_S23_1335_00
DO_S23_0681_00	DO_S23_0378_00	DO_S23_1488_00	DO_S23_1345_00


Appendix C: GPS Processing Reports for Each Mission


LASER MAPPING SPECIALISTS (LMSI)

Combined - Map Run (80)









Processing Summary Information

Program: POSGPS

Version: 4.30.3108

Project: D:\Projects\Dewberry\Va\Norfolk_2013\13080a\pos\GPS\80a.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 135984

No processed position: 123996

Missing Fwd or Rev: 4

With bad C/A code: 0

With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0300 (m)

C/A Code: 1.04 (m)

L1 Doppler: 0.020 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.042 (m)

North: 0.033 (m)

Height: 0.158 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (11827 occurrences):

East: 0.010 (m)

North: 0.009 (m)
Height: 0.031 (m)

Quality Number Percentages:

Q 1: 99.0 %
Q 2: 1.0 %
Q 3: 0.0 %
Q 4: 0.0 %
Q 5: 0.0 %
Q 6: 0.0 %

Position Standard Deviation Percentages:







0.00 - 0.10 m: 100.0 %
0.10 - 0.30 m: 0.0 %
0.30 - 1.00 m: 0.0 %
1.00 - 5.00 m: 0.0 %
5.00 m + over: 0.0 %







Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 0.0 %


Baseline Distances:


Maximum: 35.259 (km)
Minimum: 0.925 (km)
Average: 17.735 (km)
First Epoch: 9.509 (km)
Last Epoch: 3.478 (km)







Combined - Map Run (82)





80a [Combined] - PDOP, HDOP, VDOP Plots





Processing Summary Information

Program: POSGPS

Version: 4.30.3108

Project: D:\Projects\Dewberry\Va\Norfolk_2013\13080a\pos\GPS\80a.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 135984

No processed position: 125507

Missing Fwd or Rev: 4

With bad C/A code: 0

With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0298 (m)

C/A Code: 1.02 (m)

L1 Doppler: 0.019 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.013 (m)

North: 0.011 (m)

Height: 0.026 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (10471 occurrences):

East: 0.010 (m)

North: 0.009 (m)

Height: 0.026 (m)

Quality Number Percentages:

Q 1: 99.1 %

Q 2: 0.9 %

Q 3: 0.0 %

Q 4: 0.0 %

Q 5: 0.0 %

Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 100.0 %

0.10 - 0.30 m: 0.0 %

0.30 - 1.00 m: 0.0 %

1.00 - 5.00 m: 0.0 %

5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 0.0 %

Baseline Distances:







Maximum: 35.259 (km)







Minimum: 3.478 (km)

Average: 18.685 (km)


First Epoch: 14.725 (km)

Last Epoch: 3.478 (km)







Combined - Map Run (4)





81a [Combined] - Forward/Reverse or Combined Separation Plot









81a [Combined] - PDOP, HDOP, VDOP Plots



81a [Combined] - Number of Satellites Bar Plot





Processing Summary Information

Program: POSGPS

Version: 4.30.3108

Project: D:\Projects\Dewberry\Va\Norfolk_2013\13081a\pos\GPS\81a.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 70958

No processed position: 65227

Missing Fwd or Rev: 4

With bad C/A code: 0

With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0228 (m)

C/A Code: 1.12 (m)

L1 Doppler: 0.031 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.010 (m)

North: 0.021 (m)

Height: 0.040 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (5725 occurrences):

East: 0.010 (m)

North: 0.021 (m)

Height: 0.033 (m)

Quality Number Percentages:

Q 1: 99.4 %

Q 2: 0.6 %

Q 3: 0.0 %

Q 4: 0.0 %

Q 5: 0.0 %

Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 100.0 %

0.10 - 0.30 m: 0.0 %

0.30 - 1.00 m: 0.0 %

1.00 - 5.00 m: 0.0 %

5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 0.0 %

Baseline Distances:

Maximum: 32.953 (km)


Minimum: 0.656 (km)

Average: 16.175 (km)


First Epoch: 7.473 (km)

Last Epoch: 5.691 (km)


Combined - Map Run (9)




81b [Combined] - Forward/Reverse or Combined Separation Plot















81b [Combined] - PDOP, HDOP, VDOP Plots



81b [Combined] - Number of Satellites Bar Plot







Processing Summary Information

Program: POSGPS

Version: 4.30.3108

Project: D:\Projects\Dewberry\Va\Norfolk_2013\13081b\pos\GPS\81b.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 48966

No processed position: 45922

Missing Fwd or Rev: 4

With bad C/A code: 0

With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0227 (m)

C/A Code: 1.15 (m)

L1 Doppler: 0.029 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.015 (m)

North: 0.028 (m)

Height: 0.044 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (3038 occurrences):

East: 0.003 (m)

North: 0.014 (m)

Height: 0.023 (m)

Quality Number Percentages:

Q 1: 99.9 %

Q 2: 0.1 %

Q 3: 0.0 %

Q 4: 0.0 %

Q 5: 0.0 %

Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 100.0 %

0.10 - 0.30 m: 0.0 %

0.30 - 1.00 m: 0.0 %

1.00 - 5.00 m: 0.0 %

5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 0.0 %

Baseline Distances:

Maximum: 33.176 (km)


Minimum: 2.361 (km)

Average: 17.860 (km)


First Epoch: 6.556 (km)

Last Epoch: 2.361 (km)


Combined - Map Run (27)










88a [Combined] - Forward/Reverse or Combined Separation Plot








88a [Combined] - PDOP, HDOP, VDOP Plots



88a [Combined] - Number of Satellites Bar Plot





Processing Summary Information

Program: POSGPS

Version: 4.30.3108

Project: D:\Projects\Dewberry\Va\Norfolk_2013\13088a\pos\GPS\88a.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 155168

No processed position: 142444

Missing Fwd or Rev: 4

With bad C/A code: 0

With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0260 (m)

C/A Code: 1.10 (m)

L1 Doppler: 0.018 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.006 (m)

North: 0.013 (m)

Height: 0.021 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (12708 occurrences):

East: 0.005 (m)

North: 0.010 (m)

Height: 0.014 (m)

Quality Number Percentages:

Q 1: 99.5 %

Q 2: 0.5 %

Q 3: 0.0 %

Q 4: 0.0 %

Q 5: 0.0 %

Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 100.0 %

0.10 - 0.30 m: 0.0 %

0.30 - 1.00 m: 0.0 %

1.00 - 5.00 m: 0.0 %

5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 0.0 %

Baseline Distances:

Maximum: 36.679 (km)


Minimum: 3.087 (km)

Average: 18.294 (km)


First Epoch: 28.454 (km)

Last Epoch: 29.355 (km)


Combined - Map Run (37)










88b [Combined] - Forward/Reverse or Combined Separation Plot









88b [Combined] - PDOP, HDOP, VDOP Plots



88b [Combined] - Number of Satellites Bar Plot





Processing Summary Information

Program: POSGPS

Version: 4.30.3108

Project: D:\Projects\Dewberry\Va\Norfolk_2013\13088b\pos\GPS\88b.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 155934

No processed position: 143849

Missing Fwd or Rev: 8

With bad C/A code: 0

With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0265 (m)

C/A Code: 1.12 (m)

L1 Doppler: 0.027 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.011 (m)

North: 0.021 (m)

Height: 0.030 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (12073 occurrences):

East: 0.010 (m)

North: 0.020 (m)

Height: 0.029 (m)

Quality Number Percentages:

Q 1: 99.0 %

Q 2: 1.0 %

Q 3: 0.0 %

Q 4: 0.0 %

Q 5: 0.0 %

Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 88.9 %

0.10 - 0.30 m: 11.1 %

0.30 - 1.00 m: 0.0 %

1.00 - 5.00 m: 0.0 %

5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 0.0 %

Baseline Distances:

Maximum: 37.012 (km)


Minimum: 0.926 (km)


Average: 17.514 (km)


First Epoch: 29.014 (km)

Last Epoch: 28.011 (km)


Combined - Map Run (51)








89a [Combined] - PDOP, HDOP, VDOP Plots





Processing Summary Information

Program: POSGPS
 Version: 4.30.3108
 Project: D:\Projects\Dewberry\Va\Norfolk_2013\13089a\pos\GPS\89a.gnv
 Solution Type: Combined Fwd/Rev
 Number of Epochs:
 Total in GPB file: 162207
 No processed position: 151395
 Missing Fwd or Rev: 4
 With bad C/A code: 0
 With bad L1 Phase: 0
 Measurement RMS Values:
 L1 Phase: 0.0298 (m)
 C/A Code: 1.10 (m)
 L1 Doppler: 0.018 (m/s)
 Fwd/Rev Separation RMS Values:
 East: 0.008 (m)
 North: 0.019 (m)
 Height: 0.026 (m)
 Fwd/Rev Sep. RMS for 25%-75% weighting (10806 occurrences):
 East: 0.007 (m)
 North: 0.019 (m)

Height: 0.022 (m)

Quality Number Percentages:

Q 1: 99.1 %

Q 2: 0.9 %

Q 3: 0.0 %

Q 4: 0.0 %

Q 5: 0.0 %

Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 100.0 %

0.10 - 0.30 m: 0.0 %

0.30 - 1.00 m: 0.0 %

1.00 - 5.00 m: 0.0 %

5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 0.0 %

Baseline Distances:







Maximum: 33.051 (km)







Minimum: 0.954 (km)


Average: 14.602 (km)


First Epoch: 9.799 (km)


Last Epoch: 27.866 (km)
























Combined - Map Run (23)







Processing Summary Information

Program: POSGPS

Version: 4.30.3108

Project: D:\Projects\Dewberry\Va\Norfolk_2013\13089a\pos2\GPS\89a2.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 162207

No processed position: 158711

Missing Fwd or Rev: 4

With bad C/A code: 0

With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0247 (m)

C/A Code: 1.35 (m)

L1 Doppler: 0.019 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.016 (m)

North: 0.024 (m)

Height: 0.055 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (3489 occurrences):

East: 0.011 (m)

North: 0.019 (m)

Height: 0.023 (m)

Quality Number Percentages:

Q 1: 99.5 %

Q 2: 0.5 %

Q 3: 0.0 %

Q 4: 0.0 %

Q 5: 0.0 %

Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 60.5 %

0.10 - 0.30 m: 39.5 %

0.30 - 1.00 m: 0.0 %

1.00 - 5.00 m: 0.0 %

5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 39.4 %

Baseline Distances:

Maximum: 30.893 (km)


Minimum: 1.152 (km)



Average: 13.398 (km)

First Epoch: 28.490 (km)








Last Epoch: 25.968 (km)







Combined - Map Run (2)








13089b [Combined] - Number of Satellites Bar Plot


















Combined - Map Run (8)







90a [Combined] - Number of Satellites Bar Plot







Combined - Map Run (7)









Processing Summary Information

Program: POSGPS

Version: 4.30.3108

Project: C:\Projects\VA\Norfolk\13091a\pos\GPS\13091a.gnv

Solution Type: Combined Fwd/Rev

Number of Epochs:

Total in GPB file: 78684

No processed position: 71478

Missing Fwd or Rev: 4

With bad C/A code: 0

With bad L1 Phase: 0

Measurement RMS Values:

L1 Phase: 0.0192 (m)

C/A Code: 0.97 (m)

L1 Doppler: 0.020 (m/s)

Fwd/Rev Separation RMS Values:

East: 0.004 (m)

North: 0.009 (m)

Height: 0.017 (m)

Fwd/Rev Sep. RMS for 25%-75% weighting (7200 occurrences):

East: 0.003 (m)

North: 0.004 (m)

Height: 0.016 (m)

Quality Number Percentages:

Q 1: 100.0 %

Q 2: 0.0 %

Q 3: 0.0 %

Q 4: 0.0 %

Q 5: 0.0 %

Q 6: 0.0 %

Position Standard Deviation Percentages:

0.00 - 0.10 m: 77.8 %

0.10 - 0.30 m: 22.2 %

0.30 - 1.00 m: 0.0 %

1.00 - 5.00 m: 0.0 %

5.00 m + over: 0.0 %

Percentages of epochs with DD_DOP over 10.00:

DOP over Tol: 10.0 %

Baseline Distances:







Maximum: 34.181 (km)






Minimum: 1.104 (km)

Average: 14.521 (km)

First Epoch: 7.294 (km)

Last Epoch: 6.917 (km)





THE ATLANTIC GROUP
Output Results for JD13087_1

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy





Figure 9: Gyro Bias Estimation



Output Result for JD13088_1

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy





Figure 9: Gyro Bias Estimation



Output Result for JD13088_2

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy





Figure 9: Gyro Bias Estimation



Output Results for JD13088_3

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy





Figure 9: Gyro Bias Estimation



Output Results for JD13089_1

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy





Figure 9: Gyro Bias Estimation



Output Results for JD13090_1

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy





Figure 9: Gyro Bias Estimation



Output Results for JD13091_1

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy





Figure 9: Gyro Bias Estimation



Output Results for JD13091_2

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy





Figure 9: Gyro Bias Estimation



Output Result for JD13091_3

Figure 1: Trajectory Map




Figure 2: Position and Standard Deviation




Figure 3: Velocity and Standard Deviation




Figure 4: Forward/Reverse or Combined Separation Plot




Figure 5: Attitude and Standard Deviation




Figure 6: Position Accuracy and PDOP




Figure 7: Accelerometer Bias Estimation




Figure 8: Kalman Filter Residuals and Position Accuracy




Figure 9: Gyro Bias Estimation

