

# Texas Lavaca Wharton FEMA R6 Lidar

Report Produced for U.S. Geological Survey

USGS Contract: G16PC00020

Task Order: G17PD00014

Report Date: 10/23/2018

SUBMITTED BY:

**Dewberry**  
1000 North Ashley Drive Suite 801  
Tampa, FL 33602  
813.225.1325

SUBMITTED TO:

**U.S. Geological Survey**  
1400 Independence Road  
Rolla, MO 65401  
573.308.3810

## Table of Contents

Executive Summary .....	4
The Project Team.....	4
Survey Area.....	4
Date of Survey.....	4
Coordinate Reference System .....	4
Lidar Vertical Accuracy .....	5
Project Deliverables.....	5
Project Tiling Footprint.....	6
Lidar Acquisition Report .....	7
Lidar Acquisition Details.....	7
Lidar System parameters.....	7
Acquisition Status Report and Flightlines .....	8
Lidar Control .....	9
Airborn GPS Kinematic .....	9
Generation and Calibration of Laser Points (raw data) .....	9
Boresight and Relative accuracy.....	10
Lidar Processing & Qualitative Assessment .....	11
Initial Processing.....	11
Final Swath Vertical Accuracy Assessment.....	12
Inter-Swath (Between Swath) Relative Accuracy .....	13
Intra-Swath (Within a Single Swath) Relative Accuracy .....	14
Horizontal Alignment .....	15
Point Density and Spatial Distribution.....	16
Data Classification and Editing.....	17
Lidar Qualitative Assessment .....	18
Visual Review .....	19
Data Voids .....	19
Artifacts .....	19
Bridge Removal Artifacts .....	20
Culverts and Bridges .....	21
Dirt Mounds.....	22
Formatting.....	24
Lidar Positional Accuracy.....	24
Background.....	24
Survey Vertical Accuracy Checkpoints .....	25

Vertical Accuracy Test Procedures .....	28
NVA .....	28
VVA .....	28
Vertical Accuracy Results .....	29
Horizontal Accuracy Test Procedures .....	31
Horizontal Accuracy Results .....	32
Breakline Production & Qualitative Assessment Report.....	32
Breakline Production Methodology .....	32
Breakline Qualitative Assessment .....	33
Breakline Checklist .....	34
Data Dictionary .....	35
Horizontal and Vertical Datum.....	35
Coordinate System and Projection.....	35
Inland Streams and Rivers.....	35
Inland Ponds and Lakes.....	37
Beneath Bridge Breaklines.....	38
DEM Production & Qualitative Assessment.....	39
DEM Production Methodology .....	39
DEM Qualitative Assessment .....	40
DEM Vertical Accuracy Results.....	41
DEM Checklist.....	42
Appendix A: Checkpoint Survey Report .....	44
Appendix B: Ground Control Point Survey Report .....	62
Appendix C: Complete List of Delivered Tiles .....	75
Appendix D: GPS Processing.....	91

## Executive Summary

The primary purpose of this project was to develop a consistent and accurate surface elevation dataset derived from high-accuracy Light Detection and Ranging (lidar) technology for the Texas Lavaca Wharton FEMA R6 Project Area.

The lidar data were processed and classified according to project specifications. Detailed breaklines and bare-earth Digital Elevation Models (DEMs) were produced for the project area. Data was formatted according to tiles with each tile covering an area of 1500m by 1500m. A total of 3,501 tiles were produced for the project encompassing an area of approximately 2881 sq. miles.

## THE PROJECT TEAM

Dewberry served as the prime contractor for the project. The LAS classification was sub-contracted to E-terra. In addition to project management, Dewberry was responsible for LAS classification QAQC, all lidar products, breakline production, Digital Elevation Model (DEM) production, and quality assurance.

Dewberry's Gary D. Simpson completed ground surveying for the project and delivered surveyed checkpoints. His task was to acquire surveyed checkpoints for the project to use in independent testing of the vertical accuracy of the lidar-derived surface model. He also verified the GPS base station coordinates used during lidar data acquisition to ensure that the base station coordinates were accurate. Please see Appendix A to view the separate Survey Report that was created for this portion of the project.

Digital Aerial Solutions, LLC completed lidar data acquisition and data calibration for the project area.

## SURVEY AREA

The project area addressed by this report falls within the Texas counties of Colorado, DeWitt, Lavaca, and Wharton.

## DATE OF SURVEY

The lidar aerial acquisition was conducted from January 5th, 2018 thru January 15, 2018.

## COORDINATE REFERENCE SYSTEM

Data produced for the project were delivered in the following reference system.

**Horizontal Datum:** The horizontal datum for the project is North American Datum of 1983 with the 2011 Adjustment (NAD 83 (2011))

**Vertical Datum:** The Vertical datum for the project is North American Vertical Datum of 1988 (NAVD88)

**Coordinate System:** UTM Zone 14

**Units:** Horizontal units are in meters, Vertical units are in meters.

**Geoid Model:** Geoid12B (Geoid 12B was used to convert ellipsoid heights to orthometric heights).

## **LIDAR VERTICAL ACCURACY**

For the Texas Lavaca Wharton FEMA R6 Lidar Project, the tested  $RMSE_z$  of the classified lidar data for checkpoints in non-vegetated terrain equaled **7.6 cm** compared with the 10 cm specification; and the NVA of the classified lidar data computed using  $RMSE_z \times 1.9600$  was equal to **15 cm**, compared with the 19.6 cm specification.

For the Texas Lavaca Wharton FEMA R6 Lidar Project, the tested VVA of the classified lidar data computed using the 95<sup>th</sup> percentile was equal to **20.9 cm**, compared with the 29.4 cm specification.

Additional accuracy information and statistics for the classified lidar data, raw swath data, and bare earth DEM data are found in the following sections of this report.

## **PROJECT DELIVERABLES**

The deliverables for the project are listed below.

1. Classified Point Cloud Data (Tiled)
2. Bare Earth Surface (Raster DEM – IMG Format)
3. Intensity Images (8-bit gray scale, tiled, GeoTIFF format)
4. Breakline Data (File GDB)
5. Independent Survey Checkpoint Data (Report, Photos, & Points)
6. Calibration Points
7. Metadata
8. Project Report (Acquisition, Processing, QC)
9. Project Extents, Including a shapefile derived from the lidar deliverable

### PROJECT TILING FOOTPRINT

Three thousand five-hundred and one (3,501) tiles were delivered for the project. Each tile's extent is 1,500 meters by 1,500 meters (see Appendix C for a complete listing of delivered tiles).




Figure 1 - Project Map

## Lidar Acquisition Report

Dewberry elected to subcontract the lidar acquisition and calibration activities to Digital Aerial Solutions, LLC. Digital Aerial Solutions, LLC was responsible for providing lidar acquisition, calibration and delivery of lidar data files to Dewberry.

Dewberry received calibrated swath data from Digital Aerial Solutions, LLC on February 23, 2018.

### LIDAR ACQUISITION DETAILS

Digital Aerial Solutions, LLC planned 152 passes for the project area as a series of parallel flight lines with cross flightlines for the purposes of quality control. The flight plan included zigzag flight line collection as a result of the inherent IMU drift associated with all IMU systems. In order to reduce any margin for error in the flight plan, Digital Aerial Solutions, LLC followed FEMA's Appendix A "guidelines" for flight planning and, at a minimum, includes the following criteria:

- A digital flight line layout using LEICA MISSION PRO flight design software for direct integration into the aircraft flight navigation system.
- Planned flight lines; flight line numbers; and coverage area.
- Lidar coverage extended by a predetermined margin beyond all project borders to ensure necessary over-edge coverage appropriate for specific task order deliverables.
- Local restrictions related to air space and any controlled areas have been investigated so that required permissions can be obtained in a timely manner with respect to schedule. Additionally, Digital Aerial Solutions, LLC will file our flight plans as required by local Air Traffic Control (ATC) prior to each mission.

Digital Aerial Solutions, LLC monitored weather and atmospheric conditions and conducted lidar missions only when no conditions exist below the sensor that will affect the collection of data. These conditions include leaf-off for hardwoods, no snow, rain, fog, smoke, mist and low clouds. Lidar systems are active sensors, not requiring light, thus missions may be conducted during night hours when weather restrictions do not prevent collection. Digital Aerial Solutions, LLC accesses reliable weather sites and indicators (webcams) to establish the highest probability for successful collection in order to position our sensor to maximize successful data acquisition.

Within 72-hours prior to the planned day(s) of acquisition, Digital Aerial Solutions, LLC closely monitored the weather, checking all sources for forecasts at least twice daily. As soon as weather conditions were conducive to acquisition, our aircraft mobilized to the project site to begin data collection. Once on site, the acquisition team took responsibility for weather analysis.

Digital Aerial Solutions, LLC lidar sensors are calibrated at a designated site located at the Plant City Airport, Florida and are periodically checked and adjusted to minimize corrections at project sites.

### LIDAR SYSTEM PARAMETERS

Digital Aerial Solutions, LLC operated a Cessna 421 (Tail # N112MJ) outfitted with a LEICA ALS80-HP lidar system during the collection of the study area. Table 1 illustrates Digital Aerial Solutions, LLC system parameters for lidar acquisition on this project.

Item	Parameter
System	Leica ALS-80 HP
Altitude (AGL meters)	1701
Approx. Flight Speed (knots)	165
Scanner Pulse Rate (kHz)	314.6
Scan Frequency (hz)	48.8
Pulse Duration of the Scanner (nanoseconds)	0.003
Pulse Width of the Scanner (m)	0.43
Swath width (m)	1409.38
Central Wavelength of the Sensor Laser (nanometers)	1064
Did the Sensor Operate with Multiple Pulses in The Air? (yes/no)	Yes
Beam Divergence (milliradians)	0.15 – 0.25
Nominal Swath Width on the Ground (m)	1409.38
Swath Overlap (%)	11
Total Sensor Scan Angle (degree)	45.0
Computed Down Track spacing (m) per beam	0.87
Computed Cross Track Spacing (m) per beam	1.30
Nominal Pulse Spacing (single swath), (m)	0.62
Nominal Pulse Density (single swath) (ppsm), (m)	2.63
Aggregate NPS (m) (if ANPS was designed to be met through single coverage, ANPS and NPS will be equal)	0.62
Aggregate NPD (m) (if ANPD was designed to be met through single coverage, ANPD and NPD will be equal)	2.63
Maximum Number of Returns per Pulse	8

Table 1: Digital Aerial Solutions, LLC lidar system parameters

## ACQUISITION STATUS REPORT AND FLIGHTLINES

Upon notification to proceed, the flight crew loaded the flight plans and validated the flight parameters. The Acquisition Manager contacted air traffic control and coordinated flight pattern requirements. Lidar acquisition began immediately upon notification that control base stations were in place. During flight operations, the flight crew monitored weather and atmospheric conditions. Lidar missions were flown only when no condition existed below the sensor that would affect the collection of data. The pilot constantly monitored the aircraft course, position, pitch, roll, and yaw of the aircraft. The sensor operator monitored the sensor, the status of PDOPs, and performed the first Q/C review during acquisition. The flight crew constantly reviewed weather and cloud locations. Any flight lines impacted by unfavorable conditions were marked as invalid and re-flown immediately or at an optimal time.

Figure 2 shows the combined trajectory of the flightlines.






Figure 2: Trajectories as flown by Digital Aerial Solutions, LLC

## LIDAR CONTROL

Three established CORS Stations and two newly established base stations were used to control the lidar acquisition for the Texas Lavaca Wharton lidar project area. The coordinates of all used base stations are provided in the table below. All control and calibration points are also provided in shapefile format as part of the final deliverables.

Name	GCS NAD83(2011) UTM 14		Ellipsoid Ht (NAD83(2011), m)	Orthometric Ht (NAVD88 Geoid12B, m)
	Easting X (m)	Northing Y (m)		
KARM	364283.206	4013695.117	2.722	127.349
KARM2	322661.737	4041480.164	2.735	117.290
txcu	358138.885	3943017.011	54.046	148.680
TXHA	321799.245	4004728.178	63.834	95.100
TXWH	277085.155	4013099.338	8.597	85.464

Table 2 – Base stations used to control lidar acquisition

## AIRBORN GPS KINEMATIC

Airborne GPS data was processed using the Inertial Explorer software suite. Flights were flown with a minimum of 6 satellites in view ( $10^\circ$  above the horizon) and with a PDOP of better than 4. Distances from base station to aircraft were kept to a maximum of 55 km.

For all flights, the GPS data can be classified as excellent, with GPS residuals of 3 cm average or better but no larger than 10 cm being recorded.

GPS processing reports for each mission are included in Appendix D.

## GENERATION AND CALIBRATION OF LASER POINTS (RAW DATA)

The initial step of calibration is to verify availability and status of all needed GPS and Laser data against field notes and compile any data if not complete.

Subsequently the mission points are output using Leica CloudPro, initially with default values from Cloudpro or the last mission calibrated for the system. The initial point generation for each mission calibration is verified within Microstation/Terrascan for calibration errors. If a calibration error greater than specification is observed within the mission, the roll, pitch and scanner scale corrections that need to be applied are calculated. The missions with the new calibration values are regenerated and validated internally once again to ensure quality.

Data collected by the lidar unit is reviewed for completeness, acceptable density and to make sure all data is captured without errors or corrupted values. In addition, all GPS, aircraft trajectory, mission information, and ground control files are reviewed and logged into a database.

On a project level, a supplementary coverage check is carried out to ensure no data voids unreported by Field Operations are present.




Figure 3 – Lidar swath output showing complete coverage.

### **BORESIGHT AND RELATIVE ACCURACY**

The initial points for each mission calibration are inspected for flight line errors, flight line overlap, slivers or gaps in the data, point data minimums, or issues with the lidar unit or GPS. Roll, pitch and scanner scale are optimized during the calibration process until the relative accuracy is met.

Relative accuracy and internal quality are checked using at least 3 regularly spaced QC blocks in which points from all lines are loaded and inspected. Vertical differences between ground surfaces of each line are displayed. Color scale is adjusted so that errors greater than the specifications are flagged. Cross sections are visually inspected across each block to validate point to point, flight line to flight line and mission to mission agreement.

For this project the specifications used are as follow:  
Relative accuracy  $\leq 6$  cm maximum difference within individual swaths and  $\leq 8$  cm RMSDz between adjacent and overlapping swaths.




Figure 4 – Profile views showing correct roll and pitch adjustments.




Figure 5 – QC block colored by distance to ensure accuracy at swath edges.

A different set of QC blocks are generated for final review after all transformations have been applied.

## Lidar Processing & Qualitative Assessment

### INITIAL PROCESSING

Once Dewberry receives the calibrated swath data from the acquisition provider, Dewberry performs several validations on the dataset prior to starting full-scale production on the project.

These validations include vertical accuracy of the swath data, inter-swath (between swath) relative accuracy validation, intra-swath (within a single swath) relative accuracy validation, verification of horizontal alignment between swaths, and confirmation of point density and spatial distribution. This initial assessment allows Dewberry to determine if the data are suitable for full-scale production. Addressing issues at this stage allows the data to be corrected while imposing the least disruption possible on the overall production workflow and overall schedule.

### Final Swath Vertical Accuracy Assessment

Once Dewberry received the calibrated swath data from DAS, Dewberry tested the vertical accuracy of the non-vegetated terrain swath data prior to additional processing. Dewberry tested the vertical accuracy of the swath data using the fifty-one non-vegetated (open terrain and urban) independent survey check points. The vertical accuracy is tested by comparing survey checkpoints in non-vegetated terrain to a triangulated irregular network (TIN) that is created from the raw swath points. Only checkpoints in non-vegetated terrain can be tested against raw swath data because the data has not undergone classification techniques to remove vegetation, buildings, and other artifacts from the ground surface. Checkpoints are always compared to interpolated surfaces from the lidar point cloud because it is unlikely that a survey checkpoint will be located at the location of a discrete lidar point. Dewberry typically uses LP360 software to test the swath lidar vertical accuracy, Terrascan software to test the classified lidar vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project. Project specifications require a NVA of 19.6 cm based on the  $RMSE_z (10 \text{ cm}) \times 1.96$ . The dataset for the Texas Lavaca Wharton satisfies this criteria. This raw lidar swath data set was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm  $RMSE_z$  Vertical Accuracy Class. Actual NVA accuracy was found to be  $RMSE_z = 8.3 \text{ cm}$ , equating to  $\pm 16.3 \text{ cm}$  at 95% confidence level. The table below shows all calculated statistics for the raw swath data.

100 % of Totals	# of Points	$RMSE_z$ NVA Spec=0.10 m	NVA – Non-vegetated Vertical Accuracy ( $RMSE_z \times 1.9600$ ) Spec=0.196 m	Mean (m)	Median (m)	Skew	Std Dev (m)	Min (m)	Max (m)
Non-Vegetated Terrain	48	0.083	0.163	0.005	0.001	1.170	0.084	-0.240	0.362

Table 3: NVA at 95% Confidence Level for Raw Swaths

Two checkpoints (NVA-19 & NVA-33) were removed from the raw swath vertical accuracy testing due to their location underneath a power line. Only non-vegetated terrain checkpoints are used to test the raw swath data because the raw swath data has not been classified to remove vegetation, structures, and other above ground features from the ground classification. While NVA-19 & NVA-33 are located in open terrain, the overhead power lines are modeled by the lidar point cloud. These high points caused erroneous high values during the swath vertical accuracy testing so these points were removed from the final calculations. Once the data underwent the classification process, the power lines were removed from the final ground classification and these points could be used in the final vertical accuracy testing for the fully classified lidar data. Table 4, below, provides the coordinates for these checkpoints and the vertical accuracy results from the raw swath data. Table 5, below, provides the usable vertical accuracy results of this checkpoint from the fully classified lidar. The differences in the tables show how above ground features can cause erroneous vertical accuracy results in the raw swath data. Figure 6, below, shows a 3D model of the lidar point cloud and the location of the checkpoint beneath a power line.

Point ID	NAD83(2011) UTM Zone 14N		NAVD88 (Geoid 12B)	Lidar Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
NVA-19	689268.399	3272977.835	108.011	108.837	0.826	0.826
NVA-33	767784.107	3256114.212	40.189	46.137	5.948	5.948

Table 4: Checkpoints removed from raw swath vertical accuracy testing

Point ID	NAD83(2011) UTM Zone 14N		NAVD88 (Geoid 12B)	Lidar Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
NVA-19	689268.399	3272977.835	108.011	107.960	-0.051	0.051
NVA-33	767784.107	3256114.212	40.189	40.210	0.021	0.021

Table 5: Final tested vertical accuracy for NVA-19 & NVA-33 post ground classification




Figure 6 – Open Terrain checkpoints NVA-19 (left) & NVA-33 (right), approximate location shown as red points, are located underneath power line features. These points were removed from raw swath vertical accuracy testing because above ground features, including power lines (gray), have not been separated from the ground classification yet.

### Inter-Swath (Between Swath) Relative Accuracy

Dewberry verified inter-swath or between swath relative accuracy of the dataset by creating Delta-Z (DZ) orthos. According to the SOW, USGS Lidar Base Specifications v1.2, and ASPRS Positional Accuracy Standards for Digital Geospatial Data, 10 cm Vertical Accuracy Class or QL2 data must meet inter-swath relative accuracy of 8 cm RMSDz or less with maximum differences less than 16 cm. These measurements are to be taken in non-vegetated and flat open terrain using single or only returns from all classes. Measurements are calculated in the DZ orthos on 1-meter pixels or cell sizes. Areas in the dataset where overlapping flight lines are within 8 cm of each other within each pixel are colored green, areas in the dataset where overlapping flight lines have elevation differences in each pixel between 8 cm to 16 cm are colored yellow, and areas in the dataset where overlapping flight lines have elevation differences in each pixel

greater than 16 cm are colored red. Pixels that do not contain points from overlapping flight lines are colored according to their intensity values. Areas of vegetation and steep slopes (slopes with 16 cm or more of valid elevation change across 1 linear meter) are expected to appear yellow or red in the DZ orthos. If the project area is heavily vegetated, Dewberry may also create DZ Orthos from the initial ground classification only, while keeping all other parameters consistent. This allows Dewberry to review the ground classification relative accuracy beneath vegetation and to ensure flight line ridges or other issues do not exist in the final classified data.

Flat, open areas are expected to be green in the DZ orthos. Large or continuous sections of yellow or red pixels can indicate the data was not calibrated correctly or that there were issues during acquisition that could affect the usability of the data, especially when these yellow/red sections follow the flight lines and not the terrain or areas of vegetation. The DZ orthos for Texas Lavaca Wharton are shown in the figure below; this project meets inter-swath relative accuracy specifications.




Figure 7– Single return DZ Orthos for the Texas Lava Wharton. Inter-swath relative accuracy passes specifications.

### **Intra-Swath (Within a Single Swath) Relative Accuracy**

Dewberry verifies the intra-swath or within swath relative accuracy by using Quick Terrain Modeler (QTM) scripting and visual reviews. QTM scripting is used to calculate the maximum difference of all points within each 1-meter pixel/cell size of each swath. Dewberry analysts then identify planar surfaces acceptable for repeatability testing and analysts review the QTM results in those areas. According to the SOW, USGS Lidar Base Specifications v1.2, and ASPRS Positional Accuracy Standards for Digital Geospatial Data, 10 cm Vertical Accuracy Class or QL2 data must meet intra-swath relative accuracy of 6 cm maximum difference or less. The image below shows two examples of the intra-swath relative accuracy of Texas Lavaca Wharton; this project meets intra-swath relative accuracy specifications.





Figure 8—Intra-swath relative accuracy. The top image shows the full project area; areas where the maximum difference is  $\leq 6$  cm per pixel within each swath are colored green and areas exceeding 6 cm are colored red. The bottom image is a close-up of a flat area. With the exception of few trees (shown in red as the elevation/height difference in vegetated areas will exceed 6 cm) this open flat area is acceptable for repeatability testing. Intra-swath relative accuracy passes specifications.

### Horizontal Alignment


To ensure horizontal alignment between adjacent or overlapping flight lines, Dewberry uses QTM scripting and visual reviews. QTM scripting is used to create files similar to DZ orthos for each swath but this process highlights planar surfaces, such as roof tops. In particular, horizontal shifts or misalignments between swaths on roof tops and other elevated planar surfaces are highlighted. Visual reviews of these features, including additional profile verifications, are used to confirm the results of this process. The image below shows an example of the horizontal alignment between swaths for Texas Lavaca Wharton; no horizontal alignment issues were identified.



**Figure 9– Horizontal Alignment.** Two separate flight lines differentiated by color (Purple/White) are shown in this profile. There is no visible offset between these two flight lines. No horizontal alignment issues were identified.

### Point Density and Spatial Distribution

The required Aggregate Nominal Point Spacing (ANPS) for this project is no greater than 0.70 meters, which equates to an Aggregate Nominal Point Density (ANPD) of 2 points per square meter or greater. Density calculations were performed using first return data only located in the geometrically usable center portion (typically ~90%) of each swath. By utilizing statistics, the project area was determined to have an ANPS of 0.6 meters or an ANPD of 2.81 points per square meter which satisfies the project requirements. A visual review of a 1-square meter density grid (figure below) shows that most 1-meter cells that do contain 2 points per square meter (green areas). Density passes with no issues.




**Figure 10– 1-square meter density grid.** There are some 1-meter cells that do not contain 2 points per square meter (red areas) due to the irregular spacing of lidar point cloud data. Most 1-square meter



cells contain at least 2 points per square meter (green areas) showing there are no systematic density issues.

The spatial distribution of points must be uniform and free of clustering. This specification is tested by creating a grid with cell sizes equal to the design NPS\*2. ArcGIS tools are then used to calculate the number of first return points of each swath within each grid cell. At least 90% of the cells must contain 1 lidar point, excluding acceptable void areas such as water or low NIR reflectivity features, i.e. some asphalt and roof composition materials. This project passes spatial distribution requirements, as shown in the image below.



**Figure 11– Spatial Distribution.** All cells (2\*NPS cellsize) containing at least one lidar point are colored green. Cells that do not contain a lidar point, including water bodies which are acceptable NoData areas, are colored red. Without removing acceptable NoData areas due to water, 99.4% of cells contain at least one lidar point.

## **DATA CLASSIFICATION AND EDITING**

Once the calibration, absolute swath vertical accuracy, and relative accuracy of the data was confirmed, Dewberry utilized a variety of software suites for data processing. The data was processed using GeoCue and TerraScan software. The initial step is the setup of the GeoCue project, which is done by importing a project defined tile boundary index encompassing the entire project area. The acquired 3D laser point clouds, in LAS binary format, were imported into the GeoCue project and tiled according to the project tile grid. Once tiled, the laser points were classified using a proprietary routine in TerraScan. This routine classifies any obvious low outliers in the dataset to class 7 and high outliers in the dataset to class 18. Points along flight line edges that are geometrically unusable are identified as withheld and classified to a separate class so that they will not be used in the initial ground algorithm. After points that could negatively affect the ground are removed from class 1, the ground layer is extracted from this remaining point cloud. The ground extraction process encompassed in this routine takes place by building an iterative surface model.

This surface model is generated using three main parameters: building size, iteration angle and iteration distance. The initial model is based on low points being selected by a "roaming window" with the assumption that these are the ground points. The size of this roaming window is determined by the building size parameter. The low points are triangulated and the remaining points are evaluated and subsequently added to the model if they meet the iteration angle and distance constraints. This process is repeated until no additional points are added within iterations. A second critical parameter is the maximum terrain angle constraint, which determines the maximum terrain angle allowed within the classification model.

Each tile was then imported into Terrascan and a surface model was created to examine the ground classification. Dewberry analysts visually reviewed the ground surface model and corrected errors in the ground classification such as vegetation, buildings, and bridges that were present following the initial processing conducted by Dewberry. Dewberry analysts employ 3D visualization techniques to view the point cloud at multiple angles and in profile to ensure that non-ground points are removed from the ground classification. Bridge decks are classified to class 17 using bridge breaklines compiled by Dewberry. After the ground classification corrections were completed, the dataset was processed through a water classification routine that utilizes breaklines compiled by Dewberry to automatically classify hydro features. The water classification routine selects ground points within the breakline polygons and automatically classifies them as class 9, water. During this water classification routine, points that are within 1x NPS or less of the hydrographic features are moved to class 10, an ignored ground due to breakline proximity. Overage points are then identified in Terrascan and GeoCue is used to set the overlap bit for the overage points and the withheld bit is set on the withheld points previously identified in Terrascan before the ground classification routine was performed.

The lidar tiles were classified to the following classification schema:

- Class 1 = Unclassified, used for all other features that do not fit into the Classes 2, 7, 9, 10, 17, or 18, including vegetation, buildings, etc.
- Class 2 = Bare-Earth Ground
- Class 7 = Low Noise
- Class 9 = Water, points located within collected breaklines
- Class 10 = Ignored Ground due to breakline proximity
- Class 17 = Bridge Decks
- Class 18 = High Noise

After manual classification, the LAS tiles were peer reviewed and then underwent a final QA/QC. After the final QA/QC and corrections, all headers, appropriate point data records, and variable length records, including spatial reference information, are updated in GeoCue software and then verified using proprietary Dewberry tools.

## Lidar Qualitative Assessment

Dewberry's qualitative assessment utilizes a combination of statistical analysis and interpretative methodology or visualization to assess the quality of the data for a bare-earth digital terrain model (DTM). This includes creating pseudo image products such as lidar orthos produced from the intensity returns, Triangular Irregular Network (TIN)'s, Digital Elevation Models (DEM) and 3-dimensional models as well as reviewing the actual point cloud data. This process looks for anomalies in the data, areas where man-made structures or vegetation points may not have been classified properly to produce a bare-earth model, and other classification errors. This report will present representative examples where the lidar and post processing had issues as well as examples of where the lidar performed well.

## **VISUAL REVIEW**


The following sections describe common types of issues identified in lidar data and the results of the visual review for Texas Lavaca Wharton FEMA R6.

### **Data Voids**

The LAS files are used to produce density grids using the commercial software package QT Modeler (QTM) which creates a 3-dimensional data model derived from Class 2 (ground) points in the LAS files. Grid spacing is based on the project density deliverable requirement for unobscured areas. Acceptable voids (areas with no lidar returns in the LAS files) that are present in the majority of lidar projects include voids caused by bodies of water. No unacceptable voids are present in the Texas Lavaca Wharton FEMA R6 lidar project.

### **Artifacts**


Artifacts are caused by the misclassification of ground points and usually represent vegetation and/or man-made structures. The artifacts identified are usually low lying structures, such as porches or low vegetation used as landscaping in neighborhoods and other developed areas. These low lying features are extremely difficult for the automated algorithms to detect as non-ground and must be removed manually. The vast majority of these features have been removed but a small number of these features are still in the ground classification. The limited numbers of features remaining in the ground are usually 0.3 meters or less above the actual ground surface, and should not negatively impact the usability of the dataset.



**Figure 12 –14RQT2049.** Profile with points colored by class (class 2=orange) is shown in the top view and a TIN of the surface is shown in the bottom view. The arrow identifies low vegetation points. A limited number of these small features are still classified as ground but do not impact the usability of the dataset.

### **Bridge Removal Artifacts**

The DEM surface models are created from TINs or Terrains. TIN and Terrain models create continuous surfaces from the inputs. Because a continuous surface is being created, the TIN or Terrain will use interpolation to continue the surface beneath the bridge where no lidar data was acquired. Locations where bridges were removed will generally contain less detail in the bare-earth surface because these areas are interpolated.



**Figure 13 –14RPT9422.** The DEM in the bottom view shows an area where a bridge has been removed from ground. The surface model must make a continuous model and in order to do so, points are connected through interpolation. This results in less detail where the surface must be interpolated. The profile in the top view shows the lidar points of this particular feature colored by class. All bridge points have been removed from ground (orange) and are classified as bridge deck (green).

### **Culverts and Bridges**

Bridges have been removed from the bare earth surface while culverts remain in the bare earth surface. In instances where it is difficult to determine if the feature is a culvert or bridge, such as with some small bridges, Dewberry erred on assuming they would be culverts especially if they are on secondary or tertiary roads. Below is an example of a culvert that has been left in the ground surface.






Figure 14-14RQT1177. Profile with points colored by class (class 1=gray, class 2=orange) is shown in the top view and the DEM is shown in the bottom view. This culvert remains in the bare earth surface. Bridges have been removed from the bare earth surface and classified to class 17.

### Dirt Mounds

Irregularities in the natural ground exist and may be misinterpreted as artifacts that should be removed. Small hills and dirt mounds are present throughout the project area. These features are correctly included in the ground.





**Figure 15 - 14RQT1449.** Profile with the points colored by class (class 2=orange) is shown in the top view and a DEM of the surface is shown in the bottom view. These features are correctly included in the ground classification.

## FORMATTING

After the final QA/QC is performed and all corrections have been applied to the dataset, all lidar files are updated to the final format requirements and the final formatting, header information, point data records, and variable length records are verified using Dewberry proprietary tools. The table below lists some of the main lidar header fields that are updated and verified.

Classified Lidar Formatting		
Parameter	Requirement	Pass/Fail
LAS Version	1.4	Pass
Point Data Format	Format 6	Pass
Coordinate Reference System	NAD83 (2011) UTM Zone 14, meters and NAVD88 (Geoid 12B), meters in WKT Format	Pass
Global Encoder Bit	Should be set to 17 for Adjusted GPS Time	Pass
Time Stamp	Adjusted GPS Time (unique timestamps)	Pass
System ID	Should be set to the processing system/software and is set to NIIRS10 for GeoCue software	Pass
Multiple Returns	The sensor shall be able to collect multiple returns per pulse and the return numbers are recorded	Pass
Intensity	16 bit intensity values are recorded for each pulse	Pass
Classification	Required Classes include: Class 1: Unclassified Class 2: Ground Class 7: Low Noise Class 9: Water Class 10: Ignored Ground Class 17: Bridge Decks Class 18: High Noise	Pass
Overlap and Withheld Points	Overlap (Overage) and Withheld points are set to the Overlap and Withheld bits	Pass
Scan Angle	Recorded for each pulse	Pass
XYZ Coordinates	Unique Easting, Northing, and Elevation coordinates are recorded for each pulse	Pass

## Lidar Positional Accuracy

### BACKGROUND

Dewberry quantitatively tested the dataset by testing the vertical accuracy of the lidar. The vertical accuracy is tested by comparing the discreet measurement of the survey checkpoints to that of the interpolated value within the three closest lidar points that constitute the vertices of a three-dimensional triangular face of the TIN. Therefore, the end result is that only a small sample of the



lidar data is actually tested. However there is an increased level of confidence with lidar data due to the relative accuracy. This relative accuracy in turn is based on how well one lidar point "fits" in comparison to the next contiguous lidar measurement, and is verified as part of the initial processing. If the relative accuracy of a dataset is within specifications and the dataset passes vertical accuracy requirements at the location of survey checkpoints, the vertical accuracy results can be applied to the whole dataset with high confidence due to the passing relative accuracy. Dewberry typically uses LP360 software to test the swath lidar vertical accuracy, Terrascan software to test the classified lidar vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project.

Dewberry also tests the horizontal accuracy of lidar datasets when checkpoints are photo-identifiable in the intensity imagery. Photo-identifiable checkpoints in intensity imagery typically include checkpoints located at the ends of paint stripes on concrete or asphalt surfaces or checkpoints located at 90 degree corners of different reflectivity, e.g. a sidewalk corner adjoining a grass surface. The XY coordinates of checkpoints, as defined in the intensity imagery, are compared to surveyed XY coordinates for each photo-identifiable checkpoint. These differences are used to compute the tested horizontal accuracy of the lidar. As not all projects contain photo-identifiable checkpoints, the horizontal accuracy of the lidar cannot always be tested.

### **SURVEY VERTICAL ACCURACY CHECKPOINTS**

For the vertical accuracy assessment, eighty five (85) check points were surveyed for the project and are located within bare earth/open terrain, grass/weeds/crops, and forested/fully grown land cover categories. Please see appendix A to view the survey report which details and validates how the survey was completed for this project.

Checkpoints were evenly distributed throughout the project area so as to cover as many flight lines as possible using the "dispersed method" of placement.

All checkpoints surveyed for vertical accuracy testing purposes are listed in the following table.

Point ID	NAD83(2011) UTM Zone 14		NAVD88 (Geoid 12B)
	Easting X (m)	Northing Y (m)	Elevation (m)
NVA-1	679508.526	3209019.230	49.031
NVA-2	684690.845	3217411.015	65.061
NVA-3	679904.384	3226193.947	88.032
NVA-4	695867.892	3222409.481	49.188
NVA-5	706440.247	3227343.898	35.839
NVA-6	696275.778	3235889.508	51.156
NVA-7	681998.274	3235615.213	79.382
NVA-8	679435.832	3240997.352	95.831
NVA-9	677819.999	3256740.045	112.580
NVA-10	690623.817	3245339.967	74.740
NVA-11	705930.952	3236863.476	58.160
NVA-12	714236.826	3236180.880	49.912
NVA-13	723477.567	3240276.702	43.581
NVA-14	710697.182	3246248.202	70.436
NVA-15	698757.092	3258390.930	72.706
NVA-16	688502.170	3259520.656	111.038
NVA-17	679869.190	3266018.738	129.935

NVA-18	679301.628	3273596.756	131.983
NVA-19	689268.399	3272977.835	108.011
NVA-20	708459.866	3267365.596	79.302
NVA-21	714777.740	3255710.275	55.003
NVA-22	731878.814	3245360.223	48.143
NVA-23	745386.411	3235979.289	34.079
NVA-24	752345.190	3223943.314	25.882
NVA-25	763143.572	3210702.820	16.708
NVA-26	771799.931	3217597.316	20.928
NVA-27	777215.583	3228436.316	24.986
NVA-28	788928.893	3235452.029	25.817
NVA-29	796928.500	3241205.727	24.915
NVA-30	779451.106	3247795.443	32.702
NVA-31	763349.261	3234970.039	34.754
NVA-32	757751.017	3244186.712	41.185
NVA-33	767784.107	3256114.212	40.189
NVA-34	779811.688	3262574.141	35.515
NVA-35	783765.159	3270609.075	38.328
NVA-36	769848.701	3272741.639	45.225
NVA-37	759112.145	3256246.564	39.492
NVA-38	743653.087	3251455.733	46.594
NVA-39	726534.891	3255315.997	64.847
NVA-40	725720.916	3264977.491	84.641
NVA-41	740147.189	3262439.123	58.026
NVA-42	760941.986	3265363.071	49.549
NVA-43	758433.112	3275896.602	51.377
NVA-44	748876.174	3274317.282	54.259
NVA-45	738891.665	3268508.392	66.647
NVA-46	732366.026	3278874.396	90.150
NVA-47	724555.459	3271314.670	97.805
NVA-48	710435.391	3276971.428	90.265
NVA-49	715066.459	3286980.232	125.536
NVA-50	702003.475	3271605.934	105.360
VVA-1	802847.235	3238498.104	20.199
VVA-2	787490.027	3233272.980	23.397
VVA-3	771472.355	3225526.490	26.139
VVA-4	755851.743	3221918.531	23.547
VVA-5	753298.004	3234572.731	31.143
VVA-6	771812.756	3242338.307	32.661
VVA-7	777784.221	3253679.701	30.288
VVA-8	775710.453	3267292.839	37.139
VVA-9	765449.556	3258867.016	42.665
VVA-10	752396.425	3247406.020	42.824
VVA-11	738288.500	3235783.389	34.896
VVA-12	737699.842	3251898.241	49.569
VVA-13	748945.402	3259741.715	49.177
VVA-14	759555.009	3268878.379	50.390
VVA-15	766934.649	3277921.802	49.097

VVA-16	743547.500	3279855.116	62.151
VVA-17	736657.473	3261965.472	60.150
VVA-18	731551.214	3279518.806	82.764
VVA-19	715688.489	3280409.673	110.025
VVA-20	717758.136	3267807.457	94.904
VVA-21	725748.923	3258597.231	68.752
VVA-22	723457.323	3245543.720	44.654
VVA-23	713075.952	3239613.097	54.971
VVA-24	711480.820	3259955.963	55.895
VVA-25	701698.999	3274936.867	84.199
VVA-26	688928.981	3277850.294	130.007
VVA-27	684829.564	3269242.058	92.050
VVA-28	694613.773	3261723.981	73.155
VVA-29	699987.856	3254094.625	83.882
VVA-30	701548.808	3228631.722	47.058
VVA-31	690899.175	3225002.014	57.632
VVA-32	683446.962	3232079.431	73.909
VVA-33	685686.044	3249514.052	92.821
VVA-34	673854.980	3249895.490	133.760
VVA-35	674585.338	3265368.255	153.401

Table 6: Texas Lavaca Wharton FEMA R6 surveyed accuracy checkpoints

The figure below shows the location of the QA/QC checkpoints used to test the positional accuracy of the dataset.

Texas Lavaca Wharton FEMA R6 - Accuracy Check Points




Figure 16 – Location of QA/QC Checkpoints

## VERTICAL ACCURACY TEST PROCEDURES

**NVA** (Non-vegetated Vertical Accuracy) is determined with check points located only in non-vegetated terrain, including open terrain (grass, dirt, sand, and/or rocks) and urban areas, where there is a very high probability that the lidar sensor will have detected the bare-earth ground surface and where random errors are expected to follow a normal error distribution. The NVA determines how well the calibrated lidar sensor performed. With a normal error distribution, the vertical accuracy at the 95% confidence level is computed as the vertical root mean square error ( $RMSE_z$ ) of the checkpoints x 1.9600. For the Texas Lavaca Wharton FEMA R6 lidar project, vertical accuracy must be 19.6 cm or less based on an  $RMSE_z$  of 10 cm x 1.9600.

**VVA** (Vegetated Vertical Accuracy) is determined with all checkpoints in vegetated land cover categories, including tall grass, weeds, crops, brush and low trees, and fully forested areas, where there is a possibility that the lidar sensor and post-processing may yield elevation errors that do not follow a normal error distribution. VVA at the 95% confidence level equals the 95<sup>th</sup> percentile error for all checkpoints in all vegetated land cover categories combined. The Texas Lavaca Wharton FEMA R6 Lidar Project VVA standard is 29.4 cm based on the 95<sup>th</sup> percentile. The VVA is accompanied by a listing of the 5% outliers that are larger than the 95<sup>th</sup> percentile used to compute the VVA; these are always the largest outliers that may depart from a normal error distribution. Here, Accuracy<sub>z</sub> differs from VVA because Accuracy<sub>z</sub> assumes elevation errors follow a normal error distribution where RMSE procedures are valid, whereas VVA assumes lidar errors may not follow a normal error distribution in vegetated categories, making the RMSE process invalid.

The relevant testing criteria are summarized in Table 7.

Quantitative Criteria	Measure of Acceptability
Non-Vegetated Vertical Accuracy (NVA) in open terrain and urban land cover categories using $RMSE_z \times 1.9600$	19.6 cm (based on $RMSE_z$ (10 cm) * 1.9600)
Vegetated Vertical Accuracy (VVA) in all vegetated land cover categories combined at the 95% confidence level	29.4 cm (based on combined 95 <sup>th</sup> percentile)

**Table 7 – Acceptance Criteria**

The primary QA/QC vertical accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry’s team surveyed QA/QC vertical checkpoints in accordance with the project’s specifications.
2. Next, Dewberry interpolated the bare-earth lidar DTM to provide the z-value for every checkpoint.
3. Dewberry then computed the associated z-value differences between the interpolated z-value from the lidar data and the ground truth survey checkpoints and computed NVA, VVA, and other statistics.
4. The data were analyzed by Dewberry to assess the accuracy of the data. The review process examined the various accuracy parameters as defined by the scope of work. The overall descriptive statistics of each dataset were computed to assess any trends or anomalies. This report provides tables, graphs and figures to summarize and illustrate data quality.

## VERTICAL ACCURACY RESULTS

The table below summarizes the tested vertical accuracy resulting from a comparison of the surveyed checkpoints to the elevation values present within the fully classified lidar LAS files.

Land Cover Category	# of Points	NVA – Non-vegetated Vertical Accuracy ( $RMSE_z \times 1.9600$ ) Spec=19.6 cm	VVA – Vegetated Vertical Accuracy (95 <sup>th</sup> Percentile) Spec=29.4 cm
NVA	50	15.0	
VVA	35		20.9

**Table 8 – Tested NVA and VVA**

This lidar dataset was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm  $RMSE_z$  Vertical Accuracy Class. Actual NVA accuracy was found to be  $RMSE_z = 7.6$  cm, equating to +/- 15 cm at 95% confidence level. Actual VVA accuracy was found to be +/- 20.9 cm at the 95th percentile.

The figure below illustrates the magnitude of the differences between the QA/QC checkpoints and lidar data. This shows that the majority of lidar elevations were within +/- 25 cm of the checkpoints elevations, but there were one outlier where lidar and checkpoint elevations differed by 2.8 cm.




Figure 17 – Magnitude of elevation discrepancies per land cover category

Table 9 lists the 5% outliers that are larger than the VVA 95<sup>th</sup> percentile.

Point ID	NAD83(2011) UTM Zone 14		NAVD88 (Geoid 12B)	Lidar Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
VVA-28	694613.773	3261723.981	73.155	75.920	2.765	2.765

Table 9 – 5% Outliers

Table 10 provides overall descriptive statistics.

100 % of Totals	# of Points	RMSEz (m) NVA Spec=0.1 m	Mean (m)	Median (m)	Skew	Std Dev (m)	Kurtosis	Min (m)	Max (m)
NVA	50	0.076	0.003	0.000	0.401	0.077	3.691	-0.236	0.282
VVA	35	N/A	0.133	0.050	-0.148	0.465	32.799	-0.159	2.765

Table 10 – Overall Descriptive Statistics

The figure below illustrates a histogram of the associated elevation discrepancies between the QA/QC checkpoints and elevations interpolated from the lidar triangulated irregular network (TIN). The frequency shows the number of discrepancies within each band of elevation differences. Although the discrepancies vary between a low of -0.236 meters and a high of +0.282 meters, the histogram shows that the majority of the discrepancies are skewed on the positive side. The vast majority of points are within the ranges of -0.12 meters to +0.12 meters.




Figure 18 – Histogram of Elevation Discrepancies with errors in meters

**Based on the vertical accuracy testing conducted by Dewberry, the lidar dataset for the USGS Texas Lavaca Wharton FEMA R6 Lidar Project satisfies the project’s pre-defined vertical accuracy criteria.**

### **HORIZONTAL ACCURACY TEST PROCEDURES**

Horizontal accuracy testing requires well-defined checkpoints that can be identified in the dataset. Elevation datasets, including lidar datasets, do not always contain well-defined checkpoints suitable for horizontal accuracy assessment. However, the ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) recommends at least half of the NVA vertical check points should be located at the ends of paint stripes or other point features visible on the lidar intensity image, allowing them to double as horizontal check points.

Dewberry reviews all NVA checkpoints to determine which, if any, of these checkpoints are located on photo-identifiable features in the intensity imagery. This subset of checkpoints are then used for horizontal accuracy testing.

The primary QA/QC horizontal accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry’s team surveyed QA/QC vertical checkpoints in accordance with the project’s specifications and tried to locate half of the NVA checkpoints on features photo-identifiable in the intensity imagery.
2. Next, Dewberry identified the well-defined features in the intensity imagery.
3. Dewberry then computed the associated xy-value differences between the coordinates of the well-defined feature in the lidar intensity imagery and the ground truth survey checkpoints.
4. The data were analyzed by Dewberry to assess the accuracy of the data. Horizontal accuracy was assessed using NSSDA methodology where horizontal accuracy is calculated at the 95% confidence level. This report provides the results of the horizontal accuracy testing.

### HORIZONTAL ACCURACY RESULTS

Thirteen checkpoints were determined to be photo-identifiable in the intensity imagery and were used to test the horizontal accuracy of the lidar dataset. As only thirteen (13) checkpoints were photo-identifiable, the results are not statistically significant enough to report as a final tested value, but the results of the testing are still shown in the Table below.

Using NSSDA methodology (endorsed by the ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014)), horizontal accuracy at the 95% confidence level (called ACCURACY<sub>r</sub>) is computed by the formula  $RMSE_r * 1.7308$  or  $RMSE_x * 2.448$ .

No horizontal accuracy requirements or thresholds were provided for this project. However, lidar datasets are generally calibrated by methods designed to ensure a horizontal accuracy of 1 meter or less at the 95% confidence level.

# of Points	RMSE <sub>x</sub> (Target=41 cm)	RMSE <sub>y</sub> (Target=41 cm)	RMSE <sub>r</sub> (Target=58 cm)	ACCURACY <sub>r</sub> (RMSE <sub>r</sub> x 1.7308) Target=100 cm
4	45.4	32.3	55.7	96.5

Table 11 - Tested horizontal accuracy at the 95% confidence level

This data set was produced to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 41 cm RMSE<sub>x</sub>/RMSE<sub>y</sub> Horizontal Accuracy Class which equates to Positional Horizontal Accuracy = +/- 1 meter at a 95% confidence level. Four (4) checkpoints were photo-identifiable but do not produce a statistically significant tested horizontal accuracy value. Using this small sample set of photo-identifiable checkpoints, positional accuracy of this dataset was found to be RMSE<sub>x</sub> = 45.4 cm and RMSE<sub>y</sub> = 32.3 cm which equates to +/- 96.5 cm at 95% confidence level. While not statistically significant, the results of the small sample set of checkpoints are within the produced to meet horizontal accuracy.

## Breakline Production & Qualitative Assessment Report

### BREAKLINE PRODUCTION METHODOLOGY

Dewberry used GeoCue software to develop lidar stereo models of the project area so the lidar derived data could be viewed in 3-D stereo using Socet Set softcopy photogrammetric software. Using lidargrammetry procedures with lidar intensity imagery, Dewberry used the stereo models



to stereo-compile the two types of hydrographic breaklines in accordance with the project's Data Dictionary.

All drainage breaklines are monotonically enforced to show downhill flow. Water bodies are at a constant elevation where the lowest elevation of the water body has been applied to the entire water body.

## **BREAKLINE QUALITATIVE ASSESSMENT**

Dewberry completed breakline qualitative assessments according to a defined workflow. The following workflow diagram represents the steps taken by Dewberry to provide a thorough qualitative assessment of the breakline data.

Completeness and horizontal placement is verified through visual reviews against lidar intensity imagery. Automated checks are applied on all breakline features to validate topology, including the 3D connectivity of features, enforced monotonicity on linear hydrographic breaklines, and flatness on water bodies.

The next step is to compare the elevation of the breakline vertices against the ground elevation extracted from the ESRI Terrain built from the lidar ground points, keeping in mind that a discrepancy is expected because of the hydro-enforcement applied to the breaklines and because of the interpolated imagery used to acquire the breaklines. A given tolerance is used to validate if the elevations differ too much from the lidar.

After all corrections and edits to the breakline features, the breaklines are imported into the final GDB and verified for correct formatting.

## Elevation Data Processing-Breaklines




Figure 19-Breakline QA/QC workflow

### BREAKLINE CHECKLIST

The following table represents a portion of the high-level steps in Dewberry’s Production and QA/QC checklist that were performed for this project.

Pass/Fail	Validation Step
Pass	Use lidar-derived data, which may include intensity imagery, stereo pairs, bare earth ground models, density models, slope models, and terrains, to collect breaklines according to project specifications.
Pass	In areas of heavy vegetation or where the exact shoreline is hard to delineate, it is better to err on placing the breakline <i>slightly</i> inside or seaward of the shoreline (breakline can be inside shoreline by 1x-2x NPS).
Pass	After each producer finishes breakline collection for a block, each producer must perform a completeness check, breakline variance check, and all automated checks on their block before calling that block complete and ready for the final merge and QC
Pass	After breaklines are completed for production blocks, all production blocks should be merged together and completeness and automated checks should be performed on the final, merged GDB. Ensure correct snapping-horizontal (x,y) and vertical (z)-between all production blocks.

Pass	Check entire dataset for missing features that were not captured, but should be to meet baseline specifications or for consistency. Features should be collected consistently across tile bounds. Check that the horizontal placement of breaklines is correct. Breaklines should be compared to full point cloud intensity imagery and terrains
Pass	Breaklines are correctly edge-matched to adjoining datasets in completion, coding, and horizontal placement.
Pass	Using a terrain created from lidar ground (all ground including 2, 8, and 10) and water points (class 9), compare breakline Z values to interpolated lidar elevations.
Pass	Perform all Topology and Data Integrity Checks
Pass	Perform hydro-flattening and hydro-enforcement checks including monotonicity and flatness from bank to bank on linear hydrographic features and flatness of water bodies. Tidal waters should preserve as much ground as possible and can include variations or be non-monotonic.

Table 12-A subset of the high-level steps from Dewberry’s Production and QA/QC checklist performed for this project.

## DATA DICTIONARY

The following data dictionary was used for this project.

### Horizontal and Vertical Datum

The horizontal datum shall be North American Datum of 1983(2011), Units in Meters. The vertical datum shall be referenced to the North American Vertical Datum of 1988 (NAVD 88), Units in Meters. Geoid12B shall be used to convert ellipsoidal heights to orthometric heights.

### Coordinate System and Projection

All data shall be projected to UTM Zone 14, Horizontal Units in Meters and Vertical Units in Meters.

### Inland Streams and Rivers

**Feature Dataset:** BREAKLINES  
**Feature Type:** Polygon  
**Contains Z Values:** Yes  
**XY Resolution:** Accept Default Setting  
**XY Tolerance:** 0.003

**Feature Class:** STREAMS\_AND\_RIVERS  
**Contains M Values:** No  
**Annotation Subclass:** None  
**Z Resolution:** Accept Default Setting  
**Z Tolerance:** 0.001

### Description

This polygon feature class will depict linear hydrographic features with a width greater than 100 feet.

### Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

### Feature Definition

Description	Definition	Capture Rules
Streams and Rivers	Linear hydrographic features such as streams, rivers, canals, etc. with an average width greater than 100 feet. In the case	Capture features showing dual line (one on each side of the feature). Average width shall be greater than 100 feet to show as a double line. Each vertex placed should maintain vertical integrity. Generally both banks shall be collected to show

	<p>of embankments, if the feature forms a natural dual line channel, then capture it consistent with the capture rules. Other natural or manmade embankments will not qualify for this project.</p>	<p>consistent downhill flow. There are exceptions to this rule where a small branch or offshoot of the stream or river is present.</p> <p>The banks of the stream must be captured at the same elevation to ensure flatness of the water feature. If the elevation of the banks appears to be different see the task manager or PM for further guidance.</p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding lidar points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>These instructions are only for docks or piers that follow the coastline or water's edge, not for docks or piers that extend perpendicular from the land into the water. If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water's edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p> <p>Every effort should be made to avoid breaking a stream or river into segments.</p> <p>Dual line features shall break at road crossings (culverts). In areas where a bridge is present the dual line feature shall continue through the bridge.</p> <p>Islands: The double line stream shall be captured around an island if the island is greater than 1 acre. In this case a segmented polygon shall be used around the island in order to allow for the island feature to remain as a "hole" in the feature.</p>
--	---	--

## Inland Ponds and Lakes

**Feature Dataset:** BREAKLINES  
**Feature Type:** Polygon  
**Contains Z Values:** Yes  
**XY Resolution:** Accept Default Setting  
**XY Tolerance:** 0.003

**Feature Class:** PONDS\_AND\_LAKES  
**Contains M Values:** No  
**Annotation Subclass:** None  
**Z Resolution:** Accept Default Setting  
**Z Tolerance:** 0.001

### Description

This polygon feature class will depict closed water body features that are at a constant elevation.

### Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

### Feature Definition

Description	Definition	Capture Rules
Ponds and Lakes	<p>Land/Water boundaries of constant elevation water bodies such as lakes, reservoirs, ponds, etc. Features shall be defined as closed polygons and contain an elevation value that reflects the best estimate of the water elevation at the time of data capture. Water body features will be captured for features 2 acres in size or greater.</p> <p>“Donuts” will exist where there are islands within a closed water body feature.</p>	<p>Water bodies shall be captured as closed polygons with the water feature to the right. <u>The compiler shall take care to ensure that the z-value remains consistent for all vertices placed on the water body.</u></p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding lidar points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>An Island within a Closed Water Body Feature that is 1 acre in size or greater will also have a “donut polygon” compiled.</p> <p>These instructions are only for docks or piers that follow the coastline or water’s edge, not for docks or piers that extend perpendicular from the land into the water. If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water’s edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p>

## Beneath Bridge Breaklines

**Feature Dataset:** BREAKLINES  
**Feature Type:** Polyline  
**Contains Z Values:** Yes  
**XY Resolution:** Accept Default Setting  
**XY Tolerance:** 0.003

**Feature Class:** Bridge\_Breaklines  
**Contains M Values:** No  
**Annotation Subclass:** None  
**Z Resolution:** Accept Default Setting  
**Z Tolerance:** 0.001

### Description

This polyline feature class is used to enforce terrain beneath bridge decks where ground data may not have been acquired. Enforcing the terrain beneath bridge decks prevents bridge saddles.

### Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software

### Feature Definition

Description	Definition	Capture Rules
Bridge Breaklines	Bridge Breaklines should be used where necessary to enforce terrain beneath bridge decks and to prevent bridge saddles in the bare earth DEMs.	<p>Bridge breaklines should be collected beneath bridges where bridge saddles exist or are likely to exist in the bare earth DEMs.</p> <p>Bridge breaklines should be collected perpendicular to the bridge deck so that the endpoints are on either side of the bridge deck. Typically two bridge breaklines are collected per bridge deck, one at either end of the bridge deck to enforce the terrain under the full bridge deck.</p> <p>The endpoints of the bridge breaklines will match the elevation of the ground at their xy position to enforce the ground/bare earth elevations beneath the bridge deck and prevent bridge saddles from forming.</p>

## **DEM Production & Qualitative Assessment**

### **DEM PRODUCTION METHODOLOGY**

Dewberry utilized ESRI software and Global Mapper for the DEM production and QC process. ArcGIS software is used to generate the products and the QC is performed in both ArcGIS and Global Mapper. The figure below shows the entire process necessary for bare earth DEM production, starting from the lidar swath processing.

The final bare-earth lidar points are used to create a terrain. The final 3D breaklines collected for the project are also enforced in the terrain. The terrain is then converted to raster format using linear interpolation. For most projects, a single terrain/DEM can be created for the whole project. For very large projects, multiple terrains/DEMs may be created. The DEM(s) is reviewed for any issues requiring corrections, including remaining lidar mis-classifications, erroneous breakline elevations, poor hydro-flattening or hydro-enforcement, and processing artifacts. After corrections are applied, the DEM(s) is then split into individual tiles following the project tiling scheme. The tiles are verified for final formatting and then loaded into Global Mapper to ensure no missing or corrupt tiles and to ensure seamlessness across tile boundaries.



Figure 20-DEM Production Workflow

## DEM QUALITATIVE ASSESSMENT

Dewberry performed a comprehensive qualitative assessment of the bare earth DEM deliverables to ensure that all tiled DEM products were delivered with the proper extents, were free of processing artifacts, and contained the proper referencing information. This process was performed in ArcGIS software with the use of a tool set Dewberry has developed to verify that the



raster extents match those of the tile grid and contain the correct projection information. The DEM data was reviewed at a scale of 1:5000 to review for artifacts caused by the DEM generation process and to review the hydro-flattened features. To perform this review Dewberry creates HillShade models and overlays a partially transparent colored elevation model to review for these issues. All corrections are completed using Dewberry's proprietary correction workflow. Upon completion of the corrections, the DEM data is loaded into Global Mapper for its second review and to verify corrections. Once the DEMs are tiled out, the final tiles are again loaded into Global Mapper to ensure coverage, extents, and that the final tiles are seamless.

The image below show an example of a bare earth DEM.




Figure 21-Tile 14RQT0580. Bare earth DEM.

## DEM VERTICAL ACCURACY RESULTS

The same 85 checkpoints that were used to test the vertical accuracy of the lidar were used to validate the vertical accuracy of the final DEM products as well. Accuracy results may vary between the source lidar and final DEM deliverable. DEMs are created by averaging several lidar points within each pixel which may result in slightly different elevation values at each survey checkpoint when compared to the source LAS, which does not average several lidar points together but may interpolate (linearly) between two or three points to derive an elevation value. The vertical accuracy of the DEM is tested by extracting the elevation of the pixel that contains the x/y coordinates of the checkpoint and comparing these DEM elevations to the surveyed elevations. Dewberry typically uses LP360 software to test the swath lidar vertical accuracy, Terrascan software to test the classified lidar vertical accuracy, and Esri ArcMap to test the DEM vertical accuracy so that three different software programs are used to validate the vertical accuracy for each project.

Table 13 summarizes the tested vertical accuracy results from a comparison of the surveyed checkpoints to the elevation values present within the final DEM dataset.

Land Cover Category	# of Points	NVA – Non-vegetated Vertical Accuracy (RMSE <sub>z</sub> x 1.9600) Spec=19.6 cm	VVA – Vegetated Vertical Accuracy (95th Percentile) Spec=29.4 cm
NVA	50	14.7	
VVA	35		19.5

Table 13 – DEM tested NVA and VVA

This DEM dataset was tested to meet ASPRS Positional Accuracy Standards for Digital Geospatial Data (2014) for a 10 cm RMSE<sub>z</sub> Vertical Accuracy Class. Actual NVA accuracy was found to be RMSE<sub>z</sub> =5 cm, equating to +/- 10 cm at 95% confidence level. Actual VVA accuracy was found to be +/- 13 cm at the 95th percentile.

Table 14 lists the 5% outliers that are larger than the VVA 95<sup>th</sup> percentile.

Point ID	NAD83(2011) UTM Zone 14		NAVD88 (Geoid 12B)	DEM Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
VVA-2	3233272.980	787490.027	23.397	23.615	0.218	0.218
VVA-28	3261723.981	694613.773	73.155	75.922	2.767	2.767

Table 14 – 5% Outliers

Table 15 provides overall descriptive statistics.

100 % of Totals	# of Points	RMSE <sub>z</sub> (m) NVA Spec=0.1 m	Mean (m)	Median (m)	Skew	Std Dev (m)	Kurtosis	Min (m)	Max (m)
NVA	50	0.075	0.002	0.002	0.738	0.076	4.737	-0.223	0.299
VVA	35	N/A	0.131	0.052	5.656	0.465	32.919	-0.176	2.767

Table 15 – Overall Descriptive Statistics

**Based on the vertical accuracy testing conducted by Dewberry, the DEM dataset for the Texas Lavaca Wharton FEMA R6 Lidar Project satisfies the project’s pre-defined vertical accuracy criteria.**

### DEM CHECKLIST

The following table represents a portion of the high-level steps in Dewberry’s bare earth DEM Production and QA/QC checklist that were performed for this project.

Pass/Fail	Validation Step
Pass	Masspoints (LAS to multipoint) are created from ground points only (class 2 and class 8 if model key points created, but no class 10 ignored ground points or class 9 water points)
Pass	Create a terrain for each production block using the final bare earth lidar points and final breaklines.
Pass	Convert terrains to rasters using project specifications for grid type, formatting, and cell size
Pass	Create hillshades for all DEMs
Pass	Manually review bare-earth DEMs in ArcMap with hillshades to check for issues
Pass	DEM should be hydro-flattened or hydro-enforced as required by project specifications
Pass	DEM should be seamless across tile boundaries

Pass	Water should be flowing downhill without excessive water artifacts present
Pass	Water features should NOT be floating above surrounding
Pass	Bridges should NOT be present in bare-earth DEMs.
Pass	Any remaining bridge saddles where below bridge breaklines were not used need to be fixed by adding below bridge breaklines and re-processing.
Pass	All qualitative issues present in the DEMs as a result of lidar processing and editing issues must be marked for corrections in the lidar. These DEMs will need to be recreated after the lidar has been corrected.
Pass	Calculate DEM Vertical Accuracy including NVA, VVA, and other statistics
Pass	Split the DEMs into tiles according to the project tiling scheme
Pass	Verify all properties of the tiled DEMs, including coordinate reference system information, cell size, cell extents, and that compression has not been applied to the tiled DEMs
Pass	Load all tiled DEMs into Global Mapper to verify complete coverage to the (buffered) project boundary and that no tiles are corrupt.

**Table 16-A subset of the high-level steps from Dewberry’s bare earth DEM Production and QA/QC checklist performed for this project.**

## **Appendix A: Checkpoint Survey Report**

### **Check Point Survey Report**

**“Texas Lavaca-Wharton FEMA Region 6 LiDAR”  
USGS Contract: G16PC00020 Task Order  
Number: G17PC00014**

**Prepared for:  
*United States Geological Survey (USGS)***

Prepared By:  
**Dewberry Consultants LLC**  
10003 Derekwood Lane, Suite 204  
Lanham, Maryland, 20706  
Phone (301)364-1855 Fax (301)731-0188

## TABLE OF CONTENTS

□	Introduction	
	1.1 Project Summary .....	3
	1.2 Points of Contact(s).....	3
	1.3 Project Area .....	4
2.	Project Details	
	2.1 Survey Equipment .....	5
	2.2 Survey Point Details .....	5
	2.3 Network Design .....	5
	2.4 Field Survey Procedures and Analysis .....	6-7
	2.5 Adjustment .....	8
	2.6 Data Processing Procedures .....	8
3.	Final Coordinates .....	9-11
4.	GPS Observation & Re-Observation Schedule .....	12-14
5.	Point Comparison Report .....	15-16
6.	Deliverables .....	Sent via Electronic Transfer
	Including: a) Point Documentation Report & Photos of Survey Points	
	b) Final Coordinate List in Excel Format	
	c) NGS Data Sheets for Project Controls	

## 1. INTRODUCTION

---

### 1.1 *Project Summary*

Dewberry Consultants LLC is under contract to the United States Geological Survey to provide 85 Check Points in the State of Texas. Under the above referenced USGS Task Order, Dewberry is tasked to complete the quality assurance of LiDAR products. As part of this work Dewberry staff will complete Check Point surveys that will be used to evaluate vertical and horizontal accuracy. The ground survey was conducted January 8 thru January 11, 2017.

Existing NGS Control Points were located and surveyed to check the accuracy of the RTK/GPS survey equipment with the results shown in Section 2.4 of this Report.

As an internal QA/QC procedure and to verify that the Check Points meet the 95% confidence level approximately 50% of the points were re-observed and are shown in Section 5 of this report.

Final horizontal coordinates are referenced to UTM, Zone 14, NAD83 (2011) in meters. Final Vertical elevations are referenced to NAVD88 in meters using Geoid model 2012B (Geoid12B).


### 1.2 *Points of Contact*

Questions regarding the technical aspects of this report should be addressed to:

#### **Dewberry Consultants LLC**

Gary D. Simpson, L.S.  
Senior Associate  
10003 Derekwood Lane  
Suite 204  
Lanham, Maryland 20706  
(301) 364-1855 direct  
(301) 731-0188 fax

### 1.3 Project Area



## **PROJECT DETAILS**

---

### **2.1 Survey Equipment**

In performing the GPS observations Trimble R-10 GNSS receiver/antenna attached to a two meter fixed height pole with a Trimble TSC3 Data Collector to collect GPS raw data were used to perform the field surveys.

### **2.2 Survey Point Detail**

The 85 LiDAR Check Points were well distributed throughout the project area.

A sketch was made for each location and a nail was set at the point where possible or at an identifiable point. The Check Point locations are detailed on the “Check Point Documentation Report” sheets attached to this report.

### **2.3 Network Design**

The GPS survey performed by Dewberry offices located in Lanham, Maryland and Charleston, West Virginia and was tied to a Real Time Network operated by the TXDOT RTN. The network is a series of “real-time” continuously operating, high precision GPS reference stations. All of the reference stations have been linked together using Trimble GPSNet software, creating a Virtual Reference Station System (VRS).

The Trimble NetR5 Reference Station is a multi-channel, multi-frequency GNSS (Global Navigation Satellite System) receiver designed for use as a stand-alone reference station or as part of a GNSS infrastructure solution. Trimble R-Track technology in the NetR5 receiver supports the modernized GPS L2C and L5 signals as well as GLONASS L1/L2 signals.



## 2.4 Field Survey Procedures and Analysis

Dewberry field surveyors used Trimble R-10 GNSS receivers, which is a geodetic quality dual frequency GPS receiver, to collect data at each surveyed location.

All locations were occupied once with approximately 50% of the locations being re-observed. All re-observations matched the initially derived station positions within the allowable tolerance of  $\pm 5\text{cm}$  or within the 95% confidence level. Each occupation which utilized the VRS network was occupied for approximately three (3) minutes in duration and measured to 180 epochs.

Each occupation which utilized OPUS (if used) was occupied between 20 and 30 minutes.

Field GPS observations are detailed on the “Check Point Documentation Reports” submitted as part of this report.

Six (6) existing NGS monument listed in the NSRS database were located as an additional QA/QC method to check the horizontal and vertical accuracy of the VRS network as well as being the primary project control monuments designated as AX0131, AX2610, AX0107, CR1356, BZ1450 and BZ0061. The results are as follows:


PT. #	Observed Values			Data Sheet Values			$\Delta X$	$\Delta Y$	$\Delta Z$
	NORTHIN G	EASTING	ELEVS.	NORTHING	EASTING	ELEVS.			
CALPORT**	3378380.696	720142.292	118.154	3,378,380.678	720,142.269	118.360	0.018	0.023	N/A
MEXPORT**	3503174.163	735740.617	163.366	3,503,174.147	735,740.601	163.450	0.016	0.016	N/A
A 937*	3519055.737	744698.500	128.029	N/A	N/A	127.977	N/A	N/A	0.050
YOAKUM SW BASE**	3244673.301	680118.205	110.623	3,244,673.302	680,118.189	110.700	-0.001	0.016	N/A
LAKE	3280376.188	754359.115	62.738	3,280,376.190	754,359.223	62.750	-0.002	-0.008	-0.012
BERNARD 2*	3269041.251	784052.777	36.676	N/A	N/A	36.650	N/A	N/A	0.026

(\*) Indicates a vertical NGS Mark (\*\*)

Indicates a horizontal NGS Mark

The above results indicate that the VRS network is providing positional values within the 5cm parameters for this survey.

### NGS Monuments



## **2.5 Adjustment**

The survey data was collected using Virtual Reference Stations (VRS) methodology within a Virtual Reference System (VRS).

The system is designed to provide a true Network RTK performance, the RTKNet software enables high-accuracy positioning in real time across a geographic region. The RTKNet software package uses real-time data streams from the TXDOT RTN system user and generates correction models for high-accuracy RTK GPS corrections throughout the network. Therefore, corrections were applied to the points as they were being collected, thus negating the need for a post process adjustment.

## **2.6 Data Processing Procedures**

After field data is collected the information is downloaded from the data collectors into the office software. The Software program used is called TBC or Trimble Business Center.

Downloaded data is run through the TBC program to obtain the following reports; points report, point comparison report and a point detail report. The reports are reviewed for point accuracy and precision.

After review of the point data an “ASCII” or “txt” file which is the industry standard is created. Point files are loaded into our CADD program (Carlson Survey 2014) to make a visual check of the point data (Pt. #, Coordinates, Elev. and Description). The data can now be imported into the final product.

### 3. FINAL COORDINATES

UTM Zone 14, NAD83 (2011), NAVD88			
POINT ID	NORTHING (m)	EASTING (m)	ELEV. (m)
NVA			
NVA-1	3209019.230	679508.526	49.031
NVA-2	3217411.015	684690.845	65.061
NVA-3	3226193.947	679904.384	88.032
NVA-4	3222409.481	695867.892	49.188
NVA-5	3227343.898	706440.247	35.839
NVA-6	3235889.508	696275.778	51.156
NVA-7	3235615.213	681998.274	79.382
NVA-8	3240997.352	679435.832	95.831
NVA-9	3256740.045	677819.999	112.580
NVA-10	3245339.967	690623.817	74.740
NVA-11	3236863.476	705930.952	58.160
NVA-12	3236180.880	714236.826	49.912
NVA-13	3240276.702	723477.567	43.581
NVA-14	3246248.202	710697.182	70.436
NVA-15	3258390.930	698757.092	72.706
NVA-16	3259520.656	688502.170	111.038
NVA-17	3266018.738	679869.190	129.935
NVA-18	3273596.756	679301.628	131.983
NVA-19	3272977.835	689268.399	108.011
NVA-20	3267365.596	708459.866	79.302
NVA-21	3255710.275	714777.740	55.003

<b>NVA-22</b>	<b>3245360.22 3</b>	<b>731878.814</b>	<b>48.143</b>
<b>NVA-23</b>	<b>3235979.28 9</b>	<b>745386.411</b>	<b>34.079</b>
<b>NVA-23</b>	<b>3235979.28 9</b>	<b>745386.411</b>	<b>34.079</b>
<b>NVA-24</b>	<b>3223943.31 4</b>	<b>752345.190</b>	<b>25.882</b>
<b>NVA-25</b>	<b>3210702.82 0</b>	<b>763143.572</b>	<b>16.708</b>
<b>NVA-26</b>	<b>3217597.316</b>	<b>771799.931</b>	<b>20.928</b>
<b>NVA-27</b>	<b>3228436.31 6</b>	<b>777215.583</b>	<b>24.986</b>
<b>NVA-28</b>	<b>3235452.02 9</b>	<b>788928.893</b>	<b>25.817</b>
<b>NVA-29</b>	<b>3241205.72 7</b>	<b>796928.500</b>	<b>24.915</b>
<b>NVA-30</b>	<b>3247795.44 3</b>	<b>779451.106</b>	<b>32.702</b>
<b>NVA-30</b>	<b>3247795.44 3</b>	<b>779451.106</b>	<b>32.702</b>
<b>NVA-31</b>	<b>3234970.03 9</b>	<b>763349.261</b>	<b>34.754</b>
<b>NVA-32</b>	<b>3244186.71 2</b>	<b>757751.017</b>	<b>41.185</b>
<b>NVA-32</b>	<b>3244186.71 2</b>	<b>757751.017</b>	<b>41.185</b>
<b>NVA-33</b>	<b>3256114.212</b>	<b>767784.107</b>	<b>40.189</b>

---

Check Point Report – Texas Lavaca-Wharton FEMA Region 6 LiDAR - 50080904

<b>NVA-34</b>	<b>3262574.141</b>	<b>779811.688</b>	<b>35.515</b>
<b>NVA-35</b>	<b>3270609.075</b>	<b>783765.159</b>	<b>38.328</b>
<b>NVA-36</b>	<b>3272741.639</b>	<b>769848.701</b>	<b>45.225</b>
<b>NVA-37</b>	<b>3256246.564</b>	<b>759112.145</b>	<b>39.492</b>
<b>NVA-38</b>	<b>3251455.733</b>	<b>743653.087</b>	<b>46.594</b>
<b>NVA-39</b>	<b>3255315.997</b>	<b>726534.891</b>	<b>64.847</b>
<b>NVA-40</b>	<b>3264977.491</b>	<b>725720.916</b>	<b>84.641</b>
<b>NVA-41</b>	<b>3262439.123</b>	<b>740147.189</b>	<b>58.026</b>
<b>NVA-42</b>	<b>3265363.071</b>	<b>760941.986</b>	<b>49.549</b>
<b>NVA-43</b>	<b>3275896.602</b>	<b>758433.112</b>	<b>51.377</b>
<b>NVA-44</b>	<b>3274317.282</b>	<b>748876.174</b>	<b>54.259</b>
<b>NVA-45</b>	<b>3268508.392</b>	<b>738891.665</b>	<b>66.647</b>
<b>NVA-46</b>	<b>3278874.396</b>	<b>732366.026</b>	<b>90.150</b>
<b>NVA-47</b>	<b>3271314.670</b>	<b>724555.459</b>	<b>97.805</b>
<b>NVA-48</b>	<b>3276971.428</b>	<b>710435.391</b>	<b>90.265</b>
<b>NVA-49</b>	<b>3286980.232</b>	<b>715066.459</b>	<b>125.536</b>
<b>NVA-50</b>	<b>3271605.934</b>	<b>702003.475</b>	<b>105.360</b>
<b>VVA</b>			
<b>VVA-1</b>	<b>3238498.104</b>	<b>802847.235</b>	<b>20.199</b>
<b>VVA-2</b>	<b>3233272.980</b>	<b>787490.027</b>	<b>23.397</b>
<b>VVA-3</b>	<b>3225526.490</b>	<b>771472.355</b>	<b>26.139</b>
<b>VVA-4</b>	<b>3221918.531</b>	<b>755851.743</b>	<b>23.547</b>
<b>VVA-5</b>	<b>3234572.731</b>	<b>753298.004</b>	<b>31.143</b>
<b>VVA-6</b>	<b>3242338.307</b>	<b>771812.756</b>	<b>32.661</b>
<b>VVA-7</b>	<b>3253679.701</b>	<b>777784.221</b>	<b>30.288</b>
<b>VVA-8</b>	<b>3267292.839</b>	<b>775710.453</b>	<b>37.139</b>
<b>VVA-9</b>	<b>3258867.016</b>	<b>765449.556</b>	<b>42.665</b>
<b>VVA-10</b>	<b>3247406.020</b>	<b>752396.425</b>	<b>42.824</b>
<b>VVA-11</b>	<b>3235783.389</b>	<b>738288.500</b>	<b>34.896</b>
<b>VVA-12</b>	<b>3251898.241</b>	<b>737699.842</b>	<b>49.569</b>
<b>VVA-13</b>	<b>3259741.715</b>	<b>748945.402</b>	<b>49.177</b>
<b>VVA-14</b>	<b>3268878.379</b>	<b>759555.009</b>	<b>50.390</b>
<b>VVA-15</b>	<b>3277921.802</b>	<b>766934.649</b>	<b>49.097</b>
<b>VVA-16</b>	<b>3279855.116</b>	<b>743547.500</b>	<b>62.151</b>
<b>VVA-17</b>	<b>3261965.472</b>	<b>736657.473</b>	<b>60.150</b>
<b>VVA-18</b>	<b>3279518.806</b>	<b>731551.214</b>	<b>82.764</b>
<b>VVA-19</b>	<b>3280409.673</b>	<b>715688.489</b>	<b>110.025</b>
<b>VVA-20</b>	<b>3267807.457</b>	<b>717758.136</b>	<b>94.904</b>
<b>VVA-21</b>	<b>3258597.231</b>	<b>725748.923</b>	<b>68.752</b>
<b>VVA-22</b>	<b>3245543.720</b>	<b>723457.323</b>	<b>44.654</b>
<b>VVA-23</b>	<b>3239613.097</b>	<b>713075.952</b>	<b>54.971</b>
<b>VVA-24</b>	<b>3259955.963</b>	<b>711480.820</b>	<b>55.895</b>

<b>VVA-25</b>	<b>3274936.867</b>	<b>701698.999</b>	<b>84.199</b>
<b>VVA-26</b>	<b>3277850.294</b>	<b>688928.981</b>	<b>130.007</b>
<b>VVA-27</b>	<b>3269242.058</b>	<b>684829.564</b>	<b>92.050</b>
<b>VVA-28</b>	<b>3261723.981</b>	<b>694613.773</b>	<b>73.155</b>
<b>VVA-29</b>	<b>3254094.625</b>	<b>699987.856</b>	<b>83.882</b>
<b>VVA-30</b>	<b>3228631.722</b>	<b>701548.808</b>	<b>47.058</b>
<b>VVA-31</b>	<b>3225002.014</b>	<b>690899.175</b>	<b>57.632</b>
<b>VVA-32</b>	<b>3232079.431</b>	<b>683446.962</b>	<b>73.909</b>
<b>VVA-33</b>	<b>3249514.052</b>	<b>685686.044</b>	<b>92.821</b>
<b>VVA-34</b>	<b>3249895.490</b>	<b>673854.980</b>	<b>133.760</b>
<b>VVA-35</b>	<b>3265368.255</b>	<b>674585.338</b>	<b>153.401</b>

#### 4. GPS OBSERVATIONS

POINT ID	OBSERV. DATE	JULIAN DATE	TIME OF DAY	RE-OBSERV. DATE	RE-OBSERV. TIME
<b>NVA's</b>					
NVA-1	1/9/2017	9	17:25	N/A	N/A
NVA-2	1/9/2017	9	16:45	N/A	N/A
NVA-3	1/10/2017	10	11:25	N/A	N/A
NVA-4	1/9/2017	9	16:15	N/A	N/A
NVA-5	1/9/2017	9	15:05	1/11/2017	14:55
NVA-6	1/10/2017	10	13:01	1/11/2017	14:24
NVA-7	1/10/2017	10	12:09	N/A	N/A
NVA-8	1/10/2017	10	13:10	1/11/2017	15:30
NVA-9	1/10/2017	10	14:34	1/11/2017	17:09
NVA-10	1/10/2017	10	10:31	N/A	N/A
NVA-11	1/10/2017	10	13:43	N/A	N/A
NVA-12	1/9/2017	9	14:25	N/A	N/A
NVA-13	1/9/2017	9	13:39	1/11/2017	10:46
NVA-14	1/10/2017	10	14:55	N/A	N/A
NVA-15	1/10/2017	10	11:19	1/11/2017	9:11
NVA-16	1/10/2017	10	9:10	N/A	N/A
NVA-17	1/10/2017	10	15:31	1/11/2017	17:39
NVA-18	1/10/2017	10	17:30	1/11/2017	18:05
NVA-19	1/10/2017	10	16:25	N/A	N/A
NVA-20	1/10/2017	10	10:13	N/A	N/A
NVA-21	1/10/2017	10	15:48	1/11/2017	12:53
NVA-22	1/9/2017	9	13:58	N/A	N/A
NVA-23	1/9/2017	9	11:38	1/11/2017	11:21
NVA-24	1/9/2017	9	10:31	1/9/2017	10:34
NVA-25	1/9/2017	9	8:49	1/9/2017	8:52
NVA-26	1/8/2017	8	17:15	N/A	N/A
NVA-27	1/9/2017	9	7:42	N/A	N/A
NVA-28	1/8/2017	8	15:00	N/A	N/A
NVA-29	1/8/2017	8	13:05	N/A	N/A
NVA-30	1/8/2017	8	10:55	1/11/2017	13:11
NVA-31	1/8/2017	8	8:48	N/A	N/A
NVA-32	1/8/2017	8	9:45	1/11/2017	18:09
NVA-33	1/9/2017	9	8:16	1/11/2017	17:37
NVA-34	1/8/2017	8	17:34	1/11/2017	13:48



NVA-35	1/8/2017	8	16:33	1/11/2017	14:25	
NVA-36	1/8/2017	8	14:47	1/11/2017	15:04	
NVA-37	1/9/2017	9	8:47	N/A	N/A	
NVA-38	1/9/2017	9	16:09	N/A	N/A	
NVA-39	1/9/2017	9	12:34	1/11/2017	10:03	
NVA-40	1/9/2017	9	11:46	1/11/2017	9:44	
NVA-41	1/11/2017	11	18:56	N/A	N/A	
NVA-42	1/9/2017	9	9:04	1/11/2017	17:15	
NVA-43	1/8/2017	8	13:40	1/11/2017	16:37	
NVA-44	1/8/2017	8	11:53	1/11/2017	16:15	
NVA-45	1/11/2017	11	19:34	N/A	N/A	
NVA-46	1/9/2017	9	10:25	N/A	N/A	
NVA-47	1/9/2017	9	11:30	1/11/2017	9:28	
NVA-48	1/10/2017	10	20:08	1/11/2017	11:29	
NVA-49	1/10/2017	10	19:23	1/11/2017	10:58	
NVA-50	1/10/2017	10	9:48	1/11/2017	9:52	
		<b>VVA's</b>				
VVA-1	1/8/2017	8	13:37	N/A	N/A	
VVA-2	1/8/2017	8	15:43	N/A	N/A	
VVA-3	1/9/2017	9	7:14	N/A	N/A	
VVA-4	1/9/2017	9	10:08	N/A	N/A	
VVA-5	1/9/2017	9	11:18	1/11/2017	11:35	
VVA-6	1/8/2017	8	10:12	1/11/2017	12:24	
VVA-7	1/9/2017	9	7:32	N/A	N/A	
VVA-8	1/8/2017	8	15:36	N/A	N/A	
VVA-9	1/9/2017	9	8:28	1/11/2017	17:28	
VVA-10	1/8/2017	8	10:03	N/A	N/A	
VVA-11	1/9/2017	9	12:13	1/11/2017	11:04	
VVA-12	1/9/2017	9	16:39	N/A	N/A	
VVA-13	1/8/2017	8	10:54	N/A	N/A	
VVA-14	1/9/2017	9	9:20	1/11/2017	17:01	
VVA-15	1/8/2017	8	14:06	1/11/2017	15:23	
VVA-16	1/8/2017	8	11:33	1/11/2017	16:35	
VVA-17	1/11/2017	11	19:11	N/A	N/A	
VVA-18	1/9/2017	9	10:37	N/A	N/A	
VVA-19	1/10/2017	10	19:48	1/11/2017	11:10	
VVA-20	1/10/2017	10	16:53	1/11/2017	12:11	
VVA-21	1/9/2017	9	12:19	N/A	N/A	

<b>VVA-22</b>	<b>1/9/2017</b>	<b>9</b>	<b>13:11</b>	<b>1/11/2017</b>	<b>10:29</b>
<b>VVA-23</b>	<b>1/9/2017</b>	<b>9</b>	<b>14:05</b>	<b>N/A</b>	<b>N/A</b>
<b>VVA-24</b>	<b>1/10/2017</b>	<b>10</b>	<b>16:23</b>	<b>1/11/2017</b>	<b>13:08</b>
<b>VVA-25</b>	<b>1/10/2017</b>	<b>10</b>	<b>9:23</b>	<b>N/A</b>	<b>N/A</b>
<b>VVA-26</b>	<b>1/10/2017</b>	<b>10</b>	<b>16:39</b>	<b>1/11/2017</b>	<b>10:03</b>
<b>VVA-27</b>	<b>1/10/2017</b>	<b>10</b>	<b>16:07</b>	<b>N/A</b>	<b>N/A</b>
<b>VVA-28</b>	<b>1/10/2017</b>	<b>10</b>	<b>8:20</b>	<b>N/A</b>	<b>N/A</b>
<b>VVA-29</b>	<b>1/10/2017</b>	<b>10</b>	<b>11:41</b>	<b>1/11/2017</b>	<b>13:37</b>
<b>VVA-30</b>	<b>1/9/2017</b>	<b>9</b>	<b>15:32</b>	<b>1/11/2017</b>	<b>14:38</b>
<b>VVA-31</b>	<b>1/10/2017</b>	<b>10</b>	<b>11:07</b>	<b>N/A</b>	<b>N/A</b>
<b>VVA-32</b>	<b>1/10/2017</b>	<b>10</b>	<b>11:56</b>	<b>N/A</b>	<b>N/A</b>
<b>VVA-33</b>	<b>1/10/2017</b>	<b>10</b>	<b>10:15</b>	<b>1/11/2017</b>	<b>16:45</b>
<b>VVA-34</b>	<b>1/10/2017</b>	<b>10</b>	<b>14:10</b>	<b>N/A</b>	<b>N/A</b>
<b>VVA-35</b>	<b>1/10/2017</b>	<b>10</b>	<b>15:13</b>	<b>N/A</b>	<b>N/A</b>

## 5. POINT COMPARISON

Point ID	Point CK	Delta North (m)	Delta East (m)	Vertical Difference (m)
NVA-5	NVA-5CK	0.008	0.009	-0.010
NVA-6	NVA-6CK	-0.016	-0.012	0.021
NVA-8	NVA-8CK	-0.010	0.022	-0.014
NVA-9	NVA-9CK	0.010	-0.004	0.047
NVA-13	NVA-13CK	-0.005	0.000	-0.028
NVA-15	NVA-15CK	-0.012	-0.007	0.031
NVA-17	NVA-17CK	0.012	0.010	0.028
NVA-18	NVA-18CK	0.006	-0.017	-0.006
NVA-21	NVA-21CK	-0.002	-0.001	0.002
NVA-23	NVA-23CK	-0.023	0.006	0.016
NVA-24	NVA-24CK	-0.005	-0.002	0.001
NVA-25	NVA-25CK	-0.003	0.003	0.002
NVA-30	NVA-30CK	-0.002	0.000	0.009
NVA-32	NVA-32CK	0.007	0.010	0.013
NVA-33	NVA-33CK	0.010	-0.003	0.013
NVA-34	NVA-34CK	0.007	-0.002	-0.010
NVA-35	NVA-35CK	0.002	-0.015	-0.002
NVA-36	NVA-36CK	-0.006	-0.006	0.023
NVA-39	NVA-39CK	0.002	-0.009	-0.030
NVA-40	NVA-40CK	0.003	0.015	0.020
NVA-42	NVA-42CK	-0.004	-0.007	0.017
NVA-43	NVA-43CK	-0.007	-0.001	-0.016
NVA-44	NVA-44CK	-0.008	-0.009	0.004
NVA-47	NVA-47CK	-0.012	0.004	-0.005
NVA-48	NVA-48CK	0.016	-0.005	-0.010
NVA-49	NVA-49CK	-0.033	-0.037	-0.032
NVA-50	NVA-50CK	0.014	0.022	0.007
VVA-5	VVA-5CK	0.013	0.031	-0.044
VVA-6	VVA-6CK	-0.007	-0.004	-0.020
VVA-9	VVA-9CK	-0.020	-0.017	0.020
VVA-11	VVA-11CK	0.010	0.005	0.008
VVA-14	VVA-14CK	-0.011	0.001	-0.019
VVA-15	VVA-15CK	-0.015	0.004	-0.018
VVA-16	VVA-16CK	0.007	0.006	-0.021
VVA-19	VVA-19CK	-0.004	-0.004	0.013
VVA-20	VVA-20CK	0.000	0.000	-0.021
VVA-22	VVA-22CK	0.006	0.009	-0.004
VVA-24	VVA-24CK	-0.008	0.008	-0.020

<b>VVA-26</b>	<b>VVA-26CK</b>	<b>0.002</b>	<b>0.000</b>	<b>-0.020</b>
<b>VVA-29</b>	<b>VVA-29CK</b>	<b>-0.004</b>	<b>0.014</b>	<b>0.009</b>
<b>VVA-30</b>	<b>VVA-30CK</b>	<b>0.008</b>	<b>-0.030</b>	<b>-0.041</b>
<b>VVA-33</b>	<b>VVA-33CK</b>	<b>0.015</b>	<b>0.002</b>	<b>0.008</b>



## **Appendix B: Ground Control Point Survey Report**

### **Ground Control Point Survey Report**

**“Texas Lavaca-Wharton FEMA Region 6 LiDAR”  
USGS Contract: G16PC00020 Task Order  
Number: G17PC00014**

**Prepared for:  
*United States Geological Survey (USGS)***

Prepared By:  
**Dewberry Consultants LLC**  
10003 Derekwood Lane, Suite 204  
Lanham, Maryland, 20706  
Phone (301)364-1855 Fax (301)731-0188

## TABLE OF CONTENTS

□	Introduction	
	1.1 Project Summary .....	3
	1.2 Points of Contact(s).....	3
	1.3 Project Area .....	4
3.	Project Details	
	2.1 Survey Equipment .....	5
	2.2 Survey Point Details .....	5
	2.3 Network Design .....	5
	2.4 Field Survey Procedures and Analysis.....	6-7
	2.5 Adjustment.....	8
	2.6 Data Processing Procedures.....	8
3.	Final Coordinates .....	9-10
4.	GPS Observation & Re-Observation Schedule .....	11-12
5.	Point Comparison Report .....	13
7.	Deliverables .....	Sent via Electronic Transfer
	Including: a) Point Documentation Report & Photos of Survey Points	
	b) Final Coordinate List in Excel Format	
	c) NGS Data Sheets for Project Controls	

## 2. INTRODUCTION

---

### 1.1 *Project Summary*

Dewberry Consultants LLC is under contract to the United States Geological Survey to provide 60 Ground Control Points in the State of Texas. Under the above referenced USGS Task Order, Dewberry is tasked to complete the quality assurance of LiDAR products. As part of this work Dewberry staff will complete Ground Control Point surveys that will be used to evaluate vertical and horizontal accuracy. The ground survey was conducted January 8 thru January 11, 2017.

Existing NGS Control Points were located and surveyed to check the accuracy of the RTK/GPS survey equipment with the results shown in Section 2.4 of this Report.

As an internal QA/QC procedure and to verify that the Ground Control Points meet the 95% confidence level approximately 50% of the points were re-observed and are shown in Section 5 of this report.

Final horizontal coordinates are referenced to UTM, Zone 14, NAD83 (2011) in meters. Final Vertical elevations are referenced to NAVD88 in meters using Geoid model 2012B (Geoid12B).

### 1.2 *Points of Contact*


Questions regarding the technical aspects of this report should be addressed to:

#### **Dewberry Consultants LLC**

Gary D. Simpson, L.S.  
Senior Associate  
10003 Derekwood Lane  
Suite 204  
Lanham, Maryland 20706  
(302)364-1855 direct  
(302)731-0188 fax



### 1.3 Project Area



## **PROJECT DETAILS**

---

### ***2.1 Survey Equipment***

In performing the GPS observations Trimble R-10 GNSS receiver/antenna attached to a two meter fixed height pole with a Trimble TSC3 Data Collector to collect GPS raw data were used to perform the field surveys.

### ***2.2 Survey Point Detail***

The 60 Ground Control Points were well distributed throughout the project area.

A sketch was made for each location and a nail was set at the point where possible or at an identifiable point. The Ground Control Point locations are detailed on the “Check Point Documentation Report” sheets attached to this report.

### ***2.3 Network Design***

The GPS field survey performed by Dewberry offices located in Lanham, Maryland and Charleston, West Virginia and was tied to a Real Time Network operated by the TXDOT RTN. The network is a series of “real-time” continuously operating, high precision GPS reference stations. All of the reference stations have been linked together using Trimble GPSNet software, creating a Virtual Reference Station System (VRS).

The Trimble NetR5 Reference Station is a multi-channel, multi-frequency GNSS (Global Navigation Satellite System) receiver designed for use as a stand-alone reference station or as part of a GNSS infrastructure solution. Trimble R-Track technology in the NetR5 receiver supports the modernized GPS L2C and L5 signals as well as GLONASS L1/L2 signals.

## 2.4 Field Survey Procedures and Analysis

Dewberry field surveyors used Trimble R-10 GNSS receivers, which is a geodetic quality dual frequency GPS receiver, to collect data at each surveyed location.

All locations were occupied once with approximately 50% of the locations being re-observed. All re-observations matched the initially derived station positions within the allowable tolerance of  $\pm 5\text{cm}$  or within the 95% confidence level. Each occupation which utilized the VRS network was occupied for approximately three (3) minutes in duration and measured to 180 epochs.

Each occupation which utilized OPUS (if used) was occupied between 20 and 30 minutes.

Field GPS observations are detailed on the “Control Point Documentation Reports” submitted as part of this report.

Six (6) existing NGS monument listed in the NSRS database were located as an additional QA/QC method to check the horizontal and vertical accuracy of the VRS network as well as being the primary project control monuments designated as AX0131, AX2610, AX0107, CR1356, BZ1450 and BZ0061. The results are as follows:

PT. #	Observed Values			Data Sheet Values			$\Delta X$	$\Delta Y$	$\Delta Z$
	NORTHIN G	EASTING	ELEVS.	NORTHING	EASTING	ELEVS.			
CALPORT**	3378380.696	720142.292	118.154	3,378,380.678	720,142.269	118.360	0.018	0.023	N/A
MEXPORT**	3503174.163	735740.617	163.366	3,503,174.147	735,740.601	163.450	0.016	0.016	N/A
A 937*	3519055.737	744698.500	128.029	N/A	N/A	127.977	N/A	N/A	0.050
YOAKUM SW BASE**	3244673.301	680118.205	110.623	3,244,673.302	680,118.189	110.700	-0.001	0.016	N/A
LAKE	3280376.188	754359.115	62.738	3,280,376.190	754,359.223	62.750	-0.002	-0.008	-0.012
BERNARD 2*	3269041.251	784052.777	36.676	N/A	N/A	36.650	N/A	N/A	0.026

(\*) Indicates a vertical NGS Mark (\*\*)

Indicates a horizontal NGS Mark

The above results indicate that the VRS network is providing positional values within the 5cm parameters for this survey.

### NGS Monuments



## **2.5 Adjustment**

The survey data was collected using Virtual Reference Stations (VRS) methodology within a Virtual Reference System (VRS).

The system is designed to provide a true Network RTK performance, the RTKNet software enables high-accuracy positioning in real time across a geographic region. The RTKNet software package uses real-time data streams from the TXDOT RTN system user and generates correction models for high-accuracy RTK GPS corrections throughout the network. Therefore, corrections were applied to the points as they were being collected, thus negating the need for a post process adjustment.

## **2.6 Data Processing Procedures**

After field data is collected the information is downloaded from the data collectors into the office software. The Software program used is called Trimble Business Center.

Downloaded data is run through the TBC program to obtain the following reports; points report, point comparison report and a point detail report. The reports are reviewed for point accuracy and precision.

After review of the point data an “ASCII” or “txt” file which is the industry standard is created. Point files are loaded into our CADD program (Carlson Survey 2014) to make a visual check of the point data (Pt. #, Coordinates, Elev. and Description). The data can now be imported into the final product.

#### 4. FINAL COORDINATES/ELEVATIONS

<b>UTM Zone 14, NAD83 (2011), NAVD88</b>			
<b>Point ID</b>	<b>Northing (m)</b>	<b>Easting (m)</b>	<b>Elevation (m)</b>
GCP-001	3215746.852	684517.582	70.752
GCP-002	3228716.522	681742.030	72.560
GCP-003	3234745.561	673661.938	98.899
GCP-004	3238587.119	677780.951	90.674
GCP-005	3243827.251	675496.127	92.534
GCP-006	3232109.678	694889.828	64.072
GCP-007	3232083.089	710036.121	43.538
GCP-008	3240732.156	701124.400	67.971
GCP-009	3243299.452	723833.244	47.317
GCP-010	3241727.877	735095.236	40.909
GCP-011	3236528.046	742726.260	34.720
GCP-012	3230211.228	738603.192	30.504
GCP-013	3227622.989	753188.596	27.479
GCP-014	3214298.284	756323.781	20.788
GCP-015	3211775.986	772002.917	18.305
GCP-016	3225801.645	766609.021	27.446
GCP-017	3231923.038	766379.782	29.740
GCP-018	3226361.140	793522.750	22.048
GCP-019	3233490.857	801030.980	19.146
GCP-020	3238124.328	787598.292	27.041
GCP-021	3242656.617	794945.179	25.658
GCP-022	3245644.601	795971.157	22.937
GCP-023	3240424.592	776196.130	30.355
GCP-024	3246974.556	781418.737	31.571
GCP-025	3257301.321	785634.944	31.226
GCP-026	3255755.476	779617.271	34.045
GCP-027	3255773.020	768781.445	39.298
GCP-028	3267392.309	768235.127	45.254
GCP-029	3271415.845	774938.458	40.710
GCP-030	3265125.036	783472.592	35.602
GCP-031	3269041.248	784052.776	36.666
GCP-032	3270878.626	785093.451	36.795
GCP-033	3273921.737	782809.723	37.791
GCP-034	3280436.714	768065.127	47.651
GCP-035	3277640.822	759446.570	55.165

<b>GCP-036</b>	<b>3280376.170</b>	<b>754359.109</b>	<b>62.765</b>
<b>GCP-037</b>	<b>3276160.719</b>	<b>753515.577</b>	<b>53.667</b>
<b>GCP-038</b>	<b>3273784.890</b>	<b>745423.323</b>	<b>61.762</b>
<b>GCP-039</b>	<b>3264682.805</b>	<b>744546.073</b>	<b>57.593</b>
<b>GCP-040</b>	<b>3253366.184</b>	<b>741611.978</b>	<b>47.900</b>
<b>GCP-041</b>	<b>3246032.335</b>	<b>749866.172</b>	<b>40.395</b>
<b>GCP-042</b>	<b>3253616.938</b>	<b>726847.834</b>	<b>65.757</b>
<b>GCP-043</b>	<b>3271487.129</b>	<b>732162.658</b>	<b>83.838</b>
<b>GCP-044</b>	<b>3286661.062</b>	<b>723042.599</b>	<b>104.234</b>
<b>GCP-045</b>	<b>3287937.072</b>	<b>713544.220</b>	<b>123.534</b>
<b>GCP-046</b>	<b>3276083.787</b>	<b>716144.291</b>	<b>104.246</b>
<b>GCP-047</b>	<b>3270482.205</b>	<b>716621.560</b>	<b>89.553</b>
<b>GCP-048</b>	<b>3264271.547</b>	<b>722303.765</b>	<b>73.423</b>
<b>GCP-049</b>	<b>3262062.736</b>	<b>713786.800</b>	<b>60.381</b>
<b>GCP-050</b>	<b>3254774.730</b>	<b>708247.721</b>	<b>86.608</b>
<b>GCP-051</b>	<b>3247829.131</b>	<b>704089.132</b>	<b>54.342</b>
<b>GCP-052</b>	<b>3251796.041</b>	<b>693555.238</b>	<b>68.609</b>
<b>GCP-053</b>	<b>3261859.423</b>	<b>699945.326</b>	<b>91.325</b>
<b>GCP-054</b>	<b>3267904.956</b>	<b>702128.559</b>	<b>101.314</b>
<b>GCP-055</b>	<b>3277111.424</b>	<b>702051.258</b>	<b>97.870</b>
<b>GCP-056</b>	<b>3279088.136</b>	<b>679934.972</b>	<b>134.296</b>
<b>GCP-057</b>	<b>3273520.575</b>	<b>679386.824</b>	<b>129.364</b>
<b>GCP-058</b>	<b>3266817.585</b>	<b>683231.690</b>	<b>141.770</b>
<b>GCP-059</b>	<b>3259192.022</b>	<b>672887.276</b>	<b>125.955</b>
<b>GCP-060</b>	<b>3208040.719</b>	<b>679872.089</b>	<b>45.280</b>

## 5. GPS OBSERVATIONS

<b>POINT ID</b>	<b>OBSERV. DATE</b>	<b>JULIAN DATE</b>	<b>TIME OF DAY</b>	<b>RE-OBSERV. DATE</b>	<b>RE-OBSERV. TIME</b>
GCP-1	1/9/2017	9	17:00	N/A	N/A
GCP-2	1/10/2017	10	11:40	N/A	N/A
GCP-3	1/10/2017	10	12:51	1/11/2017	15:54
GCP-4	1/10/2017	10	12:26	1/11/2017	15:41
GCP-5	1/10/2017	10	13:53	N/A	N/A
GCP-6	1/9/2017	9	15:54	1/11/2017	15:08
GCP-7	1/9/2017	9	14:45	N/A	N/A
GCP-8	1/10/2017	10	13:22	1/11/2017	14:02
GCP-9	1/9/2017	9	13:24	1/11/2017	10:36
GCP-10	1/9/2017	9	13:08	N/A	N/A
GCP-11	1/9/2017	9	11:54	1/11/2017	11:11
GCP-12	1/9/2017	9	12:39	N/A	N/A
GCP-13	1/9/2017	9	10:49	N/A	N/A
GCP-14	1/9/2017	9	9:12	N/A	N/A
GCP-15	1/9/2017	9	8:23	N/A	N/A
GCP-16	1/8/2017	8	17:36	N/A	N/A
GCP-17	1/8/2017	8	9:06	1/11/2017	11:55
GCP-18	1/8/2017	8	16:14	N/A	N/A
GCP-19	1/8/2017	8	14:02	N/A	N/A
GCP-20	1/8/2017	8	15:18	N/A	N/A
GCP-21	1/8/2017	8	12:20	N/A	N/A
GCP-22	1/8/2017	8	12:42	N/A	N/A
GCP-23	1/8/2017	8	9:44	1/11/2017	12:08
GCP-24	1/8/2017	8	11:20	1/11/2017	12:42
GCP-25	1/8/2017	8	11:44	1/11/2017	13:35
GCP-26	1/9/2017	9	7:46	1/11/2017	13:24
GCP-27	1/9/2017	9	8:05	1/11/2017	17:43
GCP-28	1/8/2017	8	15:09	1/11/2017	16:24
GCP-29	1/8/2017	8	15:53	1/11/2017	14:50
GCP-30	1/8/2017	8	17:21	1/11/2017	14:00
GCP-31	1/8/2017	8	17:03	1/11/2017	14:08
GCP-32	1/8/2017	8	16:50	1/11/2017	14:17
GCP-33	1/8/2017	8	16:15	1/11/2017	14:31
GCP-34	1/8/2017	8	14:23	N/A	N/A
GCP-35	1/8/2017	8	13:24	1/11/2017	15:46



<b>GCP-36</b>	<b>1/8/2017</b>	<b>8</b>	<b>12:23</b>	<b>1/11/2017</b>	<b>16:00</b>
<b>GCP-37</b>	<b>1/9/2017</b>	<b>9</b>	<b>9:36</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-38</b>	<b>1/8/2017</b>	<b>8</b>	<b>11:17</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-39</b>	<b>1/11/2017</b>	<b>11</b>	<b>18:38</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-40</b>	<b>1/9/2017</b>	<b>9</b>	<b>17:03</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-41</b>	<b>1/8/2017</b>	<b>8</b>	<b>10:22</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-42</b>	<b>1/9/2017</b>	<b>9</b>	<b>12:45</b>	<b>1/11/2017</b>	<b>10:11</b>
<b>GCP-43</b>	<b>1/9/2017</b>	<b>9</b>	<b>11:01</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-44</b>	<b>1/10/2017</b>	<b>10</b>	<b>18:43</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-45</b>	<b>1/10/2017</b>	<b>10</b>	<b>19:05</b>	<b>1/11/2017</b>	<b>10:42</b>
<b>GCP-46</b>	<b>1/10/2017</b>	<b>10</b>	<b>17:31</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-47</b>	<b>1/10/2017</b>	<b>10</b>	<b>17:14</b>	<b>1/11/2017</b>	<b>11:57</b>
<b>GCP-48</b>	<b>1/9/2017</b>	<b>9</b>	<b>12:00</b>	<b>1/11/2017</b>	<b>11:43</b>
<b>GCP-49</b>	<b>1/10/2017</b>	<b>10</b>	<b>16:04</b>	<b>1/11/2017</b>	<b>12:41</b>
<b>GCP-50</b>	<b>1/10/2017</b>	<b>10</b>	<b>15:25</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-51</b>	<b>1/10/2017</b>	<b>10</b>	<b>12:17</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-52</b>	<b>1/10/2017</b>	<b>10</b>	<b>9:40</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-53</b>	<b>1/10/2017</b>	<b>10</b>	<b>10:52</b>	<b>1/11/2017</b>	<b>9:27</b>
<b>GCP-54</b>	<b>1/10/2017</b>	<b>10</b>	<b>10:35</b>	<b>1/11/2017</b>	<b>9:44</b>
<b>GCP-55</b>	<b>1/10/2017</b>	<b>10</b>	<b>8:47</b>	<b>N/A</b>	<b>N/A</b>
<b>GCP-56</b>	<b>1/10/2017</b>	<b>10</b>	<b>17:08</b>	<b>1/11/2017</b>	<b>18:35</b>
<b>GCP-57</b>	<b>1/10/2017</b>	<b>10</b>	<b>17:46</b>	<b>1/11/2017</b>	<b>18:15</b>
<b>GCP-58</b>	<b>1/10/2017</b>	<b>10</b>	<b>15:44</b>	<b>1/11/2017</b>	<b>17:47</b>
<b>GCP-59</b>	<b>1/10/2017</b>	<b>10</b>	<b>14:52</b>	<b>1/11/2017</b>	<b>17:23</b>
<b>GCP-60</b>	<b>1/9/2017</b>	<b>9</b>	<b>17:35</b>	<b>N/A</b>	<b>N/A</b>

**6. POINT COMPARISON**

<b>Point ID</b>	<b>Point CK</b>	<b>Delta North (M)</b>	<b>Delta East (M)</b>	<b>Vertical Difference (M)</b>
GCP-003	GCP-003CK	-0.020	0.002	0.028
GCP-004	GCP-004CK	0.017	-0.012	-0.005
GCP-006	GCP-006CK	-0.019	-0.006	-0.017
GCP-008	GCP-008CK	0.011	0.014	0.022
GCP-009	GCP-009CK	-0.007	-0.008	0.012
GCP-011	GCP-011CK	0.000	0.022	0.000
GCP-017	GCP-017CK	0.000	0.008	0.013
GCP-023	GCP-023CK	0.013	0.000	-0.018
GCP-024	GCP-024CK	0.000	-0.002	-0.010
GCP-025	GCP-025CK	-0.004	0.028	0.015
GCP-026	GCP-026CK	-0.003	-0.001	0.016
GCP-027	GCP-027CK	0.003	0.009	-0.008
GCP-028	GCP-028CK	0.005	-0.001	-0.002
GCP-029	GCP-029CK	-0.005	0.000	-0.019
GCP-030	GCP-030CK	0.002	0.001	-0.009
GCP-031	GCP-031CK	-0.001	0.017	-0.013
GCP-032	GCP-032CK	0.002	0.002	-0.004
GCP-033	GCP-033CK	0.017	0.004	0.007
GCP-035	GCP-035CK	0.001	-0.001	0.038
GCP-036	GCP-038CK	0.001	0.000	0.003
GCP-042	GCP-042CK	0.002	-0.002	-0.034
GCP-045	GCP-045CK	0.008	0.008	-0.022
GCP-047	GCP-047CK	-0.037	0.000	-0.001
GCP-048	GCP-048CK	0.015	0.004	0.005
GCP-049	GCP-049CK	-0.006	-0.006	-0.011
GCP-053	GCP-053CK	-0.012	0.006	0.010
GCP-054	GCP-054CK	0.021	0.016	-0.007
GCP-056	GCP-056CK	0.018	-0.010	0.049
GCP-057	GCP-057CK	0.005	0.021	0.012
GCP-058	GCP-058CK	-0.003	-0.015	-0.009
GCP-059	GCP-059CK	0.002	0.020	0.025

## Appendix C: Complete List of Delivered Tiles

14RPT7301	14RPT7501	14RPT7601	14RPT7302
14RPT7502	14RPT7602	14RPT7304	14RPT7504
14RPT7604	14RPT7804	14RPT7904	14RPT7505
14RPT7605	14RPT7805	14RPT7905	14RQT5905
14RQT6005	14RQT6205	14RQT6305	14RQT6505
14RPT7607	14RPT7807	14RPT7907	14RPT8107
14RPT8207	14RQT5707	14RQT5907	14RQT6007
14RQT6207	14RQT6307	14RQT6507	14RQT6607
14RQT6807	14RPT7608	14RPT7808	14RPT7908
14RPT8108	14RPT8208	14RQT5608	14RQT5708
14RQT5908	14RQT6008	14RQT6208	14RQT6308
14RQT6508	14RQT6608	14RQT6808	14RPT7910
14RPT8110	14RPT8210	14RPT8410	14RPT8510
14RPT8710	14RQT5410	14RQT5610	14RQT5710
14RQT5910	14RQT6010	14RQT6210	14RQT6310
14RQT6510	14RQT6610	14RQT6810	14RQT6910
14RPT8111	14RPT8211	14RPT8411	14RPT8511
14RPT8711	14RPT8811	14RQT5411	14RQT5611
14RQT5711	14RQT5911	14RQT6011	14RQT6211
14RQT6311	14RQT6511	14RQT6611	14RQT6811
14RQT6911	14RQT7111	14RQT7211	14RQT7411
14RPT8113	14RPT8213	14RPT8413	14RPT8513
14RPT8713	14RPT8813	14RPT9013	14RQT5313
14RQT5413	14RQT5613	14RQT5713	14RQT5913
14RQT6013	14RQT6213	14RQT6313	14RQT6513
14RQT6613	14RQT6813	14RQT6913	14RQT7113
14RQT7213	14RQT7413	14RQT7513	14RPT8114
14RPT8214	14RPT8414	14RPT8514	14RPT8714
14RPT8814	14RPT9014	14RPT9114	14RPT9914
14RQT0014	14RQT0214	14RQT5014	14RQT5114
14RQT5314	14RQT5414	14RQT5614	14RQT5714
14RQT5914	14RQT6014	14RQT6214	14RQT6314
14RQT6514	14RQT6614	14RQT6814	14RQT6914
14RQT7114	14RQT7214	14RQT7414	14RQT7514
14RQT7714	14RQT7814	14RPT8116	14RPT8216
14RPT8416	14RPT8516	14RPT8716	14RPT8816
14RPT9016	14RPT9116	14RPT9316	14RPT9416
14RPT9616	14RPT9716	14RPT9916	14RQT0016
14RQT0216	14RQT0316	14RQT4816	14RQT5016
14RQT5116	14RQT5316	14RQT5416	14RQT5616
14RQT5716	14RQT5916	14RQT6016	14RQT6216
14RQT6316	14RQT6516	14RQT6616	14RQT6816
14RQT6916	14RQT7116	14RQT7216	14RQT7416
14RQT7516	14RQT7716	14RQT7816	14RQT8016
14RPT8117	14RPT8217	14RPT8417	14RPT8517
14RPT8717	14RPT8817	14RPT9017	14RPT9117
14RPT9317	14RPT9417	14RPT9617	14RPT9717
14RPT9917	14RQT0017	14RQT0217	14RQT0317
14RQT0517	14RQT4717	14RQT4817	14RQT5017
14RQT5117	14RQT5317	14RQT5417	14RQT5617
14RQT5717	14RQT5917	14RQT6017	14RQT6217
14RQT6317	14RQT6517	14RQT6617	14RQT6817

14RQT6917	14RQT7117	14RQT7217	14RQT7417
14RQT7517	14RQT7717	14RQT7817	14RQT8017
14RQT8117	14RQT8317	14RPT8119	14RPT8219
14RPT8419	14RPT8519	14RPT8719	14RPT8819
14RPT9019	14RPT9119	14RPT9319	14RPT9419
14RPT9619	14RPT9719	14RPT9919	14RQT0019
14RQT0219	14RQT0319	14RQT0519	14RQT4519
14RQT4719	14RQT4819	14RQT5019	14RQT5119
14RQT5319	14RQT5419	14RQT5619	14RQT5719
14RQT5919	14RQT6019	14RQT6219	14RQT6319
14RQT6519	14RQT6619	14RQT6819	14RQT6919
14RQT7119	14RQT7219	14RQT7419	14RQT7519
14RQT7719	14RQT7819	14RQT8019	14RQT8119
14RQT8319	14RQT8419	14RQT8619	14RPT7820
14RPT7920	14RPT8120	14RPT8220	14RPT8420
14RPT8520	14RPT8720	14RPT8820	14RPT9020
14RPT9120	14RPT9320	14RPT9420	14RPT9620
14RPT9720	14RPT9920	14RQT0020	14RQT0220
14RQT0320	14RQT0520	14RQT0620	14RQT0820
14RQT4420	14RQT4520	14RQT4720	14RQT4820
14RQT5020	14RQT5120	14RQT5320	14RQT5420
14RQT5620	14RQT5720	14RQT5920	14RQT6020
14RQT6220	14RQT6320	14RQT6520	14RQT6620
14RQT6820	14RQT6920	14RQT7120	14RQT7220
14RQT7420	14RQT7520	14RQT7720	14RQT7820
14RQT8020	14RQT8120	14RQT8320	14RQT8420
14RQT8620	14RQT8720	14RQT8920	14RPT7822
14RPT7922	14RPT8122	14RPT8222	14RPT8422
14RPT8522	14RPT8722	14RPT8822	14RPT9022
14RPT9122	14RPT9322	14RPT9422	14RPT9622
14RPT9722	14RPT9922	14RQT0022	14RQT0222
14RQT0322	14RQT0522	14RQT0622	14RQT0822
14RQT0922	14RQT4222	14RQT4422	14RQT4522
14RQT4722	14RQT4822	14RQT5022	14RQT5122
14RQT5322	14RQT5422	14RQT5622	14RQT5722
14RQT5922	14RQT6022	14RQT6222	14RQT6322
14RQT6522	14RQT6622	14RQT6822	14RQT6922
14RQT7122	14RQT7222	14RQT7422	14RQT7522
14RQT7722	14RQT7822	14RQT8022	14RQT8122
14RQT8322	14RQT8422	14RQT8622	14RQT8722
14RQT8922	14RQT9022	14RPT7823	14RPT7923
14RPT8123	14RPT8223	14RPT8423	14RPT8523
14RPT8723	14RPT8823	14RPT9023	14RPT9123
14RPT9323	14RPT9423	14RPT9623	14RPT9723
14RPT9923	14RQT0023	14RQT0223	14RQT0323
14RQT0523	14RQT0623	14RQT0823	14RQT0923
14RQT1123	14RQT3923	14RQT4123	14RQT4223
14RQT4423	14RQT4523	14RQT4723	14RQT4823
14RQT5023	14RQT5123	14RQT5323	14RQT5423
14RQT5623	14RQT5723	14RQT5923	14RQT6023
14RQT6223	14RQT6323	14RQT6523	14RQT6623
14RQT6823	14RQT6923	14RQT7123	14RQT7223
14RQT7423	14RQT7523	14RQT7723	14RQT7823
14RQT8023	14RQT8123	14RQT8323	14RQT8423
14RQT8623	14RQT8723	14RQT8923	14RQT9023

15RQT9223	14RPT7625	14RPT7825	14RPT7925
14RPT8125	14RPT8225	14RPT8425	14RPT8525
14RPT8725	14RPT8825	14RPT9025	14RPT9125
14RPT9325	14RPT9425	14RPT9625	14RPT9725
14RPT9925	14RQT0025	14RQT0225	14RQT0325
14RQT0525	14RQT0625	14RQT0825	14RQT0925
14RQT1125	14RQT1225	14RQT3825	14RQT3925
14RQT4125	14RQT4225	14RQT4425	14RQT4525
14RQT4725	14RQT4825	14RQT5025	14RQT5125
14RQT5325	14RQT5425	14RQT5625	14RQT5725
14RQT5925	14RQT6025	14RQT6225	14RQT6325
14RQT6525	14RQT6625	14RQT6825	14RQT6925
14RQT7125	14RQT7225	14RQT7425	14RQT7525
14RQT7725	14RQT7825	14RQT8025	14RQT8125
14RQT8325	14RQT8425	14RQT8625	14RQT8725
14RQT8925	14RQT9025	15RQT9225	15RQT9325
15RQT9525	15RQT9625	14RPT7626	14RPT7826
14RPT7926	14RPT8126	14RPT8226	14RPT8426
14RPT8526	14RPT8726	14RPT8826	14RPT9026
14RPT9126	14RPT9326	14RPT9426	14RPT9626
14RPT9726	14RPT9926	14RQT0026	14RQT0226
14RQT0326	14RQT0526	14RQT0626	14RQT0826
14RQT0926	14RQT1126	14RQT1226	14RQT1426
14RQT1526	14RQT3626	14RQT3826	14RQT3926
14RQT4126	14RQT4226	14RQT4426	14RQT4526
14RQT4726	14RQT4826	14RQT5026	14RQT5126
14RQT5326	14RQT5426	14RQT5626	14RQT5726
14RQT5926	14RQT6026	14RQT6226	14RQT6326
14RQT6526	14RQT6626	14RQT6826	14RQT6926
14RQT7126	14RQT7226	14RQT7426	14RQT7526
14RQT7726	14RQT7826	14RQT8026	14RQT8126
14RQT8326	14RQT8426	14RQT8626	14RQT8726
14RQT8926	14RQT9026	15RQT9226	15RQT9326
15RQT9526	15RQT9626	15RQT9826	14RPT7528
14RPT7628	14RPT7828	14RPT7928	14RPT8128
14RPT8228	14RPT8428	14RPT8528	14RPT8728
14RPT8828	14RPT9028	14RPT9128	14RPT9328
14RPT9428	14RPT9628	14RPT9728	14RPT9928
14RQT0028	14RQT0228	14RQT0328	14RQT0528
14RQT0628	14RQT0828	14RQT0928	14RQT1128
14RQT1228	14RQT1428	14RQT1528	14RQT1728
14RQT3528	14RQT3628	14RQT3828	14RQT3928
14RQT4128	14RQT4228	14RQT4428	14RQT4528
14RQT4728	14RQT4828	14RQT5028	14RQT5128
14RQT5328	14RQT5428	14RQT5628	14RQT5728
14RQT5928	14RQT6028	14RQT6228	14RQT6328
14RQT6528	14RQT6628	14RQT6828	14RQT6928
14RQT7128	14RQT7228	14RQT7428	14RQT7528
14RQT7728	14RQT7828	14RQT8028	14RQT8128
14RQT8328	14RQT8428	14RQT8628	14RQT8728
14RQT8928	14RQT9028	15RQT9228	15RQT9328
15RQT9528	15RQT9628	15RQT9828	14RPT7529
14RPT7629	14RPT7829	14RPT7929	14RPT8129
14RPT8229	14RPT8429	14RPT8529	14RPT8729
14RPT8829	14RPT9029	14RPT9129	14RPT9329

14RPT9429 14RPT9629 14RPT9729 14RPT9929  
14RQT0029 14RQT0229 14RQT0329 14RQT0529  
14RQT0629 14RQT0829 14RQT0929 14RQT1129  
14RQT1229 14RQT1429 14RQT1529 14RQT1729  
14RQT1829 14RQT2029 14RQT3329 14RQT3529  
14RQT3629 14RQT3829 14RQT3929 14RQT4129  
14RQT4229 14RQT4429 14RQT4529 14RQT4729  
14RQT4829 14RQT5029 14RQT5129 14RQT5329  
14RQT5429 14RQT5629 14RQT5729 14RQT5929  
14RQT6029 14RQT6229 14RQT6329 14RQT6529  
14RQT6629 14RQT6829 14RQT6929 14RQT7129  
14RQT7229 14RQT7429 14RQT7529 14RQT7729  
14RQT7829 14RQT8029 14RQT8129 14RQT8329  
14RQT8429 14RQT8629 14RQT8729 14RQT8929  
14RQT9029 15RQT9229 15RQT9329 15RQT9529  
15RQT9629 15RQT9829 15RQT9929 14RPT7531  
14RPT7631 14RPT7831 14RPT7931 14RPT8131  
14RPT8231 14RPT8431 14RPT8531 14RPT8731  
14RPT8831 14RPT9031 14RPT9131 14RPT9331  
14RPT9431 14RPT9631 14RPT9731 14RPT9931  
14RQT0031 14RQT0231 14RQT0331 14RQT0531  
14RQT0631 14RQT0831 14RQT0931 14RQT1131  
14RQT1231 14RQT1431 14RQT1531 14RQT1731  
14RQT1831 14RQT2031 14RQT2131 14RQT3231  
14RQT3331 14RQT3531 14RQT3631 14RQT3831  
14RQT3931 14RQT4131 14RQT4231 14RQT4431  
14RQT4531 14RQT4731 14RQT4831 14RQT5031  
14RQT5131 14RQT5331 14RQT5431 14RQT5631  
14RQT5731 14RQT5931 14RQT6031 14RQT6231  
14RQT6331 14RQT6531 14RQT6631 14RQT6831  
14RQT6931 14RQT7131 14RQT7231 14RQT7431  
14RQT7531 14RQT7731 14RQT7831 14RQT8031  
14RQT8131 14RQT8331 14RQT8431 14RQT8631  
14RQT8731 14RQT8931 14RQT9031 15RQT9231  
15RQT9331 15RQT9531 15RQT9631 15RQT9831  
15RQT9931 14RPT7232 14RPT7332 14RPT7532  
14RPT7632 14RPT7832 14RPT7932 14RPT8132  
14RPT8232 14RPT8432 14RPT8532 14RPT8732  
14RPT8832 14RPT9032 14RPT9132 14RPT9332  
14RPT9432 14RPT9632 14RPT9732 14RPT9932  
14RQT0032 14RQT0232 14RQT0332 14RQT0532  
14RQT0632 14RQT0832 14RQT0932 14RQT1132  
14RQT1232 14RQT1432 14RQT1532 14RQT1732  
14RQT1832 14RQT2032 14RQT2132 14RQT2332  
14RQT2932 14RQT3032 14RQT3232 14RQT3332  
14RQT3532 14RQT3632 14RQT3832 14RQT3932  
14RQT4132 14RQT4232 14RQT4432 14RQT4532  
14RQT4732 14RQT4832 14RQT5032 14RQT5132  
14RQT5332 14RQT5432 14RQT5632 14RQT5732  
14RQT5932 14RQT6032 14RQT6232 14RQT6332  
14RQT6532 14RQT6632 14RQT6832 14RQT6932  
14RQT7132 14RQT7232 14RQT7432 14RQT7532  
14RQT7732 14RQT7832 14RQT8032 14RQT8132  
14RQT8332 14RQT8432 14RQT8632 14RQT8732  
14RQT8932 14RQT9032 15RQT9232 15RQT9332

15RQT9532	15RQT9632	15RQT9832	15RQT9932
15RQT0132	14RPT7234	14RPT7334	14RPT7534
14RPT7634	14RPT7834	14RPT7934	14RPT8134
14RPT8234	14RPT8434	14RPT8534	14RPT8734
14RPT8834	14RPT9034	14RPT9134	14RPT9334
14RPT9434	14RPT9634	14RPT9734	14RPT9934
14RQT0034	14RQT0234	14RQT0334	14RQT0534
14RQT0634	14RQT0834	14RQT0934	14RQT1134
14RQT1234	14RQT1434	14RQT1534	14RQT1734
14RQT1834	14RQT2034	14RQT2134	14RQT2334
14RQT2434	14RQT2734	14RQT2934	14RQT3034
14RQT3234	14RQT3334	14RQT3534	14RQT3634
14RQT3834	14RQT3934	14RQT4134	14RQT4234
14RQT4434	14RQT4534	14RQT4734	14RQT4834
14RQT5034	14RQT5134	14RQT5334	14RQT5434
14RQT5634	14RQT5734	14RQT5934	14RQT6034
14RQT6234	14RQT6334	14RQT6534	14RQT6634
14RQT6834	14RQT6934	14RQT7134	14RQT7234
14RQT7434	14RQT7534	14RQT7734	14RQT7834
14RQT8034	14RQT8134	14RQT8334	14RQT8434
14RQT8634	14RQT8734	14RQT8934	14RQT9034
15RQT9234	15RQT9334	15RQT9534	15RQT9634
15RQT9834	15RQT9934	15RQT0134	15RQT0234
14RPT7235	14RPT7335	14RPT7535	14RPT7635
14RPT7835	14RPT7935	14RPT8135	14RPT8235
14RPT8435	14RPT8535	14RPT8735	14RPT8835
14RPT9035	14RPT9135	14RPT9335	14RPT9435
14RPT9635	14RPT9735	14RPT9935	14RQT0035
14RQT0235	14RQT0335	14RQT0535	14RQT0635
14RQT0835	14RQT0935	14RQT1135	14RQT1235
14RQT1435	14RQT1535	14RQT1735	14RQT1835
14RQT2035	14RQT2135	14RQT2335	14RQT2435
14RQT2635	14RQT2735	14RQT2935	14RQT3035
14RQT3235	14RQT3335	14RQT3535	14RQT3635
14RQT3835	14RQT3935	14RQT4135	14RQT4235
14RQT4435	14RQT4535	14RQT4735	14RQT4835
14RQT5035	14RQT5135	14RQT5335	14RQT5435
14RQT5635	14RQT5735	14RQT5935	14RQT6035
14RQT6235	14RQT6335	14RQT6535	14RQT6635
14RQT6835	14RQT6935	14RQT7135	14RQT7235
14RQT7435	14RQT7535	14RQT7735	14RQT7835
14RQT8035	14RQT8135	14RQT8335	14RQT8435
14RQT8635	14RQT8735	14RQT8935	14RQT9035
15RQT9235	15RQT9335	15RQT9535	15RQT9635
15RQT9835	15RQT9935	15RQT0135	15RQT0235
15RQT0435	14RPT7237	14RPT7337	14RPT7537
14RPT7637	14RPT7837	14RPT7937	14RPT8137
14RPT8237	14RPT8437	14RPT8537	14RPT8737
14RPT8837	14RPT9037	14RPT9137	14RPT9337
14RPT9437	14RPT9637	14RPT9737	14RPT9937
14RQT0037	14RQT0237	14RQT0337	14RQT0537
14RQT0637	14RQT0837	14RQT0937	14RQT1137
14RQT1237	14RQT1437	14RQT1537	14RQT1737
14RQT1837	14RQT2037	14RQT2137	14RQT2337
14RQT2437	14RQT2637	14RQT2737	14RQT2937

14RQT3037	14RQT3237	14RQT3337	14RQT3537
14RQT3637	14RQT3837	14RQT3937	14RQT4137
14RQT4237	14RQT4437	14RQT4537	14RQT4737
14RQT4837	14RQT5037	14RQT5137	14RQT5337
14RQT5437	14RQT5637	14RQT5737	14RQT5937
14RQT6037	14RQT6237	14RQT6337	14RQT6537
14RQT6637	14RQT6837	14RQT6937	14RQT7137
14RQT7237	14RQT7437	14RQT7537	14RQT7737
14RQT7837	14RQT8037	14RQT8137	14RQT8337
14RQT8437	14RQT8637	14RQT8737	14RQT8937
14RQT9037	15RQT9237	15RQT9337	15RQT9537
15RQT9637	15RQT9837	15RQT9937	15RQT0137
15RQT0237	15RQT0437	15RQT0537	15RQT0737
14RPT7238	14RPT7338	14RPT7538	14RPT7638
14RPT7838	14RPT7938	14RPT8138	14RPT8238
14RPT8438	14RPT8538	14RPT8738	14RPT8838
14RPT9038	14RPT9138	14RPT9338	14RPT9438
14RPT9638	14RPT9738	14RPT9938	14RQT0038
14RQT0238	14RQT0338	14RQT0538	14RQT0638
14RQT0838	14RQT0938	14RQT1138	14RQT1238
14RQT1438	14RQT1538	14RQT1738	14RQT1838
14RQT2038	14RQT2138	14RQT2338	14RQT2438
14RQT2638	14RQT2738	14RQT2938	14RQT3038
14RQT3238	14RQT3338	14RQT3538	14RQT3638
14RQT3838	14RQT3938	14RQT4138	14RQT4238
14RQT4438	14RQT4538	14RQT4738	14RQT4838
14RQT5038	14RQT5138	14RQT5338	14RQT5438
14RQT5638	14RQT5738	14RQT5938	14RQT6038
14RQT6238	14RQT6338	14RQT6538	14RQT6638
14RQT6838	14RQT6938	14RQT7138	14RQT7238
14RQT7438	14RQT7538	14RQT7738	14RQT7838
14RQT8038	14RQT8138	14RQT8338	14RQT8438
14RQT8638	14RQT8738	14RQT8938	14RQT9038
15RQT9238	15RQT9338	15RQT9538	15RQT9638
15RQT9838	15RQT9938	15RQT0138	15RQT0238
15RQT0438	15RQT0538	15RQT0738	14RPT7240
14RPT7340	14RPT7540	14RPT7640	14RPT7840
14RPT7940	14RPT8140	14RPT8240	14RPT8440
14RPT8540	14RPT8740	14RPT8840	14RPT9040
14RPT9140	14RPT9340	14RPT9440	14RPT9640
14RPT9740	14RPT9940	14RQT0040	14RQT0240
14RQT0340	14RQT0540	14RQT0640	14RQT0840
14RQT0940	14RQT1140	14RQT1240	14RQT1440
14RQT1540	14RQT1740	14RQT1840	14RQT2040
14RQT2140	14RQT2340	14RQT2440	14RQT2640
14RQT2740	14RQT2940	14RQT3040	14RQT3240
14RQT3340	14RQT3540	14RQT3640	14RQT3840
14RQT3940	14RQT4140	14RQT4240	14RQT4440
14RQT4540	14RQT4740	14RQT4840	14RQT5040
14RQT5140	14RQT5340	14RQT5440	14RQT5640
14RQT5740	14RQT5940	14RQT6040	14RQT6240
14RQT6340	14RQT6540	14RQT6640	14RQT6840
14RQT6940	14RQT7140	14RQT7240	14RQT7440
14RQT7540	14RQT7740	14RQT7840	14RQT8040
14RQT8140	14RQT8340	14RQT8440	14RQT8640



14RQT8740	14RQT8940	14RQT9040	15RQT9240
15RQT9340	15RQT9540	15RQT9640	15RQT9840
15RQT9940	15RQT0140	15RQT0240	15RQT0440
15RQT0540	15RQT0740	14RPT7241	14RPT7341
14RPT7541	14RPT7641	14RPT7841	14RPT7941
14RPT8141	14RPT8241	14RPT8441	14RPT8541
14RPT8741	14RPT8841	14RPT9041	14RPT9141
14RPT9341	14RPT9441	14RPT9641	14RPT9741
14RPT9941	14RQT0041	14RQT0241	14RQT0341
14RQT0541	14RQT0641	14RQT0841	14RQT0941
14RQT1141	14RQT1241	14RQT1441	14RQT1541
14RQT1741	14RQT1841	14RQT2041	14RQT2141
14RQT2341	14RQT2441	14RQT2641	14RQT2741
14RQT2941	14RQT3041	14RQT3241	14RQT3341
14RQT3541	14RQT3641	14RQT3841	14RQT3941
14RQT4141	14RQT4241	14RQT4441	14RQT4541
14RQT4741	14RQT4841	14RQT5041	14RQT5141
14RQT5341	14RQT5441	14RQT5641	14RQT5741
14RQT5941	14RQT6041	14RQT6241	14RQT6341
14RQT6541	14RQT6641	14RQT6841	14RQT6941
14RQT7141	14RQT7241	14RQT7441	14RQT7541
14RQT7741	14RQT7841	14RQT8041	14RQT8141
14RQT8341	14RQT8441	14RQT8641	14RQT8741
14RQT8941	14RQT9041	15RQT9241	15RQT9341
15RQT9541	15RQT9641	15RQT9841	15RQT9941
15RQT0141	15RQT0241	15RQT0441	15RQT0541
15RQT0741	14RPT7243	14RPT7343	14RPT7543
14RPT7643	14RPT7843	14RPT7943	14RPT8143
14RPT8243	14RPT8443	14RPT8543	14RPT8743
14RPT8843	14RPT9043	14RPT9143	14RPT9343
14RPT9443	14RPT9643	14RPT9743	14RPT9943
14RQT0043	14RQT0243	14RQT0343	14RQT0543
14RQT0643	14RQT0843	14RQT0943	14RQT1143
14RQT1243	14RQT1443	14RQT1543	14RQT1743
14RQT1843	14RQT2043	14RQT2143	14RQT2343
14RQT2443	14RQT2643	14RQT2743	14RQT2943
14RQT3043	14RQT3243	14RQT3343	14RQT3543
14RQT3643	14RQT3843	14RQT3943	14RQT4143
14RQT4243	14RQT4443	14RQT4543	14RQT4743
14RQT4843	14RQT5043	14RQT5143	14RQT5343
14RQT5443	14RQT5643	14RQT5743	14RQT5943
14RQT6043	14RQT6243	14RQT6343	14RQT6543
14RQT6643	14RQT6843	14RQT6943	14RQT7143
14RQT7243	14RQT7443	14RQT7543	14RQT7743
14RQT7843	14RQT8043	14RQT8143	14RQT8343
14RQT8443	14RQT8643	14RQT8743	14RQT8943
14RQT9043	15RQT9243	15RQT9343	15RQT9543
15RQT9643	15RQT9843	15RQT9943	15RQT0143
15RQT0243	14RPT7244	14RPT7344	14RPT7544
14RPT7644	14RPT7844	14RPT7944	14RPT8144
14RPT8244	14RPT8444	14RPT8544	14RPT8744
14RPT8844	14RPT9044	14RPT9144	14RPT9344
14RPT9444	14RPT9644	14RPT9744	14RPT9944
14RQT0044	14RQT0244	14RQT0344	14RQT0544
14RQT0644	14RQT0844	14RQT0944	14RQT1144

14RQT1244	14RQT1444	14RQT1544	14RQT1744
14RQT1844	14RQT2044	14RQT2144	14RQT2344
14RQT2444	14RQT2644	14RQT2744	14RQT2944
14RQT3044	14RQT3244	14RQT3344	14RQT3544
14RQT3644	14RQT3844	14RQT3944	14RQT4144
14RQT4244	14RQT4444	14RQT4544	14RQT4744
14RQT4844	14RQT5044	14RQT5144	14RQT5344
14RQT5444	14RQT5644	14RQT5744	14RQT5944
14RQT6044	14RQT6244	14RQT6344	14RQT6544
14RQT6644	14RQT6844	14RQT6944	14RQT7144
14RQT7244	14RQT7444	14RQT7544	14RQT7744
14RQT7844	14RQT8044	14RQT8144	14RQT8344
14RQT8444	14RQT8644	14RQT8744	14RQT8944
14RQT9044	15RQT9244	15RQT9344	15RQT9544
15RQT9644	15RQT9844	15RQT9944	15RQT0144
14RPT7246	14RPT7346	14RPT7546	14RPT7646
14RPT7846	14RPT7946	14RPT8146	14RPT8246
14RPT8446	14RPT8546	14RPT8746	14RPT8846
14RPT9046	14RPT9146	14RPT9346	14RPT9446
14RPT9646	14RPT9746	14RPT9946	14RQT0046
14RQT0246	14RQT0346	14RQT0546	14RQT0646
14RQT0846	14RQT0946	14RQT1146	14RQT1246
14RQT1446	14RQT1546	14RQT1746	14RQT1846
14RQT2046	14RQT2146	14RQT2346	14RQT2446
14RQT2646	14RQT2746	14RQT2946	14RQT3046
14RQT3246	14RQT3346	14RQT3546	14RQT3646
14RQT3846	14RQT3946	14RQT4146	14RQT4246
14RQT4446	14RQT4546	14RQT4746	14RQT4846
14RQT5046	14RQT5146	14RQT5346	14RQT5446
14RQT5646	14RQT5746	14RQT5946	14RQT6046
14RQT6246	14RQT6346	14RQT6546	14RQT6646
14RQT6846	14RQT6946	14RQT7146	14RQT7246
14RQT7446	14RQT7546	14RQT7746	14RQT7846
14RQT8046	14RQT8146	14RQT8346	14RQT8446
14RQT8646	14RQT8746	14RQT8946	14RQT9046
15RQT9246	15RQT9346	15RQT9546	15RQT9646
15RQT9846	15RQT9946	15RQT0146	14RPT7247
14RPT7347	14RPT7547	14RPT7647	14RPT7847
14RPT7947	14RPT8147	14RPT8247	14RPT8447
14RPT8547	14RPT8747	14RPT8847	14RPT9047
14RPT9147	14RPT9347	14RPT9447	14RPT9647
14RPT9747	14RPT9947	14RQT0047	14RQT0247
14RQT0347	14RQT0547	14RQT0647	14RQT0847
14RQT0947	14RQT1147	14RQT1247	14RQT1447
14RQT1547	14RQT1747	14RQT1847	14RQT2047
14RQT2147	14RQT2347	14RQT2447	14RQT2647
14RQT2747	14RQT2947	14RQT3047	14RQT3247
14RQT3347	14RQT3547	14RQT3647	14RQT3847
14RQT3947	14RQT4147	14RQT4247	14RQT4447
14RQT4547	14RQT4747	14RQT4847	14RQT5047
14RQT5147	14RQT5347	14RQT5447	14RQT5647
14RQT5747	14RQT5947	14RQT6047	14RQT6247
14RQT6347	14RQT6547	14RQT6647	14RQT6847
14RQT6947	14RQT7147	14RQT7247	14RQT7447
14RQT7547	14RQT7747	14RQT7847	14RQT8047

14RQT8147	14RQT8347	14RQT8447	14RQT8647
14RQT8747	14RQT8947	14RQT9047	15RQT9247
15RQT9347	15RQT9547	15RQT9647	15RQT9847
15RQT0147	14RPT7249	14RPT7349	14RPT7549
14RPT7649	14RPT7849	14RPT7949	14RPT8149
14RPT8249	14RPT8449	14RPT8549	14RPT8749
14RPT8849	14RPT9049	14RPT9149	14RPT9349
14RPT9449	14RPT9649	14RPT9749	14RPT9949
14RQT0049	14RQT0249	14RQT0349	14RQT0549
14RQT0649	14RQT0849	14RQT0949	14RQT1149
14RQT1249	14RQT1449	14RQT1549	14RQT1749
14RQT1849	14RQT2049	14RQT2149	14RQT2349
14RQT2449	14RQT2649	14RQT2749	14RQT2949
14RQT3049	14RQT3249	14RQT3349	14RQT3549
14RQT3649	14RQT3849	14RQT3949	14RQT4149
14RQT4249	14RQT4449	14RQT4549	14RQT4749
14RQT4849	14RQT5049	14RQT5149	14RQT5349
14RQT5449	14RQT5649	14RQT5749	14RQT5949
14RQT6049	14RQT6249	14RQT6349	14RQT6549
14RQT6649	14RQT6849	14RQT6949	14RQT7149
14RQT7249	14RQT7449	14RQT7549	14RQT7749
14RQT7849	14RQT8049	14RQT8149	14RQT8349
14RQT8449	14RQT8649	14RQT8749	14RQT8949
14RQT9049	15RQT9249	15RQT9349	15RQT9549
15RQT9649	15RQT9849	14RPT7250	14RPT7350
14RPT7550	14RPT7650	14RPT7850	14RPT7950
14RPT8150	14RPT8250	14RPT8450	14RPT8550
14RPT8750	14RPT8850	14RPT9050	14RPT9150
14RPT9350	14RPT9450	14RPT9650	14RPT9750
14RPT9950	14RQT0050	14RQT0250	14RQT0350
14RQT0550	14RQT0650	14RQT0850	14RQT0950
14RQT1150	14RQT1250	14RQT1450	14RQT1550
14RQT1750	14RQT1850	14RQT2050	14RQT2150
14RQT2350	14RQT2450	14RQT2650	14RQT2750
14RQT2950	14RQT3050	14RQT3250	14RQT3350
14RQT3550	14RQT3650	14RQT3850	14RQT3950
14RQT4150	14RQT4250	14RQT4450	14RQT4550
14RQT4750	14RQT4850	14RQT5050	14RQT5150
14RQT5350	14RQT5450	14RQT5650	14RQT5750
14RQT5950	14RQT6050	14RQT6250	14RQT6350
14RQT6550	14RQT6650	14RQT6850	14RQT6950
14RQT7150	14RQT7250	14RQT7450	14RQT7550
14RQT7750	14RQT7850	14RQT8050	14RQT8150
14RQT8350	14RQT8450	14RQT8650	14RQT8750
14RQT8950	14RQT9050	15RQT9250	15RQT9350
15RQT9550	14RPT7252	14RPT7352	14RPT7552
14RPT7652	14RPT7852	14RPT7952	14RPT8152
14RPT8252	14RPT8452	14RPT8552	14RPT8752
14RPT8852	14RPT9052	14RPT9152	14RPT9352
14RPT9452	14RPT9652	14RPT9752	14RPT9952
14RQT0052	14RQT0252	14RQT0352	14RQT0552
14RQT0652	14RQT0852	14RQT0952	14RQT1152
14RQT1252	14RQT1452	14RQT1552	14RQT1752
14RQT1852	14RQT2052	14RQT2152	14RQT2352
14RQT2452	14RQT2652	14RQT2752	14RQT2952

14RQT3052 14RQT3252 14RQT3352 14RQT3552  
14RQT3652 14RQT3852 14RQT3952 14RQT4152  
14RQT4252 14RQT4452 14RQT4552 14RQT4752  
14RQT4852 14RQT5052 14RQT5152 14RQT5352  
14RQT5452 14RQT5652 14RQT5752 14RQT5952  
14RQT6052 14RQT6252 14RQT6352 14RQT6552  
14RQT6652 14RQT6852 14RQT6952 14RQT7152  
14RQT7252 14RQT7452 14RQT7552 14RQT7752  
14RQT7852 14RQT8052 14RQT8152 14RQT8352  
14RQT8452 14RQT8652 14RQT8752 14RQT8952  
14RQT9052 15RQT9252 15RQT9352 15RQT9552  
14RPT7253 14RPT7353 14RPT7553 14RPT7653  
14RPT7853 14RPT7953 14RPT8153 14RPT8253  
14RPT8453 14RPT8553 14RPT8753 14RPT8853  
14RPT9053 14RPT9153 14RPT9353 14RPT9453  
14RPT9653 14RPT9753 14RPT9953 14RQT0053  
14RQT0253 14RQT0353 14RQT0553 14RQT0653  
14RQT0853 14RQT0953 14RQT1153 14RQT1253  
14RQT1453 14RQT1553 14RQT1753 14RQT1853  
14RQT2053 14RQT2153 14RQT2353 14RQT2453  
14RQT2653 14RQT2753 14RQT2953 14RQT3053  
14RQT3253 14RQT3353 14RQT3553 14RQT3653  
14RQT3853 14RQT3953 14RQT4153 14RQT4253  
14RQT4453 14RQT4553 14RQT4753 14RQT4853  
14RQT5053 14RQT5153 14RQT5353 14RQT5453  
14RQT5653 14RQT5753 14RQT5953 14RQT6053  
14RQT6253 14RQT6353 14RQT6553 14RQT6653  
14RQT6853 14RQT6953 14RQT7153 14RQT7253  
14RQT7453 14RQT7553 14RQT7753 14RQT7853  
14RQT8053 14RQT8153 14RQT8353 14RQT8453  
14RQT8653 14RQT8753 14RQT8953 14RQT9053  
15RQT9253 15RQT9353 15RQT9553 14RPT7255  
14RPT7355 14RPT7555 14RPT7655 14RPT7855  
14RPT7955 14RPT8155 14RPT8255 14RPT8455  
14RPT8555 14RPT8755 14RPT8855 14RPT9055  
14RPT9155 14RPT9355 14RPT9455 14RPT9655  
14RPT9755 14RPT9955 14RQT0055 14RQT0255  
14RQT0355 14RQT0555 14RQT0655 14RQT0855  
14RQT0955 14RQT1155 14RQT1255 14RQT1455  
14RQT1555 14RQT1755 14RQT1855 14RQT2055  
14RQT2155 14RQT2355 14RQT2455 14RQT2655  
14RQT2755 14RQT2955 14RQT3055 14RQT3255  
14RQT3355 14RQT3555 14RQT3655 14RQT3855  
14RQT3955 14RQT4155 14RQT4255 14RQT4455  
14RQT4555 14RQT4755 14RQT4855 14RQT5055  
14RQT5155 14RQT5355 14RQT5455 14RQT5655  
14RQT5755 14RQT5955 14RQT6055 14RQT6255  
14RQT6355 14RQT6555 14RQT6655 14RQT6855  
14RQT6955 14RQT7155 14RQT7255 14RQT7455  
14RQT7555 14RQT7755 14RQT7855 14RQT8055  
14RQT8155 14RQT8355 14RQT8455 14RQT8655  
14RQT8755 14RQT8955 14RQT9055 15RQT9255  
14RPT7256 14RPT7356 14RPT7556 14RPT7656  
14RPT7856 14RPT7956 14RPT8156 14RPT8256  
14RPT8456 14RPT8556 14RPT8756 14RPT8856

14RPT9056	14RPT9156	14RPT9356	14RPT9456
14RPT9656	14RPT9756	14RPT9956	14RQT0056
14RQT0256	14RQT0356	14RQT0556	14RQT0656
14RQT0856	14RQT0956	14RQT1156	14RQT1256
14RQT1456	14RQT1556	14RQT1756	14RQT1856
14RQT2056	14RQT2156	14RQT2356	14RQT2456
14RQT2656	14RQT2756	14RQT2956	14RQT3056
14RQT3256	14RQT3356	14RQT3556	14RQT3656
14RQT3856	14RQT3956	14RQT4156	14RQT4256
14RQT4456	14RQT4556	14RQT4756	14RQT4856
14RQT5056	14RQT5156	14RQT5356	14RQT5456
14RQT5656	14RQT5756	14RQT5956	14RQT6056
14RQT6256	14RQT6356	14RQT6556	14RQT6656
14RQT6856	14RQT6956	14RQT7156	14RQT7256
14RQT7456	14RQT7556	14RQT7756	14RQT7856
14RQT8056	14RQT8156	14RQT8356	14RQT8456
14RQT8656	14RQT8756	14RQT8956	14RQT9056
15RQT9256	14RPT7258	14RPT7358	14RPT7558
14RPT7658	14RPT7858	14RPT7958	14RPT8158
14RPT8258	14RPT8458	14RPT8558	14RPT8758
14RPT8858	14RPT9058	14RPT9158	14RPT9358
14RPT9458	14RPT9658	14RPT9758	14RPT9958
14RQT0058	14RQT0258	14RQT0358	14RQT0558
14RQT0658	14RQT0858	14RQT0958	14RQT1158
14RQT1258	14RQT1458	14RQT1558	14RQT1758
14RQT1858	14RQT2058	14RQT2158	14RQT2358
14RQT2458	14RQT2658	14RQT2758	14RQT2958
14RQT3058	14RQT3258	14RQT3358	14RQT3558
14RQT3658	14RQT3858	14RQT3958	14RQT4158
14RQT4258	14RQT4458	14RQT4558	14RQT4758
14RQT4858	14RQT5058	14RQT5158	14RQT5358
14RQT5458	14RQT5658	14RQT5758	14RQT5958
14RQT6058	14RQT6258	14RQT6358	14RQT6558
14RQT6658	14RQT6858	14RQT6958	14RQT7158
14RQT7258	14RQT7458	14RQT7558	14RQT7758
14RQT7858	14RQT8058	14RQT8158	14RQT8358
14RQT8458	14RQT8658	14RQT8758	14RQT8958
14RQT9058	15RQT9258	14RPT7259	14RPT7359
14RPT7559	14RPT7659	14RPT7859	14RPT7959
14RPT8159	14RPT8259	14RPT8459	14RPT8559
14RPT8759	14RPT8859	14RPT9059	14RPT9159
14RPT9359	14RPT9459	14RPT9659	14RPT9759
14RPT9959	14RQT0059	14RQT0259	14RQT0359
14RQT0559	14RQT0659	14RQT0859	14RQT0959
14RQT1159	14RQT1259	14RQT1459	14RQT1559
14RQT1759	14RQT1859	14RQT2059	14RQT2159
14RQT2359	14RQT2459	14RQT2659	14RQT2759
14RQT2959	14RQT3059	14RQT3259	14RQT3359
14RQT3559	14RQT3659	14RQT3859	14RQT3959
14RQT4159	14RQT4259	14RQT4459	14RQT4559
14RQT4759	14RQT4859	14RQT5059	14RQT5159
14RQT5359	14RQT5459	14RQT5659	14RQT5759
14RQT5959	14RQT6059	14RQT6259	14RQT6359
14RQT6559	14RQT6659	14RQT6859	14RQT6959
14RQT7159	14RQT7259	14RQT7459	14RQT7559

14RQT7759 14RQT7859 14RQT8059 14RQT8159  
14RQT8359 14RQT8459 14RQT8659 14RQT8759  
14RPT7261 14RPT7361 14RPT7561 14RPT7661  
14RPT7861 14RPT7961 14RPT8161 14RPT8261  
14RPT8461 14RPT8561 14RPT8761 14RPT8861  
14RPT9061 14RPT9161 14RPT9361 14RPT9461  
14RPT9661 14RPT9761 14RPT9961 14RQT0061  
14RQT0261 14RQT0361 14RQT0561 14RQT0661  
14RQT0861 14RQT0961 14RQT1161 14RQT1261  
14RQT1461 14RQT1561 14RQT1761 14RQT1861  
14RQT2061 14RQT2161 14RQT2361 14RQT2461  
14RQT2661 14RQT2761 14RQT2961 14RQT3061  
14RQT3261 14RQT3361 14RQT3561 14RQT3661  
14RQT3861 14RQT3961 14RQT4161 14RQT4261  
14RQT4461 14RQT4561 14RQT4761 14RQT4861  
14RQT5061 14RQT5161 14RQT5361 14RQT5461  
14RQT5661 14RQT5761 14RQT5961 14RQT6061  
14RQT6261 14RQT6361 14RQT6561 14RQT6661  
14RQT6861 14RQT6961 14RQT7161 14RQT7261  
14RQT7461 14RQT7561 14RQT7761 14RQT7861  
14RQT8061 14RQT8161 14RQT8361 14RQT8461  
14RQT8661 14RPT7262 14RPT7362 14RPT7562  
14RPT7662 14RPT7862 14RPT7962 14RPT8162  
14RPT8262 14RPT8462 14RPT8562 14RPT8762  
14RPT8862 14RPT9062 14RPT9162 14RPT9362  
14RPT9462 14RPT9662 14RPT9762 14RPT9962  
14RQT0062 14RQT0262 14RQT0362 14RQT0562  
14RQT0662 14RQT0862 14RQT0962 14RQT1162  
14RQT1262 14RQT1462 14RQT1562 14RQT1762  
14RQT1862 14RQT2062 14RQT2162 14RQT2362  
14RQT2462 14RQT2662 14RQT2762 14RQT2962  
14RQT3062 14RQT3262 14RQT3362 14RQT3562  
14RQT3662 14RQT3862 14RQT3962 14RQT4162  
14RQT4262 14RQT4462 14RQT4562 14RQT4762  
14RQT4862 14RQT5062 14RQT5162 14RQT5362  
14RQT5462 14RQT5662 14RQT5762 14RQT5962  
14RQT6062 14RQT6262 14RQT6362 14RQT6562  
14RQT6662 14RQT6862 14RQT6962 14RQT7162  
14RQT7262 14RQT7462 14RQT7562 14RQT7762  
14RQT7862 14RQT8062 14RQT8162 14RQT8362  
14RQT8462 14RPT7264 14RPT7364 14RPT7564  
14RPT7664 14RPT7864 14RPT7964 14RPT8164  
14RPT8264 14RPT8464 14RPT8564 14RPT8764  
14RPT8864 14RPT9064 14RPT9164 14RPT9364  
14RPT9464 14RPT9664 14RPT9764 14RPT9964  
14RQT0064 14RQT0264 14RQT0364 14RQT0564  
14RQT0664 14RQT0864 14RQT0964 14RQT1164  
14RQT1264 14RQT1464 14RQT1564 14RQT1764  
14RQT1864 14RQT2064 14RQT2164 14RQT2364  
14RQT2464 14RQT2664 14RQT2764 14RQT2964  
14RQT3064 14RQT3264 14RQT3364 14RQT3564  
14RQT3664 14RQT3864 14RQT3964 14RQT4164  
14RQT4264 14RQT4464 14RQT4564 14RQT4764  
14RQT4864 14RQT5064 14RQT5164 14RQT5364  
14RQT5464 14RQT5664 14RQT5764 14RQT5964

14RQT6064	14RQT6264	14RQT6364	14RQT6564
14RQT6664	14RQT6864	14RQT6964	14RQT7164
14RQT7264	14RQT7464	14RQT7564	14RQT7764
14RQT7864	14RQT8064	14RQT8164	14RQT8364
14RQT8464	14RPT7265	14RPT7365	14RPT7565
14RPT7665	14RPT7865	14RPT7965	14RPT8165
14RPT8265	14RPT8465	14RPT8565	14RPT8765
14RPT8865	14RPT9065	14RPT9165	14RPT9365
14RPT9465	14RPT9665	14RPT9765	14RPT9965
14RQT0065	14RQT0265	14RQT0365	14RQT0565
14RQT0665	14RQT0865	14RQT0965	14RQT1165
14RQT1265	14RQT1465	14RQT1565	14RQT1765
14RQT1865	14RQT2065	14RQT2165	14RQT2365
14RQT2465	14RQT2665	14RQT2765	14RQT2965
14RQT3065	14RQT3265	14RQT3365	14RQT3565
14RQT3665	14RQT3865	14RQT3965	14RQT4165
14RQT4265	14RQT4465	14RQT4565	14RQT4765
14RQT4865	14RQT5065	14RQT5165	14RQT5365
14RQT5465	14RQT5665	14RQT5765	14RQT5965
14RQT6065	14RQT6265	14RQT6365	14RQT6565
14RQT6665	14RQT6865	14RQT6965	14RQT7165
14RQT7265	14RQT7465	14RQT7565	14RQT7765
14RQT7865	14RQT8065	14RQT8165	14RQT8365
14RQT8465	14RPT7267	14RPT7367	14RPT7567
14RPT7667	14RPT7867	14RPT7967	14RPT8167
14RPT8267	14RPT8467	14RPT8567	14RPT8767
14RPT8867	14RPT9067	14RPT9167	14RPT9367
14RPT9467	14RPT9667	14RPT9767	14RPT9967
14RQT0067	14RQT0267	14RQT0367	14RQT0567
14RQT0667	14RQT0867	14RQT0967	14RQT1167
14RQT1267	14RQT1467	14RQT1567	14RQT1767
14RQT1867	14RQT2067	14RQT2167	14RQT2367
14RQT2467	14RQT2667	14RQT2767	14RQT2967
14RQT3067	14RQT3267	14RQT3367	14RQT3567
14RQT3667	14RQT3867	14RQT3967	14RQT4167
14RQT4267	14RQT4467	14RQT4567	14RQT4767
14RQT4867	14RQT5067	14RQT5167	14RQT5367
14RQT5467	14RQT5667	14RQT5767	14RQT5967
14RQT6067	14RQT6267	14RQT6367	14RQT6567
14RQT6667	14RQT6867	14RQT6967	14RQT7167
14RQT7267	14RQT7467	14RQT7567	14RQT7767
14RQT7867	14RQT8067	14RQT8167	14RQT8367
14RQT8467	14RPT7268	14RPT7368	14RPT7568
14RPT7668	14RPT7868	14RPT7968	14RPT8168
14RPT8268	14RPT8468	14RPT8568	14RPT8768
14RPT8868	14RPT9068	14RPT9168	14RPT9368
14RPT9468	14RPT9668	14RPT9768	14RPT9968
14RQT0068	14RQT0268	14RQT0368	14RQT0568
14RQT0668	14RQT0868	14RQT0968	14RQT1168
14RQT1268	14RQT1468	14RQT1568	14RQT1768
14RQT1868	14RQT2068	14RQT2168	14RQT2368
14RQT2468	14RQT2668	14RQT2768	14RQT2968
14RQT3068	14RQT3268	14RQT3368	14RQT3568
14RQT3668	14RQT3868	14RQT3968	14RQT4168
14RQT4268	14RQT4468	14RQT4568	14RQT4768

14RQT4868	14RQT5068	14RQT5168	14RQT5368
14RQT5468	14RQT5668	14RQT5768	14RQT5968
14RQT6068	14RQT6268	14RQT6368	14RQT6568
14RQT6668	14RQT6868	14RQT6968	14RQT7168
14RQT7268	14RQT7468	14RQT7568	14RQT7768
14RQT7868	14RQT8068	14RQT8168	14RQT8368
14RQT8468	14RPT7270	14RPT7370	14RPT7570
14RPT7670	14RPT7870	14RPT7970	14RPT8170
14RPT8270	14RPT8470	14RPT8570	14RPT8770
14RPT8870	14RPT9070	14RPT9170	14RPT9370
14RPT9470	14RPT9670	14RPT9770	14RPT9970
14RQT0070	14RQT0270	14RQT0370	14RQT0570
14RQT0670	14RQT0870	14RQT0970	14RQT1170
14RQT1270	14RQT1470	14RQT1570	14RQT1770
14RQT1870	14RQT2070	14RQT2170	14RQT2370
14RQT2470	14RQT2670	14RQT2770	14RQT2970
14RQT3070	14RQT3270	14RQT3370	14RQT3570
14RQT3670	14RQT3870	14RQT3970	14RQT4170
14RQT4270	14RQT4470	14RQT4570	14RQT4770
14RQT4870	14RQT5070	14RQT5170	14RQT5370
14RQT5470	14RQT5670	14RQT5770	14RQT5970
14RQT6070	14RQT6270	14RQT6370	14RQT6570
14RQT6670	14RQT6870	14RQT6970	14RQT7170
14RQT7270	14RQT7470	14RQT7570	14RQT7770
14RQT7870	14RQT8070	14RQT8170	14RQT8370
14RQT8470	14RPT7271	14RPT7371	14RPT7571
14RPT7671	14RPT7871	14RPT7971	14RPT8171
14RPT8271	14RPT8471	14RPT8571	14RPT8771
14RPT8871	14RPT9071	14RPT9171	14RPT9371
14RPT9471	14RPT9671	14RPT9771	14RPT9971
14RQT0071	14RQT0271	14RQT0371	14RQT0571
14RQT0671	14RQT0871	14RQT0971	14RQT1171
14RQT1271	14RQT1471	14RQT1571	14RQT1771
14RQT1871	14RQT2071	14RQT2171	14RQT2371
14RQT2471	14RQT2671	14RQT2771	14RQT2971
14RQT3071	14RQT3271	14RQT3371	14RQT3571
14RQT3671	14RQT3871	14RQT3971	14RQT4171
14RQT4271	14RQT4471	14RQT4571	14RQT4771
14RQT4871	14RQT5071	14RQT5171	14RQT5371
14RQT5471	14RQT5671	14RQT5771	14RQT5971
14RQT6071	14RQT6271	14RQT6371	14RQT6571
14RQT6671	14RQT6871	14RQT6971	14RQT7171
14RQT7271	14RQT7471	14RQT7571	14RQT7771
14RQT7871	14RQT8071	14RQT8171	14RQT8371
14RQT8471	14RPT7373	14RPT7573	14RPT7673
14RPT7873	14RPT7973	14RPT8173	14RPT8273
14RPT8473	14RPT8573	14RPT8773	14RPT8873
14RPT9073	14RPT9173	14RPT9373	14RPT9473
14RPT9673	14RPT9773	14RPT9973	14RQT0073
14RQT0273	14RQT0373	14RQT0573	14RQT0673
14RQT0873	14RQT0973	14RQT1173	14RQT1273
14RQT1473	14RQT1573	14RQT1773	14RQT1873
14RQT2073	14RQT2173	14RQT2373	14RQT2473
14RQT2673	14RQT2773	14RQT2973	14RQT3073
14RQT3273	14RQT3373	14RQT3573	14RQT3673




14RQT3873	14RQT3973	14RQT4173	14RQT4273
14RQT4473	14RQT4573	14RQT4773	14RQT4873
14RQT5073	14RQT5173	14RQT5373	14RQT5473
14RQT5673	14RQT5773	14RQT5973	14RQT6073
14RQT6273	14RQT6373	14RQT6573	14RQT6673
14RQT6873	14RQT6973	14RQT7173	14RQT7273
14RQT7473	14RQT7573	14RQT7773	14RQT7873
14RQT8073	14RQT8173	14RQT8373	14RQT8473
14RPT7374	14RPT7574	14RPT7674	14RPT7874
14RPT7974	14RPT8174	14RPT8274	14RPT8474
14RPT8574	14RPT8774	14RPT8874	14RPT9074
14RPT9174	14RPT9374	14RPT9474	14RPT9674
14RPT9774	14RPT9974	14RQT0074	14RQT0274
14RQT0374	14RQT0574	14RQT0674	14RQT0874
14RQT0974	14RQT1174	14RQT1274	14RQT1474
14RQT1574	14RQT1774	14RQT1874	14RQT2074
14RQT2174	14RQT2374	14RQT2474	14RQT2674
14RQT2774	14RQT2974	14RQT3074	14RQT3274
14RQT3374	14RQT3574	14RQT3674	14RQT3874
14RQT3974	14RQT4174	14RQT4274	14RQT4474
14RQT4574	14RQT4774	14RQT4874	14RQT5074
14RQT5174	14RQT5374	14RQT5474	14RQT5674
14RQT5774	14RQT5974	14RQT6074	14RQT6274
14RQT6374	14RQT6574	14RQT6674	14RQT6874
14RQT6974	14RQT7174	14RQT7274	14RQT7474
14RQT7574	14RQT7774	14RQT7874	14RQT8074
14RQT8174	14RQT8374	14RQT8474	14RPT7376
14RPT7576	14RPT7676	14RPT7876	14RPT7976
14RPT8176	14RPT8276	14RPT8476	14RPT8576
14RPT8776	14RPT8876	14RPT9076	14RPT9176
14RPT9376	14RPT9476	14RPT9676	14RPT9776
14RPT9976	14RQT0076	14RQT0276	14RQT0376
14RQT0576	14RQT0676	14RQT0876	14RQT0976
14RQT1176	14RQT1276	14RQT1476	14RQT1576
14RQT1776	14RQT1876	14RQT2076	14RQT2176
14RQT2376	14RQT2476	14RQT2676	14RQT2776
14RQT2976	14RQT3076	14RQT3276	14RQT3376
14RQT3576	14RQT3676	14RQT3876	14RQT3976
14RQT4176	14RQT4276	14RQT4476	14RQT4576
14RQT4776	14RQT4876	14RQT5076	14RQT5176
14RQT5376	14RQT5476	14RQT5676	14RQT5776
14RQT5976	14RQT6076	14RQT6276	14RQT6376
14RQT6576	14RQT6676	14RQT6876	14RQT6976
14RQT7176	14RQT7276	14RQT7476	14RQT7576
14RQT7776	14RQT7876	14RQT8076	14RQT8176
14RQT8376	14RQT8476	14RPT7677	14RPT7877
14RPT7977	14RPT8177	14RPT8277	14RPT8477
14RPT8577	14RPT8777	14RPT8877	14RPT9077
14RPT9177	14RPT9377	14RPT9477	14RPT9677
14RPT9777	14RPT9977	14RQT0077	14RQT0277
14RQT0377	14RQT0577	14RQT0677	14RQT0877
14RQT0977	14RQT1177	14RQT1277	14RQT1477
14RQT1577	14RQT1777	14RQT1877	14RQT2077
14RQT2177	14RQT2377	14RQT2477	14RQT2677
14RQT2777	14RQT2977	14RQT3077	14RQT3277

14RQT3377 14RQT3577 14RQT3677 14RQT3877  
14RQT3977 14RQT4177 14RQT4277 14RQT4477  
14RQT4577 14RQT4777 14RQT4877 14RQT5077  
14RQT5177 14RQT5377 14RQT5477 14RQT5677  
14RQT5777 14RQT5977 14RQT6077 14RQT6277  
14RQT6377 14RQT6577 14RQT6677 14RQT6877  
14RQT6977 14RQT7177 14RQT7277 14RQT7477  
14RQT7577 14RPT7679 14RPT7879 14RPT7979  
14RPT8179 14RPT8279 14RPT8479 14RPT8579  
14RPT8779 14RPT8879 14RPT9079 14RPT9179  
14RPT9379 14RPT9479 14RPT9679 14RPT9779  
14RPT9979 14RQT0079 14RQT0279 14RQT0379  
14RQT0579 14RQT0679 14RQT0879 14RQT0979  
14RQT1179 14RQT1279 14RQT1479 14RQT1579  
14RQT1779 14RQT1879 14RQT2079 14RQT2179  
14RQT2379 14RQT2479 14RQT2679 14RQT2779  
14RQT2979 14RQT3079 14RQT3279 14RQT3379  
14RQT3579 14RQT3679 14RQT3879 14RQT3979  
14RQT4179 14RQT4279 14RQT4479 14RQT4579  
14RQT4779 14RQT4879 14RQT5079 14RQT5179  
14RQT5379 14RQT5479 14RQT5679 14RQT5779  
14RQT5979 14RQT6079 14RQT6279 14RQT6379  
14RQT6579 14RQT6679 14RQT6879 14RQT6979  
14RQT7179 14RQT7279 14RQT7479 14RQT7579  
14RQT0580 14RQT0680 14RQT0880 14RQT0980  
14RQT1180 14RQT1280 14RQT1480 14RQT1580  
14RQT1780 14RQT1880 14RQT2080 14RQT2180  
14RQT2380 14RQT2480 14RQT2680 14RQT2780  
14RQT2980 14RQT3080 14RQT3280 14RQT3380  
14RQT3580 14RQT3680 14RQT3880 14RQT3980  
14RQT4180 14RQT4280 14RQT4480 14RQT4580  
14RQT4780 14RQT4880 14RQT5080 14RQT5180  
14RQT5380 14RQT5480 14RQT5680 14RQT5780  
14RQT5980 14RQT6080 14RQT6280 14RQT6380  
14RQT6580 14RQT6680 14RQT6880 14RQT6980  
14RQT7180 14RQT7280 14RQT7480 14RQT7580  
14RQT0682 14RQT0882 14RQT0982 14RQT1182  
14RQT1282 14RQT1482 14RQT1582 14RQT1782  
14RQT1882 14RQT2082 14RQT2182 14RQT2382  
14RQT2482 14RQT2682 14RQT2782 14RQT2982  
14RQT3082 14RQT3282 14RQT3382 14RQT0883  
14RQT0983 14RQT1183 14RQT1283 14RQT1483  
14RQT1583 14RQT1783 14RQT1883 14RQT2083  
14RQT2183 14RQT2383 14RQT2483 14RQT2683  
14RQT2783 14RQT2983 14RQT3083 14RQT3283  
14RQT0885 14RQT0985 14RQT1185 14RQT1285  
14RQT1485 14RQT1585 14RQT1785 14RQT1885  
14RQT2085 14RQT2185 14RQT2385 14RQT2485  
14RQT2685 14RQT2785 14RQT2985 14RQT0986  
14RQT1186 14RQT1286 14RQT1486 14RQT1586  
14RQT1786 14RQT1886 14RQT2086 14RQT2186  
14RQT2386 14RQT2486 14RQT2686 14RQT2786  
14RQT2986 14RQT1188 14RQT1288 14RQT1488  
14RQT1588


## Appendix D: GPS Processing

### Mission 01/05/2018 A


#### 20180105\_201925 [Smoothed TC Combined] - Smoothed TC Combined – Map




#### 20180105\_201925 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot





### 20180105\_201925 [Smoothed TC Combined] - PDOP Plot



### 20180105\_201925 [Smoothed TC Combined] - Number of Satellites Line Plot



### 20180105\_201925 [Smoothed TC Combined] - Accelerometer Bias Plot



### Processing Summery Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180105\_201925\Gns  
 sImu\201801 05\_201925.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 32745  
 No processed  
 position: 134  
 Missing Fwd or Rev: 2  
 With bad C/A code: 0  
 With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 97.6 %  
 Q 2: 2.0 %  
 Q 3: 0.3 %  
 Q 4: 0.0 %  
 Q 5: 0.0 %  
 Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0144 (m)  
 C/A Code: 0.42 (m)  
 L1 Doppler: 0.027 (m/s)

Position Standard Deviation  
 Percentages:

0.00 - 0.10 m: 100.0 %  
 0.10 - 0.30 m: 0.0 %  
 0.30 - 1.00 m: 0.0 %  
 1.00 - 5.00 m: 0.0 %  
 5.00 m +  
 over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.013 (m)  
 North: 0.005 (m)  
 Height: 0.014 (m)

Percentages of epochs with DD\_DOP  
 over

10.00:

DOP over Tol: 4.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
 (32609  
 occurrences):


East: 0.013 (m)  
 North: 0.005 (m)  
 Height: 0.014 (m)

Baseline Distances:


Maximum: 52.815 (km)  
 Minimum: 0.016 (km)  
 Average: 22.005 (km)  
 First Epoch: 0.022 (km)  
 Last Epoch: 0.029 (km)

### Mission 01/05/2018 B


## 20180106\_145247 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180106\_145247 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot



### 20180106\_145247 [Smoothed TC Combined] - PDOP Plot




### 20180106\_145247 [Smoothed TC Combined] - Number of Satellites Line Plot






### 20180106\_145247 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180106\_145247 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180106\_145247\Gns  
sImu\20180106\_145247.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 15073  
No processed  
position: 2  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

0.013  
L1 Phase: 6 (m)  
C/A Code: 0.37 (m)  
L1 Doppler: 0.026 (m/s)

Position Standard Deviation  
Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.005 (m)  
North: 0.005 (m)  
Height: 0.006 (m)

Percentages of epochs with DD\_DOP  
over

10.00:

DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(15069 occurrences):


East: 0.005 (m)  
North: 0.005 (m)  
Height: 0.006 (m)

Baseline Distances:


Maximum: 44.539 (km)  
Minimum: 0.086 (km)  
Average: 22.617 (km)  
First Epoch: 0.354 (km)  
Last Epoch: 1.122 (km)

### Mission 01/06/2018 A

## 20180108\_171305 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180108\_171305 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot




### 20180108\_171305 [Smoothed TC Combined] - PDOP Plot




### 20180108\_171305 [Smoothed TC Combined] - Number of Satellites Line Plot



### 20180108\_171305 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180108\_171305 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180108\_171305\Gns  
sImu\20180108\_171305.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 32664  
No processed  
position: 3  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0167 (m)  
C/A Code: 0.37 (m)  
L1 Doppler: 0.029 (m/s)

Position Standard Deviation  
Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.005 (m)  
North: 0.008 (m)  
Height: 0.020 (m)

Percentages of epochs with DD\_DOP  
over

10.00:

DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(32658  
occurrences):


East: 0.005 (m)  
North: 0.008 (m)  
Height: 0.020 (m)

Baseline Distances:


Maximum: 52.962 (km)  
Minimum: 0.053 (km)  
Average: 23.070 (km)  
First Epoch: 0.333 (km)  
Last Epoch: 0.053 (km)

### Mission 01/08/2018 A


## 20180108\_221148 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180108\_221148 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot



### 20180108\_221148 [Smoothed TC Combined] - PDOP Plot




### 20180108\_221148 [Smoothed TC Combined] - Number of Satellites Line Plot






### 20180108\_221148 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180108\_221148 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180108\_221148\Gns  
 sImu\201801 08\_221148.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 14029  
 No processed  
 position: 2  
 Missing Fwd or Rev: 19  
 With bad C/A code: 0  
 With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
 Q 2: 0.0 %  
 Q 3: 0.0 %  
 Q 4: 0.0 %  
 Q 5: 0.0 %  
 Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.017 8 (m)  
 C/A Code: 0.33 (m)  
 L1 Doppler: 0.029 (m/s)

Position Standard Deviation  
 Percentages:

100.0  
 0.00 - 0.10 m: %  
 0.10 - 0.30 m: 0.0 %  
 0.30 - 1.00 m: 0.0 %  
 1.00 - 5.00 m: 0.0 %  
 5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.042 (m)  
 North: 0.011 (m)  
 Height: 0.027 (m)

Percentages of epochs with DD\_DOP  
 over

10.00:  
 DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
 (13687 occurrences):

East: 0.020 (m)  
 North: 0.008 (m)  
 Height: 0.025 (m)

Baseline Distances:

Maximum: 53.892 (km)  
 Minimum: 0.089 (km)  
 Average: 27.467 (km)  
 First Epoch: 0.133 (km)  
 Last Epoch: 52.574 (km)

### Mission 01/09/2018 A


## 20180109\_200529 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180109\_200529 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot




### 20180109\_200529 [Smoothed TC Combined] - PDOP Plot




### 20180109\_200529 [Smoothed TC Combined] - Number of Satellites Line Plot



### 20180109\_200529 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180109\_200529 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180109\_200529\GnssImu\20180109\_200529.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 34008  
No processed position: 3  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.017 (m)  
C/A Code: 0.39 (m)  
L1 Doppler: 0.030 (m/s)

Position Standard Deviation Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.006 (m)  
North: 0.009 (m)  
Height: 0.024 (m)

Percentages of epochs with DD\_DOP over

10.00:  
DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes (34003 occurrences):


East: 0.006 (m)  
North: 0.009 (m)  
Height: 0.024 (m)

Baseline Distances:


Maximum: 56.280 (km)  
Minimum: 0.015 (km)  
Average: 29.864 (km)  
First Epoch: 0.018 (km)  
Last Epoch: 0.350 (km)

### Mission 01/12/2018 A


## 20180112\_195157 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180112\_195157 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot



### 20180112\_195157 [Smoothed TC Combined] - PDOP Plot




### 20180112\_195157 [Smoothed TC Combined] - Number of Satellites Line Plot






### 20180112\_195157 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180112\_195157 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180112\_195157\Gnss  
 Imu\20180112\_195157.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 30660  
 No processed  
 position: 3  
 Missing Fwd or Rev: 2  
 With bad C/A code: 0  
 With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
 Q 2: 0.0 %  
 Q 3: 0.0 %  
 Q 4: 0.0 %  
 Q 5: 0.0 %  
 Q 6: 0.0 %

Measurement RMS Values:

0.021  
 L1 Phase: 3 (m)  
 C/A Code: 0.39 (m)  
 L1 Doppler: 0.029 (m/s)

Position Standard Deviation  
 Percentages:

100.0  
 0.00 - 0.10 m: %  
 0.10 - 0.30 m: 0.0 %  
 0.30 - 1.00 m: 0.0 %  
 1.00 - 5.00 m: 0.0 %  
 5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.009 (m)  
 North: 0.019 (m)  
 Height: 0.041 (m)

Percentages of epochs with DD\_DOP  
 over

10.00:

DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
 (30640  
 occurrences):


East: 0.009 (m)  
 North: 0.019 (m)  
 Height: 0.041 (m)

Baseline Distances:


Maximum: 64.088 (km)  
 Minimum: 0.054 (km)  
 Average: 35.007 (km)  
 First Epoch: 24.598 (km)  
 Last Epoch: 0.054 (km)

### Mission 01/13/2018 A


## 20180113\_005249 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180113\_005249 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot




### 20180113\_005249 [Smoothed TC Combined] - PDOP Plot




### 20180113\_005249 [Smoothed TC Combined] - Number of Satellites Line Plot



### 20180113\_005249 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180113\_005249 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180113\_005249\Gns  
sImu\20180113\_005249.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 33035  
No processed  
position: 2  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0180 (m)  
C/A Code: 0.38 (m)  
L1 Doppler: 0.029 (m/s)

Position Standard Deviation  
Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.010 (m)  
North: 0.008 (m)  
Height: 0.026 (m)

Percentages of epochs with DD\_DOP  
over

10.00:

DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(33030  
occurrences):


East: 0.010 (m)  
North: 0.008 (m)  
Height: 0.026 (m)

Baseline Distances:


Maximum: 71.858 (km)  
Minimum: 0.037 (km)  
Average: 41.904 (km)  
First Epoch: 1.142 (km)  
Last Epoch: 0.037 (km)

### Mission 01/13/2018 B


## 20180113\_061100 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180113\_061100 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot



### 20180113\_061100 [Smoothed TC Combined] - PDOP Plot




### 20180113\_061100 [Smoothed TC Combined] - Number of Satellites Line Plot






### 20180113\_061100 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180113\_061100 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180113\_061100\Gns  
sImu\20180113\_061100.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 28788  
No processed  
position: 3  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0161 (m)  
C/A Code: 0.41 (m)  
L1 Doppler: 0.029 (m/s)

Position Standard Deviation  
Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.007 (m)  
North: 0.005 (m)  
Height: 0.019 (m)

Percentages of epochs with DD\_DOP  
over

10.00:  
DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(28783  
occurrences):


East: 0.007 (m)  
North: 0.005 (m)  
Height: 0.019 (m)

Baseline Distances:


Maximum: 80.534 (km)  
Minimum: 0.052 (km)  
Average: 53.666 (km)  
First Epoch: 1.142 (km)  
Last Epoch: 0.052 (km)

### Mission 01/13/2018 C


## 20180113\_182941 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180113\_182941 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot





### 20180113\_182941 [Smoothed TC Combined] - PDOP Plot



### 20180113\_182941 [Smoothed TC Combined] - Number of Satellites Line Plot



### 20180113\_182941 [Smoothed TC Combined] - Accelerometer Bias Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180113\_182941\Gnss  
Imu\201801\_13\_182941.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 33161  
No processed  
position: 4  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0174 (m)  
C/A Code: 0.36 (m)  
L1 Doppler: 0.021 (m/s)

Position Standard Deviation  
Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.009 (m)  
North: 0.009 (m)  
Height: 0.032 (m)

Percentages of epochs with DD\_DOP  
over

10.00:

DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(33155 occurrences):


East: 0.009 (m)  
North: 0.009 (m)  
Height: 0.032 (m)

Baseline Distances:


Maximum: 126.852 (km)  
Minimum: 0.055 (km)  
Average: 86.703 (km)  
First Epoch: 1.142 (km)  
Last Epoch: 0.055 (km)

### Mission 01/13/2018 D


## 20180113\_234952 [Smoothed TC Combined] - Smoothed TC Combined – Map




## 20180113\_234952 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot



### 20180113\_234952 [Smoothed TC Combined] - PDOP Plot




### 20180113\_234952 [Smoothed TC Combined] - Number of Satellites Line Plot






### 20180113\_234952 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180113\_234952 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

### Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180113\_234952\Gns  
sImu\20180113\_234952.cfg

### Solution Type: Combined

#### Number of Epochs:

Total in GPB file: 32705  
No processed  
position: 1414  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

### Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

### Measurement RMS Values:

L1 Phase: 0.0168 (m)  
C/A Code: 0.40 (m)  
L1 Doppler: 0.026 (m/s)

### Position Standard Deviation Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

### Fwd/Rev Separation RMS Values:

East: 0.006 (m)  
North: 0.010 (m)  
Height: 0.023 (m)

### Percentages of epochs with DD\_DOP over

10.00:  
DOP over Tol: 0.0 %

### Fwd/Rev Sep. RMS for dual FWD/REV fixes (31270 occurrences):


East: 0.006 (m)  
North: 0.010 (m)  
Height: 0.023 (m)

### Baseline Distances:


Maximum: 110.161 (km)  
Minimum: 0.087 (km)  
Average: 86.565 (km)  
First Epoch: 20.649 (km)  
Last Epoch: 0.762 (km)

### Mission 01/14/2018 A


### 20180114\_151855 [Smoothed TC Combined] - Smoothed TC Combined – Map




### 20180114\_151855 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot





**20180114\_151855 [Smoothed TC Combined] - PDOP Plot**



**20180114\_151855 [Smoothed TC Combined] - Number of Satellites Line Plot**



### 20180114\_151855 [Smoothed TC Combined] - Accelerometer Bias Plot



## Processing Summery Information

### Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180114\_151855\Gnss  
Imu\20180114\_151855.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 33616  
No processed  
position: 5  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 99.9 %  
Q 2: 0.1 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0170 (m)  
C/A Code: 0.37 (m)  
L1 Doppler: 0.030 (m/s)

Position Standard Deviation  
Percentages:

0.00 - 0.10 m: 100.0 %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m +  
over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.009 (m)  
North: 0.006 (m)  
Height: 0.015 (m)

Percentages of epochs with DD\_DOP  
over

10.00:

DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(33589 occurances):


East: 0.009 (m)  
North: 0.006 (m)  
Height: 0.015 (m)

Baseline Distances:


Maximum: 114.461 (km)  
Minimum: 0.086 (km)  
Average: 70.808 (km)  
First Epoch: 0.355 (km)  
Last Epoch: 0.677 (km)

### Mission 01/15/2018 A


### 20180115\_002322 [Smoothed TC Combined] - Smoothed TC Combined - Map




### 20180115\_002322 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot



### 20180115\_002322 [Smoothed TC Combined] - PDOP Plot





### 20180115\_002322 [Smoothed TC Combined] - Number of Satellites Line Plot





### 20180115\_002322 [Smoothed TC Combined] - Accelerometer Bias Plot



## Processing Summery Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180115\_002322\Gns  
sImu\20180115\_002322.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 33101  
No processed  
position: 2  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0153 (m)  
C/A Code: 0.36 (m)  
L1 Doppler: 0.028 (m/s)

Position Standard Deviation  
Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.006 (m)  
North: 0.004 (m)  
Height: 0.020 (m)

Percentages of epochs with DD\_DOP  
over

10.00:

DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(33095  
occurrences):


East: 0.006 (m)  
North: 0.004 (m)  
Height: 0.020 (m)

Baseline Distances:


Maximum: 87.010 (km)  
Minimum: 0.087 (km)  
Average: 61.739 (km)  
First Epoch: 0.217 (km)  
Last Epoch: 0.764 (km)

### Mission 01/15/2018 B


### 20180115\_052112 [Smoothed TC Combined] - Smoothed TC Combined – Map




### 20180115\_052112 [Smoothed TC Combined] - Forward/Reverse or Combined Separation Plot





### 20180115\_052112 [Smoothed TC Combined] - PDOP Plot



### 20180115\_052112 [Smoothed TC Combined] - Number of Satellites Line Plot



### 20180115\_052112 [Smoothed TC Combined] - Accelerometer Bias Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180115\_052112\Gnss  
Imu\20180115\_052112.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 14799  
No processed  
position: 4  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 100.0 %  
Q 2: 0.0 %  
Q 3: 0.0 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0147 (m)  
C/A Code: 0.35 (m)  
L1 Doppler: 0.030 (m/s)

Position Standard Deviation  
Percentages:

100.0  
0.00 - 0.10 m: %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m + over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.005 (m)  
North: 0.003 (m)  
Height: 0.011 (m)

Percentages of epochs with DD\_DOP  
over

10.00:

DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(14793 occurrences):


East: 0.005 (m)  
North: 0.003 (m)  
Height: 0.011 (m)

Baseline Distances:


Maximum: 91.273 (km)  
Minimum: 0.085 (km)  
Average: 61.238 (km)  
First Epoch: 0.364 (km)  
Last Epoch: 0.754 (km)



### 20180115\_171406 [Smoothed TC Combined] - PDOP Plot




### 20180115\_171406 [Smoothed TC Combined] - Number of Satellites Line Plot





### 20180115\_171406 [Smoothed TC Combined] - Accelerometer Bias Plot



### 20180115\_171406 [Smoothed TC Combined] - Gyro Drift Plot



## Processing Summary Information

Project:

N:\Production\LiDAR\_Projects\18001\_TX\_FL16\_Addon\Flight\_Raw\20180115\_171406\Gnss  
Imu\201801\_15\_171406.cfg

Solution Type: Combined

Number of Epochs:

Total in GPB file: 8734  
No processed  
position: 3  
Missing Fwd or Rev: 2  
With bad C/A code: 0  
With bad L1 Phase: 0

Quality Number Percentages:

Q 1: 94.5 %  
Q 2: 5.3 %  
Q 3: 0.1 %  
Q 4: 0.0 %  
Q 5: 0.0 %  
Q 6: 0.0 %

Measurement RMS Values:

L1 Phase: 0.0183 (m)  
C/A Code: 0.71 (m)  
L1 Doppler: 0.023 (m/s)

Position Standard Deviation  
Percentages:

0.00 - 0.10  
m: 100.0 %  
0.10 - 0.30 m: 0.0 %  
0.30 - 1.00 m: 0.0 %  
1.00 - 5.00 m: 0.0 %  
5.00 m +  
over: 0.0 %

Fwd/Rev Separation RMS Values:

East: 0.005 (m)  
North: 0.005 (m)  
Height: 0.021 (m)

Percentages of epochs with DD\_DOP  
over

10.00:  
DOP over Tol: 0.0 %

Fwd/Rev Sep. RMS for dual FWD/REV fixes  
(8729 occurrences):

East: 0.005 (m)  
North: 0.005 (m)  
Height: 0.021 (m)

Baseline Distances:

Maximum: 78.494 (km)  
Minimum: 11.818 (km)  
Average: 52.342 (km)  
First Epoch: 77.176 (km)  
Last Epoch: 77.963 (km)