C-4.1 Report on Nominal Pulse Spacing (NPS)

The USGS Lidar Base Specification Version 1.3 states: "Assessment and reporting of the NPS are made against single swath, single instrument, first-return-only data, including only the geometrically usable part of the swath and excluding acceptable data voids. Higher net densities of lidar point measurements are being achieved more often by flying multiple passes of the lidar instrument over the project area or flying with large amounts (greater than [>] 50 percent) of overlap between swaths, creating a need for a new term to describe total pulse density without being confused with NPS and NPD. This specification will use the terms aggregate nominal pulse spacing (ANPS) and aggregate nominal pulse density (ANPD) to describe the net overall pulse spacing and density, respectively. The required ANPS and ANPD by QL are listed in Table 1. Dependent on the local terrain and land cover conditions in a project, a greater pulse density may be required on specific projects."

Table 1. Aggregate nominal pulse spacing and density.

[QL, quality level; pls/m^2 , pulses per square meter; m, meter; \leq , less than or equal to; \geq , greater than or equal to]

Quality level	Aggregate nominal pulse spacing (m)	Aggregate nominal pulse density (pls/m²)	
QL0	≤0.35	≥8.0	
QL1	≤0.35	≥8.0	
QL2	≤0.71	≥2.0	
QL3	≤1.41	≥0.5	

The purpose of this section is to report on the lidar point density and nominal point spacing by LAS file. Averages by files (not including overlap), project boundary polygons (including overlap) are reported.

Quality level tested: QL2

Units: Meter

File	Number of First Returns	Area	Point Density	NPS
Average			2.901/0.270	0.587/1.926
			pp Square Meter/	Meter/

C-4.1 Report on Nominal Pulse Spacing (NPS) - continued

Boundary ID	Number of First Returns	Area	Point Density	NPS
Aggregate	57,321,269,629	14,857,815,185	3.858/0.358	0.509/1.670
			pp Square Meter/ pp Square US Survey Foot	Meter/ US Survey Feet