

# Ulster, Dutchess, and Orange Counties NY-Sandy LiDAR

Report Produced for U.S. Geological Survey

USGS Contract: G10PC00013

Task Order: G13PD00855

Report Date: 08/14/2015

SUBMITTED BY:

**Dewberry**

1000 North Ashley Drive Suite 801  
Tampa, FL 33602  
813.225.1325

SUBMITTED TO:

**U.S. Geological Survey**

1400 Independence Road  
Rolla, MO 65401  
573.308.3810

## Table of Contents

Executive Summary .....	4
The Project Team.....	4
Survey Area.....	4
Date of Survey.....	4
Datum Reference.....	4
LiDAR Vertical Accuracy .....	5
Project Deliverables.....	5
Project Tiling Footprint.....	6
LiDAR Acquisition Report .....	7
LiDAR Acquisition Details.....	7
LiDAR Control.....	8
Airborn GPS Kinematic .....	8
Generation and Calibration of Laser Points (raw data) .....	8
Boresight and Relative accuracy.....	10
Preliminary Vertical Accuracy Assessment .....	10
Final Swath Vertical Accuracy Assessment.....	11
LiDAR Processing & Qualitative Assessment .....	13
Data Classification and Editing.....	13
Qualitative Assessment .....	16
Analysis.....	17
Survey Vertical Accuracy Checkpoints .....	22
LiDAR Vertical Accuracy Statistics & Analysis.....	27
Background.....	27
Vertical Accuracy Test Procedures .....	27
FVA.....	27
CVA.....	27
SVA.....	28
Vertical Accuracy Testing Steps .....	28
Vertical Accuracy Results .....	30
Breakline Production & Qualitative Assessment Report.....	33
Breakline Production Methodology .....	33
Breakline Qualitative Assessment .....	33
Breakline Topology Rules.....	33
Breakline QA/QC Checklist.....	34
Data Dictionary.....	37



Horizontal and Vertical Datum .....	37
Coordinate System and Projection .....	37
Inland Streams and Rivers .....	37
Description .....	37
Table Definition .....	37
Feature Definition .....	38
Inland Ponds and Lakes .....	39
Description .....	39
Table Definition .....	39
Feature Definition .....	39
DEM Production & Qualitative Assessment .....	40
DEM Production Methodology .....	40
DEM Qualitative Assessment .....	41
DEM Vertical Accuracy Results .....	44
DEM QA/QC Checklist .....	45
Appendix A: Survey Report .....	47
Appendix B: Complete List of Delivered Tiles .....	59
Appendix C: GPS Processing Reports for Each Mission .....	73

## Executive Summary

The primary purpose of this project was to develop a consistent and accurate surface elevation dataset derived from high-accuracy Light Detection and Ranging (LiDAR) technology for the USGS Ulster, Dutchess, and Orange Counties NY LiDAR Project Area.

The LiDAR data were processed to a bare-earth digital terrain model (DTM). Detailed breaklines and bare-earth Digital Elevation Models (DEMs) were produced for the project area. Data was formatted according to tiles with each tile covering an area of 1500m by 1500m. A total of 3465 tiles were produced for the project encompassing an area of approximately 2846 sq. miles.

## THE PROJECT TEAM

Dewberry served as the prime contractor for the project. In addition to project management, Dewberry was responsible for LAS classification, all LiDAR products, breakline production, Digital Elevation Model (DEM) production, and quality assurance.

Dewberry's Gary D. Simpson completed ground surveying for the project and delivered surveyed checkpoints. His task was to acquire surveyed checkpoints for the project to use in independent testing of the vertical accuracy of the LiDAR-derived surface model. He also verified the GPS base station coordinates used during LiDAR data acquisition to ensure that the base station coordinates were accurate. Please see Appendix A to view the separate Survey Report that was created for this portion of the project.

The Atlantic Group completed LiDAR data acquisition and data calibration for the project area.

## SURVEY AREA

The project area addressed by this report falls within the New York counties of Ulster, Dutchess, and Orange.

## DATE OF SURVEY

The LiDAR aerial acquisition was conducted from November 20, 2013 thru June 1, 2014.

## DATUM REFERENCE

Data produced for the project were delivered in the following reference system.

**Horizontal Datum:** The horizontal datum for the project is North American Datum of 1983 (NAD 83) (2011)

**Vertical Datum:** The Vertical datum for the project is North American Vertical Datum of 1988 (NAVD88)

**Coordinate System:** UTM Zone 18

**Units:** Horizontal units are in meters, Vertical units are in meters.

**Geoid Model:** Geoid12a (Geoid 12a was used to convert ellipsoid heights to orthometric heights).

## **LIDAR VERTICAL ACCURACY**

For the Ulster, Dutchess, and Orange Counties NY LiDAR Project, the tested  $RMSE_z$  of the classified LiDAR data for checkpoints in open terrain equaled **0.07 m** compared with the 0.0925 m specification; and the FVA of the classified LiDAR data computed using  $RMSE_z \times 1.9600$  was equal to **0.13 m**, compared with the 0.181 m specification.

For the Ulster, Dutchess, and Orange Counties NY LiDAR Project, the tested CVA of the classified LiDAR data computed using the 95<sup>th</sup> percentile was equal to **0.25 m**, compared with the 0.269 m specification.

Additional accuracy information and statistics for the classified LiDAR data, raw swath data, and bare earth DEM data are found in the following sections of this report.

## **PROJECT DELIVERABLES**

The deliverables for the project are listed below.

1. Raw Point Cloud Data (Swaths)
2. Classified Point Cloud Data (Tiled)
3. Bare Earth Surface (Raster DEM – IMG Format)
4. Intensity Images (8-bit gray scale, tiled, GeoTIFF format)
5. Breakline Data (File GDB)
6. Independent Survey Checkpoint Data (Report, Photos, & Points)
7. Calibration Points
8. Metadata
9. Project Report (Acquisition, Processing, QC)
10. Project Extents, Including a shapefile derived from the LiDAR Deliverable

### PROJECT TILING FOOTPRINT

Three thousand four hundred and sixty five (3465) tiles were delivered for the project. Each tile's extent is 1,500 meters by 1,500 meters (see Appendix B for a complete listing of delivered tiles).

**Ulster, Dutchess, and Orange Counties NY LiDAR Project**




Figure 1 - Project Map

## LiDAR Acquisition Report

The Atlantic Group provided high accuracy, calibrated multiple return LiDAR for roughly 2,846 square miles around the Ulster, Dutchess, and Orange Counties NY area. Data was collected and delivered in compliance with the “U.S. Geological Survey National Geospatial Program Base LiDAR Specifications, Version 1.0”

### LIDAR ACQUISITION DETAILS

LiDAR acquisition began on November 20, 2013 (julian day 324) and was completed on June 01, 2014 (julian day 152). A total of 22 survey missions were flown to complete the project. The Atlantic Group utilized a Leica ALS 70-HP for the acquisition. The flight plan was flown as planned with no modifications. There were no unusual occurrences during the acquisition and the sensor performed within specifications. There were 499 flight lines required to complete the project.




Figure 2 - Flight Layout

Laser Firing Rate: 304.4  
Altitude (mtr. AGL): 1800  
Swath Overlap (%): 30  
Approx. Ground Speed (kts): 120  
Scan Rate (Hz): 43.6  
Scan Angle ( $^{\circ}\pm$ ): 17  
Computed Swath Width (mtr): 1118  
Number of Lines Required: 499  
Line Spacing (mtr): 750

## LIDAR CONTROL

Two points set by Atlantic were used to control the LiDAR acquisition for the Ulster, Dutchess, and Orange Counties NY LiDAR project area. The coordinates of all used base stations are provided in the table below. All control and calibration points are also provided in shapefile format as part of the final deliverables.

Name	Easting (m)	Northing (m)	Ellipsoid Ht (m)
KPOU ARP	593079.7	4608945	14.163
KSCH SET	587042.1	4744952.7	66.053

Table 1 – Base Stations used to control LiDAR acquisition

## AIRBORN GPS KINEMATIC

Airborne GPS data was processed using the Inertial Explorer (version 8.5.4320) software. Flights were flown with a minimum of 6 satellites in view ( $12^{\circ}$  above the horizon) and with a PDOP of less than 3 during laser scans. Distances from base station to aircraft were kept to a maximum of 32 km.

For all flights, the GPS data can be classified as good, with GPS residuals of 3 cm average or better but none larger than 10 cm being recorded.

Data collected by the LiDAR unit is reviewed for completeness, acceptable density and to make sure all data is captured without errors or corrupted values. In addition, all GPS, aircraft trajectory, mission information, and ground control files are reviewed and logged into a database.

GPS processing reports for each mission are included in Appendix C.

## GENERATION AND CALIBRATION OF LASER POINTS (RAW DATA)

The initial step of calibration is to verify availability and status of all needed GPS and Laser data against field notes and compile any data if not complete. Subsequently, the mission points are output using Leica's ALS Post Processor initially using the most recent boresight values.

The initial point generation for each mission calibration is verified within TerraScan using distance colored points to identify errors. If a calibration error greater than specification is observed within the mission, the roll, pitch and scanner scale corrections that need to be applied



are calculated. Once validated each output mission is imported into the GeoCue software package.

On a project level, a supplementary coverage check is carried out to ensure no data voids unreported by Field Operations are present.




Figure 3 – LiDAR Swath output showing complete coverage.

## BORESIGHT AND RELATIVE ACCURACY

For effective data management, each imported mission is tiled out in GeoCue to a project specific tile scheme or index. Relative accuracy and internal quality are then checked using a number of carefully selected tiles in which points from all lines are loaded and inspected.

Vertical differences between ground surfaces of each line are displayed by the generation of ZDifference colored intensity orthos in GeoCue. The color scale of these orthos are adjusted so that errors greater than the specifications are flagged. Cross sections are visually inspected across each block to validate point to point, flight line to flight line and mission to mission alignment. When available, surveyed control points are used to supplement and verify the calibration of the data.

For this project the specifications used are as follow:

Relative accuracy  $\leq 7$ cm RMSE<sub>z</sub> within individual swaths and  $\leq 10$  cm RMSE<sub>z</sub> or within swath overlap (between adjacent swaths).




Figure 4 – Profile views showing correct roll and pitch adjustments.

A different set of QC blocks are generated for final review after all transformations have been applied.

## PRELIMINARY VERTICAL ACCURACY ASSESSMENT

A preliminary RMSE<sub>z</sub> error check is performed by The Atlantic Group at this stage of the project life cycle in the raw LiDAR dataset against GPS static and kinematic data and compared to RMSE<sub>z</sub> project specifications. The LiDAR data is examined in open, flat areas away from breaks. LiDAR ground points for each flight line generated by an automatic classification routine are used.

Prior to delivery to Dewberry, the elevation data was verified internally to ensure it met fundamental accuracy requirements (vertical accuracy NSSDA RMSE<sub>z</sub> = 9.25 cm (NSSDA Accuracy<sub>z</sub> 95% = 18.13 cm) or better in open, non-vegetated terrain) when compared to static and kinematic GPS checkpoints. Below is a summary for the test:

The calibrated Ulster, Dutchess, and Orange Counties NY LiDAR dataset was tested to 0.06 m vertical accuracy at 95% confidence level based on consolidated RMSE<sub>z</sub> (0.03 m x 1.9600) when compared to 10 GPS static check points.



Average dz	+0.03 m
Minimum dz	-0.06 m
Maximum dz	+0.06 m
Root mean square	0.03 m
Std deviation	0.03 m

Overall the calibrated LiDAR data products collected by The Atlantic Group meet or exceed the requirements set out in the Statement of Work. The quality control requirements of The Atlantic Group’s quality management program were adhered to throughout the acquisition stage for this project to ensure product quality.

### FINAL SWATH VERTICAL ACCURACY ASSESSMENT

Once Dewberry received the calibrated swath data from The Atlantic Group, Dewberry tested the vertical accuracy of the open terrain swath data prior to additional processing. Dewberry tested the vertical accuracy of the swath data using the twenty open terrain independent survey check points. The vertical accuracy is tested by comparing survey checkpoints in open terrain to a triangulated irregular network (TIN) that is created from the raw swath points. Only checkpoints in open terrain can be tested against raw swath data because the data has not undergone classification techniques to remove vegetation, buildings, and other artifacts from the ground surface. Checkpoints are always compared to interpolated surfaces from the LiDAR point cloud because it is unlikely that a survey checkpoint will be located at the location of a discrete LiDAR point. Project specifications require a FVA of 0.181m based on the  $RMSE_z$  (0.0925 m) x 1.96. The dataset for the Ulster, Dutchess, and Orange Counties NY LiDAR Project satisfies this criteria. The raw LiDAR swath data tested 0.14 m vertical accuracy at 95% confidence level in open terrain, based on  $RMSE_z$  (0.07 m) x 1.9600. The table below shows all calculated statistics for the raw swath data.

100 % of Totals	RMSE <sub>z</sub> (m) Open Terrain Spec=0.0925	FVA – Fundamental Vertical Accuracy (RMSE <sub>z</sub> x 1.9600) Spec=0.181	Mean (m)	Median (m)	Skew	Std Dev (m)	# of Points	Min (m)	Max (m)
Open Terrain	0.07	0.14	0.03	0.02	1.57	0.07	20	-0.06	0.23

Table 2: FVA at 95% Confidence Level for Raw Swaths

One checkpoint (OT-020) was removed from the raw swath vertical accuracy testing due to its location within a construction site. Only open terrain checkpoints are used to test the raw swath data because the raw swath data has not been classified to remove vegetation, structures, and other above ground features from the ground classification. While OT-020 was located in open terrain at the time of the survey, there is a structure located at the same XY position when the LiDAR was acquired, preventing the LiDAR from reaching the ground at this location. These high structure points caused erroneous high values during the swath vertical accuracy testing so this point was removed from the final calculations. Once the data underwent the classification process, the construction materials were removed from the final ground classification and this point could be used in the final vertical accuracy testing for the fully classified LiDAR data. Table

3, below, provides the coordinates for this checkpoint and the vertical accuracy results from the raw swath data. Table 4, below, provides the usable vertical accuracy results of this checkpoint from the fully classified LiDAR. The differences in the tables show how above ground features can cause erroneous vertical accuracy results in the raw swath data. Figure 5, below, shows the survey point location near the construction site.

Point ID	NAD83(2011) UTM Zone 18N		NAVD88	LiDAR Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
OT-020	570154.29	4576745.66	199.367	200.86	1.493	1.49

Table 3 Checkpoint removed from raw swath vertical accuracy testing

Point ID	NAD83(2011) UTM Zone 18N		NAVD88	LiDAR Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
OT-020	570154.29	4576745.66	199.367	199.36	-0.01	0.01

Table 4: Final tested vertical accuracy for OT-020 post ground classification




Figure 5 – The top image shows the survey photo of Open Terrain checkpoint 020 located near a construction site. The bottom image shows the LiDAR profile of this area, where above ground features (white) are located at the XY position of the survey checkpoint (blue point identified by red arrow). This point was removed from raw swath vertical accuracy testing because above ground features have not been separated from the ground classification yet.

## LiDAR Processing & Qualitative Assessment

### DATA CLASSIFICATION AND EDITING

LiDAR mass points were produced to LAS 1.2 specifications, including the following LAS classification codes:

- Class 1 = Unclassified, used for all other features that do not fit into the Classes 2, 7, 9, 10, including vegetation, buildings, etc.
- Class 2 = Bare-Earth Ground
- Class 7 = Noise, low and high points

- Class 9 = Water, points located within collected breaklines
- Class 10 = Ignored Ground due to breakline proximity.


The data was processed using GeoCue and TerraScan software. The initial step is the setup of the GeoCue project, which is done by importing a project defined tile boundary index encompassing the entire project area. The acquired 3D laser point clouds, in LAS binary format, were imported into the GeoCue project and tiled according to the project tile grid. Once tiled, the laser points were classified using a proprietary routine in TerraScan. This routine classifies any obvious outliers in the dataset to class 7. After points that could negatively affect the ground are removed from class 1, the ground layer is extracted from this remaining point cloud. The ground extraction process encompassed in this routine takes place by building an iterative surface model.

This surface model is generated using three main parameters: building size, iteration angle and iteration distance. The initial model is based on low points being selected by a "roaming window" with the assumption that these are the ground points. The size of this roaming window is determined by the building size parameter. The low points are triangulated and the remaining points are evaluated and subsequently added to the model if they meet the iteration angle and distance constraints. This process is repeated until no additional points are added within iterations. A second critical parameter is the maximum terrain angle constraint, which determines the maximum terrain angle allowed within the classification model.

The following fields within the LAS files are populated to the following precision: GPS Time (0.000001 second precision), Easting (0.003 meter precision), Northing (0.003 meter precision), Elevation (0.003 meter precision), Intensity (integer value - 16 bit dynamic range), Number of Returns (integer - range of 1-4), Return number (integer range of 1-4), Scan Direction Flag (integer - range 0-1), Classification (integer), Scan Angle Rank (integer), Edge of flight line (integer, range 0-1), User bit field (integer - flight line information encoded). The LAS file also contains a Variable length record in the file header that defines the projection, datums, and units.

Once the initial ground routine has been performed on the data, Dewberry creates Delta Z (DZ) orthos to check the relative accuracy of the LiDAR data. These orthos compare the elevations of LiDAR points from overlapping flight lines on a 1 meter pixel cell size basis. If the elevations of points within each pixel are within 10 cm of each other, the pixel is colored green. If the elevations of points within each pixel are between 10 cm and 15 cm of each other, the pixel is colored yellow, and if the elevations of points within each pixel are greater than 15 cm in difference, the pixel is colored red. Pixels that do not contain points from overlapping flight lines are colored according to their intensity values. DZ orthos can be created using the full point cloud or ground only points and are used to review and verify the calibration of the data is acceptable. Some areas are expected to show sections or portions of red, including terrain variations, slope changes, and vegetated areas or buildings if the full point cloud is used. However, large or continuous sections of yellow or red pixels can indicate the data was not calibrated correctly or that there were issues during acquisition that could affect the usability of the data. The DZ orthos for Ulster, Dutchess, and Orange Counties showed that the data was calibrated correctly with no issues that would affect its usability. The figure below shows an example of the DZ orthos.





**Figure 6 - DZ orthos created from the full point cloud. Some red pixels are visible along embankments, sloped terrain, and in vegetated land cover, as expected. Open, flat areas are green indicating the calibration and relative accuracy of the data is acceptable.**

Once the calibration and relative accuracy of the data was confirmed, Dewberry utilized a variety of software suites for data processing. The LAS dataset was imported into GeoCue task management software for processing in Terrascan. Each tile was imported into Terrascan and a surface model was created to examine the ground classification. Dewberry analysts visually reviewed the ground surface model and corrected errors in the ground classification such as vegetation, buildings, and bridges that were present following the initial processing conducted by Dewberry. Dewberry analysts employ 3D visualization techniques to view the point cloud at multiple angles and in profile to ensure that non-ground points are removed from the ground classification. After the ground classification corrections were completed, the dataset was processed through a water classification routine that utilizes breaklines compiled by Dewberry to automatically classify hydro features. The water classification routine selects ground points within the breakline polygons and automatically classifies them as class 9, water. The final classification routine applied to the dataset selects ground points within a specified distance of the water breaklines and classifies them as class 10, ignored ground due to breakline proximity.

## QUALITATIVE ASSESSMENT

Dewberry's qualitative assessment utilizes a combination of statistical analysis and interpretative methodology to assess the quality of the data for a bare-earth digital terrain model (DTM). This process looks for anomalies in the data and also identifies areas where man-made structures or vegetation points may not have been classified properly to produce a bare-earth model.

Within this review of the LiDAR data, two fundamental questions were addressed:

- Did the LiDAR system perform to specifications?
- Did the vegetation removal process yield desirable results for the intended bare-earth terrain product?

Mapping standards today address the quality of data by quantitative methods. If the data are tested and found to be within the desired accuracy standard, then the data set is typically accepted. Now with the proliferation of LiDAR, new issues arise due to the vast amount of data. Unlike photogrammetrically-derived DEMs where point spacing can be eight meters or more, LiDAR nominal point spacing for this project is 1 point per 0.7 square meters. The end result is that millions of elevation points are measured to a level of accuracy previously unseen for traditional elevation mapping technologies and vegetated areas are measured that would be nearly impossible to survey by other means. The downside is that with millions of points, the dataset is statistically bound to have some errors both in the measurement process and in the artifact removal process.

As previously stated, the quantitative analysis addresses the quality of the data based on absolute accuracy. This accuracy is directly tied to the comparison of the discreet measurement of the survey checkpoints and that of the interpolated value within the three closest LiDAR points that constitute the vertices of a three-dimensional triangular face of the TIN. Therefore, the end result is that only a small sample of the LiDAR data is actually tested. However there is an increased level of confidence with LiDAR data due to the relative accuracy. This relative accuracy in turn is based on how well one LiDAR point "fits" in comparison to the next contiguous LiDAR measurement, and is verified with DZ orthos. Once the absolute and relative accuracy has been ascertained, the next stage is to address the cleanliness of the data for a bare-earth DTM.

By using survey checkpoints to compare the data, the absolute accuracy is verified, but this also allows us to understand if the artifact removal process was performed correctly. To reiterate the quantitative approach, if the LiDAR sensor operated correctly over open terrain areas, then it most likely operated correctly over the vegetated areas. This does not mean that the entire bare-earth was measured; only that the elevations surveyed are most likely accurate (including elevations of treetops, rooftops, etc.). In the event that the LiDAR pulse filtered through the vegetation and was able to measure the true surface (as well as measurements on the surrounding vegetation) then the level of accuracy of the vegetation removal process can be tested as a by-product.

To fully address the data for overall accuracy and quality, the level of cleanliness (or removal of above-ground artifacts) is paramount. Since there are currently no effective automated testing procedures to measure cleanliness, Dewberry employs a combination of statistical and visualization processes. This includes creating pseudo image products such as LiDAR orthos produced from the intensity returns, Triangular Irregular Network (TIN)'s, Digital Elevation Models (DEM) and 3-dimensional models. By creating multiple images and using overlay techniques, not only can potential errors be found, but Dewberry can also find where the data

meets and exceeds expectations. This report will present representative examples where the LiDAR and post processing had issues as well as examples of where the LiDAR performed well.

## ANALYSIS

Dewberry utilizes GeoCue software as the primary geospatial process management system. GeoCue is a three tier, multi-user architecture that uses .NET technology from Microsoft. .NET technology provides the real-time notification system that updates users with real-time project status, regardless of who makes changes to project entities. GeoCue uses database technology for sorting project metadata. Dewberry uses Microsoft SQL Server as the database of choice. Specific analysis is conducted in Terrascan and QT Modeler environments.

Following the completion of LiDAR point classification, the Dewberry qualitative assessment process flow for the Ulster, Dutchess, and Orange Counties NY LiDAR project incorporated the following reviews:

1. *Format:* The LAS files are verified to meet project specifications. The LAS files for the Ulster, Dutchess, and Orange Counties NY LiDAR project conform to the specifications outlined below.
  - Format, Echos, Intensity
    - o LAS format 1.2
    - o Point data record format 1
    - o Multiple returns (echos) per pulse
    - o Intensity values populated for each point
  - ASPRS classification scheme
    - o Class 1 – unclassified
    - o Class 2 – Bare-earth ground
    - o Class 7 – Noise
    - o Class 9 – Water
    - o Class 10 – Ignored Ground due to breakline proximity
  - Projection
    - o Datum – North American Datum 1983 (2011)
    - o Projected Coordinate System – UTM Zone 18
    - o Linear Units – Meters
    - o Vertical Datum – North American Vertical Datum 1988, Geoid 12a
    - o Vertical Units - Meters
  - LAS header information:
    - o Class (Integer)
    - o Adjusted GPS Time (0.0001 seconds)
    - o Easting (0.003 meters)
    - o Northing (0.003 meters)
    - o Elevation (0.003 meters)
    - o Echo Number (Integer 1 to 4)
    - o Echo (Integer 1 to 4)
    - o Intensity (16 bit integer)
    - o Flight Line (Integer)

- Scan Angle (Integer degree)
2. *Data density, data voids:* The LAS files are used to produce Digital Elevation Models using the commercial software package “QT Modeler” which creates a 3-dimensional data model derived from Class 2 (ground points) in the LAS files. Grid spacing is based on the project density deliverable requirement for un-obscured areas. For the Ulster, Dutchess, and Orange Counties NY LiDAR project it is stipulated that the minimum post spacing in un-obscured areas should be 1 point per 0.7 square meters.
    - a. Acceptable voids (areas with no LiDAR returns in the LAS files) that are present in the majority of LiDAR projects include voids caused by bodies of water. These are considered to be acceptable voids. No unacceptable voids are present in the Ulster, Dutchess, and Orange Counties NY LiDAR project.
  3. *Bare earth quality:* Dewberry reviewed the cleanliness of the bare earth to ensure the ground has correct definition, meets the project requirements, there is correct classification of points, and there are less than 5% residual artifacts.
    - a. *Artifacts:* Artifacts are caused by the misclassification of ground points and usually represent vegetation and/or man-made structures. The artifacts identified are usually low lying structures, such as porches or low vegetation used as landscaping in neighborhoods and other developed areas. These low lying features are extremely difficult for the automated algorithms to detect as non-ground and must be removed manually. The vast majority of these features have been removed but a small number of these features are still in the ground classification. The limited numbers of features remaining in the ground are usually 0.3 meters or less above the actual ground surface, and should not negatively impact the usability of the dataset.







Figure 7 – Tile number 18265795 Profile with points colored by class (class 1=white, class 2=orange) is shown in the top view and a TIN of the surface is shown in the bottom view. The circle identifies a porch. A limited number of these small features are still classified as ground but do not impact the usability of the dataset.

- b. *Bridge Removal Artifacts:* The DEM surface models are created from TINs or Terrains. TIN and Terrain models create continuous surfaces from the inputs. Because a continuous surface is being created, the TIN or Terrain will use interpolation to continue the surface beneath the bridge where no LiDAR data was acquired. Locations where bridges were removed will generally contain less detail in the bare-earth surface because these areas are interpolated.



**Figure 8 – Tile number 18TWL250780. The DEM in the bottom view shows an area where a bridge has been removed from ground. The surface model must make a continuous model and in order to do so, points are connected through interpolation. This results in less detail where the surface must be interpolated. The profile in the top view shows the LiDAR points of this particular feature colored by class. All bridge points have been removed from ground (orange) and are unclassified (white).**

- c. *Culverts and Bridges:* Bridges have been removed from the bare earth surface while culverts remain in the bare earth surface. In instances where it is difficult to determine if the feature is a culvert or bridge, such as with some small bridges, Dewberry erred on assuming they would be culverts especially if they are on secondary or tertiary roads. Below is an example of a culvert that has been left in the ground surface.




Figure 9– Tile number 18TWL265780. Profile with points colored by class (class 1=white, class 2=orange) is shown in the top view and the DEM is shown in the bottom view. This culvert remains in the bare earth surface. Bridges have been removed from the bare earth surface and classified to class 1.

- d. *Elevation Change Within Breaklines:* While water bodies are flattened in the final DEMs, other features such as linear hydrographic features can have significant changes in elevation within a small distance. In linear hydrographic features, this is often due to the presence of a structure that affects flow such as a dam or spillway. Dewberry has reviewed the DEMs to ensure that changes in elevation are shown from bank to bank. These changes are often shown as steps to reduce the presence of artifacts while ensuring consistent downhill flow. An example is shown below.




Figure 10 – Tile number 18TWL250995 and 18TWL250780. Elevation change has been stair stepped. The steps are flat from bank to bank and flow consistently downhill.

## Survey Vertical Accuracy Checkpoints

All checkpoints surveyed for vertical accuracy testing purposes are listed in the following table. A total of one hundred and five (105) checkpoints were surveyed for the Ulster, Dutchess, and Orange Counties NY LiDAR Project.

Point ID	NAD83 (2011) UTM Zone 18		NAVD88
	Easting X (m)	Northing Y (m)	Elevation (m)
BLT-001	613742.291	4645437.756	164.699
BLT-002	595619.951	4649719.492	67.255
BLT-003	603128.705	4636132.396	162.858
BLT-004	609287.89	4618435.937	218.99

BLT-005	587605.341	4599391.723	64.511
BLT-006	583475.673	4612356.376	130.087
BLT-007	584305.786	4581823.94	184.861
BLT-008	549917.753	4574768.497	118.068
BLT-009	556743.536	4582455.472	139.141
BLT-010	548474.677	4597007.813	184.704
BLT-011	545501.595	4616414.115	372.673
BLT-012	571006.315	4627309.926	77.02
BLT-013	584374.373	4634303.826	40.841
BLT-014	562200.793	4637500.363	230.808
BLT-015	572095.278	4654712.141	178.052
BLT-016	542135.008	4641268.201	762.011
BLT-017	545330.239	4646100.481	648.091
BLT-018	549616.124	4663641.117	332.608
BLT-019	532765.32	4657947.891	626.974
BLT-020	537463.589	4642684.366	682.092
BLT-021	527284.95	4650126.985	609.487
GWC-001	610772.112	4606713.771	148.357
GWC-002	618436.864	4614836.982	144.227
GWC-003	613564.922	4629793.124	277.217
GWC-004	613067.388	4639953.278	245.387
GWC-005	597532.926	4639003.494	195.523
GWC-006	595074.183	4627520.65	120.268
GWC-007	593924.181	4609288.577	47.696
GWC-008	566750.022	4585764.905	111.922
GWC-009	559817.167	4571862.962	161.841
GWC-010	540925.345	4581829.323	186.857
GWC-011	565200.757	4600381.391	122.645
GWC-012	565557.457	4614691.591	77.161
GWC-013	567180.984	4628772.503	100.749
GWC-014	578998.385	4638028.511	56.638
GWC-015	575631.577	4649444.663	176.699
GWC-016	582823.67	4657770.586	162.047
GWC-017	540218.412	4625416.485	339.674
GWC-018	550668.21	4641734.207	424.838
GWC-019	558464.035	4655980.656	220.303
GWC-020	545092.663	4656223.324	448.43
GWC-021	528578.379	4650778.583	641.619
OT-001	543194.751	4664757.282	449.086
OT-003	587566.321	4663513.537	44.153
OT-004	582634.844	4647830.939	46.802
OT-005	604527.498	4649018.695	134.649
OT-006	620324.637	4635251.978	178.75
OT-007	602524.625	4625876.17	106.681
OT-008	578162.244	4629972.774	54.194
OT-009	556920.869	4624541.071	82.355
OT-010	538685.782	4621623.578	331.949
OT-011	522286.303	4653550.304	538.56
OT-012	552368.154	4608699.518	177.248
OT-013	576995.043	4607672.318	172.011
OT-014	600983.321	4613921.324	109.668
OT-015	602089.503	4599913.209	97.629
OT-016	570932.547	4586341.675	94.25



OT-017	581067.722	4596320.864	72.336
OT-018	554397.435	4589395.276	130.023
OT-019	533282.104	4589841.048	153.227
OT-020	570154.29	4576745.66	199.367
OT-021	568404.033	4561795.004	145.259
OT-002	560233.298	4653225.544	204.555
UT-001	524086.368	4652515.066	557.265
UT-002	535891.353	4662675.148	480.971
UT-003	545999.024	4661367.804	369.692
UT-004	559292.793	4654927.847	212.259
UT-005	573001.618	4655174.209	177.605
UT-006	583524.674	4663531.935	115.267
UT-007	580775.977	4643323.526	48.122
UT-008	624041.99	4645585.734	216.087
UT-009	617831.082	4623236.176	126.512
UT-010	589650.326	4617866.519	48.265
UT-011	575900.626	4621483.975	90.294
UT-012	566005.04	4644022.692	155.276
UT-013	559441.735	4626022.597	114.351
UT-014	550138.384	4618345.966	105.262
UT-015	558601.016	4606088.835	107.806
UT-016	574629.402	4594364.225	134.74
UT-017	598951.427	4603765.456	74.003
UT-018	572491.837	4573939.871	169.104
UT-019	566543.331	4565819.121	220.024
UT-020	544810.808	4571824.956	127.996
UT-021	527091.373	4580719.307	133.245
FO-001	562640.354	4560668.009	223.229
FO-002	523099.09	4589975.673	358.095
FO-003	538337.251	4591468.486	257.333
FO-004	555653.452	4594940.718	174.369
FO-005	565029.38	4577678.519	146.12
FO-006	580566.007	4573218.442	158.091
FO-007	592268.141	4596930.107	63.966
FO-008	617949.402	4600347.717	146.722
FO-009	620730.493	4614523.255	122.692
FO-010	622873.383	4650178.933	232.629
FO-011	602678.995	4645217.381	163.992
FO-012	588589.451	4632633.306	4.595
FO-013	579188.507	4624436.392	114.243
FO-014	547358.168	4627509.836	284.057
FO-015	541702.666	4648774.157	609.175
FO-016	519399.065	4651988.481	513.055
FO-017	548956.377	4665849.137	396.952
FO-018	560593.038	4651267.887	203.64
FO-019	570459.819	4636921.147	84.696
FO-020	582782.249	4667722.401	113.685
FO-021	589790.392	4657565.43	48.11

Table 5: Ulster, Dutchess, and Orange Counties NY LiDAR surveyed accuracy checkpoints

One hundred and five checkpoints were surveyed for vertical accuracy testing. While reviewing the final coordinates of the provided survey checkpoints against the field sketches and intensity imagery created from the LiDAR, Dewberry identified an issue with the location of one brushland and trees checkpoint and one grass, weeds, and crops checkpoint. BLT-14 is located in an area of dense vegetation where light and therefore LiDAR cannot penetrate the ground. As this survey point was located in a poor location, it was removed from the vertical accuracy testing. The image below shows the brushland and trees checkpoint removed from final vertical accuracy testing.



**Figure 11-Checkpoint BLT 014. This survey checkpoint is located in extremely dense vegetation where light cannot reach the ground. Due to its poor location, this survey checkpoint was not used in vertical accuracy testing.**

GWC-018 was removed due to faulty satellite connection during the survey causing an inaccurate survey elevation value. The surveyed elevation of GWC-0.18 is 0.84 meters above the ground surface in the LiDAR data. The LiDAR data is consistent and Dewberry verified with the surveyors that issues may have occurred with the collection of this survey checkpoint. The images below show the checkpoint removed from final vertical accuracy testing.



**Figure 12-Checkpoint GWC 018. The surveyed elevation of this checkpoint is over 0.84 meters above the ground surface in the LiDAR data. Dewberry confirmed with the surveyors that overhead objects may have interfered with the GPS signals, resulting in an inaccurate elevation value for this checkpoint.**



**Figure 13-Checkpoint GWC 018 is shown as the blue dot circled in red. Overhead obstructions (white points) interfered with the collection of this checkpoint and it had to be removed from vertical accuracy testing.**



Point ID	NAD83 (2011) UTM Zone 18N		NAVD88	LiDAR Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
BLT-014	562200.793	4637500.363	230.808	232.3	1.49	1.49
GWC-018	550668.21	4641734.207	424.838	424	-0.838	0.84

Table 6: Checkpoints removed from vertical accuracy testing due to poor checkpoint location and overhead obstructions that interfered with GPS signals.

Even with the removal of these two points, there are enough total checkpoints and enough checkpoints per land cover category to satisfy project requirements.

## LiDAR Vertical Accuracy Statistics & Analysis

### BACKGROUND

Dewberry tests and reviews project data both quantitatively (for accuracy) and qualitatively (for usability).

For quantitative assessment (i.e. vertical accuracy assessment), one hundred and three(103) check points were surveyed for the project and are located within bare earth/open terrain, urban, tall weeds/crops, brush lands/tress, and forested/fully grown land cover categories. The checkpoints were surveyed for the project using RTK survey methods. Please see appendix A to view the survey report which details and validates how the survey was completed for this project.

Checkpoints were evenly distributed throughout the project area so as to cover as many flight lines as possible using the “dispersed method” of placement.

### VERTICAL ACCURACY TEST PROCEDURES

**FVA** (Fundamental Vertical Accuracy) is determined with check points located only in the open terrain (grass, dirt, sand, and/or rocks) land cover category, where there is a very high probability that the LiDAR sensor will have detected the bare-earth ground surface and where random errors are expected to follow a normal error distribution. The FVA determines how well the calibrated LiDAR sensor performed. With a normal error distribution, the vertical accuracy at the 95% confidence level is computed as the vertical root mean square error ( $RMSE_z$ ) of the checkpoints x 1.9600. For the Ulster, Dutchess, and Orange Counties NY LiDAR project, vertical accuracy must be 0.181 meters or less based on an  $RMSE_z$  of 0.0925 meters x 1.9600.

**CVA** (Consolidated Vertical Accuracy) is determined with all checkpoints in all land cover categories combined where there is a possibility that the LiDAR sensor and post-processing may yield elevation errors that do not follow a normal error distribution. CVA at the 95% confidence level equals the 95<sup>th</sup> percentile error for all checkpoints in all land cover categories combined. The Ulster, Dutchess, and Orange Counties NY LiDAR Project CVA standard is 0.269 meters based on the 95<sup>th</sup> percentile. The CVA is accompanied by a listing of the 5% outliers that are larger than the 95<sup>th</sup> percentile used to compute the CVA; these are always the largest outliers that may depart from a normal error distribution. Here,  $Accuracy_z$  differs from CVA because  $Accuracy_z$  assumes elevation errors follow a normal error distribution where RMSE procedures are valid, whereas CVA assumes LiDAR errors may not follow a normal error distribution in vegetated categories, making the RMSE process invalid.

**SVA** (Supplemental Vertical Accuracy) is determined for each land cover category other than open terrain. SVA at the 95% confidence level equals the 95<sup>th</sup> percentile error for all checkpoints in each land cover category. The Ulster, Dutchess, and Orange Counties NY LiDAR project SVA target is 0.269 meters based on the 95<sup>th</sup> percentile. Target specifications are given for SVA's as one individual land cover category may exceed this target value as long as the overall CVA is within specified tolerances. Again, Accuracy<sub>z</sub> differs from SVA because Accuracy<sub>z</sub> assumes elevation errors follow a normal error distribution where RMSE procedures are valid, whereas SVA assumes LiDAR errors may not follow a normal error distribution in vegetated categories, making the RMSE process invalid.

The relevant testing criteria are summarized in Table 7.

Quantitative Criteria	Measure of Acceptability
Fundamental Vertical Accuracy (FVA) in open terrain only using RMSE <sub>z</sub> *1.9600	0.181 meters (based on RMSE <sub>z</sub> (0.0925 meters) * 1.9600)
Consolidated Vertical Accuracy (CVA) in all land cover categories combined at the 95% confidence level	0.269 meters (based on combined 95 <sup>th</sup> percentile)
Supplemental Vertical Accuracy (SVA) in each land cover category separately at the 95% confidence level	0.269 meters (based on 95 <sup>th</sup> percentile for each land cover category)

**Table 7 – Acceptance Criteria**

## **VERTICAL ACCURACY TESTING STEPS**

The primary QA/QC vertical accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry's team surveyed QA/QC vertical checkpoints in accordance with the project's specifications.
2. Next, Dewberry interpolated the bare-earth LiDAR DTM to provide the z-value for every checkpoint.
3. Dewberry then computed the associated z-value differences between the interpolated z-value from the LiDAR data and the ground truth survey checkpoints and computed FVA, CVA, and SVA values.
4. The data were analyzed by Dewberry to assess the accuracy of the data. The review process examined the various accuracy parameters as defined by the scope of work. The overall descriptive statistics of each dataset were computed to assess any trends or anomalies. This report provides tables, graphs and figures to summarize and illustrate data quality.

The figure below shows the location of the QA/QC checkpoints within the project area.




Figure 14 – Location of QA/QC Checkpoints

## VERTICAL ACCURACY RESULTS

The table below summarizes the tested vertical accuracy resulting from a comparison of the surveyed checkpoints to the elevation values present within the fully classified LiDAR LAS files.

Land Cover Category	# of Points	FVA – Fundamental Vertical Accuracy (RMSE <sub>z</sub> x 1.9600) Spec=0.181 m	CVA – Consolidated Vertical Accuracy (95th Percentile) Spec=0.269 m	SVA – Supplemental Vertical Accuracy (95th Percentile) Target=0.269 m
Consolidated	103		0.25	
Bare Earth-Open Terrain	21	0.13		
Urban	21			0.24
Tall Weeds and Crops	20			0.20
Brush Lands and Trees	20			0.25
Forested and Fully Grown	21			0.40

**Table 8 – FVA, CVA, and SVA Vertical Accuracy at 95% Confidence Level**

The RMSE<sub>z</sub> for checkpoints in open terrain only tested 0.07 meters, within the target criteria of 0.0925 meters. Compared with the 0.181 meters specification, the FVA tested 0.13 meters at the 95% confidence level based on RMSE<sub>z</sub> x 1.9600.

Compared with the 0.269 meters specification, CVA for all checkpoints in all land cover categories combined tested 0.25 meters based on the 95<sup>th</sup> percentile.

Compared with the target 0.269 meters specification, SVA for checkpoints in the urban land cover category tested 0.24 meters based on the 95<sup>th</sup> percentile, checkpoints in the tall weeds and crops land cover category tested 0.20 meters based on the 95<sup>th</sup> percentile, checkpoints in the forested and fully grown land cover category tested 0.40 meters based on the 95<sup>th</sup> percentile, and checkpoints in the brush and small trees land cover category tested 0.25 meters based on the 95<sup>th</sup> percentile.

The figure below illustrates the magnitude of the differences between the QA/QC checkpoints and LiDAR data. This shows that the majority of LiDAR elevations were within +/- 0.20 meters of the checkpoints elevations, but there were some outliers where LiDAR and checkpoint elevations differed by up to -0.59 meters.




Figure 15 – Magnitude of elevation discrepancies per land cover category

Table 9 lists the 5% outliers that are larger than the 95<sup>th</sup> percentile.

Point ID	NAD83(2011) UTM Zone 18N		NAVD88	LiDAR Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			
BLT-017	545330.239	4646100.481	648.091	647.5	-0.591	0.591
GWC-020	545092.663	4656223.324	448.43	448.17	-0.26	0.26
FO-002	523099.09	4589975.673	358.095	358.43	0.335	0.335
FO-007	592268.141	4596930.107	63.966	63.57	-0.396	0.396
FO-015	541702.666	4648774.157	609.175	608.68	-0.495	0.495

Table 9 – 5% Outliers

Table 10 provides overall descriptive statistics.

100 % of Totals	RMSE <sub>z</sub> (m) Open Terrain Spec=0.0925m	Mean (m)	Median (m)	Skew	Std Dev (m)	# of Points	Min (m)	Max (m)
Consolidated		-0.01	0.01	-1.33	0.14	103	-0.59	0.33
Open Terrain	0.07	0.00	-0.01	0.48	0.07	21	-0.14	0.17
Urban		-0.01	0.01	-0.93	0.11	21	-0.25	0.14
Tall Weeds and Crops		0.00	0.02	-0.85	0.11	20	-0.26	0.15
Brush Lands and Trees		0.02	0.03	-2.42	0.17	20	-0.59	0.23
Forested and Fully Grown		-0.03	-0.03	-0.59	0.19	21	-0.50	0.33

Table 10 – Overall Descriptive Statistics

The figure below illustrates a histogram of the associated elevation discrepancies between the QA/QC checkpoints and elevations interpolated from the LiDAR triangulated irregular network (TIN). The frequency shows the number of discrepancies within each band of elevation differences. Although the discrepancies vary between a low of -0.59 meters and a high of +0.33 meters, the histogram shows that the majority of the discrepancies are skewed on the negative side. The vast majority of points are within the ranges of -0.10 meters to +0.10 meters.




Figure 16 – Histogram of Elevation Discrepancies with errors in meters

**Based on the vertical accuracy testing conducted by Dewberry, the LiDAR dataset for the Ulster, Dutchess, and Orange Counties NY LiDAR Project satisfies the project's pre-defined vertical accuracy criteria.**

## Breakline Production & Qualitative Assessment Report


### BREAKLINE PRODUCTION METHODOLOGY

Dewberry used GeoCue software to develop LiDAR stereo models of the Ulster, Dutchess, and Orange Counties NY LiDAR Project area so the LiDAR derived data could be viewed in 3-D stereo using Socet Set softcopy photogrammetric software. Using LiDARgrammetry procedures with LiDAR intensity imagery, Dewberry used the stereo models developed by Dewberry to stereo-compile the two types of hard breaklines in accordance with the project's Data Dictionary.

All drainage breaklines are monotonically enforced to show downhill flow. Water bodies are reviewed in stereo and the lowest elevation is applied to the entire waterbody.

### BREAKLINE QUALITATIVE ASSESSMENT

Dewberry completed breakline qualitative assessments according to a defined workflow. The following workflow diagram represents the steps taken by Dewberry to provide a thorough qualitative assessment of the breakline data.



### BREAKLINE TOPOLOGY RULES

Automated checks are applied on hydro features to validate the 3D connectivity of the feature and the monotonicity of the hydrographic breaklines. Dewberry's major concern was that the hydrographic breaklines have a continuous flow downhill and that breaklines do not undulate. Error points are generated at each vertex not complying with the tested rules and these potential edit calls are then visually validated during the visual evaluation of the data. This step also helped validate that breakline vertices did not have excessive minimum or maximum elevations and that elevations are consistent with adjacent vertex elevations.

The next step is to compare the elevation of the breakline vertices against the elevation extracted from the ESRI Terrain built from the LiDAR ground points, keeping in mind that a discrepancy is expected because of the hydro-enforcement applied to the breaklines and because of the interpolated imagery used to acquire the breaklines. A given tolerance is used to validate if the elevations differ too much from the LiDAR.

Dewberry's final check for the breaklines was to perform a full qualitative analysis. Dewberry compared the breaklines against LiDAR intensity images to ensure breaklines were captured in the required locations. The quality control steps taken by Dewberry are outlined in the QA Checklist below.

## **BREAKLINE QA/QC CHECKLIST**

**Project Number/Description: TO G10PC00013 Ulster, Dutchess, and Orange Counties NY LiDAR**

**Date:** \_\_\_\_\_ **08/14/2015** \_\_\_\_\_

### **Overview**

- All Feature Classes are present in GDB
- All features have been loaded into the geodatabase correctly. Ensure feature classes with subtypes are domained correctly.
- The breakline topology inside of the geodatabase has been validated. See Data Dictionary for specific rules
- Projection/coordinate system of GDB is accurate with project specifications

### **Perform Completeness check on breaklines using either intensity or ortho imagery**

- Check entire dataset for missing features that were not captured, but should be to meet baseline specifications or for consistency (See Data Dictionary for specific collection rules). Features should be collected consistently across tile bounds within a dataset as well as be collected consistently between datasets.
- Check to make sure breaklines are compiled to correct tile grid boundary and there is full coverage without overlap
- Check to make sure breaklines are correctly edge-matched to adjoining datasets if applicable. Ensure breaklines from one dataset join breaklines from another dataset that are coded the same and all connecting vertices between the two datasets match in X,Y, and Z (elevation). There should be no breaklines abruptly ending at dataset boundaries and no discrepancies of Z-elevation in overlapping vertices between datasets.



## Compare Breakline Z elevations to LiDAR elevations

- ☒ Using a terrain created from LiDAR ground points and water points, drape breaklines on terrain to compare Z values. Breakline elevations should be at or below the elevations of the immediately surrounding terrain. This should be performed before other breakline checks are completed.

## Perform automated data checks using ESRI's Data Reviewer

The following data checks are performed utilizing ESRI's Data Reviewer extension. These checks allow automated validation of 100% of the data. Error records can either be written to a table for future correction, or browsed for immediate correction. Data Reviewer checks should always be performed on the full dataset.

- ☒ Perform "adjacent vertex elevation change check" on the Inland Ponds feature class (Elevation Difference Tolerance=.001 meters). This check will return Waterbodies whose vertices are not all identical. This tool is found under "Z Value Checks."
- ☒ Perform "unnecessary polygon boundaries check" on Inland Ponds and Lakes, Tidal Waters, and Islands (if delivered as a separate feature class) feature classes. This tool is found under "Topology Checks."
- ☒ Perform "different Z-Value at intersection check" (Inland Streams and Rivers to Inland Streams and Rivers), (Ponds and Lakes to Ponds and Lakes), (Tidal Waters to Tidal Waters), (Streams and Rivers to Ponds and Lakes), (Streams and Rivers to Tidal Waters), (Ponds and Lakes to Tidal Waters), (Island to Inland Ponds and Lakes), (Island to Tidal Waters), (Island to Island),and (Islands to Inland Streams and Rivers) (Elevation Difference Tolerance= .01 meters Minimum, 600 meters Maximum, Touches). This tool is found under "Z Value Checks." [Please note that polygon feature classes will need to be converted to lines for this check.](#)
- ☒ Perform "duplicate geometry check" on (Inland Streams and Rivers to Inland Streams and Rivers), (Inland Ponds and Lakes to Inland Ponds and Lakes), (Tidal Waters to Tidal Waters), (Islands to Islands-if delivered as a separate shapefile), (Inland Streams and Rivers to Inland Ponds and Lakes), (Inland Streams and Rivers to Tidal Waters), (Inland Ponds and Lakes to Tidal Waters), (Islands to Tidal Waters), and (Islands to Inland Ponds and Lakes). Attributes do not need to be checked during this tool. This tool is found under "Duplicate Geometry Checks."
- ☒ Perform "geometry on geometry check" (Inland Streams and Rivers to Inland Ponds and Lakes), (Inland Streams and Rivers to Tidal Waters), (Inland Ponds and Lakes to Tidal Waters), (Inland Streams and Rivers to Inland Streams and Rivers), (Inland Ponds and Lakes to Inland Ponds and Lakes), (Tidal waters to Tidal waters), (Islands to Tidal Waters), and (Islands to Inland Ponds and Lakes), (Islands to Islands). Spatial relationship is crosses, attributes do not need to be checked. This tool is found under "Feature on Feature Checks." [Please note that "crosses" only works with line feature](#)

classes and not polygons. If the inputs are polygons, they will need to be converted to a line prior to running this tool.

- Perform “geometry on geometry check (Tidal Waters to Islands), and (Inland Ponds and Lakes to Islands), (Inland Streams and Rivers to Islands). Spatial relationship is contains, attributes do not need to be checked. This tool is found under “Feature on Feature Checks.”
- Perform “geometry on geometry check” (Inland Streams and Rivers to Inland Ponds and Lakes), (Inland Streams and Rivers to Tidal Waters), (Inland Ponds and Lakes to Tidal Waters), (Inland Streams and Rivers to Inland Streams and Rivers), (Inland Ponds and Lakes to Inland Ponds and Lakes), (Tidal waters to Tidal waters), (Islands to Tidal Waters), and (Islands to Inland Ponds and Lakes), (Islands to Islands). Spatial relationship is intersect, attributes do not need to be checked. This tool is found under “Feature on Feature Checks.” Please note that false positives may be returned with this tool but that this tool may identify issues not found with “crosses.”
- Perform “polygon overlap/gap is sliver check” on (Tidal Waters to Tidal Waters), (Island to Island), (Island to Inland Ponds and Lakes) and (Inland Ponds and Lakes to Inland Ponds and Lakes), (Inland Ponds and Lakes to Tidal Waters). Maximum Polygon Area is not required. This tool is found under “Feature on Feature Checks.”

### **Perform Dewberry Proprietary Tool Checks**

- Perform monotonicity check on (Inland Streams and Rivers) and (Tidal Waters to Tidal Waters if they are not a constant elevation) using “A3\_checkMonotonicityStreamLines.” This tool looks at line direction as well as elevation. Features in the output shapefile attributed with a “d” are correct monotonically, but were compiled from low elevation to high elevation. These features are ok and can be ignored. Features in the output shapefile attributed with an “m” are not correct monotonically and need elevations to be corrected. Input features for this tool need to be in a geodatabase and must be a line. If features are a polygon they will need to be converted to a line feature. Z tolerance is 0.01 meters.
- Perform connectivity check between (Inland Streams and Rivers to Inland Streams and Rivers), (Ponds and Lakes to Ponds and Lakes), (Tidal Waters to Tidal Waters), (Streams and Rivers to Ponds and Lakes), (Streams and Rivers to Tidal Waters), (Ponds and Lakes to Tidal Waters), (Island to Inland Ponds and Lakes), (Island to Tidal Waters), (Island to Island), and (Islands to Inland Streams and Rivers) using the tool “07\_CheckConnectivityForHydro.” The input for this tool needs to be in a geodatabase. The output is a shapefile showing the location of overlapping vertices from the polygon features and polyline features that are at different Z-elevation.

## Metadata

- Each XML file (1 per feature class) is error free as determined by the USGS MP tool
- Metadata content contains sufficient detail and all pertinent information regarding source materials, projections, datums, processing steps, etc. Content should be consistent across all feature classes.

**Completion Comments: Complete – Approved**

## Data Dictionary

### HORIZONTAL AND VERTICAL DATUM

The horizontal datum shall be North American Datum of 1983 (2011), Units in Meters. The vertical datum shall be referenced to the North American Vertical Datum of 1988 (NAVD 88), Units in Meters. Geoid12a shall be used to convert ellipsoidal heights to orthometric heights.

### COORDINATE SYSTEM AND PROJECTION

All data shall be projected to UTM Zone 18, Horizontal Units in Meters and Vertical Units in Meters.

### INLAND STREAMS AND RIVERS

**Feature Dataset:** BREAKLINES  
**Feature Type:** Polygon  
**Contains Z Values:** Yes  
**XY Resolution:** Accept Default Setting  
**XY Tolerance:** 0.003

**Feature Class:** STREAMS\_AND\_RIVERS  
**Contains M Values:** No  
**Annotation Subclass:** None  
**Z Resolution:** Accept Default Setting  
**Z Tolerance:** 0.001

### Description

This polygon feature class will depict linear hydrographic features with a width greater than 100 feet.

### Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

## Feature Definition

Description	Definition	Capture Rules
<p>Streams and Rivers</p>	<p>Linear hydrographic features such as streams, rivers, canals, etc. with an average width greater than 100 feet. In the case of embankments, if the feature forms a natural dual line channel, then capture it consistent with the capture rules. Other natural or manmade embankments will not qualify for this project.</p>	<p>Capture features showing dual line (one on each side of the feature). Average width shall be greater than 100 feet to show as a double line. Each vertex placed should maintain vertical integrity. Generally both banks shall be collected to show consistent downhill flow. There are exceptions to this rule where a small branch or offshoot of the stream or river is present.</p> <p>The banks of the stream must be captured at the same elevation to ensure flatness of the water feature. If the elevation of the banks appears to be different see the task manager or PM for further guidance.</p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding LiDAR points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>These instructions are only for docks or piers that follow the coastline or water's edge, not for docks or piers that extend perpendicular from the land into the water. If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water's edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p> <p>Every effort should be made to avoid breaking a stream or river into segments.</p> <p>Dual line features shall break at road crossings (culverts). In areas where a bridge is present the dual line feature shall continue through the bridge.</p> <p>Islands: The double line stream shall be captured around an island if the island is greater than 1 acre. In this case a segmented polygon shall be used around the island in order to allow for the island feature to remain as a "hole" in the feature.</p>

## INLAND PONDS AND LAKES

**Feature Dataset:** BREAKLINES  
**Feature Type:** Polygon  
**Contains Z Values:** Yes  
**XY Resolution:** Accept Default Setting  
**XY Tolerance:** 0.003

**Feature Class:** PONDS\_AND\_LAKES  
**Contains M Values:** No  
**Annotation Subclass:** None  
**Z Resolution:** Accept Default Setting  
**Z Tolerance:** 0.001

### Description

This polygon feature class will depict closed water body features that are at a constant elevation.

### Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

### Feature Definition

Description	Definition	Capture Rules
Ponds and Lakes	<p>Land/Water boundaries of constant elevation water bodies such as lakes, reservoirs, ponds, etc. Features shall be defined as closed polygons and contain an elevation value that reflects the best estimate of the water elevation at the time of data capture. Water body features will be captured for features 2 acres in size or greater.</p> <p>“Donuts” will exist where there are islands within a closed water body feature.</p>	<p>Water bodies shall be captured as closed polygons with the water feature to the right. <u>The compiler shall take care to ensure that the z-value remains consistent for all vertices placed on the water body.</u></p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding LiDAR points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>An Island within a Closed Water Body Feature that is 1 acre in size or greater will also have a “donut polygon” compiled.</p> <p>These instructions are only for docks or piers that follow the coastline or water’s edge, not for docks or piers that extend perpendicular from the land into the water. If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line</p>




		<p>will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water's edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p>
--	--	--

## DEM Production & Qualitative Assessment

### DEM PRODUCTION METHODOLOGY

Dewberry utilized ESRI software and Global Mapper for the DEM production and QC process. ArcGIS software is used to generate the products and the QC is performed in both ArcGIS and Global Mapper.

Dewberry Hydro-Flattening Workflow



1. Classify Water Points: LAS point falling within hydrographic breaklines shall be classified to ASPRS class 9 using TerraScan. Breaklines must be prepared correctly prior to performing this task.

2. **Classify Ignored Ground Points:** Classify points in close proximity to the breaklines from Ground to class 10 (Ignored Ground). Close proximity will be defined as no more than 1x the nominal point spacing on the landward side of the breakline.
3. **Terrain Processing:** A Terrain will be generated using the Breaklines and LAS data that has been imported into Arc as a Multipoint File.
4. **Create DEM Zones for Processing:** Create DEM Zones that are buffered around the edges. Zones should be created in a logical manner to minimize the number of zones without creating zones too large for processing. Dewberry will make zones no larger than 200 square miles (taking into account that a DEM will fill in the entire extent not just where LiDAR is present). Once the first zone is created it must be verified against the tile grid to ensure that the cells line up perfectly with the tile grid edge.
5. **Convert Terrain to Raster:** Convert Terrain to raster using the DEM Zones created in step 4. In the environmental properties set the extents of the raster to the buffered Zone. For each subsequent zone, the first DEM will be utilized as the snap raster to ensure that zones consistently snap to one another.
6. **Perform Initial QAQC on Zones:** During the initial QA process anomalies will be identified and corrective polygons will be created.
7. **Correct Issues on Zones:** Dewberry will perform corrections on zones following Dewberry's correction process.
8. **Extract Individual Tiles:** Dewberry will extract individual tiles from the zones utilizing a Dewberry proprietary tool.
9. **Final QA:** Final QA will be performed on the dataset to ensure that tile boundaries are seamless.

## **DEM QUALITATIVE ASSESSMENT**

Dewberry performed a comprehensive qualitative assessment of the bare earth DEM deliverables to ensure that all tiled DEM products were delivered with the proper extents, were free of processing artifacts, and contained the proper referencing information. This process was performed in ArcGIS software with the use of a tool set Dewberry has developed to verify that the raster extents match those of the tile grid and contain the correct projection information. The DEM data was reviewed at a scale of 1:5000 to review for artifacts caused by the DEM generation process and to review the hydro-flattened features. To perform this review Dewberry creates HillShade models and overlays a partially transparent colorized elevation model to review for these issues. All corrections are completed using Dewberry's proprietary correction workflow. Upon completion of the corrections, the DEM data is loaded into Global Mapper for its second review and to verify corrections. Once the DEMs are tiled out, the final tiles are again loaded into Global Mapper to ensure coverage, extents, and that the final tiles are seamless.

The images below show an example of a bare earth DEM.




Figure 17-Tile 18TWM475185 Bare earth DEM






Figure 18-Tile 18TWM490185. 3D Profile view of the bare earth DEM

When some bridges are removed from the ground surface, the distance from bridge abutment to bridge abutment is small enough that the DEM interpolates across the entire bridge opening, forming 'bridge saddles.' Dewberry collected 3D bridge breaklines in locations where bridge saddles were present and enforced these breaklines in the final DEM creation to help mitigate the bridge saddle artifacts. The image below on the left shows a bridge saddle while the image below on the right shows the same bridge after bridge breaklines have been enforced.




Figure 19-Tile 18TWL385810. The DEM on the left shows a bridge saddle artifact while the DEM on the right shows the same location after bridge breaklines have been enforced.

## DEM VERTICAL ACCURACY RESULTS

The same 103 checkpoints that were used to test the vertical accuracy of the LiDAR were used to validate the vertical accuracy of the final DEM products as well. Accuracy results may vary between the source LiDAR and final DEM deliverable. DEMs are created by averaging several LiDAR points within each pixel which may result in slightly different elevation values at each survey checkpoint when compared to the source LAS, which does not average several LiDAR points together but may interpolate (linearly) between two or three points to derive an elevation value.

Table 9 summarizes the tested vertical accuracy results from a comparison of the surveyed checkpoints to the elevation values present within the final DEM dataset.

Land Cover Category	# of Points	FVA – Fundamental Vertical Accuracy (RMSE <sub>z</sub> x 1.9600) Spec=0.181 m	CVA – Consolidated Vertical Accuracy (95th Percentile) Spec=0.269 m	SVA – Supplemental Vertical Accuracy (95th Percentile) Target=0.269 m
Consolidated	103		0.26	
Bare Earth-Open Terrain	21	0.13		
Urban	21			0.25
Tall Weeds and Crops	20			0.20
Brush Lands and Trees	20			0.25
Forested and Fully Grown	21			0.33

Table 11 – FVA, CVA, and SVA Vertical Accuracy at 95% Confidence Level

The RMSE<sub>z</sub> for checkpoints in open terrain only tested 0.06 meters, within the target criteria of 0.0925 meters. Compared with the 0.181 meters specification, the FVA tested 0.13 meters at the 95% confidence level based on RMSE<sub>z</sub> x 1.9600.

Compared with the 0.269 meters specification, CVA for all checkpoints in all land cover categories combined tested 0.26 meters based on the 95<sup>th</sup> percentile.

Compared with the target 0.269 meters specification, SVA for checkpoints in the tall weeds and crops land cover category tested 0.20 meters based on the 95<sup>th</sup> percentile, checkpoints in the forested and fully grown land cover category tested 0.33 meters based on the 95<sup>th</sup> percentile, checkpoints in the brush and small trees land cover category tested 0.25 meters based on the 95<sup>th</sup> percentile, and checkpoints in the urban land cover category tested 0.25 meters based on the 95<sup>th</sup> percentile.

Table 12 lists the 5% outliers that are larger than the 95<sup>th</sup> percentile.

Point ID	NAD83(2011) UTM Zone 18N		NAVD88	DEM Z (m)	Delta Z	AbsDeltaZ
	Easting X (m)	Northing Y (m)	Survey Z (m)			



BLT-017	545330.239	4646100.481	648.091	647.5047977	-0.59	0.59
GWC-020	545092.663	4656223.324	448.43	448.1649763	-0.27	0.27
UT-001	524086.368	4652515.066	557.265	556.9861538	-0.28	0.28
FO-002	523099.09	4589975.673	358.095	358.4139629	0.32	0.32
FO-007	592268.141	4596930.107	63.966	63.63617085	-0.33	0.33
FO-015	541702.666	4648774.157	609.175	608.6949045	-0.48	0.48

Table 12 – 5% Outliers

Table 13 provides overall descriptive statistics.

100 % of Totals	RMSE <sub>z</sub> (m) Open Terrain Spec=0.0925 m	Mean (m)	Median (m)	Skew	Std Dev (m)	# of Points	Min (m)	Max (m)
Consolidated		0.00	0.01	-1.28	0.13	103	-0.59	0.32
Open Terrain	0.06	0.00	0.00	0.70	0.07	21	-0.13	0.18
Urban		-0.02	0.02	-1.06	0.11	21	-0.28	0.16
Tall Weeds and Crops		0.00	0.02	-0.89	0.11	20	-0.27	0.14
Brush Lands and Trees		0.02	0.04	-2.32	0.17	20	-0.59	0.24
Forested and Fully Grown		-0.02	0.01	-0.54	0.19	21	-0.48	0.32

Table 13 – Overall Descriptive Statistics

## DEM QA/QC CHECKLIST

**Project Number/Description:** TO G13PD00855 Ulster, Dutchess, and Orange Counties NY LiDAR **Date:** 08/14/2015

### Overview

- Correct number of files is delivered and all files are in ERDAS IMG format
- Verify Raster Extents
- Verify Projection/Coordinate System

### Review

- Manually review bare-earth DEMs in Arc with a hillshade to check for issues with the hydro-flattening process or any general anomalies that may be present. Specifically, water should be flowing downhill, water features should NOT be floating above surrounding terrain and bridges should NOT be present in bare-earth DEM. Hydrologic breaklines should be overlaid during review of DEMs.
- DEM cell size is 1 meter
- Perform all necessary corrections in Arc using Dewberry's proprietary correction workflow.
- Review all corrections in Global Mapper
- Perform final overview on tiled data in Global Mapper to ensure seamless product.

### Metadata

- Project level DEM metadata XML file is error free as determined by the USGS MP tool

- Metadata content contains sufficient detail and all pertinent information regarding source materials, projections, datums, processing steps, etc.

**Completion Comments: Complete – Approved**

## Appendix A: Survey Report

### 1. INTRODUCTION

---

#### 1.1 *Project Summary*

Dewberry Consultants, LLC is under contract to USGS to provide 105 Check Points for USGS in the State of New York. Under the above referenced USGS Task Order, Dewberry is tasked to complete the quality assurance of high resolution LiDAR-derived elevation products. As part of this work Dewberry staff will complete checkpoint surveys that will be used to evaluate vertical accuracy on the bare-earth terrain derived from the LiDAR.

Existing NGS Control Points were located and surveyed to check the accuracy of the RTK/GPS survey equipment with the results shown in Section 2.4 of this Report.

As an internal QA/QC procedure and to verify that the Check Points meet the 95% confidence level approximately 50% of the points were re-observed and are shown in Section 5 of this report.

Final horizontal coordinates are referenced to UTM Zone 18, NAD 83 in meters. Final Vertical elevations are referenced to NAVD88 in meters using Geoid model 2012A (Geoid12A).


#### 1.2 *Points of Contact*

Questions regarding the technical aspects of this report should be addressed to:

##### **Dewberry Consultants, LLC**

Gary Simpson, L.S.  
Senior Associate  
10003 Derekwood Lane  
Suite 204  
Lanham, Maryland 20706  
(301) 364-1855 direct  
(301) 731-0188 fax

#### 1.3 *Project Areas*



## Project Details

### 2.1 Survey Equipment

In performing the GPS observations, Trimble R-8 & R-10 GNSS receiver/antenna attached to a two meter fixed height pole with a Trimble TSC3 Data Collector to collect GPS raw data were used to perform the field surveys.

### 2.2 Survey Point Detail

The 105 Check Points were well distributed throughout the project area.

A sketch was made for each location and a nail was set at the point where possible or at an identifiable point. The Check Point locations are detailed on the “Ground Control Point Documentation Report” sheets attached to this report.

### 2.3 Network Design

The GPS survey performed by Dewberry Consultants, LLC office located in Lanham, MD was tied to a Real Time Network (RTN) managed by NYDOT. The network is a series of “real-time” continuously operating, high precision GPS reference stations. All of the reference stations have been linked together using Trimble GPSNet software, creating a Virtual Reference Station System (VRS).

The Trimble NetR5 Reference Station is a multi-channel, multi-frequency GNSS (Global Navigation Satellite System) receiver designed for use as a stand-alone reference station or as part of a GNSS infrastructure solution. Trimble R-Track technology in the NetR5 receiver supports the modernized GPS L2C and L5 signals as well as GLONASS L1/L2 signals.

### 2.4 Field Survey Procedures and Analysis

Dewberry field surveyors used Trimble R-8 & R-10 GNSS receivers, which is a geodetic quality dual frequency GPS receiver, to collect data at each surveyed location.

All locations were occupied once with approximately 50% of the locations being re-observed. All re-observations matched the initially derived station positions within the allowable tolerance of  $\pm 5$ cm or within the 95% confidence level. Each occupation which utilized the VRS network was occupied for approximately three (3) minutes in duration and measured to 180 epochs.

Each occupation which utilized OPUS (if used) was occupied between 18 and 20 minutes.

Field GPS observations are detailed on the “Ground Control Point Documentation Reports” submitted as part of this report.

Four (4) existing NGS monument listed in the NSRS database were located as an additional QA/QC method to check the accuracy of the VRS network as well as being the primary project control monuments designated as PID AB3871, AB3874, AB3873 and DG9708. The results are as follows:

NGS PT. ID	As Surveyed (ft)			Published (ft)			Differences (ft)		
	Northing(ft)	Easting(ft)	Elev.(ft)	Northing(ft)	Easting(ft)	Elev.(ft)	$\Delta N$	$\Delta E$	$\Delta Elev.$
AB3871	4619880.543	551670.122	87.611	4619880.568	551670.089	87.568	0.025	0.033	0.043
AB3874	4629989.392	578168.093	54.839	4629989.406	578168.090	54.800	0.014	0.003	0.039
AB3873	4625141.237	607873.766	167.942	4625141.262	607873.756	167.900	0.025	0.010	0.042
DG9708	4589813.388	533281.806	153.114	4589813.402	533281.788	153.100	0.014	0.018	0.014



The above results indicate that the VRS network is providing positional values within the 5cm parameters for this survey.

## Ap2.5 Adjustment

The survey data was collected using Virtual Reference Stations (VRS) methodology within a Virtual Reference System (VRS).

The system is designed to provide a true Network RTK performance, the RTKNet software enables high-accuracy positioning in real time across a geographic region. The RTKNet software package uses real-time data streams from the GPSNet system user and generates correction models for high-accuracy RTK GPS corrections throughout the network. Therefore, corrections were applied to the points as they were being collected, thus negating the need for a post process adjustment.

## 2.6 Data Processing Procedures

After field data is collected the information is downloaded from the data collectors into the office software. The Software program used is called TBC or Trimble Business Center.

Downloaded data is run through the TBC program to obtain the following reports; points report, point comparison report and a point detail report. The reports are reviewed for point accuracy and precision.

After review of the point data an “ASCII” or “txt” file which is the industry standard is created. Point files are loaded into our CADD program (Carlson Survey 2014) to make a visual check of the point data (Pt. #, Coordinates, Elev. and Description). The data can now be imported into the final product.

## 3. FINAL COORDINATES

POINT #	NORTHING (M)	EASTING (M)	ELEV. (M)
<b>Brush, Low Trees Points</b>			
BLT-001	4645437.756	613742.291	164.699
BLT-002	4649719.492	595619.951	67.255
BLT-003	4636132.396	603128.705	162.858
BLT-004	4618435.937	609287.890	218.990
BLT-005	4599391.723	587605.341	64.511
BLT-006	4612356.376	583475.673	130.087
BLT-007	4581823.940	584305.786	184.861
BLT-008	4574768.497	549917.753	118.068

<b>BLT-009</b>	<b>4582455.472</b>	<b>556743.536</b>	<b>139.141</b>
<b>BLT-010</b>	<b>4597007.813</b>	<b>548474.677</b>	<b>184.704</b>
<b>BLT-011</b>	<b>4616414.115</b>	<b>545501.595</b>	<b>372.673</b>
<b>BLT-012</b>	<b>4627309.926</b>	<b>571006.315</b>	<b>77.020</b>
<b>BLT-013</b>	<b>4634303.826</b>	<b>584374.373</b>	<b>40.841</b>
<b>BLT-014</b>	<b>4637500.363</b>	<b>562200.793</b>	<b>230.808</b>
<b>BLT-015</b>	<b>4654712.141</b>	<b>572095.278</b>	<b>178.052</b>
<b>BLT-016</b>	<b>4641268.201</b>	<b>542135.008</b>	<b>762.011</b>
<b>BLT-017</b>	<b>4646100.481</b>	<b>545330.239</b>	<b>648.091</b>
<b>BLT-018</b>	<b>4663641.117</b>	<b>549616.124</b>	<b>332.608</b>
<b>BLT-019</b>	<b>4657947.891</b>	<b>532765.320</b>	<b>626.974</b>
<b>BLT-020</b>	<b>4642684.366</b>	<b>537463.589</b>	<b>682.092</b>
<b>BLT-021</b>	<b>4650126.985</b>	<b>527284.950</b>	<b>609.487</b>
<b>Grass, Weed, Crops Points</b>			
<b>GWC-001</b>	<b>4606713.771</b>	<b>610772.112</b>	<b>148.357</b>
<b>GWC-002</b>	<b>4614836.982</b>	<b>618436.864</b>	<b>144.227</b>
<b>GWC-003</b>	<b>4629793.124</b>	<b>613564.922</b>	<b>277.217</b>
<b>GWC-004</b>	<b>4639953.278</b>	<b>613067.388</b>	<b>245.387</b>
<b>GWC-005</b>	<b>4639003.494</b>	<b>597532.926</b>	<b>195.523</b>
<b>GWC-006</b>	<b>4627520.650</b>	<b>595074.183</b>	<b>120.268</b>
<b>GWC-007</b>	<b>4609288.577</b>	<b>593924.181</b>	<b>47.696</b>
<b>GWC-008</b>	<b>4585764.905</b>	<b>566750.022</b>	<b>111.922</b>
<b>GWC-009</b>	<b>4571862.962</b>	<b>559817.167</b>	<b>161.841</b>
<b>GWC-010</b>	<b>4581829.323</b>	<b>540925.345</b>	<b>186.857</b>
<b>GWC-011</b>	<b>4600381.391</b>	<b>565200.757</b>	<b>122.645</b>
<b>GWC-012</b>	<b>4614691.591</b>	<b>565557.457</b>	<b>77.161</b>
<b>GWC-013</b>	<b>4628772.503</b>	<b>567180.984</b>	<b>100.749</b>
<b>GWC-014</b>	<b>4638028.511</b>	<b>578998.385</b>	<b>56.638</b>
<b>GWC-015</b>	<b>4649444.663</b>	<b>575631.577</b>	<b>176.699</b>
<b>GWC-016</b>	<b>4657770.586</b>	<b>582823.670</b>	<b>162.047</b>
<b>GWC-017</b>	<b>4625416.485</b>	<b>540218.412</b>	<b>339.674</b>
<b>GWC-018</b>	<b>4641734.207</b>	<b>550668.210</b>	<b>424.838</b>
<b>GWC-019</b>	<b>4655980.656</b>	<b>558464.035</b>	<b>220.303</b>
<b>GWC-020</b>	<b>4656223.324</b>	<b>545092.663</b>	<b>448.430</b>
<b>GWC-021</b>	<b>4650778.583</b>	<b>528578.379</b>	<b>641.619</b>
<b>OT-001</b>			
<b>OT-001</b>	<b>4664757.282</b>	<b>543194.751</b>	<b>449.086</b>

OT-003	4663513.537	587566.321	44.153
OT-004	4647830.939	582634.844	46.802
OT-005	4649018.695	604527.498	134.649
OT-006	4635251.978	620324.637	178.750
OT-007	4625876.170	602524.625	106.681
OT-008	4629972.774	578162.244	54.194
OT-009	4624541.071	556920.869	82.355
OT-010	4621623.578	538685.782	331.949
OT-011	4653550.304	522286.303	538.560
OT-012	4608699.518	552368.154	177.248
OT-013	4607672.318	576995.043	172.011
OT-014	4613921.324	600983.321	109.668
OT-015	4599913.209	602089.503	97.629
OT-016	4586341.675	570932.547	94.250
OT-017	4596320.864	581067.722	72.336
OT-018	4589395.276	554397.435	130.023
OT-019	4589841.048	533282.104	153.227
OT-020	4576745.660	570154.290	199.367
OT-021	4561795.004	568404.033	145.259
OT-002	4653225.544	560233.298	204.555
<b>Urban Terrain Points</b>			
UT-001	4652515.066	524086.368	557.265
UT-002	4662675.148	535891.353	480.971
UT-003	4661367.804	545999.024	369.692
UT-004	4654927.847	559292.793	212.259
UT-005	4655174.209	573001.618	177.605
UT-006	4663531.935	583524.674	115.267
UT-007	4643323.526	580775.977	48.122
UT-008	4645585.734	624041.990	216.087
UT-009	4623236.176	617831.082	126.512
UT-010	4617866.519	589650.326	48.265
UT-011	4621483.975	575900.626	90.294
UT-012	4644022.692	566005.040	155.276
UT-013	4626022.597	559441.735	114.351
UT-014	4618345.966	550138.384	105.262
UT-015	4606088.835	558601.016	107.806
UT-016	4594364.225	574629.402	134.740
UT-017	4603765.456	598951.427	74.003

UT-018	4573939.871	572491.837	169.104
UT-019	4565819.121	566543.331	220.024
UT-020	4571824.956	544810.808	127.996
UT-021	4580719.307	527091.373	133.245
<b>Forest Points</b>			
FO-001	4560668.009	562640.354	223.229
FO-002	4589975.673	523099.090	358.095
FO-003	4591468.486	538337.251	257.333
FO-004	4594940.718	555653.452	174.369
FO-005	4577678.519	565029.380	146.120
FO-006	4573218.442	580566.007	158.091
FO-007	4596930.107	592268.141	63.966
FO-008	4600347.717	617949.402	146.722
FO-009	4614523.255	620730.493	122.692
FO-010	4650178.933	622873.383	232.629
FO-011	4645217.381	602678.995	163.992
FO-012	4632633.306	588589.451	4.595
FO-013	4624436.392	579188.507	114.243
FO-014	4627509.836	547358.168	284.057
FO-015	4648774.157	541702.666	609.175
FO-016	4651988.481	519399.065	513.055
FO-017	4665849.137	548956.377	396.952
FO-018	4651267.887	560593.038	203.640
FO-019	4636921.147	570459.819	84.696
FO-020	4667722.401	582782.249	113.685
FO-021	4657565.430	589790.392	48.110

#### 4. *GPS COMPARISON*

POINT ID	POINT CK	DELTA NORTH (M)	DELTA EAST (M)	VERT. DIFF (M)
<b>Brush, Low Trees Points</b>				
BLT-001	BLT-001CK	0.001	0.001	0.008
BLT-003	BLT-003CK	0.001	0.004	0.013
BLT-004	BLT-004CK	0.004	0.013	0.013
BLT-005	BLT-005CK	0.002	0.000	0.035
BLT-007	BLT-007CK	0.006	0.010	0.014
BLT-008	BLT-008CK	0.001	0.001	0.002
BLT-010	BLT-010CK	0.007	0.003	0.019

<b>BLT-011</b>	<b>BLT-011CK</b>	<b>0.003</b>	<b>0.000</b>	<b>0.021</b>
<b>BLT-012</b>	<b>BLT-012CK</b>	<b>0.002</b>	<b>0.003</b>	<b>0.004</b>
<b>BLT-016</b>	<b>BLT-016CK</b>	<b>0.011</b>	<b>0.003</b>	<b>0.001</b>
<b>BLT-017</b>	<b>BLT-017CK</b>	<b>0.003</b>	<b>0.000</b>	<b>0.031</b>
<b>BLT-018</b>	<b>BLT-018CK</b>	<b>0.003</b>	<b>0.000</b>	<b>0.031</b>
<b>Grass, Weed, Crops Points</b>				
<b>GWC-001</b>	<b>GWC-001CK</b>	<b>0.005</b>	<b>0.000</b>	<b>0.003</b>
<b>GWC-002</b>	<b>GWC-002CK</b>	<b>0.003</b>	<b>0.002</b>	<b>0.014</b>
<b>GWC-003</b>	<b>GWC-003CK</b>	<b>0.009</b>	<b>0.007</b>	<b>0.021</b>
<b>GWC-005</b>	<b>GWC-005CK</b>	<b>0.001</b>	<b>0.006</b>	<b>0.008</b>
<b>GWC-006</b>	<b>GWC-006CK</b>	<b>0.002</b>	<b>0.005</b>	<b>0.010</b>
<b>GWC-007</b>	<b>GWC-007CK</b>	<b>0.004</b>	<b>0.004</b>	<b>0.002</b>
<b>GWC-009</b>	<b>GWC-009CK</b>	<b>0.001</b>	<b>0.000</b>	<b>0.016</b>
<b>GWC-010</b>	<b>GWC-010CK</b>	<b>0.001</b>	<b>0.000</b>	<b>0.004</b>
<b>GWC-012</b>	<b>GWC-012CK</b>	<b>0.003</b>	<b>0.003</b>	<b>0.004</b>
<b>GWC-013</b>	<b>GWC-013CK</b>	<b>0.008</b>	<b>0.007</b>	<b>0.005</b>
<b>GWC-016</b>	<b>GWC-016CK</b>	<b>0.011</b>	<b>0.014</b>	<b>0.022</b>
<b>GWC-017</b>	<b>GWC-017CK</b>	<b>0.002</b>	<b>0.004</b>	<b>0.005</b>
<b>GWC-018</b>	<b>GWC-018CK</b>	<b>0.004</b>	<b>0.000</b>	<b>0.001</b>
<b>GWC-019</b>	<b>GWC-019CK</b>	<b>0.002</b>	<b>0.000</b>	<b>0.011</b>
<b>GWC-020</b>	<b>GWC-020CK</b>	<b>0.002</b>	<b>0.004</b>	<b>0.005</b>
<b>Open Terrain Points</b>				
<b>OT-005</b>	<b>OT-005CK</b>	<b>0.003</b>	<b>0.002</b>	<b>0.002</b>
<b>OT-006</b>	<b>OT-006CK</b>	<b>0.012</b>	<b>0.001</b>	<b>0.001</b>
<b>OT-007</b>	<b>OT-007CK</b>	<b>0.004</b>	<b>0.008</b>	<b>0.004</b>
<b>OT-014</b>	<b>OT-014CK</b>	<b>0.004</b>	<b>0.006</b>	<b>0.003</b>
<b>OT-015</b>	<b>OT-015CK</b>	<b>0.003</b>	<b>0.002</b>	<b>0.004</b>
<b>OT-016</b>	<b>OT-016CK</b>	<b>0.005</b>	<b>0.002</b>	<b>0.000</b>
<b>OT-018</b>	<b>OT-018CK</b>	<b>0.015</b>	<b>0.000</b>	<b>0.026</b>
<b>OT-019</b>	<b>OT-019CK</b>	<b>0.001</b>	<b>0.002</b>	<b>0.013</b>
<b>OT-020</b>	<b>OT-020CK</b>	<b>0.010</b>	<b>0.034</b>	<b>0.024</b>
<b>OT-021</b>	<b>OT-021CK</b>	<b>0.001</b>	<b>0.002</b>	<b>0.028</b>
<b>Urban Terrain Points</b>				
<b>UT-008</b>	<b>UT-008CK</b>	<b>0.007</b>	<b>0.011</b>	<b>0.008</b>
<b>UT-009</b>	<b>UT-009CK</b>	<b>0.013</b>	<b>0.022</b>	<b>0.040</b>
<b>UT-010</b>	<b>UT-010CK</b>	<b>0.003</b>	<b>0.010</b>	<b>0.004</b>
<b>UT-013</b>	<b>UT-013CK</b>	<b>0.003</b>	<b>0.006</b>	<b>0.003</b>
<b>UT-014</b>	<b>UT-014CK</b>	<b>0.014</b>	<b>0.006</b>	<b>0.008</b>



UT-015	UT-015CK	0.006	0.004	0.007
UT-018	UT-018CK	0.001	0.001	0.022
UT-019	UT-019CK	0.003	0.006	0.012
UT-020	UT-020CK	0.002	0.007	0.000
UT-021	UT-021CK	0.000	0.000	0.003
<b>Forest Points</b>				
FO-007	FO-007CK	0.006	0.031	0.015
FO-008	FO-008CK	0.010	0.020	0.034
FO-010	FO-010CK	0.001	0.006	0.021
FO-011	FO-011CK	0.005	0.006	0.015
FO-012	FO-012CK	0.021	0.007	0.010

## 5. OBSERVATION DATES

POINT ID	OBSERV. DATE	JULIAN DATE	TIME OF DAY	RE-OBSERV. DATE	RE-OBSERV. TIME
<b>Brush, Low Trees Points</b>					
BLT-001	5/21/2014	141	15:47	5/24/2014	9:19
BLT-002	5/21/2014	141	19:43	N/A	N/A
BLT-003	5/21/2014	141	17:59	5/24/2014	9:02
BLT-004	5/21/2014	141	12:33	5/24/2014	6:29
BLT-005	5/20/2014	140	16:49	5/21/2014	6:28
BLT-006	5/24/2014	144	7:55	N/A	N/A
BLT-007	5/24/2014	144	5:01	5/25/2014	19:01
BLT-008	5/23/2014	143	7:34	5/25/2014	19:51
BLT-009	5/23/2014	143	11:49	N/A	N/A
BLT-010	5/22/2014	142	15:06	5/25/2014	20:21
BLT-011	5/22/2014	142	17:12	5/25/2014	21:49
BLT-012	5/24/2014	144	10:20	5/25/2014	6:02
BLT-013	5/25/2014	145	16:52	N/A	N/A
BLT-014	5/24/2014	144	11:10	N/A	N/A
BLT-015	5/25/2014	145	13:03	N/A	N/A
BLT-016	5/24/2014	144	13:16	5/25/2014	6:49
BLT-017	5/24/2014	144	13:37	5/25/2014	7:29
BLT-018	5/24/2014	144	17:02	5/25/2014	8:03
BLT-019	5/25/2014	145	9:35	N/A	N/A
BLT-020	5/24/2014	144	14:22	N/A	N/A
BLT-021	5/25/2014	145	11:05	N/A	N/A

Grass, Weed, Crops Points					
GWC-001	5/20/2014	140	18:24	5/21/2014	5:41
GWC-002	5/20/2014	140	19:59	5/21/2014	6:01
GWC-003	5/21/2014	141	13:30	5/24/2014	10:16
GWC-004	5/21/2014	141	15:28	N/A	N/A
GWC-005	5/21/2014	141	18:23	5/24/2014	8:51
GWC-006	5/21/2014	141	11:25	5/24/2014	7:41
GWC-007	5/21/2014	141	8:46	5/24/2014	6:58
GWC-008	5/23/2014	143	12:15	N/A	N/A
GWC-009	5/23/2014	143	8:01	5/25/2014	19:31
GWC-010	5/23/2014	143	6:49	5/25/2014	20:05
GWC-011	5/24/2014	144	6:54	N/A	N/A
GWC-012	5/24/2014	144	8:26	5/25/2014	20:43
GWC-013	5/24/2014	144	10:36	5/25/2014	6:15
GWC-014	5/25/2014	145	16:29	N/A	N/A
GWC-015	5/25/2014	145	12:23	N/A	N/A
GWC-016	5/22/2014	142	8:17	5/25/2014	8:59
GWC-017	5/22/2014	142	17:47	5/25/2014	22:01
GWC-018	5/24/2014	144	12:18	5/25/2014	7:15
GWC-019	5/24/2014	144	17:41	5/25/2014	8:16
GWC-020	5/24/2014	144	15:34	5/25/2014	7:46
GWC-021	5/25/2014	145	8:40	N/A	N/A
Open Terrain Points					
OT-001	5/24/2014	144	16:42	N/A	N/A
OT-003	5/22/2014	142	8:53	N/A	N/A
OT-004	5/25/2014	145	14:40	N/A	N/A
OT-005	5/21/2014	141	19:25	5/24/2014	8:49
OT-006	5/21/2014	141	14:07	5/24/2014	9:58
OT-007	5/21/2014	141	11:45	5/24/2014	7:29
OT-008	5/24/2014	144	9:52	N/A	N/A
OT-009	5/22/2014	142	18:42	N/A	N/A
OT-010	5/22/2014	142	17:29	N/A	N/A
OT-011	5/25/2014	145	18:12	N/A	N/A
OT-012	5/22/2014	142	15:53	N/A	N/A
OT-013	5/24/2014	144	7:28	N/A	N/A
OT-014	5/21/2014	141	9:17	5/24/2014	6:43
OT-015	5/20/2014	140	17:50	5/24/2014	5:23
OT-016	5/23/2014	143	12:30	5/24/2014	5:11

OT-017	5/24/2014	144	6:10	N/A	N/A
OT-018	5/22/2014	142	14:18	5/24/2014	7:02
OT-019	5/22/2014	142	19:46	5/24/2014	6:48
OT-020	5/23/2014	143	10:52	5/24/2014	5:25
OT-021	5/23/2014	143	9:26	5/24/2014	5:59
OT-002	5/25/2014	145	11:22	N/A	N/A
<b>Urban Terrain Points</b>					
UT-001	5/25/2014	145	6:53	N/A	N/A
UT-002	5/25/2014	145	10:26	N/A	N/A
UT-003	5/24/2014	144	15:54	N/A	N/A
UT-004	5/25/2014	145	11:07	N/A	N/A
UT-005	5/25/2014	145	13:21	N/A	N/A
UT-006	5/25/2014	145	13:49	N/A	N/A
UT-007	5/25/2014	145	15:25	N/A	N/A
UT-008	5/21/2014	141	16:13	5/24/2014	9:41
UT-009	5/21/2014	141	13:06	5/24/2014	10:29
UT-010	5/21/2014	141	9:57	5/24/2014	7:16
UT-011	5/24/2014	144	8:48	N/A	N/A
UT-012	5/24/2014	144	11:41	N/A	N/A
UT-013	5/22/2014	142	18:56	5/24/2014	6:02
UT-014	5/22/2014	142	16:26	5/24/2014	5:48
UT-015	5/22/2014	142	15:33	5/24/2014	7:24
UT-016	5/24/2014	144	5:32	N/A	N/A
UT-017	5/20/2014	140	17:21	N/A	N/A
UT-018	5/23/2014	143	10:22	5/24/2014	5:37
UT-019	5/23/2014	143	8:34	5/24/2014	5:48
UT-020	5/23/2014	143	7:08	5/24/2014	6:15
UT-021	5/23/2014	143	6:19	5/24/2014	6:33
<b>Forest Points</b>					
FO-001	5/23/2014	143	20:56	N/A	N/A
FO-002	5/23/2014	143	6:04	N/A	N/A
FO-003	5/23/2014	143	5:15	N/A	N/A
FO-004	5/22/2014	142	14:41	N/A	N/A
FO-005	5/23/2014	143	11:14	N/A	N/A
FO-006	5/23/2014	143	9:55	N/A	N/A
FO-007	5/20/2014	140	15:15	5/21/2014	6:51
FO-008	5/20/2014	140	19:10	5/21/2014	5:20
FO-009	5/20/2014	140	20:30	N/A	N/A

<b>FO-010</b>	<b>5/21/2014</b>	<b>141</b>	<b>16:35</b>	<b>5/24/2014</b>	<b>9:29</b>
<b>FO-011</b>	<b>5/21/2014</b>	<b>141</b>	<b>18:45</b>	<b>5/24/2014</b>	<b>8:39</b>
<b>FO-012</b>	<b>5/21/2014</b>	<b>141</b>	<b>10:59</b>	<b>5/24/2014</b>	<b>7:59</b>
<b>FO-013</b>	<b>5/24/2014</b>	<b>144</b>	<b>9:25</b>	<b>N/A</b>	<b>N/A</b>
<b>FO-014</b>	<b>5/22/2014</b>	<b>142</b>	<b>18:19</b>	<b>N/A</b>	<b>N/A</b>
<b>FO-015</b>	<b>5/24/2014</b>	<b>144</b>	<b>14:56</b>	<b>N/A</b>	<b>N/A</b>
<b>FO-016</b>	<b>5/25/2014</b>	<b>145</b>	<b>19:15</b>	<b>N/A</b>	<b>N/A</b>
<b>FO-017</b>	<b>5/24/2014</b>	<b>144</b>	<b>17:11</b>	<b>N/A</b>	<b>N/A</b>
<b>FO-018</b>	<b>5/25/2014</b>	<b>145</b>	<b>11:45</b>	<b>N/A</b>	<b>N/A</b>
<b>FO-019</b>	<b>5/25/2014</b>	<b>145</b>	<b>15:58</b>	<b>N/A</b>	<b>N/A</b>
<b>FO-020</b>	<b>5/22/2014</b>	<b>142</b>	<b>9:10</b>	<b>5/24/2014</b>	<b>6:43</b>
<b>FO-021</b>	<b>5/21/2014</b>	<b>141</b>	<b>20:40</b>	<b>5/24/2014</b>	<b>8:28</b>

## Appendix B: Complete List of Delivered Tiles

18TWL625540	18TWM310590	18TXM165335	18TXM165185	18TWM715035	18TWL235855
18TWL640540	18TWM325590	18TXM180335	18TXM180185	18TWM730035	18TWL250855
18TWL595555	18TWM340590	18TXM195335	18TXM195185	18TWM745035	18TWL265855
18TWL610555	18TWM355590	18TXM210335	18TXM210185	18TWM760035	18TWL280855
18TWL625555	18TWM370590	18TXM225335	18TXM225185	18TWM775035	18TWL295855
18TWL640555	18TWM385590	18TXM240335	18TWM340200	18TWM790035	18TWL310855
18TWL655555	18TWM400590	18TWM430350	18TWM355200	18TWM805035	18TWL325855
18TWL565570	18TWM415590	18TWM445350	18TWM370200	18TWM820035	18TWL340855
18TWL580570	18TWM430590	18TWM460350	18TWM385200	18TWM835035	18TWL355855
18TWL595570	18TWM445590	18TWM475350	18TWM400200	18TWM850035	18TWL370855
18TWL610570	18TWM460590	18TWM490350	18TWM415200	18TWM865035	18TWL385855
18TWL625570	18TWM475590	18TWM505350	18TWM430200	18TWM880035	18TWL400855
18TWL640570	18TWM490590	18TWM520350	18TWM445200	18TWM895035	18TWL415855
18TWL655570	18TWM505590	18TWM535350	18TWM460200	18TWM910035	18TWL430855
18TWL670570	18TWM520590	18TWM550350	18TWM475200	18TWM925035	18TWL445855
18TWL550585	18TWM535590	18TWM565350	18TWM490200	18TWM940035	18TWL460855
18TWL565585	18TWM550590	18TWM580350	18TWM505200	18TWM955035	18TWL475855
18TWL580585	18TWM565590	18TWM595350	18TWM520200	18TWM970035	18TWL490855
18TWL595585	18TWM580590	18TWM610350	18TWM535200	18TWM985035	18TWL505855
18TWL610585	18TWM595590	18TWM625350	18TWM550200	18TXM000035	18TWL520855
18TWL625585	18TWM610590	18TWM640350	18TWM565200	18TXM015035	18TWL535855
18TWL640585	18TWM625590	18TWM655350	18TWM580200	18TXM030035	18TWL550855
18TWL655585	18TWM640590	18TWM670350	18TWM595200	18TXM045035	18TWL565855
18TWL670585	18TWM655590	18TWM685350	18TWM610200	18TXM060035	18TWL580855
18TWL685585	18TWM670590	18TWM700350	18TWM625200	18TXM075035	18TWL595855
18TWL520600	18TWM685590	18TWM715350	18TWM640200	18TXM090035	18TWL610855
18TWL535600	18TWM700590	18TWM730350	18TWM655200	18TXM105035	18TWL625855
18TWL550600	18TWM715590	18TWM745350	18TWM670200	18TXM120035	18TWL640855
18TWL565600	18TWM730590	18TWM760350	18TWM685200	18TXM135035	18TWL655855
18TWL580600	18TWM745590	18TWM775350	18TWM700200	18TXM150035	18TWL670855
18TWL595600	18TWM760590	18TWM790350	18TWM715200	18TXM165035	18TWL685855
18TWL610600	18TWM775590	18TWM805350	18TWM730200	18TXM180035	18TWL700855
18TWL625600	18TWM790590	18TWM820350	18TWM745200	18TXM195035	18TWL715855
18TWL640600	18TWM805590	18TWM835350	18TWM760200	18TXM210035	18TWL730855
18TWL655600	18TWM820590	18TWM850350	18TWM775200	18TXM225035	18TWL745855
18TWL670600	18TWM835590	18TWM865350	18TWM790200	18TWM505050	18TWL760855
18TWL685600	18TWM850590	18TWM880350	18TWM805200	18TWM520050	18TWL775855
18TWL700600	18TWM865590	18TWM895350	18TWM820200	18TWM535050	18TWL790855
18TWL490615	18TWM880590	18TWM910350	18TWM835200	18TWM550050	18TWL805855
18TWL505615	18TWM895590	18TWM925350	18TWM850200	18TWM565050	18TWL820855
18TWL520615	18TWM910590	18TWM940350	18TWM865200	18TWM580050	18TWL835855



18TWL535615	18TWM310605	18TWM955350	18TWM880200	18TWM595050	18TWL850855
18TWL550615	18TWM325605	18TWM970350	18TWM895200	18TWM610050	18TWL865855
18TWL565615	18TWM340605	18TWM985350	18TWM910200	18TWM625050	18TWL190870
18TWL580615	18TWM355605	18TXM000350	18TWM925200	18TWM640050	18TWL205870
18TWL595615	18TWM370605	18TXM015350	18TWM940200	18TWM655050	18TWL220870
18TWL610615	18TWM385605	18TXM030350	18TWM955200	18TWM670050	18TWL235870
18TWL625615	18TWM400605	18TXM045350	18TWM970200	18TWM685050	18TWL250870
18TWL640615	18TWM415605	18TXM060350	18TWM985200	18TWM700050	18TWL265870
18TWL655615	18TWM430605	18TXM075350	18TXM000200	18TWM715050	18TWL280870
18TWL670615	18TWM445605	18TXM090350	18TXM015200	18TWM730050	18TWL295870
18TWL685615	18TWM460605	18TXM105350	18TXM030200	18TWM745050	18TWL310870
18TWL700615	18TWM475605	18TXM120350	18TXM045200	18TWM760050	18TWL325870
18TWL715615	18TWM490605	18TXM135350	18TXM060200	18TWM775050	18TWL340870
18TWL475630	18TWM505605	18TXM150350	18TXM075200	18TWM790050	18TWL355870
18TWL490630	18TWM520605	18TXM165350	18TXM090200	18TWM805050	18TWL370870
18TWL505630	18TWM535605	18TXM180350	18TXM105200	18TWM820050	18TWL385870
18TWL520630	18TWM550605	18TXM195350	18TXM120200	18TWM835050	18TWL400870
18TWL535630	18TWM565605	18TXM210350	18TXM135200	18TWM850050	18TWL415870
18TWL550630	18TWM580605	18TXM225350	18TXM150200	18TWM865050	18TWL430870
18TWL565630	18TWM595605	18TXM240350	18TXM165200	18TWM880050	18TWL445870
18TWL580630	18TWM610605	18TWM415365	18TXM180200	18TWM895050	18TWL460870
18TWL595630	18TWM625605	18TWM430365	18TXM195200	18TWM910050	18TWL475870
18TWL610630	18TWM640605	18TWM445365	18TXM210200	18TWM925050	18TWL490870
18TWL625630	18TWM655605	18TWM460365	18TXM225200	18TWM940050	18TWL505870
18TWL640630	18TWM670605	18TWM475365	18TWM340215	18TWM955050	18TWL520870
18TWL655630	18TWM685605	18TWM490365	18TWM355215	18TWM970050	18TWL535870
18TWL670630	18TWM700605	18TWM505365	18TWM370215	18TWM985050	18TWL550870
18TWL685630	18TWM715605	18TWM520365	18TWM385215	18TXM000050	18TWL565870
18TWL700630	18TWM730605	18TWM535365	18TWM400215	18TXM015050	18TWL580870
18TWL715630	18TWM745605	18TWM550365	18TWM415215	18TXM030050	18TWL595870
18TWL730630	18TWM760605	18TWM565365	18TWM430215	18TXM045050	18TWL610870
18TWL445645	18TWM775605	18TWM580365	18TWM445215	18TXM060050	18TWL625870
18TWL460645	18TWM790605	18TWM595365	18TWM460215	18TXM075050	18TWL640870
18TWL475645	18TWM805605	18TWM610365	18TWM475215	18TXM090050	18TWL655870
18TWL490645	18TWM820605	18TWM625365	18TWM490215	18TXM105050	18TWL670870
18TWL505645	18TWM835605	18TWM640365	18TWM505215	18TXM120050	18TWL685870
18TWL520645	18TWM850605	18TWM655365	18TWM520215	18TXM135050	18TWL700870
18TWL535645	18TWM865605	18TWM670365	18TWM535215	18TXM150050	18TWL715870
18TWL550645	18TWM880605	18TWM685365	18TWM550215	18TXM165050	18TWL730870
18TWL565645	18TWM340620	18TWM700365	18TWM565215	18TXM180050	18TWL745870
18TWL580645	18TWM355620	18TWM715365	18TWM580215	18TXM195050	18TWL760870
18TWL595645	18TWM370620	18TWM730365	18TWM595215	18TXM210050	18TWL775870

18TWL610645	18TWM385620	18TWM745365	18TWM610215	18TXM225050	18TWL790870
18TWL625645	18TWM400620	18TWM760365	18TWM625215	18TWM505065	18TWL805870
18TWL640645	18TWM415620	18TWM775365	18TWM640215	18TWM520065	18TWL820870
18TWL655645	18TWM430620	18TWM790365	18TWM655215	18TWM535065	18TWL835870
18TWL670645	18TWM445620	18TWM805365	18TWM670215	18TWM550065	18TWL850870
18TWL685645	18TWM460620	18TWM820365	18TWM685215	18TWM565065	18TWL190885
18TWL700645	18TWM475620	18TWM835365	18TWM700215	18TWM580065	18TWL205885
18TWL715645	18TWM490620	18TWM850365	18TWM715215	18TWM595065	18TWL220885
18TWL730645	18TWM505620	18TWM865365	18TWM730215	18TWM610065	18TWL235885
18TWL745645	18TWM520620	18TWM880365	18TWM745215	18TWM625065	18TWL250885
18TWL430660	18TWM535620	18TWM895365	18TWM760215	18TWM640065	18TWL265885
18TWL445660	18TWM550620	18TWM910365	18TWM775215	18TWM655065	18TWL280885
18TWL460660	18TWM565620	18TWM925365	18TWM790215	18TWM670065	18TWL295885
18TWL475660	18TWM580620	18TWM940365	18TWM805215	18TWM685065	18TWL310885
18TWL490660	18TWM595620	18TWM955365	18TWM820215	18TWM700065	18TWL325885
18TWL505660	18TWM610620	18TWM970365	18TWM835215	18TWM715065	18TWL340885
18TWL520660	18TWM625620	18TWM985365	18TWM850215	18TWM730065	18TWL355885
18TWL535660	18TWM640620	18TXM000365	18TWM865215	18TWM745065	18TWL370885
18TWL550660	18TWM655620	18TXM015365	18TWM880215	18TWM760065	18TWL385885
18TWL565660	18TWM760620	18TXM030365	18TWM895215	18TWM775065	18TWL400885
18TWL580660	18TWM775620	18TXM045365	18TWM910215	18TWM790065	18TWL415885
18TWL595660	18TWM790620	18TXM060365	18TWM925215	18TWM805065	18TWL430885
18TWL610660	18TWM805620	18TXM075365	18TWM940215	18TWM820065	18TWL445885
18TWL625660	18TWM820620	18TXM090365	18TWM955215	18TWM835065	18TWL460885
18TWL640660	18TWM835620	18TXM105365	18TWM970215	18TWM850065	18TWL475885
18TWL655660	18TWM850620	18TXM120365	18TWM985215	18TWM865065	18TWL490885
18TWL670660	18TWM865620	18TXM135365	18TXM000215	18TWM880065	18TWL505885
18TWL685660	18TWM880620	18TXM150365	18TXM015215	18TWM895065	18TWL520885
18TWL700660	18TWM895620	18TXM165365	18TXM030215	18TWM910065	18TWL535885
18TWL715660	18TWM355635	18TXM180365	18TXM045215	18TWM925065	18TWL550885
18TWL730660	18TWM370635	18TXM195365	18TXM060215	18TWM940065	18TWL565885
18TWL745660	18TWM385635	18TXM210365	18TXM075215	18TWM955065	18TWL580885
18TWL760660	18TWM400635	18TXM225365	18TXM090215	18TWM970065	18TWL595885
18TWL400675	18TWM415635	18TXM240365	18TXM105215	18TWM985065	18TWL610885
18TWL415675	18TWM430635	18TWM385380	18TXM120215	18TXM000065	18TWL625885
18TWL430675	18TWM445635	18TWM400380	18TXM135215	18TXM015065	18TWL640885
18TWL445675	18TWM460635	18TWM415380	18TXM150215	18TXM030065	18TWL655885
18TWL460675	18TWM475635	18TWM430380	18TXM165215	18TXM045065	18TWL670885
18TWL475675	18TWM490635	18TWM445380	18TXM180215	18TXM060065	18TWL685885
18TWL490675	18TWM505635	18TWM460380	18TXM195215	18TXM075065	18TWL700885
18TWL505675	18TWM520635	18TWM475380	18TXM210215	18TXM090065	18TWL715885
18TWL520675	18TWM535635	18TWM490380	18TXM225215	18TXM105065	18TWL730885

18TWL535675	18TWM550635	18TWM505380	18TWM355230	18TXM120065	18TWL745885
18TWL550675	18TWM760635	18TWM520380	18TWM370230	18TXM135065	18TWL760885
18TWL565675	18TWM775635	18TWM535380	18TWM385230	18TXM150065	18TWL775885
18TWL580675	18TWM790635	18TWM550380	18TWM400230	18TXM165065	18TWL790885
18TWL595675	18TWM805635	18TWM565380	18TWM415230	18TXM180065	18TWL805885
18TWL610675	18TWM820635	18TWM580380	18TWM430230	18TXM195065	18TWL820885
18TWL625675	18TWM835635	18TWM595380	18TWM445230	18TXM210065	18TWL835885
18TWL640675	18TWM850635	18TWM610380	18TWM460230	18TXM225065	18TWL850885
18TWL655675	18TWM865635	18TWM625380	18TWM475230	18TWM505080	18TWL865885
18TWL670675	18TWM880635	18TWM640380	18TWM490230	18TWM520080	18TWL190900
18TWL685675	18TWM895635	18TWM655380	18TWM505230	18TWM535080	18TWL205900
18TWL700675	18TWM370650	18TWM670380	18TWM520230	18TWM550080	18TWL220900
18TWL715675	18TWM385650	18TWM685380	18TWM535230	18TWM565080	18TWL235900
18TWL730675	18TWM400650	18TWM700380	18TWM550230	18TWM580080	18TWL250900
18TWL745675	18TWM415650	18TWM715380	18TWM565230	18TWM595080	18TWL265900
18TWL760675	18TWM430650	18TWM730380	18TWM580230	18TWM610080	18TWL280900
18TWL775675	18TWM445650	18TWM745380	18TWM595230	18TWM625080	18TWL295900
18TWL385690	18TWM460650	18TWM760380	18TWM610230	18TWM640080	18TWL310900
18TWL400690	18TWM475650	18TWM775380	18TWM625230	18TWM655080	18TWL325900
18TWL415690	18TWM490650	18TWM790380	18TWM640230	18TWM670080	18TWL340900
18TWL430690	18TWM505650	18TWM805380	18TWM655230	18TWM685080	18TWL355900
18TWL445690	18TWM520650	18TWM820380	18TWM670230	18TWM700080	18TWL370900
18TWL460690	18TWM775650	18TWM835380	18TWM685230	18TWM715080	18TWL385900
18TWL475690	18TWM790650	18TWM850380	18TWM700230	18TWM730080	18TWL400900
18TWL490690	18TWM805650	18TWM865380	18TWM715230	18TWM745080	18TWL415900
18TWL505690	18TWM820650	18TWM880380	18TWM730230	18TWM760080	18TWL430900
18TWL520690	18TWM835650	18TWM895380	18TWM745230	18TWM775080	18TWL445900
18TWL535690	18TWM850650	18TWM910380	18TWM760230	18TWM790080	18TWL460900
18TWL550690	18TWM865650	18TWM925380	18TWM775230	18TWM805080	18TWL475900
18TWL565690	18TWM880650	18TWM940380	18TWM790230	18TWM820080	18TWL490900
18TWL580690	18TWM415665	18TWM955380	18TWM805230	18TWM835080	18TWL505900
18TWL595690	18TWM430665	18TWM970380	18TWM820230	18TWM850080	18TWL520900
18TWL610690	18TWM445665	18TWM985380	18TWM835230	18TWM865080	18TWL535900
18TWL625690	18TWM460665	18TXM000380	18TWM850230	18TWM880080	18TWL550900
18TWL640690	18TWM475665	18TXM015380	18TWM865230	18TWM895080	18TWL565900
18TWL655690	18TWM490665	18TXM030380	18TWM880230	18TWM910080	18TWL580900
18TWL670690	18TWM775665	18TXM045380	18TWM895230	18TWM925080	18TWL595900
18TWL685690	18TWM790665	18TXM060380	18TWM910230	18TWM940080	18TWL610900
18TWL700690	18TWM805665	18TXM075380	18TWM925230	18TWM955080	18TWL625900
18TWL715690	18TWM820665	18TXM090380	18TWM940230	18TWM970080	18TWL640900
18TWL730690	18TWM835665	18TXM105380	18TWM955230	18TWM985080	18TWL655900
18TWL745690	18TWM850665	18TXM120380	18TWM970230	18TXM000080	18TWL670900

18TWL760690	18TWM865665	18TXM135380	18TWM985230	18TXM015080	18TWL685900
18TWL775690	18TWM430680	18TXM150380	18TXM000230	18TXM030080	18TWL700900
18TWL790690	18TWM445680	18TXM165380	18TXM015230	18TXM045080	18TWL715900
18TWL355705	18TWM460680	18TXM180380	18TXM030230	18TXM060080	18TWL730900
18TWL370705	18TWM775680	18TXM195380	18TXM045230	18TXM075080	18TWL745900
18TWL385705	18TWM790680	18TXM210380	18TXM060230	18TXM090080	18TWL760900
18TWL400705	18TWM805680	18TXM225380	18TXM075230	18TXM105080	18TWL775900
18TWL415705	18TWM820680	18TXM240380	18TXM090230	18TXM120080	18TWL790900
18TWL430705	18TWM835680	18TWM355395	18TXM105230	18TXM135080	18TWL805900
18TWL445705	18TWM850680	18TWM370395	18TXM120230	18TXM150080	18TWL820900
18TWL460705	18TWM820695	18TWM385395	18TXM135230	18TXM165080	18TWL835900
18TWL475705	18TWM460485	18TWM400395	18TXM150230	18TXM180080	18TWL850900
18TWL490705	18TWM475485	18TWM415395	18TXM165230	18TXM195080	18TWL865900
18TWL505705	18TWM490485	18TWM430395	18TXM180230	18TXM210080	18TWL190915
18TWL520705	18TWM505485	18TWM445395	18TXM195230	18TXM225080	18TWL205915
18TWL535705	18TWM520485	18TWM460395	18TXM210230	18TWM490095	18TWL220915
18TWL550705	18TWM535485	18TWM475395	18TXM225230	18TWM505095	18TWL235915
18TWL565705	18TWM550485	18TWM490395	18TWM370245	18TWM520095	18TWL250915
18TWL580705	18TWM565485	18TWM505395	18TWM385245	18TWM535095	18TWL265915
18TWL595705	18TWM580485	18TWM520395	18TWM400245	18TWM550095	18TWL280915
18TWL610705	18TWM595485	18TWM535395	18TWM415245	18TWM565095	18TWL295915
18TWL625705	18TWM610485	18TWM550395	18TWM430245	18TWM580095	18TWL310915
18TWL640705	18TWM625485	18TWM565395	18TWM445245	18TWM595095	18TWL325915
18TWL655705	18TWM640485	18TWM580395	18TWM460245	18TWM610095	18TWL340915
18TWL670705	18TWM655485	18TWM595395	18TWM475245	18TWM625095	18TWL355915
18TWL685705	18TWM670485	18TWM610395	18TWM490245	18TWM640095	18TWL370915
18TWL700705	18TWM685485	18TWM625395	18TWM505245	18TWM655095	18TWL385915
18TWL715705	18TWM700485	18TWM640395	18TWM520245	18TWM670095	18TWL400915
18TWL730705	18TWM715485	18TWM655395	18TWM535245	18TWM685095	18TWL415915
18TWL745705	18TWM730485	18TWM670395	18TWM550245	18TWM700095	18TWL430915
18TWL760705	18TWM745485	18TWM685395	18TWM565245	18TWM715095	18TWL445915
18TWL775705	18TWM760485	18TWM700395	18TWM580245	18TWM730095	18TWL460915
18TWL790705	18TWM775485	18TWM715395	18TWM595245	18TWM745095	18TWL475915
18TWL805705	18TWM790485	18TWM730395	18TWM610245	18TWM760095	18TWL490915
18TWL325720	18TWM805485	18TWM745395	18TWM625245	18TWM775095	18TWL505915
18TWL340720	18TWM820485	18TWM760395	18TWM640245	18TWM790095	18TWL520915
18TWL355720	18TWM835485	18TWM775395	18TWM655245	18TWM805095	18TWL535915
18TWL370720	18TWM850485	18TWM790395	18TWM670245	18TWM820095	18TWL550915
18TWL385720	18TWM865485	18TWM805395	18TWM685245	18TWM835095	18TWL565915
18TWL400720	18TWM880485	18TWM820395	18TWM700245	18TWM850095	18TWL580915
18TWL415720	18TWM895485	18TWM835395	18TWM715245	18TWM865095	18TWL595915
18TWL430720	18TWM910485	18TWM850395	18TWM730245	18TWM880095	18TWL610915

18TWL445720	18TWM925485	18TWM865395	18TWM745245	18TWM895095	18TWL625915
18TWL460720	18TWM940485	18TWM880395	18TWM760245	18TWM910095	18TWL640915
18TWL475720	18TWM955485	18TWM895395	18TWM775245	18TWM925095	18TWL655915
18TWL490720	18TWM970485	18TWM910395	18TWM790245	18TWM940095	18TWL670915
18TWL505720	18TWM985485	18TWM925395	18TWM805245	18TWM955095	18TWL685915
18TWL520720	18TXM000485	18TWM940395	18TWM820245	18TWM970095	18TWL700915
18TWL535720	18TXM015485	18TWM955395	18TWM835245	18TWM985095	18TWL715915
18TWL550720	18TXM030485	18TWM970395	18TWM850245	18TXM000095	18TWL730915
18TWL565720	18TXM045485	18TWM985395	18TWM865245	18TXM015095	18TWL745915
18TWL580720	18TXM060485	18TXM000395	18TWM880245	18TXM030095	18TWL760915
18TWL595720	18TXM075485	18TXM015395	18TWM895245	18TXM045095	18TWL775915
18TWL610720	18TXM090485	18TXM030395	18TWM910245	18TXM060095	18TWL790915
18TWL625720	18TXM105485	18TXM045395	18TWM925245	18TXM075095	18TWL805915
18TWL640720	18TXM120485	18TXM060395	18TWM940245	18TXM090095	18TWL820915
18TWL655720	18TXM135485	18TXM075395	18TWM955245	18TXM105095	18TWL835915
18TWL670720	18TXM150485	18TXM090395	18TWM970245	18TXM120095	18TWL850915
18TWL685720	18TXM165485	18TXM105395	18TWM985245	18TXM135095	18TWL865915
18TWL700720	18TXM180485	18TXM120395	18TXM000245	18TXM150095	18TWL880915
18TWL715720	18TXM195485	18TXM135395	18TXM015245	18TXM165095	18TWL190930
18TWL730720	18TXM210485	18TXM150395	18TXM030245	18TXM180095	18TWL205930
18TWL745720	18TXM225485	18TXM165395	18TXM045245	18TXM195095	18TWL220930
18TWL760720	18TXM240485	18TXM180395	18TXM060245	18TXM210095	18TWL235930
18TWL775720	18TWM175500	18TXM195395	18TXM075245	18TXM225095	18TWL250930
18TWL790720	18TWM190500	18TXM210395	18TXM090245	18TWM460110	18TWL265930
18TWL805720	18TWM205500	18TXM225395	18TXM105245	18TWM475110	18TWL280930
18TWL820720	18TWM220500	18TXM240395	18TXM120245	18TWM490110	18TWL295930
18TWL835720	18TWM235500	18TWM340410	18TXM135245	18TWM505110	18TWL310930
18TWL310735	18TWM250500	18TWM355410	18TXM150245	18TWM520110	18TWL325930
18TWL325735	18TWM265500	18TWM370410	18TXM165245	18TWM535110	18TWL340930
18TWL340735	18TWM280500	18TWM385410	18TXM180245	18TWM550110	18TWL355930
18TWL355735	18TWM295500	18TWM400410	18TXM195245	18TWM565110	18TWL370930
18TWL370735	18TWM310500	18TWM415410	18TXM210245	18TWM580110	18TWL385930
18TWL385735	18TWM325500	18TWM430410	18TXM225245	18TWM595110	18TWL400930
18TWL400735	18TWM340500	18TWM445410	18TWM370260	18TWM610110	18TWL415930
18TWL415735	18TWM355500	18TWM460410	18TWM385260	18TWM625110	18TWL430930
18TWL430735	18TWM370500	18TWM475410	18TWM400260	18TWM640110	18TWL445930
18TWL445735	18TWM385500	18TWM490410	18TWM415260	18TWM655110	18TWL460930
18TWL460735	18TWM400500	18TWM505410	18TWM430260	18TWM670110	18TWL475930
18TWL475735	18TWM415500	18TWM520410	18TWM445260	18TWM685110	18TWL490930
18TWL490735	18TWM430500	18TWM535410	18TWM460260	18TWM700110	18TWL505930
18TWL505735	18TWM445500	18TWM550410	18TWM475260	18TWM715110	18TWL520930
18TWL520735	18TWM460500	18TWM565410	18TWM490260	18TWM730110	18TWL535930



18TWL535735	18TWM475500	18TWM580410	18TWM505260	18TWM745110	18TWL550930
18TWL550735	18TWM490500	18TWM595410	18TWM520260	18TWM760110	18TWL565930
18TWL565735	18TWM505500	18TWM610410	18TWM535260	18TWM775110	18TWL580930
18TWL580735	18TWM520500	18TWM625410	18TWM550260	18TWM790110	18TWL595930
18TWL595735	18TWM535500	18TWM640410	18TWM565260	18TWM805110	18TWL610930
18TWL610735	18TWM550500	18TWM655410	18TWM580260	18TWM820110	18TWL625930
18TWL625735	18TWM565500	18TWM670410	18TWM595260	18TWM835110	18TWL640930
18TWL640735	18TWM580500	18TWM685410	18TWM610260	18TWM850110	18TWL655930
18TWL655735	18TWM595500	18TWM700410	18TWM625260	18TWM865110	18TWL670930
18TWL670735	18TWM610500	18TWM715410	18TWM640260	18TWM880110	18TWL685930
18TWL685735	18TWM625500	18TWM730410	18TWM655260	18TWM895110	18TWL700930
18TWL700735	18TWM640500	18TWM745410	18TWM670260	18TWM910110	18TWL715930
18TWL715735	18TWM655500	18TWM760410	18TWM685260	18TWM925110	18TWL730930
18TWL730735	18TWM670500	18TWM775410	18TWM700260	18TWM940110	18TWL745930
18TWL745735	18TWM685500	18TWM790410	18TWM715260	18TWM955110	18TWL760930
18TWL760735	18TWM700500	18TWM805410	18TWM730260	18TWM970110	18TWL775930
18TWL775735	18TWM715500	18TWM820410	18TWM745260	18TWM985110	18TWL790930
18TWL790735	18TWM730500	18TWM835410	18TWM760260	18TXM000110	18TWL805930
18TWL805735	18TWM745500	18TWM850410	18TWM775260	18TXM015110	18TWL820930
18TWL820735	18TWM760500	18TWM865410	18TWM790260	18TXM030110	18TWL835930
18TWL835735	18TWM775500	18TWM880410	18TWM805260	18TXM045110	18TWL850930
18TWL850735	18TWM790500	18TWM895410	18TWM820260	18TXM060110	18TWL865930
18TWL280750	18TWM805500	18TWM910410	18TWM835260	18TXM075110	18TWL880930
18TWL295750	18TWM820500	18TWM925410	18TWM850260	18TXM090110	18TWL895930
18TWL310750	18TWM835500	18TWM940410	18TWM865260	18TXM105110	18TWL910930
18TWL325750	18TWM850500	18TWM955410	18TWM880260	18TXM120110	18TWL925930
18TWL340750	18TWM865500	18TWM970410	18TWM895260	18TXM135110	18TWL940930
18TWL355750	18TWM880500	18TWM985410	18TWM910260	18TXM150110	18TWL955930
18TWL370750	18TWM895500	18TXM000410	18TWM925260	18TXM165110	18TWL355945
18TWL385750	18TWM910500	18TXM015410	18TWM940260	18TXM180110	18TWL370945
18TWL400750	18TWM925500	18TXM030410	18TWM955260	18TXM195110	18TWL385945
18TWL415750	18TWM940500	18TXM045410	18TWM970260	18TXM210110	18TWL400945
18TWL430750	18TWM955500	18TXM060410	18TWM985260	18TXM225110	18TWL415945
18TWL445750	18TWM970500	18TXM075410	18TXM000260	18TWM445125	18TWL430945
18TWL460750	18TWM985500	18TXM090410	18TXM015260	18TWM460125	18TWL445945
18TWL475750	18TXM000500	18TXM105410	18TXM030260	18TWM475125	18TWL460945
18TWL490750	18TXM015500	18TXM120410	18TXM045260	18TWM490125	18TWL475945
18TWL505750	18TXM030500	18TXM135410	18TXM060260	18TWM505125	18TWL490945
18TWL520750	18TXM045500	18TXM150410	18TXM075260	18TWM520125	18TWL505945
18TWL535750	18TXM060500	18TXM165410	18TXM090260	18TWM535125	18TWL520945
18TWL550750	18TXM075500	18TXM180410	18TXM105260	18TWM550125	18TWL535945
18TWL565750	18TXM090500	18TXM195410	18TXM120260	18TWM565125	18TWL550945

18TWL580750	18TXM105500	18TXM210410	18TXM135260	18TWM580125	18TWL565945
18TWL595750	18TXM120500	18TXM225410	18TXM150260	18TWM595125	18TWL580945
18TWL610750	18TXM135500	18TXM240410	18TXM165260	18TWM610125	18TWL595945
18TWL625750	18TXM210500	18TWM310425	18TXM180260	18TWM625125	18TWL610945
18TWL640750	18TXM225500	18TWM325425	18TXM195260	18TWM640125	18TWL625945
18TWL655750	18TXM240500	18TWM340425	18TXM210260	18TWM655125	18TWL640945
18TWL670750	18TWM175515	18TWM355425	18TXM225260	18TWM670125	18TWL655945
18TWL685750	18TWM190515	18TWM370425	18TXM240260	18TWM685125	18TWL670945
18TWL700750	18TWM205515	18TWM385425	18TWM385275	18TWM700125	18TWL685945
18TWL715750	18TWM220515	18TWM400425	18TWM400275	18TWM715125	18TWL700945
18TWL730750	18TWM235515	18TWM415425	18TWM415275	18TWM730125	18TWL715945
18TWL745750	18TWM250515	18TWM430425	18TWM430275	18TWM745125	18TWL730945
18TWL760750	18TWM265515	18TWM445425	18TWM445275	18TWM760125	18TWL745945
18TWL775750	18TWM280515	18TWM460425	18TWM460275	18TWM775125	18TWL760945
18TWL790750	18TWM295515	18TWM475425	18TWM475275	18TWM790125	18TWL775945
18TWL805750	18TWM310515	18TWM490425	18TWM490275	18TWM805125	18TWL790945
18TWL820750	18TWM325515	18TWM505425	18TWM505275	18TWM820125	18TWL805945
18TWL835750	18TWM340515	18TWM520425	18TWM520275	18TWM835125	18TWL820945
18TWL850750	18TWM355515	18TWM535425	18TWM535275	18TWM850125	18TWL835945
18TWL250765	18TWM370515	18TWM550425	18TWM550275	18TWM865125	18TWL850945
18TWL265765	18TWM385515	18TWM565425	18TWM565275	18TWM880125	18TWL865945
18TWL280765	18TWM400515	18TWM580425	18TWM580275	18TWM895125	18TWL880945
18TWL295765	18TWM415515	18TWM595425	18TWM595275	18TWM910125	18TWL895945
18TWL310765	18TWM430515	18TWM610425	18TWM610275	18TWM925125	18TWL910945
18TWL325765	18TWM445515	18TWM625425	18TWM625275	18TWM940125	18TWL925945
18TWL340765	18TWM460515	18TWM640425	18TWM640275	18TWM955125	18TWL940945
18TWL355765	18TWM475515	18TWM655425	18TWM655275	18TWM970125	18TWL955945
18TWL370765	18TWM490515	18TWM670425	18TWM670275	18TWM985125	18TWL970945
18TWL385765	18TWM505515	18TWM685425	18TWM685275	18TXM000125	18TWL985945
18TWL400765	18TWM520515	18TWM700425	18TWM700275	18TXM015125	18TXL000945
18TWL415765	18TWM535515	18TWM715425	18TWM715275	18TXM030125	18TXL015945
18TWL430765	18TWM550515	18TWM730425	18TWM730275	18TXM045125	18TXL030945
18TWL445765	18TWM565515	18TWM745425	18TWM745275	18TXM060125	18TXL045945
18TWL460765	18TWM580515	18TWM760425	18TWM760275	18TXM075125	18TXL060945
18TWL475765	18TWM595515	18TWM775425	18TWM775275	18TXM090125	18TWL430960
18TWL490765	18TWM610515	18TWM790425	18TWM790275	18TXM105125	18TWL445960
18TWL505765	18TWM625515	18TWM805425	18TWM805275	18TXM120125	18TWL460960
18TWL520765	18TWM640515	18TWM820425	18TWM820275	18TXM135125	18TWL475960
18TWL535765	18TWM655515	18TWM835425	18TWM835275	18TXM150125	18TWL490960
18TWL550765	18TWM670515	18TWM850425	18TWM850275	18TXM165125	18TWL505960
18TWL565765	18TWM685515	18TWM865425	18TWM865275	18TXM180125	18TWL520960
18TWL580765	18TWM700515	18TWM880425	18TWM880275	18TXM195125	18TWL535960

18TWL595765	18TWM715515	18TWM895425	18TWM895275	18TXM210125	18TWL550960
18TWL610765	18TWM730515	18TWM910425	18TWM910275	18TXM225125	18TWL565960
18TWL625765	18TWM745515	18TWM925425	18TWM925275	18TWM430140	18TWL580960
18TWL640765	18TWM760515	18TWM940425	18TWM940275	18TWM445140	18TWL595960
18TWL655765	18TWM775515	18TWM955425	18TWM955275	18TWM460140	18TWL610960
18TWL670765	18TWM790515	18TWM970425	18TWM970275	18TWM475140	18TWL625960
18TWL685765	18TWM805515	18TWM985425	18TWM985275	18TWM490140	18TWL640960
18TWL700765	18TWM820515	18TXM000425	18TXM000275	18TWM505140	18TWL655960
18TWL715765	18TWM835515	18TXM015425	18TXM015275	18TWM520140	18TWL670960
18TWL730765	18TWM850515	18TXM030425	18TXM030275	18TWM535140	18TWL685960
18TWL745765	18TWM865515	18TXM045425	18TXM045275	18TWM550140	18TWL700960
18TWL760765	18TWM880515	18TXM060425	18TXM060275	18TWM565140	18TWL715960
18TWL775765	18TWM895515	18TXM075425	18TXM075275	18TWM580140	18TWL730960
18TWL790765	18TWM910515	18TXM090425	18TXM090275	18TWM595140	18TWL745960
18TWL805765	18TWM925515	18TXM105425	18TXM105275	18TWM610140	18TWL760960
18TWL820765	18TWM940515	18TXM120425	18TXM120275	18TWM625140	18TWL775960
18TWL835765	18TWM955515	18TXM135425	18TXM135275	18TWM640140	18TWL790960
18TWL850765	18TWM970515	18TXM150425	18TXM150275	18TWM655140	18TWL805960
18TWL865765	18TWM985515	18TXM165425	18TXM165275	18TWM670140	18TWL820960
18TWL235780	18TXM000515	18TXM180425	18TXM180275	18TWM685140	18TWL835960
18TWL250780	18TXM015515	18TXM195425	18TXM195275	18TWM700140	18TWL850960
18TWL265780	18TXM030515	18TXM210425	18TXM210275	18TWM715140	18TWL865960
18TWL280780	18TXM045515	18TXM225425	18TXM225275	18TWM730140	18TWL880960
18TWL295780	18TXM060515	18TXM240425	18TXM240275	18TWM745140	18TWL895960
18TWL310780	18TXM210515	18TWM280440	18TWM400290	18TWM760140	18TWL910960
18TWL325780	18TXM225515	18TWM295440	18TWM415290	18TWM775140	18TWL925960
18TWL340780	18TXM240515	18TWM310440	18TWM430290	18TWM790140	18TWL940960
18TWL355780	18TWM190530	18TWM325440	18TWM445290	18TWM805140	18TWL955960
18TWL370780	18TWM205530	18TWM340440	18TWM460290	18TWM820140	18TWL970960
18TWL385780	18TWM220530	18TWM355440	18TWM475290	18TWM835140	18TWL985960
18TWL400780	18TWM235530	18TWM370440	18TWM490290	18TWM850140	18TXL000960
18TWL415780	18TWM250530	18TWM385440	18TWM505290	18TWM865140	18TXL015960
18TWL430780	18TWM265530	18TWM400440	18TWM520290	18TWM880140	18TXL030960
18TWL445780	18TWM280530	18TWM415440	18TWM535290	18TWM895140	18TXL045960
18TWL460780	18TWM295530	18TWM430440	18TWM550290	18TWM910140	18TXL060960
18TWL475780	18TWM310530	18TWM445440	18TWM565290	18TWM925140	18TXL075960
18TWL490780	18TWM325530	18TWM460440	18TWM580290	18TWM940140	18TXL090960
18TWL505780	18TWM340530	18TWM475440	18TWM595290	18TWM955140	18TXL105960
18TWL520780	18TWM355530	18TWM490440	18TWM610290	18TWM970140	18TXL120960
18TWL535780	18TWM370530	18TWM505440	18TWM625290	18TWM985140	18TXL135960
18TWL550780	18TWM385530	18TWM520440	18TWM640290	18TXM000140	18TWL445975
18TWL565780	18TWM400530	18TWM535440	18TWM655290	18TXM015140	18TWL460975

18TWL580780	18TWM415530	18TWM550440	18TWM670290	18TXM030140	18TWL475975
18TWL595780	18TWM430530	18TWM565440	18TWM685290	18TXM045140	18TWL490975
18TWL610780	18TWM445530	18TWM580440	18TWM700290	18TXM060140	18TWL505975
18TWL625780	18TWM460530	18TWM595440	18TWM715290	18TXM075140	18TWL520975
18TWL640780	18TWM475530	18TWM610440	18TWM730290	18TXM090140	18TWL535975
18TWL655780	18TWM490530	18TWM625440	18TWM745290	18TXM105140	18TWL550975
18TWL670780	18TWM505530	18TWM640440	18TWM760290	18TXM120140	18TWL565975
18TWL685780	18TWM520530	18TWM655440	18TWM775290	18TXM135140	18TWL580975
18TWL700780	18TWM535530	18TWM670440	18TWM790290	18TXM150140	18TWL595975
18TWL715780	18TWM550530	18TWM685440	18TWM805290	18TXM165140	18TWL610975
18TWL730780	18TWM565530	18TWM700440	18TWM820290	18TXM180140	18TWL625975
18TWL745780	18TWM580530	18TWM715440	18TWM835290	18TXM195140	18TWL640975
18TWL760780	18TWM595530	18TWM730440	18TWM850290	18TXM210140	18TWL655975
18TWL775780	18TWM610530	18TWM745440	18TWM865290	18TXM225140	18TWL670975
18TWL790780	18TWM625530	18TWM760440	18TWM880290	18TWM400155	18TWL685975
18TWL805780	18TWM640530	18TWM775440	18TWM895290	18TWM415155	18TWL700975
18TWL820780	18TWM655530	18TWM790440	18TWM910290	18TWM430155	18TWL715975
18TWL835780	18TWM670530	18TWM805440	18TWM925290	18TWM445155	18TWL730975
18TWL850780	18TWM685530	18TWM820440	18TWM940290	18TWM460155	18TWL745975
18TWL865780	18TWM700530	18TWM835440	18TWM955290	18TWM475155	18TWL760975
18TWL235795	18TWM715530	18TWM850440	18TWM970290	18TWM490155	18TWL775975
18TWL250795	18TWM730530	18TWM865440	18TWM985290	18TWM505155	18TWL790975
18TWL265795	18TWM745530	18TWM880440	18TXM000290	18TWM520155	18TWL805975
18TWL280795	18TWM760530	18TWM895440	18TXM015290	18TWM535155	18TWL820975
18TWL295795	18TWM775530	18TWM910440	18TXM030290	18TWM550155	18TWL835975
18TWL310795	18TWM790530	18TWM925440	18TXM045290	18TWM565155	18TWL850975
18TWL325795	18TWM805530	18TWM940440	18TXM060290	18TWM580155	18TWL865975
18TWL340795	18TWM820530	18TWM955440	18TXM075290	18TWM595155	18TWL880975
18TWL355795	18TWM835530	18TWM970440	18TXM090290	18TWM610155	18TWL895975
18TWL370795	18TWM850530	18TWM985440	18TXM105290	18TWM625155	18TWL910975
18TWL385795	18TWM865530	18TXM000440	18TXM120290	18TWM640155	18TWL925975
18TWL400795	18TWM880530	18TXM015440	18TXM135290	18TWM655155	18TWL940975
18TWL415795	18TWM895530	18TXM030440	18TXM150290	18TWM670155	18TWL955975
18TWL430795	18TWM910530	18TXM045440	18TXM165290	18TWM685155	18TWL970975
18TWL445795	18TWM925530	18TXM060440	18TXM180290	18TWM700155	18TWL985975
18TWL460795	18TWM940530	18TXM075440	18TXM195290	18TWM715155	18TXL000975
18TWL475795	18TWM955530	18TXM090440	18TXM210290	18TWM730155	18TXL015975
18TWL490795	18TWM970530	18TXM105440	18TXM225290	18TWM745155	18TXL030975
18TWL505795	18TWM985530	18TXM120440	18TXM240290	18TWM760155	18TXL045975
18TWL520795	18TXM000530	18TXM135440	18TWM415305	18TWM775155	18TXL060975
18TWL535795	18TXM015530	18TXM150440	18TWM430305	18TWM790155	18TXL075975
18TWL550795	18TXM030530	18TXM165440	18TWM445305	18TWM805155	18TXL090975

18TWL565795	18TXM210530	18TXM180440	18TWM460305	18TWM820155	18TXL105975
18TWL580795	18TXM225530	18TXM195440	18TWM475305	18TWM835155	18TXL120975
18TWL595795	18TXM240530	18TXM210440	18TWM490305	18TWM850155	18TXL135975
18TWL610795	18TWM220545	18TXM225440	18TWM505305	18TWM865155	18TXL150975
18TWL625795	18TWM235545	18TXM240440	18TWM520305	18TWM880155	18TXL165975
18TWL640795	18TWM250545	18TWM250455	18TWM535305	18TWM895155	18TXL180975
18TWL655795	18TWM265545	18TWM265455	18TWM550305	18TWM910155	18TXL195975
18TWL670795	18TWM280545	18TWM280455	18TWM565305	18TWM925155	18TXL210975
18TWL685795	18TWM295545	18TWM295455	18TWM580305	18TWM940155	18TXL225975
18TWL700795	18TWM310545	18TWM310455	18TWM595305	18TWM955155	18TWL460990
18TWL715795	18TWM325545	18TWM325455	18TWM610305	18TWM970155	18TWL475990
18TWL730795	18TWM340545	18TWM340455	18TWM625305	18TWM985155	18TWL490990
18TWL745795	18TWM355545	18TWM355455	18TWM640305	18TXM000155	18TWL505990
18TWL760795	18TWM370545	18TWM370455	18TWM655305	18TXM015155	18TWL520990
18TWL775795	18TWM385545	18TWM385455	18TWM670305	18TXM030155	18TWL535990
18TWL790795	18TWM400545	18TWM400455	18TWM685305	18TXM045155	18TWL550990
18TWL805795	18TWM415545	18TWM415455	18TWM700305	18TXM060155	18TWL565990
18TWL820795	18TWM430545	18TWM430455	18TWM715305	18TXM075155	18TWL580990
18TWL835795	18TWM445545	18TWM445455	18TWM730305	18TXM090155	18TWL595990
18TWL850795	18TWM460545	18TWM460455	18TWM745305	18TXM105155	18TWL610990
18TWL865795	18TWM475545	18TWM475455	18TWM760305	18TXM120155	18TWL625990
18TWL220810	18TWM490545	18TWM490455	18TWM775305	18TXM135155	18TWL640990
18TWL235810	18TWM505545	18TWM505455	18TWM790305	18TXM150155	18TWL655990
18TWL250810	18TWM520545	18TWM520455	18TWM805305	18TXM165155	18TWL670990
18TWL265810	18TWM535545	18TWM535455	18TWM820305	18TXM180155	18TWL685990
18TWL280810	18TWM550545	18TWM550455	18TWM835305	18TXM195155	18TWL700990
18TWL295810	18TWM565545	18TWM565455	18TWM850305	18TXM210155	18TWL715990
18TWL310810	18TWM580545	18TWM580455	18TWM865305	18TXM225155	18TWL730990
18TWL325810	18TWM595545	18TWM595455	18TWM880305	18TWM385170	18TWL745990
18TWL340810	18TWM610545	18TWM610455	18TWM895305	18TWM400170	18TWL760990
18TWL355810	18TWM625545	18TWM625455	18TWM910305	18TWM415170	18TWL775990
18TWL370810	18TWM640545	18TWM640455	18TWM925305	18TWM430170	18TWL790990
18TWL385810	18TWM655545	18TWM655455	18TWM940305	18TWM445170	18TWL805990
18TWL400810	18TWM670545	18TWM670455	18TWM955305	18TWM460170	18TWL820990
18TWL415810	18TWM685545	18TWM685455	18TWM970305	18TWM475170	18TWL835990
18TWL430810	18TWM700545	18TWM700455	18TWM985305	18TWM490170	18TWL850990
18TWL445810	18TWM715545	18TWM715455	18TXM000305	18TWM505170	18TWL865990
18TWL460810	18TWM730545	18TWM730455	18TXM015305	18TWM520170	18TWL880990
18TWL475810	18TWM745545	18TWM745455	18TXM030305	18TWM535170	18TWL895990
18TWL490810	18TWM760545	18TWM760455	18TXM045305	18TWM550170	18TWL910990
18TWL505810	18TWM775545	18TWM775455	18TXM060305	18TWM565170	18TWL925990
18TWL520810	18TWM790545	18TWM790455	18TXM075305	18TWM580170	18TWL940990



18TWL535810	18TWM805545	18TWM805455	18TXM090305	18TWM595170	18TWL955990
18TWL550810	18TWM820545	18TWM820455	18TXM105305	18TWM610170	18TWL970990
18TWL565810	18TWM835545	18TWM835455	18TXM120305	18TWM625170	18TWL985990
18TWL580810	18TWM850545	18TWM850455	18TXM135305	18TWM640170	18TXL000990
18TWL595810	18TWM865545	18TWM865455	18TXM150305	18TWM655170	18TXL015990
18TWL610810	18TWM880545	18TWM880455	18TXM165305	18TWM670170	18TXL030990
18TWL625810	18TWM895545	18TWM895455	18TXM180305	18TWM685170	18TXL045990
18TWL640810	18TWM910545	18TWM910455	18TXM195305	18TWM700170	18TXL060990
18TWL655810	18TWM925545	18TWM925455	18TXM210305	18TWM715170	18TXL075990
18TWL670810	18TWM940545	18TWM940455	18TXM225305	18TWM730170	18TXL090990
18TWL685810	18TWM955545	18TWM955455	18TXM240305	18TWM745170	18TXL105990
18TWL700810	18TWM970545	18TWM970455	18TWM415320	18TWM760170	18TXL120990
18TWL715810	18TWM985545	18TWM985455	18TWM430320	18TWM775170	18TXL135990
18TWL730810	18TXM000545	18TXM000455	18TWM445320	18TWM790170	18TXL150990
18TWL745810	18TXM210545	18TXM015455	18TWM460320	18TWM805170	18TXL165990
18TWL760810	18TXM225545	18TXM030455	18TWM475320	18TWM820170	18TXL180990
18TWL775810	18TXM240545	18TXM045455	18TWM490320	18TWM835170	18TXL195990
18TWL790810	18TWM235560	18TXM060455	18TWM505320	18TWM850170	18TXL210990
18TWL805810	18TWM250560	18TXM075455	18TWM520320	18TWM865170	18TXL225990
18TWL820810	18TWM265560	18TXM090455	18TWM535320	18TWM880170	18TWM460005
18TWL835810	18TWM280560	18TXM105455	18TWM550320	18TWM895170	18TWM475005
18TWL850810	18TWM295560	18TXM120455	18TWM565320	18TWM910170	18TWM490005
18TWL865810	18TWM310560	18TXM135455	18TWM580320	18TWM925170	18TWM505005
18TWL205825	18TWM325560	18TXM150455	18TWM595320	18TWM940170	18TWM520005
18TWL220825	18TWM340560	18TXM165455	18TWM610320	18TWM955170	18TWM535005
18TWL235825	18TWM355560	18TXM180455	18TWM625320	18TWM970170	18TWM550005
18TWL250825	18TWM370560	18TXM195455	18TWM640320	18TWM985170	18TWM565005
18TWL265825	18TWM385560	18TXM210455	18TWM655320	18TXM000170	18TWM580005
18TWL280825	18TWM400560	18TXM225455	18TWM670320	18TXM015170	18TWM595005
18TWL295825	18TWM415560	18TXM240455	18TWM685320	18TXM030170	18TWM610005
18TWL310825	18TWM430560	18TWM220470	18TWM700320	18TXM045170	18TWM625005
18TWL325825	18TWM445560	18TWM235470	18TWM715320	18TXM060170	18TWM640005
18TWL340825	18TWM460560	18TWM250470	18TWM730320	18TXM075170	18TWM655005
18TWL355825	18TWM475560	18TWM265470	18TWM745320	18TXM090170	18TWM670005
18TWL370825	18TWM490560	18TWM280470	18TWM760320	18TXM105170	18TWM685005
18TWL385825	18TWM505560	18TWM295470	18TWM775320	18TXM120170	18TWM700005
18TWL400825	18TWM520560	18TWM310470	18TWM790320	18TXM135170	18TWM715005
18TWL415825	18TWM535560	18TWM325470	18TWM805320	18TXM150170	18TWM730005
18TWL430825	18TWM550560	18TWM340470	18TWM820320	18TXM165170	18TWM745005
18TWL445825	18TWM565560	18TWM355470	18TWM835320	18TXM180170	18TWM760005
18TWL460825	18TWM580560	18TWM370470	18TWM850320	18TXM195170	18TWM775005
18TWL475825	18TWM595560	18TWM385470	18TWM865320	18TXM210170	18TWM790005

18TWL490825	18TWM610560	18TWM400470	18TWM880320	18TXM225170	18TWM805005
18TWL505825	18TWM625560	18TWM415470	18TWM895320	18TWM370185	18TWM820005
18TWL520825	18TWM640560	18TWM430470	18TWM910320	18TWM385185	18TWM835005
18TWL535825	18TWM655560	18TWM445470	18TWM925320	18TWM400185	18TWM850005
18TWL550825	18TWM670560	18TWM460470	18TWM940320	18TWM415185	18TWM865005
18TWL565825	18TWM685560	18TWM475470	18TWM955320	18TWM430185	18TWM880005
18TWL580825	18TWM700560	18TWM490470	18TWM970320	18TWM445185	18TWM895005
18TWL595825	18TWM715560	18TWM505470	18TWM985320	18TWM460185	18TWM910005
18TWL610825	18TWM730560	18TWM520470	18TXM000320	18TWM475185	18TWM925005
18TWL625825	18TWM745560	18TWM535470	18TXM015320	18TWM490185	18TWM940005
18TWL640825	18TWM760560	18TWM550470	18TXM030320	18TWM505185	18TWM955005
18TWL655825	18TWM775560	18TWM565470	18TXM045320	18TWM520185	18TWM970005
18TWL670825	18TWM790560	18TWM580470	18TXM060320	18TWM535185	18TWM985005
18TWL685825	18TWM805560	18TWM595470	18TXM075320	18TWM550185	18TXM000005
18TWL700825	18TWM820560	18TWM610470	18TXM090320	18TWM565185	18TXM015005
18TWL715825	18TWM835560	18TWM625470	18TXM105320	18TWM580185	18TXM030005
18TWL730825	18TWM850560	18TWM640470	18TXM120320	18TWM595185	18TXM045005
18TWL745825	18TWM865560	18TWM655470	18TXM135320	18TWM610185	18TXM060005
18TWL760825	18TWM880560	18TWM670470	18TXM150320	18TWM625185	18TXM075005
18TWL775825	18TWM895560	18TWM685470	18TXM165320	18TWM640185	18TXM090005
18TWL790825	18TWM910560	18TWM700470	18TXM180320	18TWM655185	18TXM105005
18TWL805825	18TWM925560	18TWM715470	18TXM195320	18TWM670185	18TXM120005
18TWL820825	18TWM940560	18TWM730470	18TXM210320	18TWM685185	18TXM135005
18TWL835825	18TWM955560	18TWM745470	18TXM225320	18TWM700185	18TXM150005
18TWL850825	18TWM970560	18TWM760470	18TXM240320	18TWM715185	18TXM165005
18TWL865825	18TXM210560	18TWM775470	18TWM430335	18TWM730185	18TXM180005
18TWL880825	18TXM225560	18TWM790470	18TWM445335	18TWM745185	18TXM195005
18TWL205840	18TXM240560	18TWM805470	18TWM460335	18TWM760185	18TXM210005
18TWL220840	18TWM265575	18TWM820470	18TWM475335	18TWM775185	18TXM225005
18TWL235840	18TWM280575	18TWM835470	18TWM490335	18TWM790185	18TWM475020
18TWL250840	18TWM295575	18TWM850470	18TWM505335	18TWM805185	18TWM490020
18TWL265840	18TWM310575	18TWM865470	18TWM520335	18TWM820185	18TWM505020
18TWL280840	18TWM325575	18TWM880470	18TWM535335	18TWM835185	18TWM520020
18TWL295840	18TWM340575	18TWM895470	18TWM550335	18TWM850185	18TWM535020
18TWL310840	18TWM355575	18TWM910470	18TWM565335	18TWM865185	18TWM550020
18TWL325840	18TWM370575	18TWM925470	18TWM580335	18TWM880185	18TWM565020
18TWL340840	18TWM385575	18TWM940470	18TWM595335	18TWM895185	18TWM580020
18TWL355840	18TWM400575	18TWM955470	18TWM610335	18TWM910185	18TWM595020
18TWL370840	18TWM415575	18TWM970470	18TWM625335	18TWM925185	18TWM610020
18TWL385840	18TWM430575	18TWM985470	18TWM640335	18TWM940185	18TWM625020
18TWL400840	18TWM445575	18TXM000470	18TWM655335	18TWM955185	18TWM640020
18TWL415840	18TWM460575	18TXM015470	18TWM670335	18TWM970185	18TWM655020

18TWL430840	18TWM475575	18TXM030470	18TWM685335	18TWM985185	18TWM670020
18TWL445840	18TWM490575	18TXM045470	18TWM700335	18TXM000185	18TWM685020
18TWL460840	18TWM505575	18TXM060470	18TWM715335	18TXM015185	18TWM700020
18TWL475840	18TWM520575	18TXM075470	18TWM730335	18TXM030185	18TWM715020
18TWL490840	18TWM535575	18TXM090470	18TWM745335	18TXM045185	18TWM730020
18TWL505840	18TWM550575	18TXM105470	18TWM760335	18TXM060185	18TWM745020
18TWL520840	18TWM565575	18TXM120470	18TWM775335	18TXM075185	18TWM760020
18TWL535840	18TWM580575	18TXM135470	18TWM790335	18TXM090185	18TWM775020
18TWL550840	18TWM595575	18TXM150470	18TWM805335	18TXM105185	18TWM790020
18TWL565840	18TWM610575	18TXM165470	18TWM820335	18TXM120185	18TWM805020
18TWL580840	18TWM625575	18TXM180470	18TWM835335	18TXM135185	18TWM820020
18TWL595840	18TWM640575	18TXM195470	18TWM850335	18TXM150185	18TWM835020
18TWL610840	18TWM655575	18TXM210470	18TWM865335	18TXM165020	18TWM850020
18TWL625840	18TWM670575	18TXM225470	18TWM880335	18TXM180020	18TWM865020
18TWL640840	18TWM685575	18TXM240470	18TWM895335	18TXM195020	18TWM880020
18TWL655840	18TWM700575	18TWM205485	18TWM910335	18TXM210020	18TWM895020
18TWL670840	18TWM715575	18TWM220485	18TWM925335	18TXM225020	18TWM910020
18TWL685840	18TWM730575	18TWM235485	18TWM940335	18TWM490035	18TWM925020
18TWL700840	18TWM745575	18TWM250485	18TWM955335	18TWM505035	18TWM940020
18TWL715840	18TWM760575	18TWM265485	18TWM970335	18TWM520035	18TWM955020
18TWL730840	18TWM775575	18TWM280485	18TWM985335	18TWM535035	18TWM970020
18TWL745840	18TWM790575	18TWM295485	18TXM000335	18TWM550035	18TWM985020
18TWL760840	18TWM805575	18TWM310485	18TXM015335	18TWM565035	18TXM000020
18TWL775840	18TWM820575	18TWM325485	18TXM030335	18TWM580035	18TXM015020
18TWL790840	18TWM835575	18TWM340485	18TXM045335	18TWM595035	18TXM030020
18TWL805840	18TWM850575	18TWM355485	18TXM060335	18TWM610035	18TXM045020
18TWL820840	18TWM865575	18TWM370485	18TXM075335	18TWM625035	18TXM060020
18TWL835840	18TWM880575	18TWM385485	18TXM090335	18TWM640035	18TXM075020
18TWL850840	18TWM895575	18TWM400485	18TXM105335	18TWM655035	18TXM090020
18TWL865840	18TWM910575	18TWM415485	18TXM120335	18TWM670035	18TXM105020
18TWL190855	18TWM925575	18TWM430485	18TXM135335	18TWM685035	18TXM120020
18TWL205855	18TWM940575	18TWM445485	18TXM150335	18TWM700035	18TXM135020
18TWL220855	18TWM295590	18TXM150020			

## Appendix C: GPS Processing Reports for Each Mission Output Results for Mission\_JD13324F01

Figure 1: Trajectory Map




Figure 2: Estimated Standard Deviation




Figure 3: Height Profile






Figure 4: Combined Separation






Figure 5: PDOP



**Figure 6: Baseline Distance**



**Output Results for Mission\_JD13324F02**

**Figure 1: Trajectory Map**






Figure 2: Estimated Standard Deviation



**Figure 3: Height Profile**



**Figure 4: Combined Separation**




Figure 5: PDOP





Figure 6: Baseline Distance





## Output Results for Mission\_JD13327F01

Figure 1: Trajectory Map







Figure 2: Estimated Standard Deviation




**Figure 3: Height Profile**




**Figure 4: Combined Separation**



**Figure 5: PDOP**



**Figure 6: Baseline Distance**



**Output Results for Mission\_JD13329F01**

**Figure 1: Trajectory Map**






Figure 2: Estimated Standard Deviation





**Figure 3: Height Profile**



**Figure 4: Combined Separation**




Figure 5: PDOP





Figure 6: Baseline Distance



## Output Results for Mission\_JD13334F01

Figure 1: Trajectory Map




Figure 2: Estimated Standard Deviation




Figure 3: Height Profile




Figure 4: Combined Separation






Figure 5: PDOP





**Figure 6: Baseline Distance**



**Output Results for Mission\_JD13335F01**

**Figure 1: Trajectory Map**






Figure 2: Estimated Standard Deviation



**Figure 3: Height Profile**



**Figure 4: Combined Separation**




Figure 5: PDOP





Figure 6: Baseline Distance



## Output Results for Mission\_JD14115F01

Figure 1: Trajectory Map




Figure 2: Estimated Standard Deviation






Figure 3: Height Profile




Figure 4: Combined Separation






Figure 5: PDOP



**Figure 6: Baseline Distance**



**Output Results for Mission\_JD14115F02**

**Figure 1: Trajectory Map**






Figure 2: Estimated Standard Deviation



**Figure 3: Height Profile**



**Figure 4: Combined Separation**






Figure 5: PDOP





Figure 6: Baseline Distance



## Output Results for Mission\_JD14118F01

Figure 1: Trajectory Map




Figure 2: Estimated Standard Deviation




Figure 3: Height Profile




Figure 4: Combined Separation






Figure 5: PDOP



**Figure 6: Baseline Distance**



**Output Results for Mission\_JD14126F01**

**Figure 1: Trajectory Map**









Figure 2: Estimated Standard Deviation




**Figure 3: Height Profile**




**Figure 4: Combined Separation**



**Figure 5: PDOP**



**Figure 6: Baseline Distance**



## Output Results for Mission\_JD14127F01

Figure 1: Trajectory Map




Figure 2: Estimated Standard Deviation






Figure 3: Height Profile







**Figure 4: Combined Separation**



**Figure 5: PDOP**



**Figure 6: Baseline Distance**



**Output Results for Mission\_JD14127F02**

**Figure 1: Trajectory Map**






Figure 2: Estimated Standard Deviation



**Figure 3: Height Profile**



**Figure 4: Combined Separation**




Figure 5: PDOP





Figure 6: Baseline Distance





## Output Results for Mission\_JD14131F01

Figure 1: Trajectory Map




Figure 2: Estimated Standard Deviation




Figure 3: Height Profile




Figure 4: Combined Separation






Figure 5: PDOP



**Figure 6: Baseline Distance**




**Output Results for Mission\_JD14131F02**

**Figure 1: Trajectory Map**




Figure 2: Estimated Standard Deviation







**Figure 3: Height Profile**




**Figure 4: Combined Separation**



**Figure 5: PDOP**



**Figure 6: Baseline Distance**



## Output Results for Mission\_JD14132F01

Figure 1: Trajectory Map





Figure 2: Estimated Standard Deviation



**Figure 3: Height Profile**




Figure 4: Combined Separation





Figure 5: PDOP





**Figure 6: Baseline Distance**



**Output Results for Mission\_JD14133F01**

**Figure 1: Trajectory Map**






Figure 2: Estimated Standard Deviation



**Figure 3: Height Profile**



**Figure 4: Combined Separation**




Figure 5: PDOP






Figure 6: Baseline Distance









**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




**Output Results for Mission\_JD14138F01**

**Figure 1: Trajectory Map**




**Figure 2: Estimated Standard Deviation**





**Figure 3: Height Profile**



**Figure 4: Combined Separation**






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14139F01

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP



**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14140F01

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




**Output Results for Mission\_JD14140F02A**

**Figure 1: Trajectory Map**





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14140F02B

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14140F04

Figure 1: Trajectory Map






**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**



**Figure 4: Combined Separation**




Figure 5: PDOP






Figure 6: Baseline Distance




## Output Results for Mission\_JD14140F03A

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14140F03B

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14141F01

Figure 1: Trajectory Map






**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**



**Figure 4: Combined Separation**






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14145F01

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation




Figure 5: PDOP





Figure 6: Baseline Distance




## Output Results for Mission\_JD14145F02

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP



**Figure 6: Baseline Distance**




## Output Results for Mission\_JD114146F01

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14146F02

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14147F01

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14149F01

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation






Figure 5: PDOP



**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14152F01

Figure 1: Trajectory Map






**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**



**Figure 4: Combined Separation**






Figure 5: PDOP




**Figure 6: Baseline Distance**




## Output Results for Mission\_JD14152F02

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**




Figure 4: Combined Separation




Figure 5: PDOP






Figure 6: Baseline Distance




## Output Results for Mission\_JD14152F03

Figure 1: Trajectory Map





**Figure 2: Estimated Standard Deviation**



**Figure 3: Height Profile**






Figure 4: Combined Separation



**Figure 5: PDOP**



**Figure 6: Baseline Distance**

