




quantum
SPATIAL

AN NV5 COMPANY



ASHLAND IRON FLORENCE 2019 DI9
LIDAR PROCESSING REPORT

Work Package: 183663

Work Unit: 183715

2020

Submitted: October 7, 2020

Prepared for:



1400 Independence Drive
Rolla, MO 65401

573.308.3500

Prepared by:



523 Wellington Way, Suite 375
Lexington, KY 40503

859.277.8700

Contents

1. Summary / Scope	1
1.1. Summary.....	1
1.2. Scope.....	1
1.3. Coverage.....	1
1.4. Duration.....	1
1.5. Issues	1
2. Planning / Equipment	4
2.1. Flight Planning	4
2.2. LiDAR Sensor.....	4
2.3. Aircraft.....	7
2.4. Time Period.....	8
3. Processing Summary	9
3.1. Flight Logs.....	9
3.2. LiDAR Processing.....	10
3.3. LAS Classification Scheme	11
3.4. Classified LAS Processing	11
3.5. Hydro-Flattened Breakline Processing.....	12
4. Project Coverage Verification	15

List of Figures

Figure 1. Project Boundary	3
Figure 2. Planned Flight Lines	5
Figure 3. Riegl VQ1560i LiDAR Sensor	6
Figure 4. Some of Quantum Spatial's Planes	7
Figure 5. LiDAR Tile Layout	14
Figure 6. LiDAR Flight Line Coverage	16

List of Tables

Table 1. Originally Planned LiDAR Specifications	1
Table 2. LiDAR System Specifications	6
Table 3. LAS Classifications	11

1. Summary / Scope

1.1. Summary

This report contains a summary of the Ashland Iron Florence 2019 D19, Work Unit 183715 LiDAR acquisition task order, issued by USGS under their Contract G16PC00016 on September 23, 2019. The task order yielded a project area covering approximately 1,065 square miles over Wisconsin. The intent of this document is only to provide specific validation information for the data acquisition/collection, processing, and production of deliverables completed as specified in the task order.

1.2. Scope

Aerial topographic LiDAR was acquired using state of the art technology along with the necessary surveyed ground control points (GCPs) and airborne GPS and inertial navigation systems. The aerial data collection was designed with the following specifications listed in Table 1 below.

Table 1. Originally Planned LiDAR Specifications

Average Point Density	Flight Altitude (AGL)	Field of View	Minimum Side Overlap	RMSEz
8 pts / m ²	1329 m	58.52°	20%	≤ 10 cm

1.3. Coverage

The QL1 boundary covers 1,065 square miles over Ashland County, Wisconsin. A buffer of 100 meters was created to meet task order specifications. Project extents are shown in Figure 1.

1.4. Duration

QL LiDAR data was acquired from October 25, 2019 to October 30, 2019 in 8 total lifts. See “Section: 2.4. Time Period” for more details.

1.5. Issues

There were no major issues to report for this project.

WI_AshlandIronFlorence_2019_D19 Work Unit 183715 Projected Coordinate System: WISCRS Ashland County Horizontal Datum: NAD83 (2011) Vertical Datum: NAVD88 (GEOID 12B) Units: Feet	
Lidar Point Cloud	Classified Point Cloud in LAS 1.4 format
Rasters	2-Foot GeoTiffs <ul style="list-style-type: none"> • Hydroflattened Bare Earth Model (DEM) • Highest Hit Digital Surface Model (DSM) • Highest Hit Digital Surface Model (DSM) Mosaic • Intensity Images
Vectors	Shapefiles (*.shp) <ul style="list-style-type: none"> • Project Boundary • LiDAR Tile Index • Coverage polygon ESRI Geodatabase (*.gdb) <ul style="list-style-type: none"> • Continuous Hydro-flattened Breaklines
Reports	Reports in PDF format <ul style="list-style-type: none"> • Focus on Delivery • Lidar Processing Report
Metadata	XML Files (*.xml) <ul style="list-style-type: none"> • Breaklines • Classified Point Cloud • DEM • Intensity Imagery • DSM




Figure 1. Project Boundary

2. Planning / Equipment

2.1. Flight Planning

Flight planning was based on the unique project requirements and characteristics of the project site. The basis of planning included: required accuracies, type of development, amount / type of vegetation within project area, required data posting, and potential altitude restrictions for flights in project vicinity.

Detailed project flight planning calculations were performed for the project using RiPARAMETER planning software. Planned flight lines are shown in Figure 2.

2.2. LiDAR Sensor

Quantum Spatial utilized a Riegl VQ1560i LiDAR sensor (Figure 3), serial number 3070, for lidar data acquisition.

The Riegl 1560i system has a laser pulse repetition rate of up to 2 MHz resulting in more than 1.3 million measurements per second. The system utilizes a Multi-Pulse in the Air option (MPIA). The sensor is also equipped with the ability to measure up to an unlimited number of targets per pulse from the laser.

A brief summary of the aerial acquisition parameters for the project are shown in the LiDAR System Specifications in Table 2.

Ashland QL1 Lidar Flight Lines




Figure 2. Planned Flight Lines

Table 2. LiDAR System Specifications

		Riegl VQ1560i
Terrain and Aircraft Scanner	Flying Height	1329 m
	Recommended Ground Speed	160 kts
Scanner	Field of View	58.52°
	Scan Rate Setting Used	334 Hz
Laser	Laser Pulse Rate Used	2000 kHz
	Multi Pulse in Air Mode	yes
Coverage	Full Swath Width	1489 m
	Line Spacing	1191 m
Point Spacing and Density	Average Point Spacing	0.384 m
	Average Point Density	10.88 pts / m ²

Figure 3. Riegl VQ1560i LiDAR Sensor


2.3. Aircraft

All flights for the project were accomplished through the use of customized planes. Plane type and tail numbers are listed below.

LiDAR Collection Planes

- 2015 TEXTRON AVIATION INC 208B, Tail Number: N256DG

These aircraft provided an ideal, stable aerial base for LiDAR acquisition. These aerial platforms have relatively fast cruise speeds, which are beneficial for project mobilization / demobilization while maintaining relatively slow stall speeds, proving ideal for collection of high-density, consistent data posting using a state-of-the-art Riegl VQ1560i LiDAR system. Some of Quantum Spatial's operating aircraft can be seen in Figure 4 below.

Figure 4. Some of Quantum Spatial's Planes



2.4. Time Period

Project specific flights were conducted between October 25, 2019 and October 30, 2019. Eight aircraft lifts were completed. Accomplished lifts are listed below.

- 10252019A (SN3070,N256DG)
- 10262019A (SN3070,N256DG)
- 10262019B (SN3070,N256DG)
- 10272019A (SN3070,N256DG)
- 10292019A1 (SN3070,N256DG)
- 10292019A2 (SN3070,N256DG)
- 10302019A (SN3070,N256DG)
- 10302019B (SN3070,N256DG)

3. Processing Summary

3.1. Flight Logs

Flight logs were completed by LIDAR sensor technicians for each mission during acquisition. These logs depict a variety of information, including:

- Job / Project #
- Flight Date / Lift Number
- FOV (Field of View)
- Scan Rate (HZ)
- Pulse Rate Frequency (Hz)
- Ground Speed
- Altitude
- Base Station
- PDOP avoidance times
- Flight Line #
- Flight Line Start and Stop Times
- Flight Line Altitude (AMSL)
- Heading
- Speed
- Returns
- Crab

Notes: (Visibility, winds, ride, weather, temperature, dew point, pressure, etc).

3.2. LiDAR Processing

Applanix + POSPac software was used for post-processing of airborne GPS and inertial data (IMU), which is critical to the positioning and orientation of the LiDAR sensor during all flights. Applanix POSPac combines aircraft raw trajectory data with stationary GPS base station data yielding a “Smoothed Best Estimate Trajectory” (SBET) necessary for additional post processing software to develop the resulting geo-referenced point cloud from the LiDAR missions.

During the sensor trajectory processing (combining GPS & IMU datasets) certain statistical graphs and tables are generated within the Applanix POSPac processing environment which are commonly used as indicators of processing stability and accuracy. This data for analysis include: max horizontal / vertical GPS variance, separation plot, altitude plot, PDOP plot, base station baseline length, processing mode, number of satellite vehicles, and mission trajectory.

Point clouds were created using the RiPROCESS software. The generated point cloud is the mathematical three dimensional composite of all returns from all laser pulses as determined from the aerial mission. The point cloud is imported into GeoCue distributive processing software. Imported data is tiled and then calibrated using TerraMatch and proprietary software. Using TerraScan, the vertical accuracy of the surveyed ground control is tested and any bias is removed from the data. TerraScan and TerraModeler software packages are then used for automated data classification and manual cleanup. The data are manually reviewed and any remaining artifacts removed using functionality provided by TerraScan and TerraModeler.

DEMs and Intensity Images are then generated using proprietary software. In the bare earth surface model, above-ground features are excluded from the data set. Global Mapper is used as a final check of the bare earth dataset.

Finally, proprietary software is used to perform statistical analysis of the LAS files.

Software	Version
Applanix + POSPac	8.4
RiPROCESS	1.8.6
GeoCue	2017.1.14.1
Global Mapper	19.1;20.1
TerraModeler	20.004
TerraScan	20.011
TerraMatch	20.004

3.3. LAS Classification Scheme

The classification classes are determined by the USGS Version 1.3 specifications and are an industry standard for the classification of LIDAR point clouds. All data starts the process as Class 1 (Unclassified), and then through automated classification routines, the classifications are determined using TerraScan macro processing.

The classes used in the dataset are as follows and have the following descriptions:

Table 3. LAS Classifications

	Classification Name	Description
1	Processed, but Unclassified	Laser returns that are not included in the ground class, or any other project classification
2	Bare earth	Laser returns that are determined to be ground using automated and manual cleaning algorithms
3	Low Vegetation	Points that fall on vegetation (0.5ft-6ft)
4	Medium Vegetation	Points that fall on vegetation (6ft-30ft)
5	High Vegetation	Points that fall on vegetation (>30ft)
6	Buildings	Points falling on buildings, structures inside of water bodies, docks, and piers.
7	Low Noise	Laser returns that are often associated with scattering from reflective surfaces, or artificial points below the ground surface
9	Water	Laser returns that are found inside of hydro features
17	Bridge Deck	Laser returns falling on bridge decks
18	High Noise	Laser returns that are often associated with birds or artificial points above the ground surface
20	Ignored Ground	Ground points that fall within the given threshold of a collected hydro feature.
21	Snow	Ground points that fall on snow, where identifiable
22	Temporal Exclusion	Points that are excluded due to differences in collection dates

3.4. Classified LAS Processing

The bare earth surface is then manually reviewed to ensure correct classification on the Class 2 (Ground) points. After the bare- earth surface is finalized; it is then used to generate all hydro-

breaklines through heads-up digitization.

All ground (ASPRS Class 2) LiDAR data inside of the Lake Pond and Double Line Drain hydro flattening breaklines were then classified to water (ASPRS Class 9) using TerraScan macro functionality. A buffer of 3 feet was also used around each hydro flattened feature to classify these ground (ASPRS Class 2) points to Ignored ground (ASPRS Class 20). All Lake Pond Island and Double Line Drain Island features were checked to ensure that the ground (ASPRS Class 2) points were reclassified to the correct classification after the automated classification was completed.

All overlap data was processed through automated functionality provided by TerraScan to classify the overlapping flight line data to approved classes by USGS. The overlap data was identified using the Overlap Flag, per LAS 1.4 specifications.

All data was manually reviewed and any remaining artifacts removed using functionality provided by TerraScan and TerraModeler. Global Mapper is used as a final check of the bare earth dataset. GeoCue was then used to create the deliverable industry-standard LAS files for all point cloud data. Quantum Spatial's proprietary software was used to perform final statistical analysis of the classes in the LAS files, on a per tile level to verify final classification metrics and full LAS header information.

3.5. Hydro-Flattened Breakline Processing

Class 2 LiDAR was used to create a bare earth surface model. The surface model was then used to heads-up digitize 2D breaklines of Inland Streams and Rivers with a 100 foot nominal width and Inland Ponds and Lakes of 2 acres or greater surface area.

Elevation values were assigned to all Inland Ponds and Lakes, Inland Pond and Lake Islands, Inland Streams and Rivers and Inland Stream and River Islands using TerraModeler functionality.

Elevation values were assigned to all Inland streams and rivers using Quantum Spatial's proprietary software.

All ground (ASPRS Class 2) LiDAR data inside of the collected inland breaklines were then classified to water (ASPRS Class 9) using TerraScan macro functionality. A buffer of 3 feet was also used around each hydro flattened feature. These points were moved from ground (ASPRS Class 2) to Ignored Ground (ASPRS Class 20).

The breakline files were then translated to Esri file geodatabase format using Esri conversion tools.

Breaklines are reviewed against lidar intensity imagery to verify completeness of capture. All breaklines are then compared to TINs (triangular irregular networks) created from ground only points prior to water classification. The horizontal placement of breaklines is compared to terrain features and the breakline elevations are compared to lidar elevations to ensure all breaklines match the lidar within acceptable tolerances. Some deviation is expected between breakline and lidar elevations due to monotonicity, connectivity, and flattening rules that are enforced on the breaklines. Once completeness, horizontal placement, and vertical variance is reviewed, all

breaklines are reviewed for topological consistency and data integrity using a combination of Esri Data Reviewer tools and proprietary tools.

3.6. Hydro-Flattened Raster DEM Processing

Class 2 LiDAR in conjunction with the hydro breaklines were used to create a 2-foot Raster DEM. Using automated scripting routines within proprietary software, a GeoTIFF file was created for each tile. Each surface is reviewed using Global Mapper to check for any surface anomalies or incorrect elevations found within the surface.

3.7. Intensity Image Processing

GeoCue software was used to create the deliverable intensity images. All overlap classes were ignored during this process. This helps to ensure a more aesthetically pleasing image. The GeoCue software was then used to verify full project coverage as well. GeoTIFF files with a cell size of 2-foot were then provided as the deliverable for this dataset requirement.

3.8. Raster DSM Processing

First return LiDAR points were used to create a 2 foot first-return raster DSM. Using automated scripting routines within ArcMap, GeoTIFF files were created for each tile. Each surface is reviewed using Global Mapper to check for any surface anomalies or incorrect elevations found within the surface.




Figure 5. LiDAR Tile Layout

4. Project Coverage Verification

Coverage verification was performed by comparing coverage of processed .LAS files captured during project collection to generate project shape files depicting boundaries of specified project areas. Please refer to Figure 6.




Figure 6. LiDAR Flight Line Coverage