

LIDAR REMOTE SENSING DATA COLLECTION:

DOGAMI, SOUTH COAST STUDY AREA

TABLE OF CONTENTS

1. Overview	
1.1 Study Area (South Coast)	
1.2 Area Delivered to Date	
1.3 Acquisition and Ground Survey	
2. Accuracy	12
2.1 Relative Accuracy	12
2.2 Absolute Accuracy	12
3. Data Density/Resolution	
3.1 Density Statistics	
3.2 Data Density/Resolution per Delivery	
3.2.1 Delivery 1	
3.2.2 Delivery 2	19
3.2.3 Delivery 3	
3.2.4 Delivery 4	
4. Selected Imagery	

1. Overview

1.1 Study Area (South Coast)

Watershed Sciences, Inc. is currently collecting Light Detection and Ranging (LiDAR) data of the South Coast study area for the Oregon Department of Geology and Mineral Industries (DOGAMI). The Area of Interest (AOI) covers portions of four counties in southwest Oregon. The requested LiDAR area totals ~1,610,136 acres; the map below shows the Total Area to be Flown (TAF), covering ~1,632,390 acres. The TAF acreage is greater than the original AOI acreage due to buffering and flight planning optimization. This report will be amended to reflect new data and cumulative statistics for the overall LiDAR survey. DOGAMI data are *delivered* in OGIC(HARN): Projection: Oregon Statewide Lambert Conformal Conic; horizontal and vertical datums: NAD83 (HARN)/NAVD88(Geoid03); Units: International Feet.

Figure 1.1. DOGAMI South Coast study area.




1.2 Area Delivered to Date

Total delivered acreage to date is detailed below.

	DOGAMI Southern Oregon Coast			
	Delivery Date	Acquisition Date	AOI Acres	TAF Acres
Delivery 1	September 3, 2008	May 3 - June 26, 2008	46,568	47,798
Delivery 2	October 2, 2008	May 3 - June 26, 2008	86,505	88,789
Delivery 3	October 16, 2008	May 3 - June 26, 2008	68,913	71,791
Delivery 4	November 21, 2008	June 12 - June 29, 2008	111,851	113,638
Delivery 5	January 19, 2009	June 12 - June 29, 2008	113,350	113,794
Delivery 6	April 15, 2009	June 15 - August 9, 2008	221,939	222,692
Delivery 7	April 15, 2009	June 15 - August 9, 2008	133,226	134,276
Delivery 8a	April 15, 2009	June 15 - August 9, 2008	91,453	93,631
		Total	873,805	886,409

Figure 1.2. DOGAMI southern Oregon coast study area, illustrating the delivered portion of the TAF.




43124C2 43124C1 43123C8 43123C7 43123C6 43124B2 43124B1 43123B8 43123B7 43123B6 43124A2 43124A1 43123A8 43123A7 43123A6 42124H2 42124H1 42123H8 42123H7 42123H6 0.75-Minute USGS Quads 42124G2 42124G1 7.5-Minute USGS Quads 42123G8 **Previous Deliveries** Delivery 6 Delivery 7 Delivery 8a 42123F8 Miles Total Area Flown 0 2.5 5

Figure 1.3. South Coast study area, illustrating the delivered 7.5 and 0.75-minute USGS quads.

1.3 Acquisition and Ground Survey

LiDAR acquisition for deliveries 6, 7 and 8a occurred from June 15 - August 9, 2008 for the South Coast study area.

Figure 1.4. Actual flightlines for the South Coast study area illustrating the dates flown (based on GPS week).



OLCPWH8 OLCJN8 **OLCCF3** OLCCF1 OLCCF2 **AA5136 OLGPWH1 OLCET Base Stations** Data delivered to date ■ Miles Total Area Flown 10 5

Figure 1.5. Base stations for the South Coast study area for data delivered to date.

Table 1.1. Base Station Surveyed Coordinates, (NAD83/NAVD88, OPUS corrected) used for kinematic post-processing of the aircraft GPS data for the South Coast study area.

	Datum	NAD83(HARN)	GRS80
Base	Latitude	Longitude	Ellipsoid
Station ID	(North)	(West)	Height (m)
OLC5CD1	43 15 20.76929	123 53 22.87770	217.600
OLC5CD2	43 20 23.11132	124 11 55.76971	-20.988
OLC5CD3	43 20 56.06002	123 54 36.20001	217.506
OLC5PW	43 21 2.60751	124 20 13.64907	-2.435
OLCCF1	42 58 00.42449	124 06 55.61889	28.559
OLCCF2	42 57 55.66164	124 07 06.22758	102.674
OLCCF3	43 01 54.71258	124 06 43.96709	-7.289
OLCJN1	42 08 30.08496	124 12 49.11911	428.475
OLCJN2	42 08 27.95822	124 12 49.29884	427.870
OLCJN3	42 03 04.54697	124 17 30.17996	1.811
OLCJN4	42 03 50.25255	124 12 46.39603	31.933
OLCJN5	42 28 05.44507	124 20 46.24558	-21.890
OLCJN6	42 25 33.04097	124 25 35.72884	-19.346
OLCJN7	42 48 31.65550	124 29 21.62711	33.225
OLCJN8	43 09 26.13789	124 22 44.20041	-19.734
OLCJN9	42 47 10.43094	124 28 52.40738	-13.568
OLCJN10	43 00 44.63261	123 41 38.18942	307.728
OLCJN11	42 57 16.07660	123 46 38.70609	543.201
OLCPWH1	42 19 43.74040	124 25 33.76978	177.778
OLCPWH2	42 32 11.15305	124 23 59.59628	-13.175
OLCPWH3	42 27 48.10893	124 21 45.53382	-15.340
OLCPWH4	42 16 31.44293	124 24 15.39346	-21.678
OLCPWH5	42 48 26.82761	124 20 09.43708	68.264
OLCPWH6	43 07 56.53594	124 21 10.15905	-22.854
OLCPWH7	43 15 44.29178	123 49 12.34815	32.003
OLCPWH8	43 10 23.32427	124 12 00.96021	-19.743
OLCPWH9	42 59 01.23604	123 48 06.84695	733.518
OLCPWH10	43 15 44.25471	123 49 12.35897	285.251
OLCPWH11	43 09 54.31855	124 02 56.98822	62.611
OLCPWH12	43 15 44.29178	123 49 12.34815	285.248
OLCPWH13	43 00 21.54079	123 53 20.67738	50.495
OLCPWH14	42 59 29.68950	123 50 23.50621	328.574
OLCPWH15	42 56 37.78974	124 05 51.77012	43.503
OLCPWH16	42 54 02.56554	124 07 27.51313	117.941
OLCPWH17	43 21 47.87472	124 04 51.53211	-19.865
OLCBTK1	42 07 32.49487	124 18 37.00074	295.173
OLCBTK2	42 04 08.31008	124 18 52.63704	-16.064
OLCBTK3	42 08 39.24373	124 21 22.62505	-6.578
OLCBTK4	42 02 44.62353	124 16 04.64324	-21.946
AA5136	42 52 23.01388	124 03 42.88679	64.842
NGS_PID_OA07	43 5 54.88105	124 24 55.03463	-0.860
DH7020	43 5 11.08316	124 24 26.18403	7.977

For data delivered to date, 19,102 RTK points were collected in the study area. Figures 1.6-1.10 show detailed views of RTK point locations.

Figure 1.6. RTK point locations in the study area; images are NAIP Orthoimages.




Figure 1.7. RTK point locations in the study area; images are NAIP Orthoimages.





Figure 1.8. RTK point locations in the study area; images are NAIP Orthoimages.



 $\textbf{\textit{Figure 1.9}}. \ \ \textit{RTK point locations in the study area; images are NAIP Orthoimages}.$





Figure 1.10. RTK point locations in the study area; images are NAIP Orthoimages.



2. Accuracy

2.1 Relative Accuracy

Relative accuracy statistics evaluate internal consistency (line to line reproducibility) for a LiDAR dataset, and are measured as the divergence between points from distinct, overlapping flightlines. The final report will include relative accuracy statistics for the entire South Coast study area. To date, reported project averages are well within contracted specifications.


2.2 Absolute Accuracy


Absolute accuracy compares known Real Time Kinematic (RTK) ground survey points to the closest laser point. For the South Coast study area, 19,102 RTK points were collected for data delivered to date. Accuracy statistics are reported in **Table 2.1** and shown in Figures **2.3-2.4**.


Table 2.1. Absolute Accuracy - Deviation between laser points and RTK survey points.

Sample S	ize (n): 19,102
Root Mean Square	Error (RMSE): 0.10 feet
Standard Deviations	Deviations
1 sigma (σ): 0.14 feet	Minimum Δz: -0.88 feet
2 sigma (σ): 0.32 feet	Maximum Δz: 0.67 feet
	Average Δz: 0.12 feet

Figure 2.3. South Coast Study area histogram statistics







3. Data Density/Resolution

3.1 Density Statistics

Some types of surfaces (i.e., dense vegetation or water) may return fewer pulses than the laser originally emitted. Therefore, the delivered density can be less than the native density and vary according to distributions of terrain, land cover and water bodies. Density histograms and maps (Figures 3.1 - 3.4) have been calculated based on first return laser point density and ground-classified laser point density.

Table 3.1. Average density statistics for South Coast data delivered to date.

Average Pulse	Average Pulse	Average Ground	Average Ground
Density	Density	Density	Density
	l .	l	· · · · · · · · · · · · · · · · · · ·
(per square ft)	(per square m)	(per square ft)	(per square m)





Figure 3.2. Image shows first return laser point per 0.75' USGS Quad for data delivered to date.



Ground classifications were derived from ground surface modeling. Supervised classifications were performed by reseeding of the ground model where it was determined that the ground model failed, usually under dense vegetation and/or at breaks in terrain, steep slopes and at bin boundaries.






Figure 3.4. Ground-classified laser point density per 0.75' USGS Quad for data delivered to date.



3.2 Data Density/Resolution per Delivery


3.2.1 Delivery 1

Figure 3.5. Quadrants containing few ground classified points include coastal areas and areas of dense vegetation.




3.2.2 Delivery 2

Figure 3.6. This quadrant illustrates a high number of ground classified points due to flightline overlap and areas of little or no ground cover.




LiDAR Remote Sensing Data: Department of Geology and Mineral Industries - Southern Oregon Coast Prepared by Watershed Sciences, Inc.



LiDAR Remote Sensing Data: Department of Geology and Mineral Industries - Southern Oregon Coast Prepared by Watershed Sciences, Inc.

3.2.3 Delivery 3

Figure 3.8. Quadrants containing few ground classified points include coastal areas and areas of dense vegetation.



3.2.4 Delivery 4

Figure 3.9. Quadrants with exposed ground or little vegetation result in higher ground-classified point density.





Figure 3.10. Quadrants with higher flightline density result in greater numbers of first return points.



4. Selected Imagery

Example areas are presented to show sample imagery (see Figures 4.1-4.9).

Figure 4.1. View to Northwest at oceanside near Harris Beach State Park, Oregon (quad 42124-A3). Top image derived from highest hit LiDAR, lower image derived from bare earth LiDAR.




Figure 4.2. View to Southeast and upstream along Chetco River at its confluence with Jack Creek (quad 42124-A2). Top image is derived from highest hit LiDAR, lower image derived from bare earth LiDAR.




Figure 4.3. View upstream and to Northeast of Chetco River at confluence with North Fork Chetco River (quad 42124-a2). Top image derived from highest hit LiDAR, lower image derived from bare earth LiDAR.




Figure 4.4. Oblique view of coastline at confluence of Whalehead Creek and ocean (quad 42124-b3). Upper image derived from highest hit LiDAR, lower image derived from bare earth LiDAR.




Figure 4.5. Oblique view to North over Chetco Rive river and North Fork Chetco River (quad 42124-a2). Top image derived from LiDAR highest hits, bottom from bare earth LiDAR.




Figure 4.6. Chetco River upstream of confluence with Elk Creek (quad 42124-b2). Upper image derived from highest hit LiDAR, center image derived from bare earth LiDAR, lower image derived from NAIP orthophoto.




Figure 4.7. Whalehead and Coon Creek at terminus in ocean near Highway 101 (quad42124-b3). Top image derived from highest hit LiDAR, center image from bare earth LiDAR, lower image derived from NAIP orthophotos.



Figure 4.8. View of the Sixes River and Bea Creek confluence in delivery tile 42124g3. Top image derived from bare earth LiDAR, center image from highest hit LiDAR, and lower image derived from NAIP orthophotos.




Figure 4.9. View of the confluence of Sixes River and Edson Creek in delivery tile 42124g4. Top image derived from bare earth LiDAR, center image from highest hit LiDAR, and lower image derived from NAIP orthophotos.

