

LIDAR DATA CALIBRATION REPORT

Terrapoint #: 2011-103-U

FEMA Virginia LiDAR (T/O G11PD00089) – King William

Originally submitted: Thursday, August 04, 2011

Presented to:

Dewberry

Submitted by:



Client Program Management Group
Ottawa, Canada



EXECUTIVE SUMMARY

This LiDAR project was to provide high accuracy, calibrated multiple return LiDAR for 285 square miles (excluding 200* NPS buffer = 150m) representing Dewberry, FEMA Virginia LiDAR acquisition Task Order #6 – (G11PD00089). Data are collected and delivered in compliance with the “U.S. Geological Survey National Geospatial Program Base LiDAR Specifications, Version 13 – ILMF 2010”.

This report concerns the King William County area, the primary deliverable product is raw calibrated LiDAR.

The elevation data was verified internally prior to delivery to ensure it met fundamental accuracy requirements (vertical accuracy NSSDA RMSE_Z = 9.25cm (NSSDA Accuracy_Z 95% = 18 cm) or better; in open, non-vegetated terrain) when compared to kinematic and static Terrapoint GPS checkpoints. Below is the summary for both tests:

- The LiDAR dataset was tested to 0.131m vertical accuracy at 95% confidence level based on consolidated RMSE_Z (0.038m x 1.960) when compared to 1126 GPS kinematic check points.
- The LiDAR dataset was tested to 0.0784m vertical accuracy at 95% confidence level based on consolidated RMSE_Z (0.04m x 1.960) when compared to 11 GPS static check points.

Please note that this report focuses solely on the Terrapoint activities pertaining to the LiDAR data processing component of this project.

All data delivered meets or exceeds Terrapoint’s deliverable product requirements as set out by Terrapoint’s Quality Management program.



Executive Summary	2
Introduction.....	4
1. LiDAR Data Processing	5
1.1. Airborne GPS Kinematic	5
1.2. Generation and Calibration of Laser Points (raw data)	5
1.3. Vertical Bias Resolution	6
1.4. Deliverable Product Generation.....	6
2. Quality Control for Data Processing LiDAR Calibration	6
2.1. Calibration Setup and Data Inventory	6
2.2. Boresight and Relative accuracy	7
2.3. Absolute accuracy	7
3. Conclusion	8
Appendix A GPS Validation	9



INTRODUCTION

LiDAR data is remotely sensed high-resolution elevation data collected by an airborne collection platform. By positioning laser range finding with the use of 1 second GPS with 200 Hz inertial measurement unit corrections; Terrapoint's LiDAR instruments are able to make highly detailed geospatial elevation products of the ground, man-made structures and vegetation.

The purpose of this LiDAR data was to produce high accuracy 3D terrain geospatial products for flood mapping and other applications.

This report covers the LiDAR processing methods and deliverable products. A GPS Validation Report has been included as an appendix.

Please note that this report focuses solely on the Terrapoint activities pertaining to the LiDAR data processing component of this project.

1. LiDAR Data Processing

1.1. Airborne GPS Kinematic

Airborne GPS kinematic data was processed on-site using GrafNav kinematic On-The-Fly (OTF) software. Flights were flown with a minimum of 6 satellites in view (13° above the horizon) and with a PDOP of better than 4. Distances from base station to aircraft were kept to a maximum of 40km.

For all flights, the GPS data can be classified as excellent, with GPS residuals of 3cm average or better but no larger than 10cm being recorded.

1.2. Generation and Calibration of Laser Points (raw data)

The initial step of calibration is to verify availability and status of all needed GPS and Laser data against field notes and compile any data if not complete.

Subsequently the mission points are output using Optech's Dashmap, initially with default values from Optech or the last mission calibrated for system. The initial point generation for each mission calibration is verified within Microstation/Terrascan for calibration errors. If a calibration error greater than specification is observed within the mission, the roll pitch and scanner scale corrections that need to be applied are calculated. The missions with the new calibration values are regenerated and validated internally once again to ensure quality.

All missions are validated against the adjoining missions for relative vertical biases and collected GPS kinematic validation points for absolute vertical accuracy purposes.

On a project level, a supplementary coverage check is carried out, to ensure no data voids unreported by Field Operations are present.

1.3. Vertical Bias Resolution

When the LiDAR data was compared to the GPS kinematic and static points, a bias was detected. Hence the following corrections were applied:

Mission	Total Vertical Adjustment (m)
o211126a	0.13
o211127c	0.16
o211130a	0.18
o511122a	0.18
o511122b	0.27
o511124a	0.38
o511125a	0.68
o511126a	0.53
o511127b	0.45
o511129a	0.58

1.4. Deliverable Product Generation

The raw, unclassified LiDAR data were delivered in LAS format 1.2 adjusted GPS time, both as raw strips, with files bigger than 2 GB split in 2 both. Header is populated with the projection information and the withheld angles (+/-2deg) are flagged using the Withheld bit. In some isolated areas polygons were used to extend the withheld bit classification in areas of bad data due to extreme wind.

All products were delivered in UTM 18 north meters, NAD83(NSRS 07), NAVD88(Geoid09).

2. Quality Control for Data Processing LiDAR Calibration

Quality assurance and quality control procedures for the raw LiDAR data are performed in an iterative fashion through the entire data processing cycle.

The following list provides a step-by-step explanation of the process used by Terrapoint to review the data prior to customer delivery.

2.1. Calibration Setup and Data Inventory

Data collected by the LiDAR unit is reviewed for completeness, acceptable density and to make sure all data is captured without errors or corrupted

values. In addition, all GPS, aircraft trajectory, mission information, and ground control files are reviewed and logged into a database.

2.2. Boresight and Relative accuracy

The initial points for each mission calibration are inspected for flight line errors, flight line overlap, slivers or gaps in the data, point data minimums, or issues with the LiDAR unit or GPS. Roll, pitch and scanner scale are optimized during the calibration process until the relative accuracy is met.

Relative accuracy and internal quality are checked using at least 3 regularly spaced QC blocks in which points from all lines are loaded and inspected. Vertical differences between ground surfaces of each line are displayed. Color scale is adjusted so that errors greater than the specifications are flagged. Cross sections are visually inspected across each block to validate point to point, flightline to flightline and mission to mission agreement. For this project the specifications used are as follow: Relative accuracy $\leq 7\text{cm}$ RMSE_Z within individual swaths and $\leq 10\text{ cm}$ RMSE_Z or within swath overlap (between adjacent swaths) .

A different set of QC blocks are generated for final review after all transformations have been applied.

2.3. Absolute accuracy

A preliminary RMSE_Z error check is performed at this stage of the project life cycle in the raw LiDAR dataset against GPS static and kinematic data and compared to RMSE_Z project specifications. The LiDAR data is examined in open, flat areas away from breaks. Lidar ground points for each flightline generated by an automatic classification routine are used.

Results:

Prior to delivery the elevation data was verified internally to ensure it met fundamental accuracy requirements of 18.5cm vertical accuracy at the 95% confidence level ($2\text{ sigma} = \text{RMSE} * 1.96$) in when compared to Terrapoint kinematic and static GPS checkpoints.

Data is compiled to meet 1m horizontal accuracy at the 95% confidence level ($2\text{ sigma} = \text{RMSE} * 1.96$)

- The LiDAR dataset was tested to 0.131m vertical accuracy at 95% confidence level based on consolidated RMSE_Z (0.038m x 1.960) when compared to 1126 GPS kinematic check points.

- The LiDAR dataset was tested to 0.078m vertical accuracy at 95% confidence level based on consolidated $RMSE_z$ (0.04×1.960) when compared to 11 GPS static check points.

A detailed comparison is provided in Appendix A - GPS Validation.

3. Conclusion

Overall the LiDAR data products collected for Dewberry meets or exceed the requirements set out in the Statement of Work for this project. The quality control requirements of Terrapoint's Quality management program were adhered to throughout the acquisition stage of this project to ensure product quality.



Appendix A GPS Validation

Static GPS Validation

UTM18 meters

K:\11103u_Virginia\2_Operations\5_Ground_Truthing\Static King Willian County.txt

Easting Northing Known Z Laser Z Dz

341123.244	4155946.452	2.469	2.550	+0.082
307066.173	4185980.440	50.553	50.600	+0.047
307509.837	4180256.220	46.785	46.830	+0.045
318275.810	4172395.242	41.552	41.590	+0.038
307836.282	4173671.368	20.084	20.090	+0.006
317341.196	4176575.065	52.005	52.010	+0.005
306047.923	4194288.216	53.978	53.980	+0.002
329637.662	4165960.723	34.979	34.980	+0.001
336641.656	4160599.931	27.593	27.590	-0.003
299813.161	4187203.992	58.277	58.270	-0.007
327215.261	4169960.550	40.262	40.190	-0.072

Average dz +0.013

Minimum dz -0.072

Maximum dz +0.082

Average magnitude 0.028

Root mean square 0.040

Std deviation 0.040

Kinematic GPS Validation

Sample Size	1126	Points
average	0.016	metres
RMSE	0.067	metres
NSSDA	0.131	metres

