General Information

Mission Information

Project name	200717_B_5060449_nad2011_FINAL
Processing date	2020-07-20 11:46:53
Mission date	2020-07-17 17:56:57
Mission duration	01:24:04.293
Processing mode	IN-Fusion PP-RTX

Rover Hardware Information

Product	POS AV 610 VER6 HW2.5-12
Serial number	S/N11407
IMU type	57
Receiver type	BD982
Antenna type	AV39

Project File List

Rover Data Files

File name	File type
200717B.597	POS Data
200717B.598	POS Data
200717B.599	POS Data
200717B.600	POS Data
200717B.601	POS Data
200717B.602	POS Data
200717B.603	POS Data
200717B.604	POS Data
200717B.605	POS Data
200717B.606	POS Data
200717B.607	POS Data
200717B.608	POS Data

Input Files

File Name	File Type
Ephm1990.20g	GLONASS Broadcast Ephemeris
Ephm1990.20n	GPS Broadcast Ephemeris

Output Files

Filename	File type
sbet_200717_B_5060449_nad2011_FINAL.out	SBET Trajectory File
sbet_200717_B_5060449_nad2011_FINAL.shp	Shapefile Export Output

Rover Data Summary

First raw data file	200717B.597		
Last raw data file	200717B.608		
Start GPS week	2114		
Start time	496616.358 (07/17/2020 17:56:56)		
End time	501822.680 (07/17/2020 19:23:42)		
Start of fine alignment	496779.373 (07/17/2020 17:59:39)		
Available subsystems	Primary GNSS, IMU		
POS Event Input	None		
Correction data	None		
IMU Installation Lever Arms & Mounting Angles			
Reference to IMU lever arm (m)	0.000	0.000	0.000
Reference to IMU mounting angles (deg)	0.000	0.000	180.000
Reference to Primary GNSS lever arm (m)	-0.026	-0.220	-0.918
Reference to Primary GNSS lever arm std dev (m)	-1.000		
Aircraft to Reference mounting angles (deg)	0.000	0.000	0.000

Rover Data QC

Raw IMU Import QC Summary

IMU data input file	imu_200717_B_5060449_nad2011_FINAL.dat
IMU data check log file	imudt_200717_B_5060449_nad2011_FINAL.log
IMU Records Processed	1041178
Termination Status	Normal
IMU Anomalies	0

Primary Observables & Satellite Data

L1 Satellite Lock/Elevation



L2 Satellite Lock/Elevation



GPS L1 SNR



GPS L2 SNR



GLONASS L1 SNR



GLONASS L2 SNR



BEIDOU SNR



GALILEO SNR


54
52
50
48
46
44
42
40
38
36
34
32
30
28
497,000
497,500
498,000
498,500
499,000
499,500
500,000
500,500
501,000
501,500
Time (sec)
GALILEO 03 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 05 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 13 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 15 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 21 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 27 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 30 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 03 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 05 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 13 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 15 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 21 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 27 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 30 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 03 E5B BPSK10_PD SNR (dB/Hz)
GALILEO 05 E5B BPSK10_PD SNR (dB/Hz)
GALILEO 13 E5B BPSK10_PD SNR (dB/Hz)
GALILEO 15 E5B BPSK10_PD SNR (dB/Hz)
GALILEO 21 E5B BPSK10_PD SNR (dB/Hz)
GALILEO 27 E5B BPSK10_PD SNR (dB/Hz)

Smoothed Trajectory Information

Top View



Altitude



Roll/Pitch



Heading



North/East Velocity



Down Velocity



Total Speed



Ground Speed



Body Acceleration

Total Body Acceleration



Body Angular Rate



Forward Processed Trajectory Information

Top View



Altitude



Roll/Pitch



Heading



North/East Velocity



Down Velocity



Total Speed



Ground Speed



Body Acceleration

Total Body Acceleration



Body Angular Rate



GNSS QC

GNSS QC Statistics

Statistics	Min	Max	Mean
Baseline length (km)	0.00	0.00	
Number of GPS SV	6	8	7
Number of GLONASS SV	4	7	6
Number of QZSS SV	0	0	0
Number of BEIDOU SV	0	0	0
Number of GALILEO SV	4	7	6
Total number of SV	17	21	19
PDOP	1.07	1.35	1.19
QC Solution Gaps	0.00	0.00	
Solution Type	Fixed	Float	No solution
Epoch (sec)	5171.00	0.00	0.00
Percentage	100.00	0.00	0.00

Num SVs in solution



Forward/Reverse Separation



PDOP



Estimated Position Accuracy



GPS Residuals



GLONASS Residuals



GALILEO Residuals



GNSS-Inertial Processor Configuration

Processing mode	IN-Fusion PP-RTX		
Stabilized mount	False		
Processing start time	496778.707 (07/17/2020 17:59:38)		
Processing end time	501823.000 (07/17/2020 19:23:43)		
Initial attitude source	Real-Time VNAV/RNAV Attitude		
IMU Sensor Context	Processing with Onboard IMU		
Reference to IMU lever arm (m)	0.000	0.000	0.000
Reference to IMU mounting angles (deg)	0.000	0.000	180.000
Reference to Primary GNSS lever arm (m)	0.000	-0.249	-0.923
Reference to Primary GNSS lever arm std dev (m)	0.030	0.030	0.030
Aircraft to Reference mounting angles (deg)	0.000	0.000	0.000

Calibrated Installation Parameters

Reference-Primary GNSS Lever Arm (m)

X Reference-Primary GNSS Lever Arm (m)



Y Reference-Primary GNSS Lever Arm (m)



Z Reference-Primary GNSS Lever Arm (m)



Reference-Primary GNSS Lever Arm Figure of Merit



IN-Fusion QC

Forward Processed Estimated Errors, Reference Frame

Accelerometer Bias (micro-g)



X Accelerometer Bias (micro-g)



Y Accelerometer Bias (micro-g)



Z Accelerometer Bias (micro-g)



Accelerometer Scale Error (ppm)



X Accelerometer Scale Error (ppm)



Y Accelerometer Scale Error (ppm)



Z Accelerometer Scale Error (ppm)



Gyro Bias (deg/h)



X Gyro Bias (deg/h)



Y Gyro Bias (deg/h)



Z Gyro Bias (deg/h)



Gyro Scale Error (ppm)



X Gyro Scale Error (ppm)



Y Gyro Scale Error (ppm)



Z Gyro Scale Error (ppm)



Forward Processed Estimated Constant Errors, Reference Frame

Accelerometer Bias (micro-g)



X Accelerometer Bias (micro-g)



Y Accelerometer Bias (micro-g)



Z Accelerometer Bias (micro-g)



Gyro Bias (deg/h)



X Gyro Bias (deg/h)



Y Gyro Bias (deg/h)



Z Gyro Bias (deg/h)



Smoothed Performance Metrics

Position Error RMS (m)



Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)



Heading Error RMS (arc-min)



Forward Processed Performance Metrics

Position Error RMS (m)



Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)



Heading Error RMS (arc-min)



Forward Processed Solution Status

Processing Mode



Number of Satellites



Baseline Length



Export Summary

Export file	sbet_200717_B_5060449_nad2011_FINAL.shp		
Export format	Shapefile		
Solution in use	Post-processed		
Output rate	Specified Distance Interval		
Distance Interval (m)	10.000		
Reference to Output lever arm (m)	0.000	0.000	0.000
Reference mounting angles (deg)	0.000	0.000	0.000
Output units (Coordinate / Lat & Lon)	Meter	Deg Decimal	
Export start time	496781.003 (07/17/2020 17:59:41)		
Export end time	501823.000 (07/17/2020 19:23:43)		
Height option	Ellipsoid Height		
WGS84 height flag	False		
Grid	CONUS Albers		
Zone	CONUS Albers		
Datum	NAD83 (2011)		
Ellipsoid	GRS 1980		
Local Transformation	NONE		
Target Epoch	2010		