General Information

Mission Information

Project name	200719_A_5060449_nad2011_FINAL
Processing date	2020-07-21 23:53:23
Mission date	2020-07-19 15:09:51
Mission duration	03:13:17.000
Processing mode	IN-Fusion PP-RTX

Rover Hardware Information

Product	POS AV 610 VER6 HW2.5-12
Serial number	S/N11407
IMU type	57
Receiver type	BD982
Antenna type	AV39

Project File List

Rover Data Files

File name	File type
200719A.675	POS Data
200719A.676	POS Data
200719A.677	POS Data
200719A.678	POS Data
200719A.679	POS Data
200719A.680	POS Data
200719A.681	POS Data
200719A.682	POS Data
200719A.683	POS Data
200719A.684	POS Data
200719A.685	POS Data
200719A.686	POS Data
200719A.687	POS Data
200719A.688	POS Data
200719A.689	POS Data
200719A.690	POS Data
200719A.691	POS Data
200719A.692	POS Data
200719A.693	POS Data
200719A.694	POS Data
200719A.695	POS Data
200719A.696	POS Data
200719A.697	POS Data
200719A.698	POS Data
200719A.699	POS Data
200719A.700	POS Data

Input Files

File Name	File Type
Ephm2010.20g	GLONASS Broadcast Ephemeris
Ephm2010.20n	GPS Broadcast Ephemeris

Output Files

Filename	File type
sbet_200719_A_5060449_nad2011_FINAL.out	SBET Trajectory File
sbet_200719_A_5060449_nad2011_FINAL.shp	Shapefile Export Output

Rover Data Summary

First raw data file	200719A.675		
Last raw data file	200719A.700		
Start GPS week	2115		
Start time	54590.972 (07/19/2020 15:09:50)		
End time	66187.875 (07/19/2020 18:23:07)		
Start of fine alignment	54635.198 (07/19/2020 15:10:35)		
Available subsystems	Primary GNSS, IMU		
POS Event Input	None		
Correction data	None		
IMU Installation Lever Arms & Mounting Angles			
Reference to IMU lever arm (m)	0.000	0.000	0.000
Reference to IMU mounting angles (deg)	0.000	0.000	180.000
Reference to Primary GNSS lever arm (m)	-0.026	-0.220	-0.918
Reference to Primary GNSS lever arm std dev (m)	-1.000		
Aircraft to Reference mounting angles (deg)	0.000	0.000	0.000

Rover Data QC

Raw IMU Import QC Summary

IMU data input file	imu_200719_A_5060449_nad2011_FINAL.dat
IMU data check log file	imudt_200719_A_5060449_nad2011_FINAL.log
IMU Records Processed	2318942
Termination Status	Normal
IMU Anomalies	0

Primary Observables & Satellite Data

L1 Satellite Lock/Elevation



L2 Satellite Lock/Elevation



GPS L1 SNR



GPS L2 SNR



GLONASS L1 SNR



GLONASS L2 SNR



BEIDOU SNR



GALILEO SNR


54
52
50
48
46
44
42
40
38
36
34
32
30
55,000
56,000
57,000
58,000
59,000
60,000
61,000
62,000
63,000
64,000
65,000
66,000
Time (sec)
GALILEO 01 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 07 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 12 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 13 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 21 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 24 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 26 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 31 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 33 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 01 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 07 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 12 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 13 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 21 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 24 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 26 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 31 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 33 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 01 E5B BPSK10_PD SNR (dB/Hz)
GALILEO 07 E5B BPSK10_PD SNR (dB/Hz)

Smoothed Trajectory Information

Top View



Altitude



Roll/Pitch



Heading



North/East Velocity



Down Velocity



Total Speed



Ground Speed



Body Acceleration



Total Body Acceleration



Body Angular Rate

Forward Processed Trajectory Information

Top View



Altitude



Roll/Pitch



Heading



North/East Velocity



Down Velocity



Total Speed



Ground Speed



Body Acceleration



Total Body Acceleration



Body Angular Rate

GNSS QC

GNSS QC Statistics

Statistics	Min	Max	Mean
Baseline length (km)	0.00	0.00	
Number of GPS SV	7	9	8
Number of GLONASS SV	4	9	7
Number of QZSS SV	0	0	0
Number of BEIDOU SV	2	2	2
Number of GALILEO SV	5	7	6
Total number of SV	19	26	22
PDOP	0.92	1.50	1.14
QC Solution Gaps	0.00	0.00	
Solution Type	Fixed	Float	No solution
Epoch (sec)	11543.00	0.00	0.00
Percentage	100.00	0.00	0.00

Num SVs in solution



Forward/Reverse Separation



PDOP



Estimated Position Accuracy



GPS Residuals



GLONASS Residuals



BEIDOU Residuals



GALILEO Residuals



GNSS-Inertial Processor Configuration

Processing mode	IN-Fusion PP-RTX		
Stabilized mount	False		
Processing start time	54591.000 (07/19/2020 15:09:51)		
Processing end time	66188.000 (07/19/2020 18:23:08)		
Initial attitude source	Real-Time VNAV/RNAV Attitude		
IMU Sensor Context	Processing with Onboard IMU		
Reference to IMU lever arm (m)	0.000	0.000	0.000
Reference to IMU mounting angles (deg)	0.000	0.000	180.000
Reference to Primary GNSS lever arm (m)	-0.054	-0.216	-0.914
Reference to Primary GNSS lever arm std dev (m)	0.030	0.030	0.030
Aircraft to Reference mounting angles (deg)	0.000	0.000	0.000

Calibrated Installation Parameters

Reference-Primary GNSS Lever Arm (m)

X Reference-Primary GNSS Lever Arm (m)



Y Reference-Primary GNSS Lever Arm (m)



Z Reference-Primary GNSS Lever Arm (m)



Reference-Primary GNSS Lever Arm Figure of Merit



IN-Fusion QC

Forward Processed Estimated Errors, Reference Frame

Accelerometer Bias (micro-g)



X Accelerometer Bias (micro-g)



Y Accelerometer Bias (micro-g)



Z Accelerometer Bias (micro-g)



Accelerometer Scale Error (ppm)



X Accelerometer Scale Error (ppm)



Y Accelerometer Scale Error (ppm)



Z Accelerometer Scale Error (ppm)



Gyro Bias (deg/h)



X Gyro Bias (deg/h)



Y Gyro Bias (deg/h)



Z Gyro Bias (deg/h)



Gyro Scale Error (ppm)



X Gyro Scale Error (ppm)



Y Gyro Scale Error (ppm)



Z Gyro Scale Error (ppm)



Forward Processed Estimated Constant Errors, Reference Frame

Accelerometer Bias (micro-g)



X Accelerometer Bias (micro-g)



Y Accelerometer Bias (micro-g)



Z Accelerometer Bias (micro-g)



Gyro Bias (deg/h)



X Gyro Bias (deg/h)



Y Gyro Bias (deg/h)



Z Gyro Bias (deg/h)



Smoothed Performance Metrics

Position Error RMS (m)

Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)



Heading Error RMS (arc-min)



Forward Processed Performance Metrics

Position Error RMS (m)



Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)



Heading Error RMS (arc-min)



Forward Processed Solution Status

Processing Mode



Number of Satellites



Baseline Length



Export Summary

Export file	sbet_200719_A_5060449_nad2011_FINAL.shp		
Export format	Shapefile		
Solution in use	Post-processed		
Output rate	Specified Distance Interval		
Distance Interval (m)	10.000		
Reference to Output lever arm (m)	0.000	0.000	0.000
Reference mounting angles (deg)	0.000	0.000	0.000
Output units (Coordinate / Lat & Lon)	Meter	Deg Decimal	
Export start time	54637.004 (07/19/2020 15:10:37)		
Export end time	66188.005 (07/19/2020 18:23:08)		
Height option	Ellipsoid Height		
WGS84 height flag	False		
Grid	CONUS Albers		
Zone	CONUS Albers		
Datum	NAD83 (2011)		
Ellipsoid	GRS 1980		
Local Transformation	NONE		
Target Epoch	2010		