General Information

Mission Information

Project name	19-058_110519
Processing date	2019-11-13 19:44:21
Mission date	2019-11-05 16:42:01
Mission duration	07:37:57.000
Processing mode	IN-Fusion Trimble RTX Nav

Rover Hardware Information

Product	POS AV 510 VER6 HW2.4-11
Serial number	S/N6310
IMU type	46
Receiver type	BD982
Antenna type	AV39

Project File List

Rover Data Files

File name	File type
191105_164142_AV510_5361.raw	POS Data

Input Files

File Name	File type
Ephm3090.19g	GLONASS Broadcast Ephemeris
Ephm3090.19n	GPS Broadcast Ephemeris
Ephm3100.19g	GLONASS Broadcast Ephemeris
Ephm3100.19n	GPS Broadcast Ephemeris

Output Files

Filename	File type
sbet_19-058_110519.out	SBET Trajectory File

Rover Data Summary

First raw data file	191105_164142_AV510_5361.raw		
Last raw data file	191105_164142_AV510_5361.raw		
Start GPS week	2078		
Start time	232902.587 (11/05/2019 16:41:42)		
End time	260368.885 (11/06/2019 00:19:28)		
Start of fine alignment	232921.089 (11/05/2019 16:42:01)		
Available subsystems	Primary GNSS, IMU		
POS Event Input	None		
Correction data	Trimble RTX		
IMU Installation Lever Arms & Mounting Angles			
Reference to IMU lever arm [m]	0.000	0.000	0.000
Reference to IMU mounting angles [deg]	0.000	0.000	0.000
Reference to Primary GNSS lever arm [m]	-0.011	0.039	-1.017
Reference to Primary GNSS lever arm std dev [m]	-1.000		
Aircraft to Reference mounting angles [deg]	0.000	0.000	0.000

Raw Data QC

L1 Satellite Lock/Elevation



L2 Satellite Lock/Elevation



GPS L1 SNR



GPS L2 SNR



GLONASS L1 SNR



GLONASS L2 SNR



BEIDOU SNR


BEIDOU SNR
50
48
46
44
42
40
38
36
34
32
30
28
26
24
235,000
240,000
245,000
250,000
255,000
260,000
Time (sec)
BEIDOU 08 E5B B2 SNR (dB/Hz)
BEIDOU 11 E5B B2 SNR (dB/Hz)
BEIDOU 14 E5B B2 SNR (dB/Hz)
BEIDOU 20 E5B B2 SNR (dB/Hz)
BEIDOU 21 E5B B2 SNR (dB/Hz)
BEIDOU 23 E5B B2 SNR (dB/Hz)
BEIDOU 24 E5B B2 SNR (dB/Hz)
BEIDOU 25 E5B B2 SNR (dB/Hz)
BEIDOU 26 E5B B2 SNR (dB/Hz)
BEIDOU 27 E5B B2 SNR (dB/Hz)
BEIDOU 28 E5B B2 SNR (dB/Hz)
BEIDOU 29 E5B B2 SNR (dB/Hz)
BEIDOU 30 E5B B2 SNR (dB/Hz)
BEIDOU 08 B1 B1 SNR (dB/Hz)
BEIDOU 11 B1 B1 SNR (dB/Hz)
BEIDOU 14 B1 B1 SNR (dB/Hz)
BEIDOU 20 B1 B1 SNR (dB/Hz)
BEIDOU 21 B1 B1 SNR (dB/Hz)
BEIDOU 23 B1 B1 SNR (dB/Hz)
BEIDOU 24 B1 B1 SNR (dB/Hz)
BEIDOU 25 B1 B1 SNR (dB/Hz)
BEIDOU 26 B1 B1 SNR (dB/Hz)
BEIDOU 27 B1 B1 SNR (dB/Hz)
BEIDOU 28 B1 B1 SNR (dB/Hz)
BEIDOU 29 B1 B1 SNR (dB/Hz)
BEIDOU 30 B1 B1 SNR (dB/Hz)

Trajectory Information

Top View



Altitude



Roll/Pitch



Heading



North/East Velocity



Down Velocity



Total Speed



Ground Speed



Body Acceleration



Total Body Acceleration



Body Angular Rate



GNSS-Inertial Processor Configuration

Processing mode	IN-Fusion Trimble RTX Nav		
Stabilized mount	False		
Processing start time	232903.000 (11/05/2019 16:41:43)		
Processing end time	260380.000 (11/06/2019 00:19:40)		
Initial attitude source	Real-Time VNAV/RNAV Attitude		
IMU Sensor Context	Processing with Onboard IMU		
Reference to IMU lever arm [m]	0.000	0.000	0.000
Reference to IMU mounting angles [deg]	0.000	0.000	0.000
Reference to Primary GNSS lever arm [m]	-0.008	0.046	-1.014
Reference to Primary GNSS lever arm std dev [m]	0.030	0.030	0.030
Aircraft to Reference mounting angles [deg]	0.000	0.000	0.000

Calibrated Installation Parameters

Reference-Primary GNSS Lever Arm

X Reference-Primary GNSS Lever Arm (m)



Y Reference-Primary GNSS Lever Arm (m)



Z Reference-Primary GNSS Lever Arm (m)



Reference-Primary GNSS Lever Arm Figure of Merit



Smoothed IN-Fusion QC

Smoothed Estimated Errors, Reference Frame

Accelerometer Bias (micro-g)



X Accelerometer Bias (micro-g)



Y Accelerometer Bias (micro-g)



Z Accelerometer Bias (micro-g)



Accelerometer Scale Error (ppm)



X Accelerometer Scale Error (ppm)



Y Accelerometer Scale Error (ppm)



Z Accelerometer Scale Error (ppm)



Gyro Bias (deg/h)



X Gyro Bias (deg/h)



Y Gyro Bias (deg/h)



Z Gyro Bias (deg/h)



Gyro Scale Error (ppm)



X Gyro Scale Error (ppm)



Y Gyro Scale Error (ppm)



Z Gyro Scale Error (ppm)



Smoothed Performance Metrics

Position Error RMS (m)



Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)



Heading Error RMS (arc-min)