General Information

Mission Information

Project name	19118_DewberryID_1007
Processing date	2020-10-22 22:59:25
Mission date	2019-10-07 14:17:43
Mission duration	03:23:00.000
Processing mode	IN-Fusion PP-RTX

Rover Hardware Information

Product	POS AV 610 VER6 HW2.5-12
Serial number	S/N10659
IMU type	57
Receiver type	BD982
Antenna type	Unknown External

Project File List

Rover Data Files

File name	File type
20191007b.251	POS Data
20191007b.252	POS Data
20191007b.253	POS Data
20191007b.254	POS Data
20191007b.255	POS Data
20191007b.256	POS Data
20191007b.257	POS Data
20191007b.258	POS Data
20191007b.259	POS Data
20191007b.260	POS Data
20191007b.261	POS Data
20191007b.262	POS Data
20191007b.263	POS Data
20191007b.264	POS Data
20191007b.265	POS Data
20191007b.266	POS Data
20191007b.267	POS Data
20191007b.268	POS Data
20191007b.269	POS Data
20191007b.270	POS Data
20191007b.271	POS Data
20191007b.272	POS Data
20191007b.273	POS Data
20191007b.274	POS Data
20191007b.275	POS Data
20191007b.276	POS Data
20191007b.277	POS Data

Input Files

File Name	File Type
Ephm2800.19g	GLONASS Broadcast Ephemeris
Ephm2800.19n	GPS Broadcast Ephemeris

Output Files

Filename	File type
sbet_Mission 1.out	SBET Trajectory File

Rover Data Summary

First raw data file	20191007b.251		
Last raw data file	20191007b.277		
Start GPS week	2074		
Start time	137862.374 (10/7/2019 2:17:42 PM)		
End time	150043.249 (10/7/2019 5:40:43 PM)		
Start of fine alignment	138107.700 (10/7/2019 2:21:47 PM)		
Available subsystems	Primary GNSS, IMU		
POS Event Input	None		
Correction data	None		
IMU Installation Lever Arms & Mounting Angles			
Reference to IMU lever arm (m)	0.000	0.000	0.000
Reference to IMU mounting angles (deg)	0.000	0.000	180.000
Reference to Primary GNSS lever arm (m)	0.326	-0.406	-1.087
Reference to Primary GNSS lever arm std dev (m)	-1.000		
Aircraft to Reference mounting angles (deg)	0.000	0.000	0.000

Rover Data QC

Raw IMU Import QC Summary

IMU data input file	imu_Mission 1.dat
IMU data check log file	imudt_Mission 1.log
IMU Records Processed	2435799
Termination Status	Normal
IMU Anomalies	0

Primary Observables & Satellite Data

L1 Satellite Lock/Elevation



L2 Satellite Lock/Elevation



GPS L1 SNR



GPS L2 SNR



GLONASS L1 SNR



GLONASS L2 SNR



BEIDOU SNR



GALILEO SNR


52
50
48
46
44
42
40
38
36
34
32
30
28
26
24
22
139,000
140,000
141,000
142,000
143,000
144,000
145,000
146,000
147,000
148,000
149,000
150,000
Time (sec)
GALILEO 02 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 04 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 09 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 11 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 12 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 18 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 19 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 24 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 25 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 31 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 33 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 36 L1 BOC_1_1_D_MBOC SNR (dB/Hz)
GALILEO 02 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 04 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 09 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 11 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 12 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 18 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 19 L5E5A BPSK10_PD SNR (dB/Hz)
GALILEO 24 L5E5A BPSK10_PD SNR (dB/Hz)

Smoothed Trajectory Information

Top View



Altitude



Roll/Pitch



Heading



North/East Velocity



Down Velocity



Total Speed



Ground Speed



Body Acceleration



Total Body Acceleration



Body Angular Rate

Forward Processed Trajectory Information

Top View



Altitude



Roll/Pitch



Heading



North/East Velocity



Down Velocity



Total Speed



Ground Speed



Body Acceleration



Total Body Acceleration



Body Angular Rate

GNSS QC

Num SVs in solution



Forward/Reverse Separation



PDOP



Estimated Position Accuracy



GPS Residuals



GLONASS Residuals



GALILEO Residuals



GNSS-Inertial Processor Configuration

Processing mode	IN-Fusion PP-RTX		
Stabilized mount	False		
Processing start time	137863.000 (10/7/2019 2:17:43 PM)		
Processing end time	150043.000 (10/7/2019 5:40:43 PM)		
Initial attitude source	Real-Time VNAV/RNAV Attitude		
IMU Sensor Context	Processing with Onboard IMU		
Reference to IMU lever arm (m)	0.000	0.000	0.000
Reference to IMU mounting angles (deg)	0.000	0.000	180.000
Reference to Primary GNSS lever arm (m)	0.310	-0.156	-0.942
Reference to Primary GNSS lever arm std dev (m)	0.030	0.030	0.030
Aircraft to Reference mounting angles (deg)	0.000	0.000	0.000

Calibrated Installation Parameters

Reference-Primary GNSS Lever Arm (m)

IN-Fusion QC

Forward Processed Estimated Errors, Reference Frame

Smoothed Performance Metrics

Position Error RMS (m)

Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)



Heading Error RMS (arc-min)



Forward Processed Performance Metrics

Position Error RMS (m)

Velocity Error RMS (m/s)



Roll/Pitch Error RMS (arc-min)



Heading Error RMS (arc-min)



Forward Processed Solution Status

Processing Mode



Number of Satellites



Baseline Length